CMT ORANGE TOOLS™


Saw Blades



Jig Saw Blades



Sabre Saw Blades



Tools for Multi-Cutters




Tools with Bore & Knives




Router Bits & Sets



CNC Router Cutters & Chucks



Industrial Dowel Drills



Bits for Hand Power Tools




Hole Saws



Power Tools



Accessories



Catalogue 2016/2017

English edition

C. DAHM
MASKINFORRETNING AS



Nordåsdalen 10, 5235 RÅDAL- BERGEN
Tlf 55 11 24 70 Fax 55 11 24 71
firmapost@dahm.no
www.dahm.no

WOOD® Magazine
WOOD'S CHOICE 1994 Best Overall ROUTER BITS

CMT Overall Rating 10!
Top Performing Router Bits

www.dahm.no

Welcome to the 2016/2017 catalogue

Dear Customer,

Thank you for your interest in CMT products.
Take a moment to browse our new catalogue and choose from a wider range of innovative and state-of-the-art woodworking tools, from router bits, saw blades, jig and sabre saw blades, hole saws, and boring bits to oscillating tools, CNC cutters, cutter heads, chucks, power tools, and so much more!

A detailed list of spare parts on each product category is also provided to guide you through your purchase.

We continually strive to develop our technical know-how and invest in research and development, but our priority is customer care.
A satisfied customer is worth more than any other achievement, therefore each page of this catalog contains CMT's highest commitment to the professional woodworker.

Should you not find a product that suits your needs, please let us know.
Our highly skilled engineers and design technicians are always keen to assist you with your woodworking operations.

Thank you for your interest in CMT Orange Tools.

Your CMT Team


www.dahm.no

Abbreviations

A = Cutting angle
α = Hook angle
ATB = Alternate top bevel grind
B = Bore diameter
β = Type of grind
COMBI3 = Pin-Hole 2/7/42 + 2/9/46,4 + 2/10/60
COMBI5 = Pin-Hole 2/7/110 + 2/8,4/130 + 2/14/110 + 4/9/100 + 4/19/120
COMBI7 = Pin-Hole 2/10/80 + 1/11/85 + 2/11/115 + 2/11/148 + 2/14/100 + 2/14/125 + 2/19/120
d = Small cutting diameter
D = Diameter
D_2 = Overall diameter
D_3 = For shank diameter
Ø = Diameter
FFT = Flat flat trapezoidal
FTG = Flat top grind
FWF = Flat with alternate chamfer
H = Cutting depth
HDF = Hollow ground teeth
I = Cutting length
I_1 = Short cutting length
Inches = Inches
K = Kerf thickness
L = Overall length
L_1 = Working length
LB = Adjusting length
LH = Left-hand rotation
MATB = Alternate top bevel with chamfer grind
MTCG = Triple chip grind (trapezoidal) with chamfer
mm = Millimeters
P = Plate thickness
PTFE = Non-stick industrial coating, black and orange
R = Radius
R_1 = Radius
RH = Right-hand rotation
RPM = Round per minute
S = Shank diameter
S_1 = Shank diameter
T_1 = Thickness / Maximum joint thickness
TCG = Triple chip grind (trapezoidal)
V = Spurs
Z = Number of teeth
□ = On request
● = Solid tungsten carbide

THE RIGHT TOOLS FOR THE BEST RESULTS!

Quick reference charts and pictograms help you choose the right tools for your application.



	SAW BLADES	JIG SAW BLADES	SABRE SAW BLADES	MULTI-CUTTERS	HOLE SAWS
WOOD					CARBIDE
WOOD & METAL			✓	✓	
METAL					BI-METAL
ALUMINIUM					
MULTI-MATERIAL					
PLASTIC					
MASONRY					DIAMOND
SPECIAL					

CMT ORANGE TOOLS™

www.dahm.no




SAW BLADES 4~46



JIG SAW BLADES 47~52



SABRE SAW BLADES 53~62



TOOLS FOR MULTI-CUTTERS 63~72



TOOLS WITH BORE & KNIVES 73~116



ROUTER BITS & SETS 117~213



CNC ROUTER CUTTERS & CHUCKS 214~252



INDUSTRIAL DOWEL DRILLS 253~278




BITS FOR HAND POWER TOOLS 279~297



HOLE SAW BLADES 298~310



POWER TOOLS & ACCESSORIES 311~341



DISPLAY CABINETS & SPARE PARTS 342~353

www.dahm.no

SINCE 1962 - MADE IN ITALY THEN, STILL MADE IN ITALY TODAY

By now, the story has been told. After over 50 years of success and quality in manufacturing woodworking tools - orange woodworking tools, to be precise - word just sort of gets around. We have grown and we have changed, but one thing still remains the same: our commitment to making only the highest quality woodworking tools.




Pesaro, Italy



Greensboro, United States



Valencia, Spain



OUR TOOLS So, what does it take to make a CMT tool? Like all things of quality, it's not only what you do but how you do it. And anyone who works wood knows that you get out of a piece only what you put into it, and it is no different when manufacturing a tool. You choose your designs and materials carefully and you work using all of your skill and know-how. You'll be happy to know that's what we do at CMT too.

DESIGN

Everything starts with a clear idea and having the potential to express it. We have both. At CMT, our technical department uses the best of both worlds - computer technology and hands-on experience - to engineer and design each tool so that it performs flawlessly each time you use it, and to guarantee that you'll be using it for a long, long time.

MATERIALS

Turning a design into a finished product means finding the right material that will do the job and that lives up to the specifications set out in the design - quality performance from the final product depends on it. When it comes to selecting raw materials, we don't cut corners. At CMT, we know that high quality tools come only from high quality raw materials, so we use only solid bar stock steel and specially formulated micrograin carbide to manufacture our bits and blades.

MANUFACTURING

Like we said, it's not just what you do but how you do it. Over the years we have continuously invested in the latest technology in CNC machining equipment and innovative software to manufacture our tools. The result is that now our entire manufacturing process, from turning and milling the steel shanks to brazing and sharpening the carbide cutting tips, is completely automated. And since a machine is only as intelligent at the person using it, everything is operated by specifically trained operators.

THE FINAL TOUCH

A tool simply wouldn't be a CMT tool if it didn't have the trademark orange color non-stick PTFE coating on it. This unique industrial-strength surface coating is designed to withstand the physical stresses the tool undergoes during use while protecting it from residue build-up and burning. And we really like the orange color too.

www.dahm.no






QUALITY CONTROL

Nobody's perfect, but we're trying. CMT uses rigorous quality control programs and equipment to ensure that each bit has been manufactured with precision and accuracy and that it will give the long-lasting performance you expect from a CMT orange tool. CMT is in the process of adopting the directives set out in ISO 9001 which will give SPC quality control by an independent party under the Common Market Directives ISO 9001. Quality control is the final step of the production process, but it's just as important as the first.

WE RECYCLE

The water used during production must be pure and free from contaminants or hard minerals like iron or calcium which can build up and damage the machinery. CMT filters and purifies its water using a reverse osmosis system located inside the plant. Also the oil used in grinding and machining our tools must be clean and absolutely free of contaminants. Clean oil, after enough use, gets dirty, so we filter and reprocess dirty oil on the premises. This is our way of guaranteeing the quality of the oil we use, as well as contributing to help protect the environment.

OUR TRADEMARK COLOR ORANGE

As the story goes, we began small. We also put orange color surface coating on our tools, then we put our tools on the market and soon our orange tools were all over the world. Now, any woodworker anywhere in the world can tell you that orange tools means CMT, and that CMT means quality. Here at CMT we know we produce quality. You should too. That's why we have trademarked the color orange on woodworking tools - it's your guarantee that you are getting a genuine high-quality CMT product.



Loading the automated multi-axis CNC sharpening machines.



Fully automated assembly and marking.

www.dahm.no



www.dahm.no



Saw Blades

PRODUCTS	PAGE
Multi-Rip Saw Blades	9~11
Building Contractors Saw Blades	11
Universal Saw Blades	12~14
Saw Blades for Melamine & Laminated	15~19
DP Saw Blades & Scoring	20
Panel Sizing Saw Blades	21
Scoring Saw Blades	22-23
Saw Blades for Aluminium & Non-Ferrous Materials	24-25
Saw Blades for Metal & Special Materials	26-27
ITK Plus Saw Blades	28~30
DP Saw Blades for Ultra-Hard Materials	31
Saw Blades for Portable Machines	31~34
Grooving Saw Blades	35~37
Saw Blade Accessories	37
Portable Machine Index	38-39
Saw Blade Index	40~46

www.dahm.no

HOW WE PRODUCE OUR HIGH QUALITY BLADES

CMT stands for quality, which means we put quality into everything we do. It only makes sense. At CMT we figure that if our router bits are going to be top quality, high-performance and orange, then our saw blades should be too. And to do that, we simply follow the same guidelines for our blades that we do for our bits: we start with a solid design, use only the best materials and manufacture with skill and care. And of course, make sure they are trademark orange.







DESIGN

The simplicity of a circular saw blade design is in reality a complexity of technical considerations. Each blade has to make a certain type of cut, and this requires careful analysis of hook and grind angles, gullet designs, to location of sound dampening slots and the thickness of the blade - just to name a few. So in order for us to get the best design for our blades - and for you to get the best performance from them - we use the same method that we use to engineer our router bits: we combine the knowledgeable minds and experience of our technical department and the latest computer technology. The result is a superior blade that has some rather special "standard" features:

Anti-vibration Design. The anti-vibration cuts in the blade do exactly what their name implies: they are the anti in anti-vibration. This translates into less chattering during cutting and consequently it lengthens the life of the blade. Anti-vibration also means a flawless cut, so stabilizers and scoring blades are no longer necessary.

Expansion Slots. These little hook-shaped cuts in the blade help to reduce noise while regulating the expansion and contraction of the blade as it generates heat during cutting operations.



MATERIALS

When it comes down to it, saw blades are much like router bits - it's just two components: steel and carbide. So in selecting the raw materials, we are every bit as picky with our saw blades as we are with our router bits. Besides, why mess with a winning formula like superior steel and tungsten carbide?

Steel. It's the heart of the blade, so CMT uses only the finest steel available: super 42-44 Rockwell hardness steel.

Carbide. The cutting tips of every CMT blade are made from the best grades of micrograin carbide.

MANUFACTURING

CMT saw blades are machined on automated CNC machines, from start to finish. The advanced technology and precision of these machines ensures uniform quality on every blade while giving us the possibility to carry out more efficient quality controls.

Laser Cutting. The steel plate of the blade is laser cut, NEVER die cut, from superior strength steel. This way of cutting steel is not only extremely precise but it makes it possible to cut harder strengths of steel and does not stress the plate while cutting, so the resulting blade is flat and true and more resistant to warping.

Grinding & Tensioning. After it has been cut, the blade is polished and tensioned, the evidence of which can be seen in the superior finish and a tension ring that are visible on the blade. Then the central bore is ground to a smooth finish so that the blade will fit precisely on the saw arbor and will have perfect concentricity during rotation. The seats for the carbide teeth are also ground, making sure that the carbide tips fit perfectly, providing the right conditions for making a secure braze.

www.dahm.no






Silver-Copper-Silver Sandwich Brazing. Once again, experience has been a good teacher. Automated brazing with a special silver-copper-silver "sandwich" brazing compound yields excellent results and reduces the chances of failed welds. In addition, this combination of metals is critical during brazing because as the steel body and the carbide tipped teeth are heated and cooled, they expand and contract at different rates.

The copper layer acts as a buffer and keeps the carbide from cracking during cool down shrinkage.

When woodworking, the copper provides flexibility and resistance to impact which in turn protects the carbide tips and steel shoulders when cutting through harder substances or knots in the wood.

Specially Formulated Carbide Tips. What is true for router bit carbide tips is also true for the carbide tips on saw blades: what's good for one type of blade may not be good for another.

At CMT, we have studied carbide formulas and their impact on blade performance and have developed specially formulated carbide tips to match each blade's application. Larger blades require an extra-fine harder carbide that holds its edge and resharpens easily, while smaller blades need a special carbide that can withstand the occasional nail or imperfections that often occur in construction work.

For each blade and each use, there is carbide made especially for it.

Sharpening & Laser Marking. The final step is sharpening the micrograin carbide teeth. During the sharpening phase, each angle is ground to razor-sharp precision - down to the Milacron - on multi-axis CNC machines.

We also laser mark our blades so you have all the details about the blade type and its uses, right there on the blade.


Quality Control. We always manually check the quality of our blades at each step of the manufacturing process. However, now we also use a fully automatic measuring process that measures every dimension of the blades without actually coming into contact with it.



CMT's fully automatic measuring system.

Packaging & Instructions. CMT blades are packed and protected for shipping, display and storage in either a sturdy cardboard box or in a patented heavy duty HDPE plastic case that's as durable as our tools. Illustrated instructions for resharpening are included with your CMT blade so that you have all the details you need to keep the blade sharp, which will also help you extend the life of the blade.





CMT ORANGE TOOLS. *Manufacturers of high quality woodworking tools since 1962, we are still proud to put "Made in Italy" on all our orange tools.*

www.dahm.no

Maximizing Saw Performance

CMT ORANGE TOOLS™

BLADE'S RANGE	ORANGE CHROME	INDUSTRIAL / XTREME	ITK PLUS	CONTRACTOR
PERFORMANCE	SUPERIOR ★★★★★	BEST ★★★★	BETTER ★★★	GOOD ★★
DESCRIPTION	Designed for professional woodworkers who require high precision and durability from their saw blades. Special chrome carbide reduces tooth abrasion, whereas the chrome plated body protects against rust, corrosion and guarantees long-lasting performance. 	Designed for fine woodworkers, finish carpenters, construction and industrial users who run their blades all day long demanding ultimate precision and extended life, while conquering the most challenging applications. 	Designed for the professional contractor and remodeler, CMT's ITK Plus delivers a clean, fast, effortless cut through wood and wood composite material. With a nice balance of features to price the ITK Plus line as a great value. 	Designed for the contractor and remodeler CMT's Contractor thin-kerf blade line delivers solid performance at a very economical price. Ideal for any construction projects that require cutting wood and wood composite material. 
USER	Professional Woodworker	Professional	Contractor & Remodeler	Contractor & Remodeler
USAGE	Run All Day	Run All Day	Daily Use	Daily Use
PRICE POINT	Premium	Premium	Mid	Value
MATERIALS	Wood, plywood, OSB, laminate, melamine, mouldings, MDF.	Wood, Wood with nails, Plywood, OSB, Laminate, Melamine, MDF, Non-Ferrous, Metals, Stainless Steel, Plastics, Fiberglass, Solid Surface.	Wood, Composite Decking, Plywood, OSB, Laminate, Melamine, MDF, Fibercement.	Wood, Composite Decking, Plywood, OSB, Laminate, Melamine, MDF.
STEEL PLATE	LASER-CUT PREMIUM QUALITY STEEL PLATE Made of 46-48 HRC precision German steel which is laser-cut to provide tighter tolerances ensuring longer life and more accurate cuts.	LASER-CUT PREMIUM QUALITY STEEL PLATE Made of 46-48 HRC precision German steel which is laser-cut to provide tighter tolerances ensuring longer life and more accurate cuts.	HEAVY-DUTY LASER-CUT PLATE Made of a thin & strong plate, laser cut from the finest steel which is then hardened to 44 HRC to ensure a longer life and more accurate cuts.	HEAVY-DUTY STAMPED DIE CUT PLATE Made of a thin & strong plate cut from the finest steel which is then hardened to 44 HRC to ensure a longer life and more accurate cuts.
CARBIDE TEETH	INDUSTRIAL CHROMIUM MICROGRAIN CARBIDE Cutting teeth are made from a specially formulated chromium micrograin carbide which stays sharper longer by reducing cutting edge abrasion, improving cut quality and tool life.	INDUSTRIAL CHROMIUM MICROGRAIN CARBIDE Special formulated chromium micrograin carbide which stays sharper longer by reducing cutting edge abrasion, improving cut quality and tool life.	INDUSTRIAL SINTERHIP HI-DENSITY CARBIDE™ The new process SinterHIP (high temperature 1025°C and high pressure 105 bar) creates a porosity-free and Hi-Density carbide which provides a longer cutting life than traditional carbide.	LONG LASTING CONSTRUCTION GRADE CARBIDE A specially formulated construction grade carbide which provides a longer cutting life and great resistance to impact.
KERF	THICK	FULL KERF	THIN-KERF	THIN-KERF
BRAZING	TRI-METAL BRAZING The Silver-Copper-Silver tri-metal brazing process lets the teeth withstand the severe impact caused by cutting harder woods and composite material.	TRI-METAL BRAZING The Silver-Copper-Silver tri-metal brazing process lets the teeth withstand the severe impact caused by cutting harder woods and composite material.	SILVER BRAZING The silver brazing process lets the teeth withstand the standard impact caused by cutting soft woods and composite material.	SILVER BRAZING The silver brazing process lets the teeth withstand the standard impact caused by cutting soft woods and composite material.
COATING	CHROME COATING Blade plate is covered with a chrome layer to protect your tool against corrosion and rust, guaranteeing a longer tool life.	HARD LACQUER Protects against corrosion and rust.	NON-STICK ORANGE SHIELD COATING Keeps the blade running cool, reduces pitch build up and protects against corrosion. Ideal for all types of wood including wet lumber.	HARD LACQUER Protects against corrosion and rust.
EXPANSION SLOTS	LASER-CUT HEAT EXPANSION SLOTS Are engineered to allow the blade to expand when heat build-up occurs from use, preventing blade warping.	LASER-CUT HEAT EXPANSION SLOTS Are engineered to allow the blade to expand when heat build-up occurs from use, preventing blade warping.	LASER-CUT HEAT EXPANSION SLOTS Are engineered to allow the blade to expand when heat build-up occurs from use, preventing blade warping.	HEAT EXPANSION SLOTS Are engineered to allow the blade to expand when heat build-up occurs from use, preventing blade warping.
SOUND DAMPENING CHANNELS	LASER-CUT SLOTS FILLED WITH SOUND-DAMPENING MATERIAL Slots are filled with polyurethane to reduce vibrations and noise (10% less than standard saw blades), improving cut quality and blade life.	LASER-CUT SOUND-DAMPENING CHANNELS Are specifically designed to dampen running noise and control wobbling caused by unwanted harmonic vibration.	LASER-CUT SOUND-DAMPENING CHANNELS Are specifically designed to dampen running noise and control wobbling caused by unwanted harmonic vibration.	✕
TENSIONING RINGS	TENSIONING RING A visible tension ring on the blade body provides stability during cut and perfect concentricity during rotation.	TENSIONING RING A visible tension ring on the blade body provides stability during cut and perfect concentricity during rotation.	✕	✕
SHARPENING	PRECISION MIRROR FINISH SHARPENING Each tooth is ground to razor sharp precision on a multi-axis CNC machine which creates the perfect edge angles, guaranteeing extra-clean cuts and extended life. Featuring less than 0.25 µm Rmax in edge roughness.	PRECISION MIRROR FINISH SHARPENING Each tooth is ground to razor sharp precision on a multi-axis CNC machine which creates the perfect edge angles, guaranteeing extra-clean cuts and extended life. Featuring less than 0.25 µm Rmax in edge roughness.	SHEAR ANGLE SHARPENING The shear angle grind on the teeth's front face produces smooth cuts, while reducing the cutting force needed and improving cutting speed, setting a new standard for performance.	STANDARD SHARPENING Each tooth is sharpened with accuracy and control to guarantee clean cuts and longer lifetime.

www.dahm.no


Multi-Rip Saw Blades with Rakers *Industrial Line*





279

HW MEC

Application: for rip cuts where the rakers prevent the wood contact with the steel plate.
Machines: multi-rip machines with one or two shafts.
Material: (wet or dry) soft and hardwood.









D mm	B mm	Key way	Z	K mm	P mm	H mm	α	β	ORDER NO.
250	30		20+4	3,2	2,2	65	18°	10° ATB	**279.020.10M**
250	70	21 x 5	20+4	3,2	2,2	65	18°	10° ATB	**279.020.10V**
250	80	13 x 5	20+4	3,2	2,2	65	18°	10° ATB	**279.020.10W**
300	30		24+4	3,2	2,2	80	18°	10° ATB	**279.024.12M**
300	60	21 x 5	24+4	3,2	2,2	80	18°	10° ATB	**279.024.12U**
300	70	21 x 5	24+4	3,2	2,2	80	18°	10° ATB	**279.024.12V**
300	80	13 x 5	24+4	3,2	2,2	80	18°	10° ATB	**279.024.12W**
350	30		28+4	3,5	2,5	105	18°	10° ATB	**279.028.14M**
350	60	21 x 5	28+4	3,5	2,5	105	18°	10° ATB	**279.028.14U**
350	70	21 x 5	28+4	3,5	2,5	105	18°	10° ATB	**279.028.14V**
350	80	14 x 5	28+4	3,5	2,5	105	18°	10° ATB	**279.028.14W**
400	30		28+6	4,0	2,8	120	18°	10° ATB	**279.028.16M**
400	70	21 x 5	28+6	4,0	2,8	120	18°	10° ATB	**279.028.16V**


Multi-Rip Anti-Kickback Saw Blades *Industrial Line*




278

HW

Application: for rip cuts where the special steel plate prevents vibrations during work
Machines: multi-rip machines with one or two shafts.
Material: dry, soft and hardwood.







D mm	B mm	Pin Hole	Key way	Z	K mm	P mm	α	β	ORDER NO.
300	30	2/10/60		28	3,2	2,2	18°	10° ATB	**278.028.12M**
300	70		21 x 5	28	3,2	2,2	18°	10° ATB	**278.028.12V**
350	30	2/10/60		36	3,5	2,5	18°	10° ATB	**278.036.14M**
350	70		21 x 5	36	3,5	2,5	18°	10° ATB	**278.036.14V**

www.dahm.no

Thin-Kerf Multi-Rip Saw Blades with Rakers *Industrial Line*


CMT ORANGE TOOLS





280

HW MEC

Application: for rip cuts where the thin-kerf reduces material wastes.
Machines: multi-rip machines with one or two shafts.
Material: wet or dry hardwood.









D mm	B mm	Key way	Z	K mm	P mm	H mm	α	β	ORDER NO.
180	40		21+3	2,5	1,8	30	18°	FLAT	**280.021.07S**
200	40		21+3	2,5	1,8	35	18°	FLAT	**280.021.08S**
250	70	21 x 5	20+4	2,7	1,8	50	18°	10° ATB	**280.020.10V**
250	80	13 x 5	20+4	2,7	1,8	50	18°	10° ATB	**280.020.10W**
300	70	21 x 5	24+4	2,7	1,8	60	18°	10° ATB	**280.024.12V**
300	80	13 x 5	24+4	2,7	1,8	60	18°	10° ATB	**280.024.12W**


Thick-Kerf Multi-Rip Saw Blades with Rakers *Industrial Line*





277

HW MEC

Application: for rip cuts. Mounted on the sides of gang rip saws, these act as shoulder saw blades and help ensure stability and reduce vibrations under extreme work load.
Machines: multi-rip machines with one or two shafts.
Material: thick wet or dry hardwood.









D mm	B mm	Key way	Z	K mm	P mm	H mm	α	β	ORDER NO.
300	30		24+4	4,0	2,8	80	18°	10° ATB	**277.024.12M**
300	70	21 x 5	24+4	4,0	2,8	80	18°	10° ATB	**277.024.12V**
300	80	13 x 5	24+4	4,0	2,8	80	18°	10° ATB	**277.024.12W**
350	30		24+6	4,2	2,8	105	18°	10° ATB	**277.024.14M**
350	70	21 x 5	24+6	4,2	2,8	105	18°	10° ATB	**277.024.14V**

www.dahm.no

CMT ORANGE TOOLS™





286

HW


Application: for rip and crosscuts especially designed for building contractors.
Machines: table saws and portable machines.
Material: soft and hardwood, panels with nails, metal clips and pieces of concrete.







EXCELLENT — Soft Wood with Nails, Screw, Concrete, etc.



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	16	2,8	1,8	15°	5° ATB	**286.016.10M**
300	30	COMBI3	20	2,8	1,8	15°	5° ATB	**286.020.12M**
new 300*	30	COMBI3	48	3,2	2,2	15°	10° ATB	**286.048.12M**
315	30	COMBI3	24	3,2	2,2	15°	5° ATB	**286.024.13M**
350	30	COMBI3	24	3,2	2,2	15°	5° ATB	**286.024.14M**
400	30	COMBI3	28	3,2	2,2	15°	5° ATB	**286.028.16M**
450	30	2/10/60	32	3,8	2,8	15°	5° ATB	**286.032.18M**
500	30	2/10/60	36	3,8	2,8	15°	5° ATB	**286.036.20M**
550	30	2/10/60	40	4,2	3,2	15°	5° ATB	**286.040.22M**
600	30	2/10/60	40	4,2	3,2	15°	5° ATB	**286.040.24M**
700	30	2/10/60	46	4,4	3,2	15°	5° ATB	**286.046.28M**

Shop tips: Use our reduction ring from 30 to 25mm order n. 299.225.00 (for rip saw blades Ø250-300-315)
Use our reduction ring from 30 to 25mm order n. 299.228.00 (for rip saw blades Ø350 and larger)

without limiter

Rip Saw Blades *Industrial Line*




285-290-293


HW


Application: for rip and glue line rip cuts.
Machines: table and special saws, portable and ripping machines for automatic or manual feeding.
Material: soft and hardwood.












EXCELLENT — Rip Wood



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	24	2,8	1,8	20°	10° ATB	**290.250.24M**
270	30	2/7/42	28	2,8	1,8	20°	10° ATB	**290.270.28M**
300	30	COMBI3	24	3,2	2,2	20°	10° ATB	**293.024.12M**
300	35		24	3,2	2,2	20°	10° ATB	**293.024.12R**
305	30	2/10/60	28	2,8	1,8	20°	10° ATB	**293.028.22M**
315	30	COMBI3	28	3,2	2,2	20°	10° ATB	**293.028.12M**
315	30	2/10/60 + 2/7/42	36	3,2	1,8	15°	5° ATB	**285.036.13M**
350	30	COMBI3	28	3,5	2,5	20°	10° ATB	**293.028.14M**
350	35		28	3,5	2,5	20°	10° ATB	**293.028.14R**
400	30	COMBI3	36	3,5	2,5	20°	10° ATB	**285.036.16M**
450	30	2/10/60	36	3,8	2,8	20°	10° ATB	**285.036.18M**
500	30	COMBI3	44	4,0	2,8	20°	10° ATB	**285.044.20M**

www.dahm.no

Rip & Crosscut Saw Blades *Industrial Line*


CMT ORANGE TOOLS





285-291-294


HW

Application: for optimal quality rip and crosscuts.
Machines: table and special saws, portable machines.
Material: soft and hardwood, wood-based panels.









D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
200	30	2/10/60 + 2/7/42	36	3,2	2,2	15°	10° ATB	**285.036.08M**
200	30	2/10/60 + 2/7/42	48	3,2	2,2	15°	15° ATB	**285.048.08M**
250*	20	COMBI3	40	3,2	2,2	15°	10° ATB	**285.040.10H**
250	30	COMBI3	40	3,2	2,2	15°	10° ATB	**285.040.10M**
250	30	COMBI3	48	3,2	2,2	15°	10° ATB	**285.048.10M**
250	30	COMBI3	60	3,2	2,2	10°	15° ATB	**285.060.10M**
250	35		40	3,2	2,2	15°	10° ATB	**285.040.10R**
250	35		60	3,2	2,2	10°	15° ATB	**285.060.10R**
254	30	COMBI3	48	2,4	1,8	- 5° Neg.	15° ATB	**294.048.10M**
254	30	COMBI3	60	2,4	1,8	- 5° Neg.	15° ATB	**294.060.10M**
260	30	2/10/60 + 2/7/42	48	2,8	1,8	15°	10° ATB	**285.048.11M**
260	30	2/10/60 + 2/7/42	60	2,8	1,8	10°	15° ATB	**285.060.11M**
260	30	COMBI3	60	2,5	1,8	- 5° Neg.	15° ATB	**294.060.11M**
270*	30	2/7/42	42	2,8	1,8	15°	15° ATB	**291.270.42M**
275	20		42	3,2	2,2	15°	10° ATB	**285.042.11H**
280*	30	2/10/60 + 2/7/42	64	2,8	1,8	10°	15° ATB	**295.064.11M**
300*	20	COMBI3	48	3,2	2,2	15°	10° ATB	**285.048.12H**
300	30	COMBI3	36	3,2	2,2	15°	10° ATB	**285.036.12M**
300	30	COMBI3	48	3,2	2,2	15°	10° ATB	**285.048.12M**
300	30	COMBI3	60	3,2	2,2	15°	10° ATB	**285.060.12M**
300	30	COMBI3	72	3,2	2,2	10°	15° ATB	**285.072.12M**
300	35		48	3,2	2,2	15°	10° ATB	**285.048.12R**
300	35		72	3,2	2,2	10°	15° ATB	**285.072.12R**
305*	30	2/10/60 + 2/7/42	54	2,8	1,8	-5° Neg.	15° ATB	**294.054.22M**
315*	30	COMBI3	54	3,2	2,2	15°	10° ATB	**294.054.12M**
350	30	COMBI3	54	3,5	2,5	15°	10° ATB	**285.054.14M**
350	30	COMBI3	72	3,5	2,5	15°	10° ATB	**285.072.14M**
350	30	COMBI3	84	3,5	2,5	10°	15° ATB	**285.084.14M**
350	35		54	3,5	2,5	15°	10° ATB	**285.054.14R**
350	35		84	3,5	2,5	10°	15° ATB	**285.084.14R**
400	30	COMBI3	48	3,5	2,5	20°	10° ATB	**285.048.16M**
400	30	COMBI3	60	3,5	2,5	10°	15° ATB	**285.060.16M**
450	30	2/10/60	54	3,8	2,8	15°	15° ATB	**285.054.18M**
450	30	2/10/60	66	3,8	2,8	10°	15° ATB	**285.066.18M**
500	30	2/10/60	60	3,8	2,8	15°	15° ATB	**285.060.20M**
500	30	2/10/60	72	3,8	2,8	10°	15° ATB	**285.072.20M**
550	30	2/10/60	60	4,2	3,2	10°	15° ATB	**285.060.22M**
550	30	2/10/60	96	4,2	3,2	10°	15° ATB	**285.096.22M**
600	30	2/10/60	66	4,2	3,2	10°	15° ATB	**285.066.24M**
700	30	2/10/60	72	4,4	3,2	10°	15° ATB	**285.072.28M**

*Non-low noise


www.dahm.no



285-294


HW

Application: for optimal quality crosscuts.
Machines: table and sizing saws, portable machines.
Material: soft, hard and exotic wood, wood-based panels.




EXCELLENT

Two-Sided Melamine




Plywood





GOOD

Rip Wood




Cross Wood





HV10: 1.950
N/mm²: 2.300



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
150	30	2/7/42	48	3,2	2,2	5°	15° ATB	**285.048.06M**
160	20	2/6/32	48	2,2	1,6	5°	15° ATB	**285.160.48H**
180	30	2/7/42	56	3,2	2,2	5°	15° ATB	**285.056.07M**
200	30	2/10/60 + 2/7/42	64	3,2	2,2	5°	15° ATB	**285.064.08M**
250	30	COMBI3	80	3,2	2,2	5°	15° ATB	**285.080.10M**
250	35		80	3,2	2,2	5°	15° ATB	**285.080.10R**
300	30	COMBI3	96	3,2	2,2	5°	15° ATB	**285.096.12M**
300	35		96	3,2	2,2	5°	15° ATB	**285.096.12R**
305	30	COMBI3	72	3,2	2,2	10°	15° ATB	**285.072.22M**
305	30	COMBI3	72	3,2	2,2	-5° Neg.	15° ATB	**294.072.22M**
315	30	2/10/60 + 2/7/42	72	3,2	2,2	10°	15° ATB	**285.072.13M**
350	30	COMBI3	108	3,5	2,5	5°	15° ATB	**285.108.14M**
350	35		108	3,5	2,5	5°	15° ATB	**285.108.14R**
400	30	COMBI3	96	3,5	2,5	10°	15° ATB	**285.096.16M**
400	30	2/10/60 + 2/7/42	120	3,5	2,5	10°	15° ATB	**285.120.16M**

Super Finishing Saw Blades for Cutting Frames *XTreme Line*





285.5 XTREME

HW

Application: for optimal quality crosscuts on moulds and end trimming for perfect joints.
Machines: table and sizing saws, single or double mitre saws.
Material: soft and hardwood, MDF.


Double side grind







EXCELLENT

Wooden Frames
MDF & PVC





HV10: 1.950
N/mm²: 2.300



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	80	3,0	2,5	10°	20° ATB	**285.580.10M**
300	30	COMBI3	96	3,0	2,5	10°	20° ATB	**285.596.12M**

■ Orange PTFE coated blades: a great choice for the shop that keeps its blades running all day, every day. With their heavy-gauge plate, these blades have the stamina for saws with lots of power.

www.dahm.no


Low Noise & Chrome Coated Saw Blades with ATB Grind


CMT ORANGE TOOLS™


HW

285 ORANGE CHROME™











Application: for optimal quality rip and crosscuts.
Machines: table and special saws, portable machines.
Material: soft and hardwood, wood-based panels.




HV10: 1.870
N/mm²: 2.200

GOOD




D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	40	3,2	2,2	15°	10° ATB	**285.640.10M**
300	30	COMBI3	48	3,2	2,2	15°	10° ATB	**285.648.12M**
350	30	COMBI3	54	3,5	2,5	15°	10° ATB	**285.654.14M**
new 400	30	COMBI3	60	3,5	2,5	10°	15° ATB	**285.660.16M**

Application: for optimal quality crosscuts.
Machines: table and sizing saws, portable machines.
Material: soft, hard and exotic wood, wood-based panels.




HV10: 1.930
N/mm²: 2.300

EXCELLENT




D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	60	3,2	2,2	10°	15° ATB	**285.660.10M**
300	30	COMBI3	72	3,2	2,2	10°	15° ATB	**285.672.12M**
350	30	COMBI3	84	3,5	2,5	10°	15° ATB	**285.684.14M**
new 400	30	COMBI3	96	3,5	2,5	10°	15° ATB	**285.696.16M**

Application: for high-quality cross cutting.
Machines: table and sizing saws, portable machines.
Material: soft, hard and exotic wood, wood-based panels, one-sided veneer, paper-base laminates and thermoplastic material.



HV10: 1.930
N/mm²: 2.300

EXCELLENT



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	80	3,2	2,2	5°	15° ATB	**285.680.10M**
300	30	COMBI3	96	3,2	2,2	5°	15° ATB	**285.696.12M**
350	30	COMBI3	108	3,5	2,5	5°	15° ATB	**285.708.14M**

www.dahm.no

Fine Cut-Off Saw Blades for Two-Sided Melamine *Industrial Line*




283


HW

Application: for sizing cuts, perfect finishing on both sizes of double-sided panels without using scoring blades.

Machines: table and vertical saws, sizing and portable machines.


Material: single or double-sided laminated panels with coating and veneer.







HV10:	1.950
N/mm²:	2.300







EXCELLENT



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
220*	30	2/7/42	64	3,2	2,2	-5°	40° ATB	**283.064.09M**
250	30	COMBI3	80	3,2	2,2	-2°	40° ATB	**283.080.10M**
300	30	COMBI3	96	3,2	2,2	2°	40° ATB	**283.096.12M**
350	30	COMBI3	108	3,5	2,5	5°	40° ATB	**283.108.14M**

*Non-low noise

Fine Cut-Off Saw Blades for Two-Sided Melamine *Industrial Line*

new




283 ORANGE CHROME™


HW LONG LIFE

Application: for sizing cuts, perfect finishing on both sizes of double-sided panels without using scoring blades.


Machines: table and vertical saws, sizing and portable machines.

Material: single or double-sided laminated panels with coating and veneered panels.






HV10:	2.150
N/mm²:	2.500



EXCELLENT



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	80	3,2	2,2	-2°	38° ATB	**283.680.10M**
300	30	COMBI3	96	3,2	2,2	2°	38° ATB	**283.696.12M**

www.dahm.no

Super Fine Finishing Blade *XTreme Line*


CMT ORANGE TOOLS




274 XTREME

HW


Application: for high-quality cross cutting.
Machines: table and sizing saws, portable machines.
Material: soft, hard and exotic wood, wood-based panels, one-sided veneered panels, paper-based laminate and thermoplastic material.




Max run out tolerance 0,05mm







EXCELLENT



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	80	3,2	2,2	15°	1FTG+4ATB	**274.080.10M**
300	30	COMBI3	100	3,2	2,2	15°	1FTG+4ATB	**274.100.12M**


Fine Cut-Off Saw Blades for Two-Sided Melamine *Industrial Line*





287

HW


Application: for sizing cuts, perfect finishing with high feed rate and long tool life without using scoring blade.
Machines: table and vertical saws, sizing and portable machines.
Material: single or double-sided laminated panels with hard coating and veneered panels.







EXCELLENT



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
Negative Hook Angle								
220	30	2/7/42	42	3,2	2,2	-6°	HDF	**287.043.09M**
250	30	COMBI3	48	3,2	2,2	-6°	HDF	**287.049.10M**
303	30	COMBI3	60	3,2	2,2	-6°	HDF	**287.061.12M**

www.dahm.no

Fine Cut-Off Saw Blades for Two-Sided Melamine *Industrial Line*

new

CMT ORANGE TOOLS™




287 ORANGE CHROME™


HW LONG LIFE


Application: for sizing cuts, perfect finishing with high feed rate and long tool life without using scoring blade.


Machines: table and vertical saws, sizing and portable machines.

Material: single or double-sided laminated panels with hard coating and veneered panels.









D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
Positive Hook Angle								
250	30	COMBI3	48	3,2	2,2	10°	HDF	**287.648.10M**
303	30	COMBI3	60	3,2	2,2	10°	HDF	**287.660.12M**

Fine Cut-Off Saw Blades for Two-Sided Melamine *Industrial Line*




287


HW


Application: for sizing cuts, perfect finishing with high feed rate and long tool life without using scoring blade.

Machines: table and vertical saws, sizing and portable machines.

Material: single or double-sided laminated panels with hard coating and veneered panels.







D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
Positive Hook Angle								
160	20	2/6/32	34	2,6	1,8	10°	HDF	**287.034.06H**
220	30	2/7/42	42	3,2	2,2	10°	HDF	**287.042.09M**
250	30	COMBI3	48	3,2	2,2	10°	HDF	**287.048.10M**
303	30	COMBI3	60	3,2	2,2	10°	HDF	**287.060.12M**

www.dahm.no

Low Noise & Chrome Coated Saw Blades with TCG Grind


CMT ORANGE TOOLS™




281 ORANGE CHROME™


HW LONG LIFE


Application: for sizing cuts, perfect finishing with scoring blades.
Machines: table saws, horizontal and vertical sizing machines.
Material: single or double-sided plastic-laminated panels.














D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	80	3,2	2,2	5°	TCG	**281.680.10M**
300	30	COMBI3	72	3,2	2,2	10°	TCG	**281.672.12M**
300	30	COMBI3	96	3,2	2,2	5°	TCG	**281.696.12M**
new 350	30	COMBI3	84	3,5	2,5	10°	TCG	**281.684.14M**
350	30	COMBI3	108	3,5	2,5	5°	TCG	**281.708.14M**


Melamine & Laminated Long-Lasting Saw Blades *XTreme Line*




295 XTREME

HW LONG LIFE


Application: for sizing cuts, perfect finishing without using scoring blade.
Machines: table saws, horizontal and vertical sizing machines.
Material: double-sided laminated panels.




Max run out tolerance 0,05mm









D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	78	3,2	2,2	10°	FFT	**295.078.10M**
300	30	COMBI3	96	3,2	2,2	10°	FFT	**295.096.12M**
350	30	COMBI3	108	3,5	2,5	10°	FFT	**295.108.14M**


www.dahm.no




281

HW


Application: for sizing cuts, perfect finishing by using scoring blades.
Machines: table saws, horizontal and vertical sizing machines.
Material: single or double-sided plastic-laminated panels.








HV10: 1.950
N/mm²: 2.300




EXCELLENT

Two-Sided Melamine



Crosscut Plywood



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
160	20 (Virutex)	4/7/32 45°	40	2,2	1,6	10°	TCG	**281.160.40H**
160*	20	2/6/32	40	2,2	1,6	10°	TCG	**281.160.40H2**
200*	30	2/7/42	64	3,2	2,2	10°	TCG	**281.064.08M**
220*	30	2/7/42	64	3,2	2,2	10°	TCG	**281.064.09M**
250	30	COMBI3	60	3,2	2,2	10°	TCG	**281.060.10M**
250	30	COMBI3	80	3,2	2,2	10°	TCG	**281.080.10M**
300	30	COMBI3	72	3,2	2,2	10°	TCG	**281.072.12M**
300	30	COMBI3	96	3,2	2,2	10°	TCG	**281.096.12M**
350	30	COMBI3	84	3,5	2,5	10°	TCG	**281.084.14M**
350	30	COMBI3	108	3,5	2,5	10°	TCG	**281.108.14M**


*Non-low noise




281 XTREME


HW LONG LIFE


Application: for sizing cuts, perfect finishing without using scoring blade.
Machines: table saws, horizontal and vertical sizing machines.
Material: single or double-sided laminated panels.






HV10: 1.950
N/mm²: 2.300









EXCELLENT

Two-Sided Melamine



Plywood



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
220	30	COMBI3	63	3,2	2,2	-3°	FFT	**281.063.09M**
250	30	COMBI3	60	3,2	2,2	-3°	FFT	**281.061.10M**
250	30	COMBI3	81	3,2	2,2	-3°	FFT	**281.081.10M**
300	30	COMBI3	72	3,2	2,2	-3°	FFT	**281.073.12M**
300	30	COMBI3	96	3,2	2,2	-3°	FFT	**281.097.12M**

www.dahm.no

DP Laminated & Chipboard Saw Blades *XTreme Line*

CMT ORANGE TOOLS



237 XTREME


DP LONG LIFE


APPLICATION: for sizing cuts, perfect finishing (using scoring blade) and increased tool life up to 50 times longer than HW blades thanks to a special polycrystalline diamond formula. The best quality/price ratio!

MACHINES: table saws, horizontal and vertical sizing machines.


MATERIAL: single or double-sided plastic-laminated panels, MDF and HDF.

50X LONGER LIFE THAN CARBIDE





EXCELLENT



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	48	3,2	2,2	10°	45° TCG	**237.048.10M**
300	30	COMBI3	60	3,2	2,2	10°	45° TCG	**237.060.12M**
300	30	COMBI3	96	3,2	2,2	15°	45° TCG	**237.096.12M**
350	30	COMBI3	72	3,5	2,4	15°	45° TCG	**237.072.14M**

High-quality nickel-plated saw blades with anti-friction and anti-corrosion properties.

DP Conical Scoring Blades *XTreme Line*



238 XTREME


DP LONG LIFE


APPLICATION: for chip-free scoring of plastic-laminated panels; increased tool life up to 50 times longer than HW blades thanks to a special polycrystalline diamond formula. The best quality/price ratio!

MACHINES: horizontal and vertical sizing machines equipped with scoring device.


MATERIAL: single or double-sided plastic-laminated panels, MDF and HDF.

50X LONGER LIFE THAN CARBIDE





EXCELLENT



D mm	B mm		Z	K mm		α	β	ORDER NO.
120	20		20	3,1-3,7		5°	CONICAL	**238.120.20H**
125	20		20	3,1-3,7		5°	CONICAL	**238.125.20H**

High-quality nickel-plated saw blades with anti-friction and anti-corrosion properties.


www.dahm.no




281-282


HW LONG LIFE

APPLICATION: for sizing single sheets and multiple panels.
MACHINES: horizontal panel sizing machines.
MATERIAL: single or double-sided plastic-laminated panels, MDF.







HV10: 2.150
N/mm²: 2.500




EXCELLENT — Two-Sided Melamine




D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	Low Noise	ORDER NO.
250	30	COMBI3	60	3,2	2,2	10°	TCG		**281.060.10M**
250	30	COMBI3	80	3,2	2,2	10°	TCG		**281.080.10M**
300	30	COMBI3	60	4,4	3,2	16°	TCG		**282.060.12M**
300	30	COMBI3	72	3,2	2,2	10°	TCG		**281.072.12M**
300	30	COMBI3	96	3,2	2,2	10°	TCG		**281.096.12M**
300	75		60	4,4	3,2	16°	TCG		**282.060.12X**
300	80	COMBI5	60	4,4	3,2	16°	TCG		**282.060.12W**
320	65	2/9/100 + 2/9/110	60	4,4	3,2	16°	TCG		**Y282.060.13J**
new 320	65	2/9/100 + 2/9/110	72	4,4	3,2	16°	TCG		**282.072.13J**
350	30	COMBI3	54	4,4	3,2	16°	TCG		**282.054.14M**
350	30	COMBI3	72	4,4	3,2	16°	TCG		**282.072.14M**
350	30	COMBI3	108	3,5	2,5	10°	TCG		**281.108.14M**
350	50	3/12,5/80	72	4,4	3,2	16°	TCG		**282.072.14T**
350	60	2/14/100	72	4,4	3,2	16°	TCG		**Y282.072.14U**
350	75	4/15/105 + 3/7/100	54	4,4	3,2	16°	TCG		**282.054.14X**
350	75	4/15/105 + 3/7/100	72	4,4	3,2	16°	TCG		**282.072.14X**
350	80	COMBI5	54	4,4	3,2	16°	TCG		**282.054.14W**
350	80	COMBI5	72	4,4	3,2	16°	TCG		**282.072.14W**
355	30	2/7/42 + 2/10/60	72	4,4	3,2	16°	TCG		**S282.03556**
new 355	65	COMBI5	72	4,4	3,2	16°	TCG		**282.072.14J2**
380	60	COMBI7	72	4,8	3,5	16°	TCG		**282.072.15U**
new 380	80	COMBI5	72	4,4	3,2	16°	TCG		**282.072.15W**
400	30	2/10/60	60	4,4	3,2	16°	TCG		**282.060.16M**
400	30	2/10/60	72	4,4	3,2	16°	TCG		**282.072.16M**
400	60	COMBI7	72	4,4	3,2	16°	TCG		**282.072.16U**
400	75	4/15/105	60	4,4	3,2	16°	TCG		**282.060.16X**
400	75	4/15/105	72	4,4	3,2	16°	TCG		**282.072.16X**
400	80	COMBI5	60	4,4	3,2	16°	TCG		**282.060.16W**
400	80	COMBI5	72	4,4	3,2	16°	TCG		**282.072.16W**
430	75	4 /15/105	72	4,4	3,2	16°	TCG		**282.072.17X**
430	80	COMBI5	72	4,4	3,2	16°	TCG		**282.072.17W2**
450	60	COMBI7	72	4,8	3,5	16°	TCG		**282.072.18U**
450	80	COMBI5	72	4,8	3,5	16°	TCG		**282.072.18W2**
500	60	COMBI7	72	4,8	3,5	16°	TCG		**282.072.20U**
500	80	COMBI5	72	4,8	3,5	16°	TCG		**Y282.072.20W**
550	100		72	5,2	3,5	16°	TCG		**282.072.22A**



COMBI3
2/7/42mm
2/9/46,4mm
2/10/60mm



COMBI5
2/7/110mm
2/8,4/130mm
2/14/110mm
4/9/100mm
4/19/120mm



COMBI7
2/10/80mm
1/11/85mm
2/11/115mm
2/11/148mm
2/14/100mm
2/14/125mm
2/19/120mm

www.dahm.no


Industrial Chrome-Coated Scoring Blades




288 ORANGE CHROME™

HW LONG LIFE

Application: for chip-free scoring on plastic-laminated panels.
Machines: horizontal and vertical sizing machines equipped with scoring device.
Material: single or double-sided plastic-laminated panels, MDF.





D mm	B mm		Z	K mm	P mm	α	β	ORDER NO.
120	20		24	3,1-4,3	2,2	0°	CO+6° ATB	**288.720.24H**
120	22		24	3,1-4,3	2,2	0°	CO+6° ATB	**288.720.24K**
125	20		24	3,1-4,3	2,2	0°	CO+6° ATB	**288.725.24H**


Conical Scoring Blades *Industrial Line*





288

HW LONG LIFE

Application: for chip-free scoring on plastic-laminated panels.
Machines: horizontal and vertical sizing machines equipped with scoring device for vertical adjustment.
Material: single or double-sided plastic-laminated panels, MDF.







D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
80	20		12	3,1-4,0	2,2	10°	CO+FTG	**S288.080.12H**
100	20		20	3,1-4,0	2,5	5°	CO+5° ATB	**288.100.20H**
100	22		20	3,1-4,0	2,5	5°	CO+5° ATB	**288.100.20K**
120	20		24	3,1-4,0	2,5	5°	CO+5° ATB	**288.120.24H**
120	20		24	3,4-4,2	2,5	5°	CO+5° ATB	**288.120.24H1**
120	22		24	3,1-4,0	2,5	5°	CO+5° ATB	**288.120.24K**
125	20		24	3,1-4,0	2,5	5°	CO+5° ATB	**288.125.24H**
125	20		24	3,4-4,2	2,5	5°	CO+5° ATB	**288.125.24H1**
125	20		24	4,3-5,5	3,2	10°	CO+FTG	**288.125.24H2**
125	22		24	3,1-4,0	2,5	5°	CO+5° ATB	**288.125.24K**
125	45		24	4,3-5,5	3,2	10°	CO+FTG	**288.125.24Q**
140	16	1/6/33	24	3,1-4,0	2,2	10°	CO+FTG	**Y288.140.24E**
150	45		36	4,3-5,5	3,2	10°	CO+FTG	**288.150.36Q**
160	45	3/11/70	36	4,3-5,5	3,2	10°	CO+FTG	**288.160.36Q**
160	55	3/7/66	36	4,3-5,5	3,2	10°	CO+FTG	**288.160.360**
160	55	3/7/66 + 3/6/84	36	4,7-6,0	3,5	10°	CO+FTG	**Y288.160.3602**
180	20		36	4,3-5,5	3,2	10°	CO+FTG	**Y288.180.36H**
180	30		36	4,3-5,5	3,2	10°	CO+FTG	**288.180.36M**
180	45		36	4,7-6,0	3,5	10°	CO+FTG	**288.180.36Q**
180	55		36	5,0-6,2	3,5	10°	CO+FTG	**288.180.360**
180	50	3/12,5/80	44	4,3-5,5	3,2	10°	CO+FTG	**288.180.44T**
200	20		36	4,3-5,5	3,2	10°	CO+FTG	**288.200.36H**
200	45		36	4,7-6,0	3,5	10°	CO+FTG	**288.200.36Q**
200	45		36	4,3-5,5	3,2	10°	CO+FTG	**Y288.200.36Q2**
200	65	2/9/100 + 2/9/110	36	4,3-5,5	3,2	10°	CO+FTG	**288.200.36J**
215	50	3/15/80	42	4,3-5,5	3,2	10°	CO+FTG	**288.215.42T**
300	50	3/15/80	48	4,3-5,5	3,2	10°	CO+FTG	**288.300.48T**
300	65	2/9/100 + 2/9/110	72	4,3-5,5	3,2	10°	CO+FTG	**288.300.72J**

www.dahm.no


Industrial Chrome-Coated Adjustable Blades





289 ORANGE CHROME™

HW LONG LIFE

APPLICATION: for chip-free scoring on plastic-laminated panels.
MACHINES: horizontal and vertical sizing machines equipped with scoring device.
MATERIAL: single or double-sided plastic-laminated panels, MDF.







D mm	B mm	Pin Hole	Z	K mm	α	β	ORDER NO.
120	20	2/4,2/42	12+12	2,8-3,6	11°	5° ATB	**289.720.24H**
120	22	2/4,2/42	12+12	2,8-3,6	11°	5° ATB	**289.720.24K**
125	20	2/4,2/42	12+12	2,8-3,6	11°	5° ATB	**289.725.24H**


Adjustable Scoring Blades *Industrial Line*





289

HW LONG LIFE

APPLICATION: for chip-free scoring on plastic-laminated panels.
MACHINES: horizontal and vertical sizing machines equipped with scoring device not allowing for cutting depth adjustment.
MATERIAL: single or double-sided plastic-laminated panels, MDF.







D mm	B mm	Pin Hole	Z	K mm	α	β	ORDER NO.	Spare parts PVC SHIMS
70	20	2/3,1 - 3,8/32	8+8	2,8-3,6	12°	FLAT	**289.070.16H**	299.000.05H
80	20	2/3,1 - 3,8/42	10+10	2,8-3,6	12°	FLAT	**289.080.20H**	299.000.06H
100	20	2/3,1 - 3,8/42	10+10	2,8-3,6	12°	FLAT	**289.100.20H**	299.000.02K
100	22	2/3,1 - 3,8/42	10+10	2,8-3,6	12°	FLAT	**289.100.20K**	299.000.02K
120	20	2/3,1 - 3,8/42	12+12	2,8-3,6	12°	FLAT	**289.120.24H**	299.000.02K
120	22	2/3,1 - 3,8/42	12+12	2,8-3,6	12°	FLAT	**289.120.24K**	299.000.02K
120	50	4/6,2 - 10/62	12+12	2,8-3,6	12°	FLAT	**289.120.24T**	
125	20	2/3,1 - 3,8/42	12+12	2,8-3,6	12°	FLAT	**289.125.24H**	299.000.02K
125	22	2/3,1 - 3,8/42	12+12	2,8-3,6	12°	FLAT	**289.125.24K**	299.000.02K

www.dahm.no

Non-Ferrous Metal & Plastic Material Saw Blades *Industrial Line*


CMT ORANGE TOOLS





284

HW

Application: for cutting and dividing tubes, wire drawn products and solid blocks.
Machines: table saws, single or double mitre saws with mechanical clamping of the workpiece.
Material: aluminium, brass, copper alloys, plastic, composite materials.
Warning: it is recommended to properly clamp the workpiece during cutting operations and to use a liquid lubricant.
Wax sticks are NOT RECOMMENDED.







Saw Blades for Portable Machines. Positive Hook Angle


D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
160	20	-	24	2,2	1,6	5°	TCG	**284.160.24H**
190	30	-	30	2,6	2,2	5°	TCG	**284.190.30M**
216	30	2/7/42	40	2,6	2,2	5°	TCG	**284.216.40M**


Remarks: in plastic carrying case.

Saw Blades for Industrial Machines. Positive Hook Angle

D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	32	2/12/64	80	3,2	2,5	5°	TCG	**284.080.10P**
300	32	2/12/64	96	3,2	2,5	5°	TCG	**284.096.12P**
350	32	2/12/64	92	3,2	2,5	5°	TCG	**284.092.14P**
350	32	2/12/64	108	3,2	2,5	5°	TCG	**284.108.14P**
400	32	2/12/64	96	3,8	3,2	5°	TCG	**284.096.16P**
420	32	2/12/64	96	3,8	3,2	5°	TCG	**284.096.17P**
450	32	2/12/64	108	3,8	3,2	5°	TCG	**284.108.18P**
500	32	2/12/64	120	4,0	3,2	5°	TCG	**284.120.20P**

Remarks: in cardboard box.





www.dahm.no




296-297


Application: for cutting and dividing tubes, profile/extrusion products and solid blocks.

Machines: single or double mitre saws, radial saws.
Use series 296 for portable machines.

Material: aluminium, brass, copper alloys, plastic, composite material, melamine and laminated panels.


Warning: it is recommended to use a liquid lubricant.
Wax sticks are NOT RECOMMENDED.






EXCELLENT

For All Non-Ferrous Metals & PVC



Two-Sided Melamine



Saw Blades for Portable Machines. Negative Hook Angle

D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
120*	20	2/5,5/30	36	1,8	1,2	-6° Neg.	TCG	**296.120.36H**
160*	20	2/6/32	40	2,2	1,6	-6° Neg.	TCG	**296.160.40H**
160*	20	2/6/32	56	2,2	1,6	-6° Neg.	TCG	**296.160.56H**
new 165*	20	2/6/32	40	2,2	1,6	-6° Neg.	TCG	**296.165.40H**
new 165*	20	2/6/32	56	2,2	1,6	-6° Neg.	TCG	**296.165.56H**
180*	20	2/6/32	40	2,8	2,2	-6° Neg.	TCG	**296.180.40H**
190*	30	2/7/42	40	2,8	2,2	-6° Neg.	TCG	**296.190.40M**
190*	30	2/7/42	64	2,8	2,2	-6° Neg.	TCG	**296.190.64M**
190*	20 (Festool® FF)	Key 5/7/2,5	64	2,8	2,2	-6° Neg.	TCG	**296.190.64FF**
200*	30	COMBI3	48	2,8	2,2	-6° Neg.	TCG	**296.200.48M**
210*	30	2/7/42	48	2,8	2,2	-6° Neg.	TCG	**296.210.48M**
210*	30	2/7/42	64	2,8	2,2	-6° Neg.	TCG	**296.210.64M**
216*	30	2/7/42	64	2,8	2,2	-6° Neg.	TCG	**297.064.09M**
225*	30	2/7/42	64	2,8	2,2	-6° Neg.	TCG	**296.225.64M**
230*	30	2/7/42	48	2,8	2,2	-6° Neg.	TCG	**296.230.48M**
235*	30	2/7/42	48	2,8	2,2	-6° Neg.	TCG	**296.235.48M**

*Non-low noise

Remarks: in plastic carrying case.

Saw Blades to Fit on Trim- & Mitre Saws, Table Saws & Combined Joinery Machines. Negative Hook Angle

D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	80	3,2	2,5	-6° Neg.	TCG	**297.080.10M**
250	32	2/12/64	80	3,2	2,5	-6° Neg.	TCG	**297.080.10P**
254	30	COMBI3	80	3,2	2,5	-5° Neg.	TCG	**297.081.10M**
260	30	2/10/60 + 2/7/42	80	2,8	2,2	-6° Neg.	TCG	**297.080.11M**
280*	30	2/10/60 + 2/7/42	64	3,2	2,5	-6° Neg.	TCG	**297.064.11M**
300	30	COMBI3	96	3,2	2,5	-6° Neg.	TCG	**297.096.12M**
300	32	2/12/64	96	3,2	2,5	-6° Neg.	TCG	**297.096.12P**
305*	30	2/10/60 + 2/7/42	96	3,2	2,5	-6° Neg.	TCG	**297.096.13M**
315	30	2/10/60 + 2/7/42	96	3,2	2,5	-6° Neg.	TCG	**297.096.23M**
330	30	COMBI3	96	3,2	2,5	-6° Neg.	TCG	**297.096.33M**
330	32	COMBI3	96	3,2	2,5	-6° Neg.	TCG	**297.096.33P**
350	30	COMBI3	108	3,2	2,5	-6° Neg.	TCG	**297.108.14M**
350	32	4/12/64	108	3,2	2,5	-6° Neg.	TCG	**297.108.14P**
400	30	2/10/60	120	3,8	3,2	-6° Neg.	TCG	**297.120.16M**
400	32	4/12/64	108	3,8	3,2	-6° Neg.	TCG	**297.108.16P**
450	30	2/10/60	140	3,8	3,2	-6° Neg.	TCG	**Y297.140.18M**
450	32	2/12/64	108	3,8	3,2	-6° Neg.	TCG	**297.108.18P**
500	32	2/12/64	120	4,0	3,2	-6° Neg.	TCG	**297.120.20P**


*Non-low noise

Remarks: in cardboard box.

www.dahm.no

Dry Cutter Saw Blades for Metal *Industrial Line*


CMT ORANGE TOOLS




226

HW

Application: for crosscutting a variety of materials such as iron, steel, pvc, compound materials, melamine.
Machines: dry-cutter and mitre saws without lubrication.
Material: for ferrous materials and constructional steel.
Warning: not recommended for non-ferrous metals, wood, glass, concrete, plastic.




HV10: 1.520
N/mm²: 2.300



EXCELLENT

For Iron, Steel, PVC, Compound Materials, Melamine



D mm	B mm	Pin Hole	RPM suggested	Z	K mm	P mm	α	β	ORDER NO.
136,5*	10		5500	30	1,5	1,2	0°	8° FWF	**226.030.05**
136,5*	20		5500	30	1,5	1,2	0°	8° FWF	**226.030.05H**
160	20	2/6/32	4700	30	2,0	1,6	0°	8° FWF	**226.030.06H**
165	15,87<>		4600	36	1,6	1,2	0°	8° FWF	**226.036.06**
165	20	2/6/32	4600	36	1,6	1,2	0°	8° FWF	**226.036.06H**
new 165	30	2/7/42	4600	36	1,6	1,2	0°	8° FWF	**226.036.06M**
184	15,87<>		4100	48	2,0	1,6	0°	8° FWF	**226.048.07**
190	30	2/7/42	4000	40	2,0	1,6	0°	8° FWF	**226.040.07M**
210	15,87<>		3600	48	2,2	1,8	0°	8° FWF	**226.048.08**
210	30	2/7/42	3600	48	2,2	1,8	0°	8° FWF	**226.048.08M**
216	30	2/7/42	3500	48	2,2	1,8	0°	8° FWF	**226.047.09M**
235	30	2/7/42	3200	48	2,2	1,8	0°	8° FWF	**226.048.09M**
254	15,87		3000	48	2,2	1,8	0°	8° FWF	**226.048.10**
254	15,87		3000	60	2,2	1,8	0°	8° FWF	**226.060.10**
254**	30	COMBI3	3000	60	2,2	1,8	0°	8° FWF	**226.060.10M**
305	25,4		2500	60	2,2	1,8	0°	8° FWF	**226.060.12**
305	25,4		2500	80	2,2	1,8	0°	8° FWF	**226.080.12**
305**	30	COMBI3	2500	80	2,2	1,8	0°	8° FWF	**226.080.12M**
355	25,4		2100	72	2,2	1,8	0°	8° FWF	**226.072.14**
355	25,4		2100	90	2,2	1,8	0°	8° FWF	**226.090.14**
355**	30	COMBI3	2100	90	2,2	1,8	0°	8° FWF	**226.090.14M**

*Non-low noise

** **Remarks:** in cardboard box.

Industrial XTreme Saw Blades for Stainless Steel

CERMET

CERMET CARBIDE LONG LIFE

D mm	B mm	Pin Hole	RPM suggested	Z	K mm	P mm	α	β	ORDER NO.
160	20	2/6/32	4700	40	1,8	1,4	10°	8° FWF	**226.540.06H**
184	15,87<>		4100	48	2,0	1,6	10°	8° FWF	**226.548.07**
190	30	2/7/42	4000	48	1,8	1,4	10°	8° FWF	**226.548.07M**
216	30	2/7/42	3600	56	1,8	1,4	10°	8° FWF	**226.556.09M**
250**	30	COMBI3	3000	72	2,2	1,8	10°	8° FWF	**226.572.10M**
254	15,87		3000	72	2,2	1,8	10°	8° FWF	**226.572.10**
300**	30	COMBI3	2500	80	2,2	1,8	10°	8° FWF	**226.580.12M**
305	25,4		2500	80	2,2	1,8	10°	8° FWF	**226.580.12**
355	25,4		2100	90	2,2	1,8	10°	8° FWF	**226.590.14**
355**	30	COMBI3	2100	90	2,2	1,8	10°	8° FWF	**226.590.14M**

** **Remarks:** in cardboard box.

www.dahm.no


Solid Surface Saw Blades *Industrial Line*





223

HW

Application: for swirl free cuts.
Machines: table saws and panel sizing.
Material: solid surface materials (Dupont Corian®, Wilsonart®, Gibraltar®, SSV Fountainhead®, Varicor®, etc.) and thick plastic.
Warning: not recommended for use on mitre saws.







D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	72	3,2	2,5	0°	MTCG	**223.072.10M**
300	30	COMBI3	84	3,2	2,5	0°	MTCG	**223.084.12M**


PVC & Plexiglass Saw Blades *Industrial Line*





222


HW

Application: for perfect cuts without melting and scratching.
Machines: table saws, panel sizing and mitre saws.
Material: thin plastic, plexiglass, vinyl, plywood, laminated flooring.










D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	80	2,8	2,2	-3°	MATB	**222.080.10M**
300	30	COMBI3	96	2,8	2,2	-3°	MATB	**222.096.12M**

www.dahm.no

ITK Plus Ripping Saw Blades

CMT ORANGE TOOLS™




271


HW


Application: for rip cuts at high-speed rotation. The blade considerably reduces material waste thanks to the thin-kerf design. Particularly suitable for valuable wood.

Machines: miter saws, table saws, portable and cordless saws.

Material: soft and hardwood.









D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
250	30	COMBI3	24	2,4	1,6	20°	10° ATB + 8° Shear	**271.250.24M**
300	30	COMBI3	24	2,6	1,8	22°	10° ATB + 8° Shear	**271.300.24M**

ITK Plus Rip & Crosscut Saw Blades




271


HW


Application: for rip and crosscuts at high-speed rotation. The blade considerably reduces material waste thanks to the thin-kerf design. Particularly suitable for valuable wood.

Machines: miter saws, table saws, portable and cordless saws.


Material: soft and hardwood, plywood.











D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
136	20 (+10)		18	1,5	1,0	20°	10° ATB + 8° Shear	**271.136.18H**
150	20 (+16)		24	1,5	1,0	18°	10° ATB + 8° Shear	**271.150.24H**
160	20 (+16)	2/6/32	24	1,7	1,1	18°	10° ATB + 8° Shear	**271.160.24H**
165	20 (+15,87)	2/6/32	24	1,7	1,1	18°	10° ATB + 8° Shear	**271.165.24H**
165	30	2/7/42	24	1,7	1,1	18°	10° ATB + 8° Shear	**271.165.24M**
184	20 (+16+15,87)	2/7/42	24	1,7	1,1	20°	10° ATB + 8° Shear	**271.184.24H**
184	30	2/7/42	24	1,7	1,1	20°	10° ATB + 8° Shear	**271.184.24M**
190	30 (+20+16)	2/7/42	24	1,7	1,1	20°	10° ATB + 8° Shear	**271.190.24M**
200	30	2/7/42	36	1,8	1,2	15°	10° ATB + 8° Shear	**271.200.36M**
210	30 (+25)	2/7/42	36	1,8	1,2	15°	10° ATB + 8° Shear	**271.210.36M**
216	30	2/7/42	36	1,8	1,2	-5° Neg.	10° ATB + 8° Shear	**271.216.36M**
235	30 (+25)	2/7/42	36	2,4	1,6	18°	10° ATB + 8° Shear	**271.235.36M**
250	30	COMBI3	42	2,4	1,6	18°	10° ATB + 8° Shear	**271.250.42M**
300	30	COMBI3	48	2,6	1,8	18°	10° ATB + 8° Shear	**271.300.48M**

www.dahm.no

ITK Plus Crosscut Saw Blades




272

HW


Application: for rip and crosscuts at high-speed rotation. The blade considerably reduces material waste thanks to the thin-kerf design. Particularly suitable for valuable wood.


Machines: miter saws, table saws, portable and cordless saws.


Material: soft and hardwood, plywood.




HV10:	1.840
N/mm²:	2.050







EXCELLENT





D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
136	20 (+10)		36	1,5	1,0	18°	10° ATB + 8° Shear	**272.136.36H**
150	20 (+16)		40	1,5	1,0	16°	10° ATB + 8° Shear	**272.150.40H**
160	20 (+16)	2/6/32	40	1,7	1,1	16°	10° ATB + 8° Shear	**272.160.40H**
165	20 (+15,87)	2/6/32	36	1,7	1,1	20°	10° ATB + 8° Shear	**272.165.36H**
184	20 (+16+15,87)	2/7/42	40	1,7	1,1	18°	10° ATB + 8° Shear	**272.184.40H**
184	30	2/7/42	40	1,7	1,1	18°	10° ATB + 8° Shear	**272.184.40M**
190	30 (+20+16)	2/7/42	42	1,7	1,1	18°	10° ATB + 8° Shear	**272.190.42M**
200	30	2/7/42	48	1,8	1,2	15°	10° ATB + 8° Shear	**272.200.48M**
210	30 (+25)	2/7/42	48	1,8	1,2	15°	10° ATB + 8° Shear	**272.210.48M**
216	30	2/7/42	48	1,8	1,2	-5° Neg.	10° ATB + 8° Shear	**272.216.48M**
235	30 (+25)	2/7/42	48	2,4	1,6	18°	10° ATB + 8° Shear	**272.235.48M**
250	30	COMBI3	60	2,4	1,6	15°	10° ATB + 8° Shear	**272.250.60M**
300	30	COMBI3	72	2,6	1,8	15°	10° ATB + 8° Shear	**272.300.72M**

ITK Plus Fine Cut-Off Saw Blades




273


HW

Application: for crosscuts and finish cuts. The blade considerably reduces material waste thanks to the thin-kerf design. Particularly suitable for valuable wood.


Machines: miter saws, table saws, portable and cordless saws.

Material: soft and hardwood, exotic wood, plywood and laminates.







HV10:	1.840
N/mm²:	2.050







EXCELLENT



D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
160	20 (+16)	2/6/32	56	1,7	1,1	12°	10° ATB + 8° Shear	**273.160.56H**
190	30 (+20+16)	2/7/42	64	1,7	1,1	15°	10° ATB + 8° Shear	**273.190.64M**
216	30	2/7/42	64	1,8	1,2	-5° Neg.	10° ATB + 8° Shear	**273.216.64M**
250	30	COMBI3	80	2,4	1,6	12°	10° ATB + 8° Shear	**273.250.80M**
300	30	COMBI3	96	2,6	1,8	12°	10° ATB + 8° Shear	**273.300.96M**

www.dahm.no

Ultra Thin-Kerf Saw Blades *for Cordless Saws*

CMT ORANGE TOOLS™




271-272-226


HW

APPLICATION: (series 271-272) for rip and crosscuts where the ultra thin-kerf reduces material waste.
MACHINES: (series 271-272) portable cordless machines.
MATERIAL: (series 271-272) soft and hardwood, plywood.


EXCELLENT — Rip Cut on Wood (series 271)




EXCELLENT — Crosscut on Wood (series 272)





EXCELLENT — Metals & PVC (series 226)





APPLICATION: (series 226) for crosscuts on different kinds of materials.
MACHINES: (series 226) portable cordless machines.
MATERIAL: (series 226) for ferrous materials and construction steel.





D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
Ripping Cordless Saw Blades *(series 271)*								
136	20 (+10)		18	1,5	1,0	20°	10° ATB + 8° Shear	**271.136.18H**
165	20 (+15,87)	2/6/32	24	1,7	1,1	18°	10° ATB + 8° Shear	**271.165.24H**
165	30	2/7/42	24	1,7	1,1	18°	10° ATB + 8° Shear	**271.165.24M**
184	20 (+16+15,87)	2/7/42	24	1,7	1,1	20°	10° ATB + 8° Shear	**271.184.24H**
Crosscutting Cordless Saw Blades *(series 272)*								
136	20 (+10)		36	1,5	1,0	18°	10° ATB + 8° Shear	**272.136.36H**
165	20 (+15,87)	2/6/32	36	1,7	1,1	20°	10° ATB + 8° Shear	**272.165.36H**
184	20 (+16+15,87)	2/7/42	40	1,7	1,1	18°	10° ATB + 8° Shear	**272.184.40H**
Metal, PVC & Compound Material Cordless Saw Blades *(series 226)*								
136,5	10		30	1,5	1,2	0°	8° FWF	**226.030.05**
136,5	20		30	1,5	1,2	0°	8° FWF	**226.030.05H**
165	15,87<>		36	1,5	1,2	0°	8° FWF	**226.036.06**


Garden Trimmer Saw Blades




298

HW


APPLICATION: for cutting grass, bushes and small trees.
MACHINES: hedge trimmers.
MATERIAL: grass, bushes and small trees.
WARNING: always wear safety glasses and ear protection.
Carefully read the safety recommendations provided for this product.



SECURED TOOTH



HV10: 1.550
N/mm²: 2.600



EXCELLENT



D mm	B mm	RPM max	Z	K mm	P mm	α	β	ORDER NO.
250	20	12.000	20	2,2	1,4	15°	10° ATB	**298.250.20H**
250	25,4	12.000	20	2,2	1,4	15°	10° ATB	**298.250.20**

www.dahm.no





236


Application: for rip and crosscuts on abrasive materials.
Machines: mitre saws, portable and cordless machines.
Material: Eternit®, Swisspearl®, Fermacell®, Ivarplank®, HardiePlank®, HardiePanel®, Corian®, Duroplast®, Formica®, and other generic panel as chipboard, MDF, plasterboard and thermoplastic.

DP











GOOD

Eternit®, Swisspearl®, Fermacell®, Ivarplank®, HardiePlank®, HardiePanel®, Corian®, Duroplast®, Formica®, and other generic panel as chipboard, MDF, plasterboard and thermoplastic.





60X LONGER LIFE THAN CARBIDE

D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
85	15		6	1,8	1,4	12°	TCG	**236.085.06G**
160	20	2/6/32	4	2,4	1,8	12°	TCG	**236.160.04H**
160	20	2/6/32	10	2,4	1,8	5°	TCG	**236.160.10H**
180	20	2/6/32	4	2,4	1,8	12°	TCG	**236.180.04H**
184,5	15,87<>		4	1,8	1,4	12°	TCG	**236.004.07**
190	30	2/7/42	4	2,4	1,8	12°	TCG	**236.190.04M**
190	30	2/7/42	12	2,4	1,8	12°	TCG	**236.190.12M**
210	30	2/7/42	12	2,4	1,8	12°	TCG	**236.210.12M**
216	30	2/7/42	14	2,4	1,8	12°	TCG	**236.216.14M**
230	30	2/7/42	4	2,4	1,8	12°	TCG	**236.230.04M**
250	30	COMBI3	16	2,4	1,8	12°	TCG	**236.250.16M**
254	15,87		6	2,2	1,6	12°	TCG	**236.006.10**
300	30	COMBI3	20	2,4	1,8	12°	TCG	**236.300.20M**
305	25,4		8	2,2	1,6	12°	TCG	**236.008.12**

Rip Saw Blades *for Portable Machines*




290

Application: for rip cuts.
Machines: mitre saws and portable machines.
Material: soft and hardwood.


HW







EXCELLENT

Rip Cut on Wood







HV10: 1.765
N/mm²: 2.150

D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
150	20		12	2,4	1,4	20°	10° ATB	**290.150.12H**
160	16		12	2,2	1,6	20°	10° ATB	**290.160.12E**
160	20	2/6/32	12	2,2	1,6	20°	10° ATB	**290.160.12H**
180	30	2/7/42	12	2,6	1,6	20°	10° ATB	**290.180.12M**
190	16	2/6/32	12	2,6	1,6	20°	10° ATB	**290.190.12E**
190	20	2/6/32	12	2,6	1,6	20°	10° ATB	**290.190.12H**
190	30	2/7/42	12	2,6	1,6	20°	10° ATB	**290.190.12M**
200	30	2/7/42	24	2,8	1,8	20°	10° ATB	**290.200.24M**
210	30	2/7/42	24	2,8	1,8	20°	10° ATB	**290.210.24M**
216	30	2/7/42	24	2,8	1,8	-5° Neg.	15° ATB	**290.216.24M**
220	30	2/7/42	24	2,8	1,8	20°	10° ATB	**290.220.24M**
230	30	2/7/42	24	2,8	1,8	20°	10° ATB	**290.230.24M**
235	25		24	2,8	1,8	20°	10° ATB	**290.235.24L**
235	30	2/7/42	24	2,8	1,8	20°	10° ATB	**290.235.24M**
240	30	2/7/42	24	2,8	1,8	20°	10° ATB	**290.240.24M**
250	30	COMBI3	24	2,8	1,8	20°	10° ATB	**290.250.24M***
260	30	COMBI3	28	2,8	1,8	20°	10° ATB	**290.260.28M***
270	30	2/7/42	28	2,8	1,8	20°	10° ATB	**290.270.28M***

∗ *Industrial quality*

www.dahm.no

Contractor Saw Blade Masterpack

CMT ORANGE TOOLS



K (Contractor)


Machines: portable benchtop and table saws.
Material: soft/hard wood, plywood, OSB panels.


Designed for construction, remodeling and DIY projects.
These blades deliver solid performance at a very economical price.

HW



Kit 10 pcs.





GREAT VALUE

DESCRIPTION	D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
Crosscut *(pack 10 blades)*	160	20	2/6/32	24	2,2	1,4	15°	15° ATB	**K16024H-X10**
Fine cut-off *(pack 10 blades)*	160	20	2/6/32	40	2,2	1,4	10°	15° ATB	**K16040H-X10**
Crosscut *(pack 10 blades)*	190	30	2/7/42	24	2,2	1,4	20°	10° ATB	**K19024M-X10**
Crosscut *(pack 10 blades)*	216	30	2/7/42	24	2,4	1,6	-5° Neg.	15° ATB	**K21624M-X10**
Fine cut-off *(pack 10 blades)*	216	30	2/7/42	48	2,4	1,6	-5° Neg.	15° ATB	**K21648M-X10**
Crosscut *(pack 5 blades)*	250	30	COMBI3	40	2,6	1,8	15°	10° ATB	**K25040M-X05**

Contractor Saw Blade Combo



K (Contractor)

Machines: portable benchtop and table saws.
Material: soft/hard wood, plywood, OSB panels.

Designed for construction, remodeling and DIY projects.
These blades deliver solid performance at a very economical price.

GREAT VALUE



HW

K160H-X03 3-pc Set for Crosscut & Fine Cut Circular Saw Blades Ø160mm. Bore 20mm.

Set contains	ORDER NO.	D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	Q.ty
Crosscut	K16024H	160	20	2/6/32	24	2,2	1,4	15°	15° ATB	1
Fine cut-off	K16040H	160	20	2/6/32	40	2,2	1,4	10°	15° ATB	2

K190M-X03 3-pc Set for Crosscut & Fine Cut Circular Saw Blades Ø190mm. Bore 30mm.

Set contains	ORDER NO.	D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	Q.ty
Crosscut	K19024M	190	30	2/7/42	24	2,2	1,4	20°	10° ATB	2
Fine cut-off	K19040M	190	30	2/7/42	40	2,2	1,4	15°	10° ATB	1

K216M-X03 3-pc Set for Crosscut & Fine Cut Circular Saw Blades Ø216mm. Bore 30mm.

Set contains	ORDER NO.	D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	Q.ty
Crosscut	K21624M	216	30	2/7/42	24	2,4	1,6	-5°	15° ATB	1
Fine cut-off	K21648M	216	30	2/7/42	48	2,4	1,6	-5°	15° ATB	2

K250M-X02 2-pc Set for Rip & Crosscut Circular Saw Blades Ø250mm. Bore 30mm.

Set contains	ORDER NO.	D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	Q.ty
Rip	K25024M	250	30	COMBI3	24	2,6	1,8	20°	10° ATB	1
Crosscut	K25040M	250	30	COMBI3	40	2,6	1,8	15°	10° ATB	1

K305M-X02 2-pc Set for Crosscut & Fine Cut Circular Saw Blades Ø305mm. Bore 30mm.

Set contains	ORDER NO.	D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	Q.ty
Crosscut	K30540M	305	30	COMBI3	40	2,8	2,0	-5°	10° ATB	1
Fine cut-off	K30560M	305	30	COMBI3	60	2,8	2,0	-5°	10° ATB	1


www.dahm.no




285-291


HW


APPLICATION: for rip and crosscuts.
MACHINES: table and mitre saws, portable machines.
MATERIAL: soft and hardwood, plywood.



HV10:	1.765
N/mm²:	2.150







D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
120	20	2/5,5/30	18	1,8	1,2	15°	15° ATB	**291.120.18H***
125	20		20	2,4	1,4	15°	15° ATB	**291.125.20H**
130	20		20	2,4	1,4	15°	15° ATB	**291.130.20H**
140	20		20	2,4	1,4	15°	15° ATB	**291.140.20H**
150	16		24	2,4	1,4	15°	15° ATB	**291.150.24E**
150	20		24	2,4	1,4	15°	15° ATB	**291.150.24H**
160	16		24	2,2	1,6	15°	15° ATB	**291.160.24E**
160	20	2/6/32	24	2,2	1,6	15°	15° ATB	**291.160.24H**
160	30	2/7/42	24	2,2	1,6	15°	15° ATB	**291.160.24M**
165	20	2/6/32	24	2,2	1,6	15°	15° ATB	**291.165.24H**
165	30	2/7/42	24	2,6	1,6	15°	15° ATB	**291.165.24M**
170	30	2/7/42	24	2,6	1,6	20°	10° ATB	**291.170.24M**
180	20	2/6/32	24	2,6	1,6	20°	10° ATB	**291.180.24H**
180	30	2/7/42	24	2,6	1,6	20°	10° ATB	**291.180.24M**
184	16		24	2,6	1,6	20°	10° ATB	**291.184.24E**
184	30		24	2,6	1,6	20°	10° ATB	**291.184.24M**
190	16	2/6/32	24	2,6	1,6	20°	10° ATB	**291.190.24E**
190	20	2/6/32	24	2,6	1,6	20°	10° ATB	**291.190.24H**
190	30	2/7/42	24	2,6	1,6	20°	10° ATB	**291.190.24M**
190	20 (Festool® FF)	Key 5/7/2,5	32	2,6	1,6	10°	10° ATB	**291.190.32FF**
200	30	2/7/42	36	2,8	1,8	15°	15° ATB	**291.200.36M**
210	25		36	2,8	1,8	15°	15° ATB	**291.210.36L**
210	30	2/7/42	36	2,8	1,8	15°	15° ATB	**291.210.36M**
216	30	2/7/42	48	2,8	1,8	-5° Neg.	15° ATB	**291.216.48M**
220	30	2/7/42	36	2,8	1,8	15°	15° ATB	**291.220.36M**
225	30	2/7/42	36	2,8	1,8	20°	15° ATB	**291.225.36M**
230	30	2/7/42	36	2,8	1,8	15°	15° ATB	**291.230.36M**
235	25		36	2,8	1,8	15°	15° ATB	**291.235.36L**
235	30	2/7/42	36	2,8	1,8	15°	15° ATB	**291.235.36M**
240	30	2/7/42	36	2,8	1,8	15°	15° ATB	**291.240.36M**
250	20	COMBI3	40	3,2	2,2	15°	10° ATB	**285.040.10H***
250	30	COMBI3	40	3,2	2,2	15°	10° ATB	**285.040.10M***
260	30	2/10/60 + 2/7/42	48	2,8	1,8	15°	10° ATB	**285.048.11M***
270	30	2/7/42	42	2,8	1,8	15°	15° ATB	**291.270.42M***


* *Industrial quality*


www.dahm.no





281-285-292

APPLICATION: for crosscuts, perfect finishing.
MACHINES: table and mitre saws, portable machines.
MATERIAL: soft, hard and exotic wood, wood-based panels, single-sided veneer, paper-based laminates.










D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
120	20	2/5,5/30	36	1,8	1,2	10°	15° ATB	**292.120.36H***
120	20	2/5,5/30	40	1,8	1,2	10°	15° ATB	**292.120.40H**
125	20	-	36	2,4	1,4	15°	15° ATB	**292.125.36H**
130	20	-	36	2,4	1,4	15°	15° ATB	**292.130.36H**
140	20	-	36	2,4	1,4	15°	15° ATB	**292.140.36H**
150	20	-	40	2,4	1,4	15°	15° ATB	**292.150.40H**
160	16	-	40	2,2	1,6	10°	15° ATB	**292.160.40E**
160	20	2/6/32	40	2,2	1,6	10°	15° ATB	**292.160.40H**
160	20 (Virutex)	4/7/32 (45°)	40	2,2	1,6	10°	TCG	**281.160.40H**
160*	20	2/6/32	40	2,2	1,6	10°	TCG	**281.160.40H2**
160	30	2/7/42	40	2,2	1,6	10°	15° ATB	**292.160.40M**
160	20	2/6/32	56	2,2	1,6	15°	15° ATB	**292.160.56H**
165	20	2/6/32	40	2,2	1,6	10°	15° ATB	**292.165.40H**
165	20	2/6/32	56	2,2	1,6	15°	15° ATB	**292.165.56H**
165	30	2/7/42	40	2,6	1,6	10°	15° ATB	**292.165.40M**
170	30	2/7/42	40	2,6	1,6	15°	15° ATB	**292.170.40M**
180	20	2/6/32	40	2,6	1,6	15°	15° ATB	**292.180.40H**
180	30	2/7/42	40	2,6	1,6	15°	15° ATB	**292.180.40M**
184	16		40	2,6	1,6	15°	15° ATB	**292.184.40E**
184	30		40	2,6	1,6	15°	15° ATB	**292.184.40M**
190	16	2/6/32	40	2,6	1,6	15°	15° ATB	**292.190.40E**
190	20	2/6/32	40	2,6	1,6	15°	15° ATB	**292.190.40H**
190	30	2/7/42	40	2,6	1,6	15°	15° ATB	**292.190.40M**
190	30	2/7/42	64	2,6	1,6	15°	15° ATB	**292.190.64M**
190	20 (Festool® FF)	5/7/2,5	48	2,4	1,6	10°	15° ATB	**292.190.48FF**
200	30	2/7/42	48	2,8	1,8	15°	15° ATB	**292.200.48M**
210	25		48	2,8	1,8	15°	15° ATB	**292.210.48L**
210	30	2/7/42	48	2,8	1,8	15°	15° ATB	**292.210.48M**
210	30	2/7/42	64	2,8	1,8	15°	15° ATB	**292.210.64M**
216	30	2/7/42	64	2,8	1,8	-5° Neg.	15° ATB	**292.216.64M**
216	30	2/7/42	80	2,8	1,8	-5° Neg.	15° ATB	**292.216.80M**
220	30	2/7/42	48	2,8	1,8	15°	15° ATB	**292.220.48M**
225	30	2/7/42	48	2,8	1,8	10°	15° ATB	**292.225.48M**
230	30	2/7/42	48	2,8	1,8	15°	15° ATB	**292.230.48M**
230	30	2/7/42+2/10/60	64	2,8	1,8	15°	15° ATB	**292.230.64M**
235	25		48	2,8	1,8	15°	15° ATB	**292.235.48L**
235	30	2/7/42	48	2,8	1,8	15°	15° ATB	**292.235.48M**
240	30	2/7/42	48	2,8	1,8	15°	15° ATB	**292.240.48M**
250	30	COMBI3	60	3,2	2,2	10°	15° ATB	**285.060.10M***
260	30	2/10/60 + 2/7/42	60	2,8	1,8	10°	15° ATB	**285.060.11M***

* *Industrial quality*

www.dahm.no


230 CMT thoroughly researched the shortcomings of “standard” dado sets and learned what cabinet makers required most from an “ideal” dado.
The result was the superior CMT precision dado, designed with the following features:
- anti-kickback design to reduce the possibility of overfeeding that can occur when cutting mass material.
- splinter resistant cuts in veneer plywood, melamine and hard and soft woods;
- shim sets included for cuts between 6,35mm (1/4”) and 22,23mm (7/8”).










Precision Dado set includes:



2 BLADES


6 CARBIDE TIPPED FOUR TOOTH CHIPPERS


SHIM SET

Shims set contains	
No.	Shim Width
4	0.1mm
2	0.2mm
2	0.3mm
2	0.5mm









D mm	B mm	Z	P (inside blades) 3,2mm	2,4mm	1,6mm	K min.	max	α	β	ORDER NO.
150	15,87	20	4 pcs.	1 pcs.	1 pcs.	6,35	22,23	-5°	FTG+ATB	**230.520.06**
200	15,87	24	4 pcs.	1 pcs.	1 pcs.	6,35	22,23	-5°	FTG+ATB	**230.524.08**
200	30	24	4 pcs.	1 pcs.	1 pcs.	6,35	22,23	-5°	FTG+ATB	**230.524.08M**


K mm	Number of required inside blades 1,6mm	2,4mm	3,2mm
6,35	0	0	0
7,94	1	0	0
8,73	0	1	0
9,53	0	0	1
10,32	1	1	0
11,11	1	0	1
11,91	0	1	1
12,70	0	0	2
13,49	1	1	1
14,29	1	0	2
15,08	0	1	2
15,88	0	0	3
16,67	1	1	2
17,46	1	0	3
18,26	0	1	3
19,05	0	0	4
19,84	1	1	3
20,64	1	0	4
21,43	0	1	4
22,23	1	1	4




Dado Pro set includes:



2 BLADES



5 CARBIDE TIPPED TWO TOOTH CHIPPERS


SHIM SET

Shims set contains	
No.	Shim Width
3	0.1mm
2	0.2mm
1	0.3mm
1	0.5mm







D mm	B mm	Z	P (inside blades) 3,2mm	1,6mm	K min.	max	α	β	ORDER NO.
200	15,87	12	4 pcs.	1 pcs.	6,35	20,64	-12°	FTG+ATB	**230.012.08**

K mm	Number of required inside blades 1,6mm	3,2mm
6,35	0	0
7,94	1	0
9,53	0	1
11,11	1	1
12,70	0	2
14,29	1	2
15,88	0	3
17,46	1	3
19,05	0	4
20,64	1	4

www.dahm.no


Grooving Saw Blades *Industrial Line*





240

HW

Application: for grooving cuts or for rebating, chamfering, grooving and profiling as a set of tools.
Machines: double-end tenoners and moulding machines.
Material: soft and hardwood, wood-based panels, plastic.









The new design allows multi-rip grooves using different kerf thickness.

D mm	B mm		Z	K mm	P mm	α	β	ORDER NO.
150	30		12	2,0	1,4	15°	FLAT	**240.020.06M**
150	35		12	2,0	1,4	15°	FLAT	**240.020.06R**
150	30		12	3,0	2,0	15°	FLAT	**240.030.06M**
150	35		12	3,0	2,0	15°	FLAT	**240.030.06R**
150	30		12	4,0	3,0	15°	FLAT	**240.040.06M**
150	35		12	4,0	3,0	15°	FLAT	**240.040.06R**
150	30		12	5,0	3,0	15°	FLAT	**240.050.06M**
150	35		12	5,0	3,0	15°	FLAT	**240.050.06R**
150	30		12	6,0	3,0	15°	FLAT	**240.060.06M**
150	35		12	6,0	3,0	15°	FLAT	**240.060.06R**
180	30		18	3,0	2,0	15°	FLAT	**240.030.07M**
180	35		18	3,0	2,0	15°	FLAT	**240.030.07R**
180	30		18	4,0	3,0	15°	FLAT	**240.040.07M**
180	35		18	4,0	3,0	15°	FLAT	**240.040.07R**
180	30		18	5,0	3,0	15°	FLAT	**240.050.07M**
180	35		18	5,0	3,0	15°	FLAT	**240.050.07R**
180	30		18	6,0	3,0	15°	FLAT	**240.060.07M**
180	35		18	6,0	3,0	15°	FLAT	**240.060.07R**

Biscuit Joiner Saw Blades










240-241

HW

CMT's 100mm biscuit joiner saw blades with orange PTFE industrial coating trademark make biscuit joints quickly and easily. High-grade German steel and 8 micrograin carbide-tipped teeth guarantee years of use. These blades fit Lamello®, Dewalt®, Porter-Cable®, Skil®, Bosch®, Freud® and other popular biscuit joints models.









D mm	B mm	Pin Hole	Z	K mm	P mm	α	β	ORDER NO.
100	22	4/4,5 - 9,5/36	6	3,96	3,0	18°	10°ATB	**240.006.04**
100	22	4/4,5 - 9,5/36	8	3,96	3,0	15°	10°ATB	**240.008.04**
100*	22	-	8	3,96	3,1-3,8	15°	FLAT	**241.008.04**

*** For Virutex®, Porter-Cable® Machines**

www.dahm.no


Mini-Spot Circular Saw Blade for Lamello®




240.004.04

HW

The CMT mini-spot saw blade is ideal for any type of repairing on solid wood. Resin, knots and other wood flaws are no longer a problem. Thanks to this product, cut points using original patches become practically invisible because wood and patch grains will match up in the same direction.
For use with Lamello® or other machines.







D mm	B mm		Z	K mm	P mm	α	β	ORDER NO.
100	22		4	8,0	6,0	18°	R30	**240.004.04**

Calibration & Sanding Disks



299.11

If you're looking for fast and easy saw alignment and balancing, the cut calibration and sanding disk is for you. First, mount your calibration and sanding disk in your table saw and line it up with a square for accuracy. Then, remove the calibration and sanding disk and mount your saw blade for true precise cuts. You can also use the calibration and sanding disk as a sander by simply attaching self-stick sandpaper and installing the disk in your table saw.

D mm	B mm	P mm	ORDER NO.
200	15,87	2,8	**299.111.00**
200	30	2,8	**299.111.00M**
250	15,87	2,8	**299.112.00**
250	30	2,8	**299.112.00M**

Saw Blades Stabilizers




299.10

The CMT blade stabilizer virtually eliminates rim vibration to make cleaner, straighter cuts and extend the life of your CMT saw blade. It also helps lessen noise caused by vibration during cutting.

NOTE: for use on stationary saws only. Each order includes 2 stabilizers.

DESCRIPTION	D mm	B mm	P mm	ORDER NO.
Stabilizer (2 pcs.) for Ø200mm	75	15,87	3,0	**299.101.00**
Stabilizer (2 pcs.) for Ø200mm	75	30	3,0	**299.101.00M**
Stabilizer (2 pcs.) for Ø250mm	125	15,87	3,0	**299.102.00**
Stabilizer (2 pcs.) for Ø250mm	125	30	3,0	**299.102.00M**
Stabilizer (2 pcs.) for Ø300mm	152	25,4	3,0	**299.103.00**
Stabilizer (2 pcs.) for Ø300mm	152	30	3,0	**299.103.00M**

Reduction Rings for Saw Blades



299

D mm	B mm	P mm	ORDER NO.	D mm	B mm	P mm	ORDER NO.
15,87	10	1,2	**299.218.00**	30	15	1,4	**299.240.00**
15,87	12,7	1,2	**299.217.00**	30	15,87	1,4	**299.211.00**
20	12,7	1,2	**299.221.00**	30	16	1,4	**299.223.00**
20	15,87	1,4	**299.243.00**	30	16	2,0	**299.226.00**
20	16	1,2	**299.222.00**	30	18	1,4	**299.232.00**
20	18	1,4	**299.236.00**	30	19,05	1,4	**299.241.00**
22,2	15	1,4	**299.237.00**	30	20	1,4	**299.224.00**
22,2	16	1,4	**299.242.00**	30	22	1,4	**299.231.00**
22,2	20	1,4	**299.238.00**	30	20	2,0	**299.227.00**
25,4	15,87	1,4	**299.216.00**	30	25	1,4	**299.225.00**
25,4	19,05	1,4	**299.213.00**	30	25	2,0	**299.228.00**
25,4	20	1,4	**299.214.00**	30	25,4	2,0	**299.212.00**
25,4	20	2,3	**299.220.00**	32	30	2,0	**299.229.00**
25,4	22	1,4	**299.215.00**	35	30	2,0	**299.230.00**
25,4	22,2	1,4	**299.239.00**	35	32	2,0	**299.233.00**
25,4	22,2	2,3	**299.219.00**				

www.dahm.no

Saw Blades for Portable Machines

CMT ORANGE TOOLS™

MACHINE	DxB mm
AEG	
HK 125	120x20
HK 125 A, HK 125 B, HK 125 H	125x20
TKS 42, PC 300	132x20
HK 40, TK 40, TKS 42	140x20
HK 86, HK 707	143x19
HK 45, HK 717, HK 727	150x19
AHK 52, HK 45 A, HK 46, HK 46 S, HK 46 N,	150x20
HKS 46, HKS 46 S, HKS 46 N, HK 50,	
HK 52, HKS 52, HK 737	
HK 55, HK 55 A, HK 55 B, HKS 55,	160x20
HK 160 A, HK 160B, KS 55 S, KS 55 SE	
HKS 64 A, HK 65, HK 65 A, HKS 65,	190x30
HKS 65 A, HK 66, HKE 66, HKS 66,	
HKSE 66, HK 190, K 66, K 66 E, K 66 S,	
K 66 SE, KS 65, KS 66 S	
HK 200	200x25
HK 201	200x30
HK 75, HK 75 A, HKS 75	210x30
HKS 35, HKS 85	230x30
HK 240	240x30
MK 65	280x30
ALKO	
Basic 205 GK	205x18
Pro 250 GK	250x20
Basic, HS 3, HS 4, Hobby, Holzmeister H,	315x30
Holzmeister S, Holzmeister NHS, Pro-X	
W 450, W 500 450x30	
W 50 Profi, W 450, W 500	500x30
RM 60, W 60	600x30
RM 70, RZ 70, TWM 70, TWZ 700, W 70	700x30
ALPHA-TOOLS	
KS 250	205x18
ATIKA	
Toptronic	250x30
ATK 315 H, BTA 90, HAT 315	315x30
ABH 400, ABK 400, BTH 400, BTK 400	400x30
ABH 450, ABK 450, ATU 450,	450x30
BTH 450, BTK 450, BTU 450, BWK 450	
ABH 500, ABK 500, BTH 500,	500x30
BTK 500, BTU 500, BWK 500	
AVOLA	
LH 315, TZV 315, TVZ 315 W	315x30
TZH 350, TZH 350 W 350 30, ZB 400,	450x30
ZBV 400 400 30IC 450, ZB 450, ZBV 450	
ZB 500, ZBV 500	500x30
BWS 550	550x30
KWK 600, RK 600	600x30
BWS 700, BWTS 700, KWK 700	700x30
BLACK & DECKER	
D 984, D 985, DN 55, DN 56,	125x12,75
DN 254, DN 984, DN 985	
KC 1440 SK	136x10
BD 227, BD 228, BD 846, CD 600, DN 227,	140x12,75
DN 227 H, KS 40, KS 227, KS 840, KS 846,	
P 3501	
P 88-09 (Akku, 12 V)	150x20
BD 228, BD 228 CK, BD 228 L,	156x12,75
DN 57, DN 228, SR 352, SR 352 E, P 3601	
BD 855, GKS 54 CE, KS 55, KS 855, KS 855 N,	160x16
M 336, M 975, M 976,U 336, U 975, U 976	
BD 229, BD 865, BD 865 E, DN 59, DN 229,	180x16
DN 820, GD 60, HD 100, HD 1000,	
HD 1200 P, HD 2062, KS 65 K, KS 865, KS	
865 E, KS 865 KN, SEC 718, SR	
300, SR 362 E, P 37-03, P 37-05	
HD 1200	180x20
BD 365	190x30
M 338, U 338	200x16
BD 88, BD 800, DN 800,	210x30
DN 810, HD 2075 S HD 20755,	
KS 800, KS 805, KS 810, KS 810 A,	
P 38-02, PS 174, SEC 818, SR 700	
BOSCH	
GUF 4-22 A, PSF 22 (Schatten-fugensäge)	105x20
PKS 38, PKS 40, PKS 40 S, S 43	130x16
1551, 1559	140x20
GKS 12 V, GKS 46, PKS 46,	150x16
PKS 416, PKS 48, S 1, S 33	
GKS 24 V, GKS 54, GKS 54 C,	160x16
GKS 54 CE, GKS 54 E, GKS 59,	
KS 550, PKS 54, PKS 54 CE	
1552, 1556, 1563, GKS 55	170x30
0550, 1550, 1553, 1557, 1560	180x30
P 300, PKS 65	190x16
0051, 1553, 1564, GKS 65, GKS 66,	190x30
GKS 66 CE, GKS 68 B, GKS 68 BC,	
GKS 68 CE, P 30, PKS 66, PKS 66 CE	
0551, 1561	200x30
1554, 1558, 1565, 1588, GKS 72 S	210x30
GCM 8 S	216x30
0052, 0552, 1562, 1566, 1662, GKS 85 S	230x30
1555	240x30
GCM 10, GCM 10 S, GCM 10	250x30
SD, GTS 10	250x30
GCM 12, GCM 12 S	305x30

MACHINE	DxB mm
CASAIS	
SC 650	150x20
VSC 65	200x30
HKS 2000	210x30
SC 320	230x30
DEWALT	
DW 935 K, DW 936 K	136x10
DW 351	150x20
DW 007 K, DW 007 KH	165x10
DC 390 KA, DC 390 KA/3, DC 390 KB	165x20
DW 62	184x16
DW 365	190x30
DW 700, DW 701, DW 707	216x30
DW 383	235x30
DW 86	240x30
DW 100, DW 110, DW 111	250x16
DW 120, DW 125, DW 150, DW 170, DW 250,	250x30
DW 252, DW 320, DW 702, DW 703, DW 710,	
DW 742, DW 743, DW 744, DW 720 K,	
DW 746 K, DW 1251, DW 1370, DW 1501,	
DW 1503	
DW 709, DW 711	260x30
DW 721, DW 722 K, DW 725 K, DW 726 K,	300x30
DW 810, DW1370, DW 1935/31L, 142 DS,	
160 DS, 1635, 1875, 2155	
MC 20	300x32
DW 704, DW 705, DW 706,	305x30
DW 708, D 27105	350x30
DW 728 K, DW 729 K, 1600 S, C 14	
C 14, 1600 S, 1635 GL, 2155 G	400x30
6 K, 6 L, DA 1635	500x30
EINHELL	
BT-CS 1200, HES 55, HES 160	160x20
RT-CS 165	165x16
BHS 1300	184x16
BT-CS 1400	190x20
RT-CS 190 L	190x30
BT-TS 800	200x16
HES 200	200x30
RT-TS 920	205x16
RT-FF 1220 U	205x30
BT-MS 210, BT-SM 2050, KGST	210x30
210, RT-SM 305 L, RT-TS 1221	
KGT 500	250x20
BT-MS 250 L, BT-SM 3100,	250x30
BT-TS 1500 U, KGS 250, KGS, 300 UG,	
KGS 301, KGS 330, KGTN 245, KGTN 250,	
RT-SM 430 U, RT-TS, 1725 U, RT-TS 1825 U,	
RT-UD, 1825, RT-UD 1825, RT-XM 305 U	
RT-SM 330 U	305x30
RT-CC 315 U, RT-TS 2031 U, RT-TS 2231 DU	215x30
BT-LC 400/1	400x30
BT-LC 500	450x30
BT-LC 700 D	700x30
ELEKTRA BECKUM	
Multi 180	200x30
KS 205	205x18
KS 210, GKS 255, P200, PK 200,	210x30
PK 220, UK 220 W, UK 220 E	
Secanta	220x30
PK 250, PK 255, KGT 500, KGS	250x20
300, KGT 550, UK 330, KS 250	
KGS 250, KGS 250 K, KGS 300, KGS 301,	250x30
KGS 303,KGS 330, KGS 331, KGT 250,	
KGT 500, KGT 501, KGT 550, KS 250, KS	
304, Multi 260, Multi 310, PK 250,	
PK 255, PK 2800, PK 3100, PK	
4200, PK 6000, PKF 255, UK250, UK 330	
PK 300, PK 300 K, PKV 300 G	300x30
KS 304	304x30
1800, 2200, 2800, 3100, 4100,	315x30
Combi und Standard HS 315,	
Combi HSG, TKHS 315, TK, HS 315 E	
TK 350	350x30
BKH 400, BKS 400, BKS 450,	400x30
BS 3100 W, BS 4200, BS 5500 W	
BKH 450, BKS 450, BS 6000 D,	450x30
BS 8000 D	
BKH 450, BS 6000 D, BS 8000 D	500x30
BW 400, BW 600, BW 700	600x30
BW 700, BW 750, BW 4000	700x30
ELU/DEWALT	
MKK 26	86x12
MH 25, MH 25 K	100x12
DS 140 Doublo Schatten-fugensäge	105x22
MHA 14 KA, MHA 18 KA	136x10
MH 151, MH 151/10, MHA 151	150x20
MH 18, MH 30, MH 82, MH 182, PS 174	150x30
MH 55, MH 155	170x30
MH 65	180x30
MH 165, MH 265	190x30
MH 30, MH 82, MH 182	215x30
ETS 41, PS 174, PS 274, PS 244 E	216x30
MH 85, MH 286	240x30

MACHINE	DxB mm
ELU/DEWALT (vervolg)	
ETS 21, ETS 23, ETS 31, ETS 33, KSU 101,	250x30
RAS 1251, RAS 1253, RKS 1251, RKS 1253,	
TGS 71, TGS 170, TGS 171, TGS 172,	
TGS 173, TGS 271, TGS 273	
EMTS 711	260x30
ETS 3001, ETS 3003, PS 374	300x30
EMS 705, PS 374	305x30
RKS 1603	350x30
MTS 24	355x25,4
RSA 133/25	500x30
ELUMATEC	
KS 101, MGS 460	254x32
DG 163, RS 160, TS 161	280x32
KS 101, MGS 460	300x32
MGS 72/04, MGS 73/23	330x32
DG 79/03-05, DG 79/50, SA 73/25	330x32
DG 79/30-32, DG 79/51, MGS	380x32
72/30, MGS 73/33, SA 73/35	
DG 102, DG 104, DG 140, MGS	420x30
105, MGS 461, SA 103/25	
DG 142, MGS 142, SA 142	500x30
DG 204, DG 240, MGS 205	550x30
EMCO	
Universal	200x15
Rex 2000, Super 1011	250x20
KS 80, MK 81	250x30
EUMENIA	
ML 50 L	220x30
FEIN	
SSK 646, SSL 646	150x20
SSK 660	160x20
SSK 661	210x30
FELDER	
KF 700	250x30
BF 6-26, BF 6-31, BF 6-41,	315x30
BF 31, K 37, KFS 37	
FELISATTI	
TP 751	150x20
TP 756	160x20
TP 765	190x20
TP 781	230x30
T 84, T 85, T 87, T 770, T 771,	250x20
T 777, T 777 B, T 777 CE, T 778, T 867 GS	
M 74, M 75, M 76, M 77, T 84,	250x30
T 85, T 87, T 88	
T 82, T 83, T 91, T 91 CE, T 97 CE	300x30
FERM	
FZT 250, FZT 250 EN	250x30
FESTOOL	
AUF 35-S3, AUF 35-S4	105x20
AUF 35-S2	120x20
AF 45 E, AXF 45	150x30
AP 55, AP 55 E, AP 55 E-FS, AP 55 FS,	160x20
ATF 55, ATF 55 E, ATF 55 EB, ATF 55 E-FS,	
ATF 55 FS, AP 55 EB, TS 55, TS 55	
EQ, TS 55 EBQ, TS 55 Q	
AAU, AU 50, AUP 50	160x30
AM 42 A, AM 42 S, AM 42 T, AMT 42 S,	170x33
AT 55 B, AT 55 C, AT 55 E, ATU 42-S,	
AU 42 S, AUT 42 S, AXT 50 LA, AXT 55	
AU 55 S, AU 60 P, AU 60 S, A	180x30
UP 60 S, AUT 60 S	
AP 65, AP 65 E, AP 65 E-FS, AP 65 EB,	190x30
AP 65 EB-FS, AT 65, AT 65 E, AT 65 E-FS,	
AT 65 EB, AT 65 EB-FS	
AD 65, AP 68 E, AP 65 S, AU 65 S,	200x30
AUP 65 S, AUT 65 S, AXP 65, AXP 200	
TS 75, TS 75 EBQ, TS 75	210x30
EBQ-FS, TS 75 EQ	
Symmetric SYM 70	216x30
AU 77 S	220x30
CS 70, CS 70 EB	225x30
AU 80 S	230x30
AP 85, AP 85 E, AP 85 E-FS, AP 85 E-TS,	240x30
AP 85 EB, AP 88, AP 88 E, AXP 85	
AD 85, AD 100, AE 85, AE 88	250x30
Kapex KS 88, Kapex KS 120	260x30
AXP 130, AXP 132 E, BD 125	350x30
BD 145, BD 145/1	400x30
BD 170	450x30
FEZER	
KG 20	200x18
KG 205	205x18
KG 25	250x32
KG 30	300x32
KG 40 S	400x32
AB 600	600x32
FLOTT/FLOTTJET/KRAKU	
1000, 2000, Profi 3000	250x20
KS 1011, TKS 2011 D, TKS 2011 W,	250x30
KS 2011 D, KS 2011 W, KS 2012, 3011,	
Profi 2000, Profi 2001,	
Profi 3011, Uni-Profi 2011	
FKS 3000, KKS 305 M	315x30

www.dahm.no

Saw Blades for Portable Machines

CMT ORANGE TOOLS™

MACHINE	DxB mm
GRAULE	
AKF F, AKF 4/200	200x40
AKF 2, AKF 4/250, AKF 6/250, KS, TS	250x40
85 N, AGL, AGT, AKF 6/300, Typ 85, ZS 85	300x40
Typ 135, ZS 135, ZS 135 N	350x40
Typ 170, ZS 170, ZS 170 N	420x40
ZS 200	520x50
GÜDE	
GTK 721	205x18
GTK 800	205x20
GKS 1100 P, GRK 210/300,	210x30
GUKS 2100, KT 210	
GFO 1401	216x30
GKS 250 L, GKS 250 T, GRK	250x20
250/300, GRK 250/500	
TK 2500 UG, GFO 1801	254x20
TK 2400 ECO	254x30
GTKS 315	315x30
GWS 400 Eco	400x30
GWS 450 Eco	450x30
FP 600 Plus, GWS 600 EC,	600x30
GWS 600 HM, QWS 600	
DTW 700, DWS 700, DWS 700 Z, GWS 700,	700x30
FP 700 Plus, GWS 700 HM, GWS 700 EC,	
PRS 700/7 HMF, PTW 700/7	
HMF, PWS 700/7 HMF	
HAAGER	
HTK 200	200x30
HKGS 250, HMS 10 RA	250x20
GKS 250 HR, HBTS 10 A	250x30
HTK 300	300x30
HAFFNER	
RF 60	100x20
KSU 40	120x20
KSU 105, KSU 125	125x20
KSU 50	160x20
KSU 110	170x30
KSU 60, KSU 113	180x20
KSU 60 alt	200x30
GL 136	200x20
AKS	210x30
AS 75, KS 75, RS 75	220x30
140, KL 177, KL 178, KSU 118	220x30
HSU 85, KL 176, KS 85, KSU 85,	250x30
SP 187, US 85	
AKS, GS 1, GS 2W, GS 2 D, GS 150, GS 163,	250x30
GS 165, GS 166, KL 140, SP 189, SP 195,	
SP 196, SP 197, SP 198, TGS 161,	
TGS 162, TGS 163, TGS 198	
MK 251 B	300x32
950, GS 146, GS 147, GS 148, GS 155,	330x30
GS 156, GS 157, GS 158, GS 165, GS 166,	
GS 183, GS 183 M, KS 120, KS 155,	
SP 221, SP 223, SP 224, TGS 168, TGS 169,	
TGS 200, TK 42, US 151	
DGS 180, DGS 182, GSM 180, GSA 180	350x30
GS 159, GS 160	340x30
MK 350 Vario	400x32
DGS 123, DGS 124, DGS 180, DGS 181,	500x30
DGS 182, DGS 184, DGS 184 E, DGS 188,	
DGS 185, GS 183, GS 184, GS 188 M,	
GS 188 P, GSA 184 E, KS 155, ZS 640,	
ZS 800	
DGS 187, DGS 202, GS 161,	600x30
GS 162, US 161, US 162 30	
HANNING	
TK 20 N, TK 20 S, TK 200,	200x16
TK 300, ZK 205, HKS 250	250x16
3 VS, HTK 315/1.6, HTK 315/2.1,	315x30
HTK 315/3.0, HTK 315/3 SV, HTK 315/4.0	
HANSEATIC	
PSC 160 D	160x20
HILTI	
WSC 55	160x20
WSC 85	230x30
HERCULES	
KG 205	205x16
TKS 250 UV	250x16
BK 315/1	315x30
HITACHI	
C 5 Y	125x20
C 5, FC 5, FC 5 SA	150x20
C 6, C 6 DA, C 60 A, FC 65 A, FC 6 SA	160x20
C 6 BU, C 6 U, C 6 DD-Akku, FC 6 SB	165x30
C 6 SA, PSU 6	170x30
C 7 U, C 7 BU, FC 7 SA, PSM 7, PSM 7 A,	190x30
PSU 7 C 8 U, C 8 FA, PSM 8, PSU 8	210x30
C 8 FC, C 8 FS	216x30
C 9 U	235x30
PSM 9, PSM 9 A, PSU 9	240x30
U 210	250x30
C 10 FB, C 10 FCA, C 10 FCS, C 10 RA	255x30
C 13 U, PSU 13	335x30
C 15 FC	380x30
HOLZ-HER (REICH)	
Derby 2110, Mosquito 2111, Mosquito 2171	132x30
2260, 2270	140x30
2103, 2104, 2105, 2106, 2107,	160x30
2108, HKU 50	
1563, 2115, 2266, 2271, 2281	170x30
2112, 2272, 2291, HKU 55	180x30
2114, 2116, 2117, 2119, 2126,	190x30
2127, 2269, 2282	
2113, 2292, 2555, HK 201	200x30
2267, 2284, PKS 267	210x30
Leistensäge 2141	216x30
2267, 2274, 2279, 2284, HKU 75, PKS	220x30
2118, 2120, 2171, 2279, 2293, 2294	230x30
2128, 2268, HKD 65	240x30
HKD 85, HKD 275, HKD 1212, PKS 1210,	300x30
PKS 1211, PKS 1213, PKS 1225,	
PKS 1230 303	
HKS 130, HKS 150, HKS 276	350x30
HKS 2136	380x30
HKS 155, HKS 277, HKS B 7 K, BTK 155	400x30
JEPSON	
8219	192x20
9211 D	255x25,4
9312 E, 9430	305x25,4
9314, 9435	355x25,4
KITY	
626	150x20
510, 616, 617, 2617	180x15
0419, 7419, 0618, Kombi 2000,	200x30
Kombi 5023, Junior 6	
618	250x30
1609, 1619, 5619, 6619, 9619 2	70x30
819	315x30
KRESS	
CHKS 6050, CHKS 6055	160x20
CHKS 6060, 1400 HKS, 1500 KS, 1800 KSE	190x20
MAFFEL	
A 35, FS 35, KSS 300, KSP 40	120x20
SF 32, X 40, XE 40	125x20
A 55, B 55, FU 50, KSP 55, KSP 55 F,	160x20
KSS 330, KSS 400, KST 55, MKS 55, MS 55,	
MT 55, PS 52, PSS 3000, PS 3100, X 55,	
XE 55	
KS 320	160x30
Erika 55	180x30
Erika 60, KSP 65, KSP 65 F, MS 65, MKS 65	190x30
B 65, X 72	200x30
AS 65, FUS 65	210x20
MS 75, MKS 75	210x20
Erika 70 E, MKS 85	225x20
KSP 85, KSP 85 FC	230x30
B 82	240x30
Erika 85, MS 85, MKS 85, MKS 85 S	250x30
A 85, Erika 65, FS 65, FU 585, FUS 85	280x30
Erika 70 L, Erika 70 K	290x20
Biberex, MKS 105, Monika,	315x30
TFK 85 L, TKF 85 K	
Biber, FS 85	325x30
MKS 130 EC	330x30
MKS 125, MKS 125 E	355x30
MKS 145, MKS 145 EC	370x30
BK 3, BKS 4, FS 130, FS 130 S, TD 3, VKS 1	400x30
MKS 165, MKS 165 EC, FS 130K	410x30
TDH 4, TDH 425	425x30
BK 4, BKV 4, BKS 5, FSG 165,	450x30
MKS 185 EC, TDH 5, TDH 450	
BKV 5, BKS 6, TDH 5-170	500x30
FSG 200	550x30
FSG 240 K	640x30
MAKITA	
4341 S, BTK 0, KS 0852 S, 61+2, 52 S	150x20
5600 NB, 5600 RDW	160x20
167, 0846 S, 0946 S, 5600 BR, 5603 R,	165x20
5604 R, TK 1256, KS 1155, KST 1157 S,	
KSTE 1357, S-Signal, SBTK 1, SR 1600	
5500 S, 5800 B, 5801 B, 6317 S	180x20
5800 BR, SR 1800	185x20
4346 S, KS 65, KS 1266 S, KS	190x20
1468, KS 4345 S, KSE 1668, TK 5348	
5703 R, 5705 R, 5017 RKB	190x30
Radial-Eudora 5700	200x25
LS 0810, SR 2100	210x25
KGS E 1670 S, KSE 1678 S	210x30
6322 S	220x30
SR 2300, SR 5900 B, SR 5900 BR	235x25
5903 R	235x30
KS 1785, KS 6323 S	240x30
LS 1013, LS 1014	260x25
SR 2600	266x25
5103 R, SR 2600	270x30
5100 BR	335x25
5143 R	355x30
METABO	
F 0520	100x22
4340 S, BHK 2, BHK 3, 4345 S 140 20	140x13
4341 S, BTK 0, 61 + 2, KS 52,	150x20
KS 0846 S, KS 0852 S	
BTK 1, KS 1155 S, Magnum, TK 1256	165x20
6317 S	180x20
KS 655, KS 1266, KS 1468 S,	190x20
KS 4345 S, KS 4346 S, KS5348,	
KSE 1668, Robert	
KGSE 1670, KSE 1678 S-Signal,	210x30
Magnum TK 1066, TKU 225	
6322 S	220x30
KS 1785 S, KS 6323 S	240x30
TK 1633, TKU 1633, TKU 1693	250x30
TK 1688, TK 1688 D	315x30
PANASONIC	
EY 3501	110x20
EY 3530	135x20
PERLES	
25 S	100x12
SC 47 C	140x20
KS 50, Peugot, SC 53 C	150x20
FIP 50 S	180x20
KS 85	230x30
PROTOOL	
CSP 55-2, CSP 56 EQ,	160x20
CSP 56 Q, CSP 68	
CSP 68 E	190x30
CSP 85	240x30
ROBLAND	
K 210 - 260	240x30
X 260	250x30
K 310, X 310	300x30
ROCKWELL	
346, 63416	170x16
315, 4500, 63417	184x16
368, 63418	220x20
SCHEER	
HM 5, HM 6	100x22
MS 50	150x16
MS 45, MS 45 E	150x20
FM	160x16
MS 55	160x20
FM	180x16
MS 65, MKS 65	190x30
MS 70	200x30
MS 80	220x30
MS 85	230x30
FM 10, A 3100, A 4200	240x30
SCHEPPACH	
KG 205	205x18
TS 2000	200x30
Capas 1, Capas 2	216x30
KG 250, TKG 250, TS 2500	250x20
KSE 250, TS 2500, KG 260, TKG	250x30
260, KG 280, TKG 280	
Capas 3, TKG 305 E	305x30
TS 315 GT, TS 400, TS 4010, TKU	315x30
BSH 400	400x30
BSH 500	500x30
SKIL	
22501 B	125
5140 A, 5140 B, 5240	130
532	140
533, 553, 5246, 1800 H, 1850 H	150
416 H, 534, 536, 552 B, 1408 H,	160
1409 H, 1410 H, 1440 H, 5750 A	
77 U, 537 U, 553 B, 553 H,	184
559 U, 574 U, 599 U, 857	
1865, 1866, 5266, 5565, 5566,	190
5666, 5866 A, 1899, 1965 U, 1986	
554 B, 554 H, 825, 858, 1524 H, 1873 H	210
555 H, 1525 H, 1886 H, 1985 U	230
1523 H, 1526 H, 1899 H	260
STAYER	
CP 50	150x20
KS 700, SC 205, TKS 2000	205x18
SC 250, SC 251, SCU 75	250x20
SC 260, SCE 1610, SLL 250	250x30
TD 305	305x25,4
TIP	
HKS 160	160x20
HKS 200	200x16
TKS 250	250x15,8
TGS 250	250x25,4
ULMIA	
1409 B	160x20
1706, 1708	200x16
1710 S, 1710 R	250x15,8
Gecombineerde machines	300x25,4
WEGOMA	
TB 204	105x22
HS 50	150x20
TS 250	250x30
S 4 D, S 4 W	350x30
TS 400	400x30

www.dahm.no

Saw Blade Index

CMT ORANGE TOOLS™

D mm	B mm	APPLICATION	Z	K mm	P mm	α	β	ORDER NO.	PAGE
70	20	Panel Sizing	8+8	2,8-3,6		12°	FLAT	289.070.16H	23
80	20	Panel Sizing	12	3,1-4,0	2,2	10°	CO+FTG	S288.080.12H	22
80	20	Panel Sizing	10+10	2,8-3,6		12°	FLAT	289.080.20H	23
85	15	Abrasive Materials	6	1,8	1,4	12°	TCG	236.085.06G	30
100	20	Panel Sizing	20	3,1-4,0	2,5	5°	CO+5° ATB	288.100.20H	22
100	20	Panel Sizing	10+10	2,8-3,6		12°	FLAT	289.100.20H	23
100	22	Panel Sizing	20	3,1-4,0	2,5	5°	CO+5° ATB	288.100.20K	22
100	22	Panel Sizing	10+10	2,8-3,6		12°	FLAT	289.100.20K	23
100	22	Grooving	6	3,96	3	18°	10°ATB	240.006.04	36
100	22	Grooving	8	3,96	3	15°	10°ATB	240.008.04	36
100	22	Grooving	8	3,96	3,1-3,8	15°	FLAT	241.008.04	36
100	22	Grooving	4	8	6	18°	R30	240.004.04	36
120	20	Two-Sided Melamine	20	3,1-3,7		5°	CONICAL	238.120.20H	20
120	20	Panel Sizing	24	3,1-4,3	2,2	0°	CO+6° ATB	288.720.24H	22
120	20	Panel Sizing	24	3,1-4,0	2,5	5°	CO+5° ATB	288.120.24H	22
120	20	Panel Sizing	24	3,4-4,2	2,5	5°	CO+5° ATB	288.120.24H1	22
120	20	Panel Sizing	12+12	2,8-3,6		11°	5° ATB	289.720.24H	23
120	20	Panel Sizing	12+12	2,8-3,6		12°	FLAT	289.120.24H	23
120	20	Aluminium	36	1,8	1,2	-6° Neg.	TCG	296.120.36H	25
120	20	Portable Machines	18	1,8	1,2	15°	15° ATB	291.120.18H	33
120	20	Portable Machines	36	1,8	1,2	10°	15° ATB	292.120.36H	34
120	20	Portable Machines	40	1,8	1,2	10°	15° ATB	292.120.40H	34
120	22	Panel Sizing	24	3,1-4,3	2,2	0°	CO+6° ATB	288.720.24K	22
120	22	Panel Sizing	24	3,1-4,0	2,5	5°	CO+5° ATB	288.120.24K	22
120	22	Panel Sizing	12+12	2,8-3,6		11°	5° ATB	289.720.24K	23
120	22	Panel Sizing	12+12	2,8-3,6		12°	FLAT	289.120.24K	23
120	50	Panel Sizing	12+12	2,8-3,6		12°	FLAT	289.120.24T	23
125	20	Two-Sided Melamine	20	3,1-3,7		5°	CONICAL	238.125.20H	20
125	20	Panel Sizing	24	3,1-4,3	2,2	0°	CO+6° ATB	288.725.24H	22
125	20	Panel Sizing	24	3,1-4,0	2,5	5°	CO+5° ATB	288.125.24H	22
125	20	Panel Sizing	24	3,4-4,2	2,5	5°	CO+5° ATB	288.125.24H1	22
125	20	Panel Sizing	24	4,3-5,5	3,2	10°	CO+FTG	288.125.24H2	22
125	20	Panel Sizing	12+12	2,8-3,6		11°	5° ATB	289.725.24H	23
125	20	Panel Sizing	12+12	2,8-3,6		12°	FLAT	289.125.24H	23
125	20	Portable Machines	20	2,4	1,4	15°	15° ATB	291.125.20H	33
125	20	Portable Machines	36	2,4	1,4	15°	15° ATB	292.125.36H	34
125	22	Panel Sizing	24	3,1-4,0	2,5	5°	CO+5° ATB	288.125.24K	22
125	22	Panel Sizing	12+12	2,8-3,6		12°	FLAT	289.125.24K	23
125	45	Panel Sizing	24	4,3-5,5	3,2	10°	CO+FTG	288.125.24Q	22
130	20	Portable Machines	20	2,4	1,4	15°	15° ATB	291.130.20H	33
130	20	Portable Machines	36	2,4	1,4	15°	15° ATB	292.130.36H	34
136	20 (+10)	Portable Machines	18	1,5	1	20°	10° ATB + 8° Shear	271.136.18H	28, 30
136	20 (+10)	Portable Machines	36	1,5	1	18°	10° ATB + 8° Shear	272.136.36H	29, 30
136,5	10	Metal	30	1,5	1,2	0°	8° FWF	226.030.05	26, 30
136,5	20	Metal	30	1,5	1,2	0°	8° FWF	226.030.05H	26, 30
140	16	Panel Sizing	24	3,1-4,0	2,2	10°	CO+FTG	Y288.140.24E	22
140	20	Portable Machines	20	2,4	1,4	15°	15° ATB	291.140.20H	33
140	20	Portable Machines	36	2,4	1,4	15°	15° ATB	292.140.36H	34
150	15,87	Grooving		6,35-22,23		-5°	FTG+ATB	230.520.06	35
150	16	Portable Machines	24	2,4	1,4	15°	15° ATB	291.150.24E	33
150	20	Portable Machines	12	2,4	1,4	20°	10° ATB	290.150.12H	31
150	20	Portable Machines	24	2,4	1,4	15°	15° ATB	291.150.24H	33
150	20	Portable Machines	40	2,4	1,4	15°	15° ATB	292.150.40H	34
150	30	Wood	48	3,2	2,2	5°	15° ATB	285.048.06M	13
150	30	Grooving	12	2	1,4	15°	FLAT	240.020.06M	36
150	30	Grooving	12	3	2	15°	FLAT	240.030.06M	36
150	30	Grooving	12	4	3	15°	FLAT	240.040.06M	36
150	30	Grooving	12	5	3	15°	FLAT	240.050.06M	36
150	30	Grooving	12	6	3	15°	FLAT	240.060.06M	36
150	35	Grooving	12	2	1,4	15°	FLAT	240.020.06R	36
150	35	Grooving	12	3	2	15°	FLAT	240.030.06R	36
150	35	Grooving	12	4	3	15°	FLAT	240.040.06R	36
150	35	Grooving	12	5	3	15°	FLAT	240.050.06R	36
150	35	Grooving	12	6	3	15°	FLAT	240.060.06R	36
150	45	Panel Sizing	36	4,3-5,5	3,2	10°	CO+FTG	288.150.36Q	22
150	20 (+16)	Portable Machines	24	1,5	1	18°	10° ATB + 8° Shear	271.150.24H	28
150	20 (+16)	Portable Machines	40	1,5	1	16°	10° ATB + 8° Shear	272.150.40H	29
160	16	Portable Machines	12	2,2	1,6	20°	10° ATB	290.160.12E	31
160	16	Portable Machines	24	2,2	1,6	15°	15° ATB	291.160.24E	33
160	16	Portable Machines	40	2,2	1,6	10°	15° ATB	292.160.40E	34
160	20	Wood	48	2,2	1,6	5°	15° ATB	285.160.48H	13
160	20	Two-Sided Melamine	34	2,6	1,8	10°	HDF	287.034.06H	17

www.dahm.no

D mm	B mm	APPLICATION	Z	K mm	P mm	α	β	ORDER NO.	PAGE
160	20	Portable Machines	40	2,2	1,6	10°	TCG	281.160.40H2	19
160	20	Aluminium	24	2,2	1,6	5°	TCG	284.160.24H	24
160	20	Aluminium	40	2,2	1,6	-6° Neg.	TCG	296.160.40H	25
160	20	Aluminium	56	2,2	1,6	-6° Neg.	TCG	296.160.56H	25
160	20	Metal	30	2	1,6	0°	8° FWF	226.030.06H	26
160	20	Metal	40	1,8	1,4	10°	8° FWF	226.540.06H	26
160	20	Abrasive Materials	4	2,4	1,8	12°	TCG	236.160.04H	31
160	20	Abrasive Materials	10	2,4	1,8	5°	TCG	236.160.10H	31
160	20	Portable Machines	12	2,2	1,6	20°	10° ATB	290.160.12H	31
160	20	Portable Machines	24	2,2	1,4	15°	15° ATB	K16024H-X10	32
160	20	Portable Machines	40	2,2	1,4	10°	15° ATB	K16040H-X10	32
160	20	Wood	24	2,2	1,4	15°	15° ATB	K16024H	32
160	20	Wood	40	2,2	1,4	10°	15° ATB	K16040H	32
160	20	Portable Machines	24	2,2	1,6	15°	15° ATB	291.160.24H	33
160	20	Portable Machines	40	2,2	1,6	10°	15° ATB	292.160.40H	34
160	20	Portable Machines	40	2,2	1,6	10°	TCG	281.160.40H2	34
160	20	Portable Machines	56	2,2	1,6	15°	15° ATB	292.160.56H	34
160	30	Portable Machines	24	2,2	1,6	15°	15° ATB	291.160.24M	33
160	30	Portable Machines	40	2,2	1,6	10°	15° ATB	292.160.40M	34
160	45	Panel Sizing	36	4,3-5,5	3,2	10°	CO+FTG	288.160.36Q	22
160	55	Panel Sizing	36	4,3-5,5	3,2	10°	CO+FTG	288.160.360	22
160	55	Panel Sizing	36	4,7-6,0	3,5	10°	CO+FTG	Y288.160.3602	22
160	20 (+16)	Portable Machines	24	1,7	1,1	18°	10° ATB + 8° Shear	271.160.24H	28
160	20 (+16)	Portable Machines	40	1,7	1,1	16°	10° ATB + 8° Shear	272.160.40H	29
160	20 (+16)	Portable Machines	56	1,7	1,1	12°	10° ATB + 8° Shear	273.160.56H	29
160	20 (Virutex)	Portable Machines	40	2,2	1,6	10°	TCG	281.160.40H	19
160	20 (Virutex)	Portable Machines	40	2,2	1,6	10°	TCG	281.160.40H	34
165	20	Portable Machines	24	2,2	1,6	15°	15° ATB	291.165.24H	33
165	20	Metal	36	1,6	1,2	0°	8° FWF	226.036.06H	26
165	20	Portable Machines	40	2,2	1,6	10°	15° ATB	292.165.40H	34
165	20	Aluminium	40	2,2	1,6	-6° Neg.	TCG	296.165.40H	25
165	20	Portable Machines	56	2,2	1,6	15°	15° ATB	292.165.56H	34
165	20	Aluminium	56	2,2	1,6	-6° Neg.	TCG	296.165.56H	25
165	30	Metal	36	1,6	1,2	0°	8° FWF	226.036.06M	26
165	30	Portable Machines	24	1,7	1,1	18°	10° ATB + 8° Shear	271.165.24M	28, 30
165	30	Portable Machines	24	2,6	1,6	15°	15° ATB	291.165.24M	33
165	30	Portable Machines	40	2,6	1,6	10°	15°_ATB	292.165.40M	34
165	15,87<>	Metal	36	1,6	1,2	0°	8° FWF	226.036.06	26, 30
165	20 (+15,87)	Portable Machines	24	1,7	1,1	18°	10° ATB + 8° Shear	271.165.24H	28, 30
165	20 (+15,87)	Portable Machines	36	1,7	1,1	20°	10° ATB + 8° Shear	272.165.36H	29, 30
170	30	Portable Machines	24	2,6	1,6	20°	10° ATB	291.170.24M	33
170	30	Portable Machines	40	2,6	1,6	15°	15° ATB	292.170.40M	34
180	20	Panel Sizing	36	4,3-5,5	3,2	10°	CO+FTG	Y288.180.36H	22
180	20	Aluminium	40	2,8	2,2	-6° Neg.	TCG	296.180.40H	25
180	20	Abrasive Materials	4	2,4	1,8	12°	TCG	236.180.04H	31
180	20	Portable Machines	24	2,6	1,6	20°	10° ATB	291.180.24H	33
180	20	Portable Machines	40	2,6	1,6	15°	15° ATB	292.180.40H	34
180	30	Wood	56	3,2	2,2	5°	15° ATB	285.056.07M	13
180	30	Panel Sizing	36	4,3-5,5	3,2	10°	CO+FTG	288.180.36M	22
180	30	Portable Machines	12	2,6	1,6	20°	10° ATB	290.180.12M	31
180	30	Portable Machines	24	2,6	1,6	20°	10° ATB	291.180.24M	33
180	30	Portable Machines	40	2,6	1,6	15°	15° ATB	292.180.40M	34
180	30	Grooving	18	3	2	15°	FLAT	240.030.07M	36
180	30	Grooving	18	4	3	15°	FLAT	240.040.07M	36
180	30	Grooving	18	5	3	15°	FLAT	240.050.07M	36
180	30	Grooving	18	6	3	15°	FLAT	240.060.07M	36
180	35	Grooving	18	3	2	15°	FLAT	240.030.07R	36
180	35	Grooving	18	4	3	15°	FLAT	240.040.07R	36
180	35	Grooving	18	5	3	15°	FLAT	240.050.07R	36
180	35	Grooving	18	6	3	15°	FLAT	240.060.07R	36
180	40	Multi-Rip	21+3	2,5	1,8	18°	FLAT	280.021.07S	10
180	45	Panel Sizing	36	4,7-6,0	3,5	10°	CO+FTG	288.180.36Q	22
180	50	Panel Sizing	44	4,3-5,5	3,2	10°	CO+FTG	288.180.44T	22
180	55	Panel Sizing	36	5,0-6,2	3,5	10°	CO+FTG	288.180.360	22
184	16	Portable Machines	24	2,6	1,6	20°	10° ATB	291.184.24E	33
184	16	Portable Machines	40	2,6	1,6	15°	15° ATB	292.184.40E	34
184	30	Portable Machines	24	1,7	1,1	20°	10° ATB + 8° Shear	271.184.24M	28
184	30	Portable Machines	40	1,7	1,1	18°	10° ATB + 8° Shear	272.184.40M	29
184	30	Portable Machines	24	2,6	1,6	20°	10° ATB	291.184.24M	33
184	30	Portable Machines	40	2,6	1,6	15°	15° ATB	292.184.40M	34
184	15,87<>	Metal	48	2	1,6	10°	8° FWF	226.548.07	26
184	15,87<>	Metal	48	2	1,6	0°	8° FWF	226.048.07	26

www.dahm.no

Saw Blade Index

CMT ORANGE TOOLS™

D mm	B mm	APPLICATION	Z	K mm	P mm	α	β	ORDER NO.	PAGE
184	20 (+16+15,87)	Portable Machines	24	1,7	1,1	20°	10° ATB + 8° Shear	271.184.24H	28, 30
184	20 (+16+15,87)	Portable Machines	40	1,7	1,1	18°	10° ATB + 8° Shear	272.184.40H	29, 30
184,5	15,87<>	Abrasive Materials	4	1,8	1,4	12°	TCG	236.004.07	31
190	16	Portable Machines	12	2,6	1,6	20°	10° ATB	290.190.12E	31
190	16	Portable Machines	24	2,6	1,6	20°	10° ATB	291.190.24E	33
190	16	Portable Machines	40	2,6	1,6	15°	15° ATB	292.190.40E	34
190	20	Portable Machines	12	2,6	1,6	20°	10° ATB	290.190.12H	31
190	20	Portable Machines	24	2,6	1,6	20°	10° ATB	291.190.24H	33
190	20	Portable Machines	40	2,6	1,6	15°	15° ATB	292.190.40H	34
190	30	Aluminium	30	2,6	2,2	5°	TCG	284.190.30M	24
190	30	Aluminium	40	2,8	2,2	-6° Neg.	TCG	296.190.40M	25
190	30	Aluminium	64	2,8	2,2	-6° Neg.	TCG	296.190.64M	25
190	30	Metal	40	2	1,6	0°	8° FWF	226.040.07M	26
190	30	Metal	48	1,8	1,4	10°	8° FWF	226.548.07M	26
190	30	Abrasive Materials	4	2,4	1,8	12°	TCG	236.190.04M	31
190	30	Abrasive Materials	12	2,4	1,8	12°	TCG	236.190.12M	31
190	30	Portable Machines	12	2,6	1,6	20°	10° ATB	290.190.12M	31
190	30	Portable Machines	24	2,2	1,4	20°	10° ATB	K19024M-X10	32
190	30	Wood	24	2,2	1,4	20°	10° ATB	K19024M	32
190	30	Wood	40	2,2	1,4	15°	10° ATB	K19040M	32
190	30	Portable Machines	24	2,6	1,6	20°	10° ATB	291.190.24M	33
190	30	Portable Machines	40	2,6	1,6	15°	15° ATB	292.190.40M	34
190	30	Portable Machines	64	2,6	1,6	15°	15°_ATB	292.190.64M	34
190	20 (Festool® FF)	Aluminium	64	2,8	2,2	-6° Neg.	TCG	296.190.64FF	25
190	20 (Festool® FF)	Portable Machines	32	2,6	1,6	10°	10° ATB	291.190.32FF	33
190	20 (Festool® FF)	Portable Machines	48	2,4	1,6	10°	15° ATB	292.190.48FF	34
190	30 (+20+16)	Portable Machines	24	1,7	1,1	20°	10° ATB + 8° Shear	271.190.24M	28
190	30 (+20+16)	Portable Machines	42	1,7	1,1	18°	10° ATB + 8° Shear	272.190.42M	29
190	30 (+20+16)	Portable Machines	64	1,7	1,1	15°	10° ATB + 8° Shear	273.190.64M	29
200	15,87	Grooving		6,35-22,23		-5°	FTG+ATB	230.524.08	35
200	15,87	Grooving		6,35-20,64		-12°	FTG+ATB	230.012.08	35
200	20	Panel Sizing	36	4,3-5,5	3,2	10°	CO+FTG	288.200.36H	22
200	30	Wood	36	3,2	2,2	15°	10° ATB	285.036.08M	12
200	30	Wood	48	3,2	2,2	15°	15° ATB	285.048.08M	12
200	30	Wood	64	3,2	2,2	5°	15° ATB	285.064.08M	13
200	30	Portable Machines	64	3,2	2,2	10°	TCG	281.064.08M	19
200	30	Aluminium	48	2,8	2,2	-6° Neg.	TCG	296.200.48M	25
200	30	Portable Machines	36	1,8	1,2	15°	10° ATB + 8° Shear	271.200.36M	28
200	30	Portable Machines	48	1,8	1,2	15°	10° ATB + 8° Shear	272.200.48M	29
200	30	Portable Machines	24	2,8	1,8	20°	10° ATB	290.200.24M	31
200	30	Portable Machines	36	2,8	1,8	15°	15° ATB	291.200.36M	33
200	30	Portable Machines	48	2,8	1,8	15°	15° ATB	292.200.48M	34
200	30	Grooving		6,35-22,23		-5°	FTG+ATB	230.524.08M	35
200	40	Multi-Rip	21+3	2,5	1,8	18°	FLAT	280.021.08S	10
200	45	Panel Sizing	36	4,7-6,0	3,5	10°	CO+FTG	288.200.36Q	22
200	45	Panel Sizing	36	4,3-5,5	3,2	10°	CO+FTG	Y288.200.36Q2	22
200	65	Panel Sizing	36	4,3-5,5	3,2	10°	CO+FTG	288.200.36J	22
210	25	Portable Machines	36	2,8	1,8	15°	15° ATB	291.210.36L	33
210	25	Portable Machines	48	2,8	1,8	15°	15° ATB	292.210.48L	34
210	30	Aluminium	48	2,8	2,2	-6° Neg.	TCG	296.210.48M	25
210	30	Aluminium	64	2,8	2,2	-6° Neg.	TCG	296.210.64M	25
210	30	Metal	48	2,2	1,8	0°	8° FWF	226.048.08M	26
210	30	Portable Machines	24	2,8	1,8	20°	10° ATB	290.210.24M	31
210	30	Portable Machines	36	2,8	1,8	15°	15° ATB	291.210.36M	33
210	30	Portable Machines	48	2,8	1,8	15°	15° ATB	292.210.48M	34
210	30	Portable Machines	64	2,8	1,8	15°	15° ATB	292.210.64M	34
210	15,87<>	Metal	48	2,2	1,8	0°	8° FWF	226.048.08	26
210	30 (+25)	Portable Machines	36	1,8	1,2	15°	10° ATB + 8° Shear	271.210.36M	28
210	30 (+25)	Portable Machines	48	1,8	1,2	15°	10° ATB + 8° Shear	272.210.48M	29
215	50	Panel Sizing	42	4,3-5,5	3,2	10°	CO+FTG	288.215.42T	22
216	30	Aluminium	40	2,6	2,2	5°	TCG	284.216.40M	24
216	30	Aluminium	64	2,8	2,2	-6°_Neg.	TCG	297.064.09M	25
216	30	Metal	48	2,2	1,8	0°	8° FWF	226.047.09M	26
216	30	Metal	56	1,8	1,4	10°	8° FWF	226.556.09M	26
216	30	Portable Machines	36	1,8	1,2	-5° Neg.	10° ATB + 8° Shear	271.216.36M	28
216	30	Portable Machines	48	1,8	1,2	-5° Neg.	10° ATB + 8° Shear	272.216.48M	29
216	30	Portable Machines	64	1,8	1,2	-5° Neg.	10° ATB + 8° Shear	273.216.64M	29
216	30	Abrasive Materials	14	2,4	1,8	12°	TCG	236.216.14M	31
216	30	Portable Machines	24	2,8	1,8	-5° Neg.	15° ATB	290.216.24M	31
216	30	Portable Machines	24	2,4	1,6	-5° Neg.	15° ATB	K21624M-X10	32
216	30	Portable Machines	48	2,4	1,6	-5° Neg.	15° ATB	K21648M-X10	32
216	30	Wood	24	2,4	1,6	-5°	15° ATB	K21624M	32

www.dahm.no

D mm	B mm	APPLICATION	Z	K mm	P mm	α	β	ORDER NO.	PAGE
216	30	Wood	48	2,4	1,6	-5°	15° ATB	K21648M	32
216	30	Portable Machines	48	2,8	1,8	-5° Neg.	15° ATB	291.216.48M	33
216	30	Portable Machines	64	2,8	1,8	-5° Neg.	15° ATB	292.216.64M	34
216	30	Portable Machines	80	2,8	1,8	-5° Neg.	15° ATB	292.216.80M	34
220	30	Two-Sided Melamine	64	3,2	2,2	-5°	40° ATB	283.064.09M	15
220	30	Two-Sided Melamine	42	3,2	2,2	-6°	HDF	287.043.09M	16
220	30	Two-Sided Melamine	42	3,2	2,2	10°	HDF	287.042.09M	17
220	30	Portable Machines	64	3,2	2,2	10°	TCG	281.064.09M	19
220	30	Two-Sided Melamine	63	3,2	2,2	-3°	FFT	281.063.09M	19
220	30	Portable Machines	24	2,8	1,8	20°	10° ATB	290.220.24M	31
220	30	Portable Machines	36	2,8	1,8	15°	15° ATB	291.220.36M	33
220	30	Portable Machines	48	2,8	1,8	15°	15° ATB	292.220.48M	34
225	30	Aluminium	64	2,8	2,2	-6° Neg.	TCG	296.225.64M	25
225	30	Portable Machines	36	2,8	1,8	20°	15° ATB	291.225.36M	33
225	30	Portable Machines	48	2,8	1,8	10°	15°_ATB	292.225.48M	34
230	30	Aluminium	48	2,8	2,2	-6° Neg.	TCG	296.230.48M	25
230	30	Abrasive Materials	4	2,4	1,8	12°	TCG	236.230.04M	31
230	30	Portable Machines	24	2,8	1,8	20°	10° ATB	290.230.24M	31
230	30	Portable Machines	36	2,8	1,8	15°	15° ATB	291.230.36M	33
230	30	Portable Machines	48	2,8	1,8	15°	15° ATB	292.230.48M	34
230	30	Portable Machines	64	2,8	1,8	15°	15°_ATB	292.230.64M	34
235	25	Portable Machines	24	2,8	1,8	20°	10° ATB	290.235.24L	31
235	25	Portable Machines	36	2,8	1,8	15°	15° ATB	291.235.36L	33
235	25	Portable Machines	48	2,8	1,8	15°	15° ATB	292.235.48L	34
235	30	Aluminium	48	2,8	2,2	-6° Neg.	TCG	296.235.48M	25
235	30	Metal	48	2,2	1,8	0°	8° FWF	226.048.09M	26
235	30	Portable Machines	24	2,8	1,8	20°	10° ATB	290.235.24M	31
235	30	Portable Machines	36	2,8	1,8	15°	15° ATB	291.235.36M	33
235	30	Portable Machines	48	2,8	1,8	15°	15° ATB	292.235.48M	34
235	30 (+25)	Portable Machines	36	2,4	1,6	18°	10° ATB + 8° Shear	271.235.36M	28
235	30 (+25)	Portable Machines	48	2,4	1,6	18°	10° ATB + 8° Shear	272.235.48M	29
240	30	Portable Machines	24	2,8	1,8	20°	10° ATB	290.240.24M	31
240	30	Portable Machines	36	2,8	1,8	15°	15° ATB	291.240.36M	33
240	30	Portable Machines	48	2,8	1,8	15°	15° ATB	292.240.48M	34
250	20	Wood	40	3,2	2,2	15°	10° ATB	285.040.10H	12
250	20	Garden	20	2,2	1,4	15°	10°_ATB	298.250.20H	24
250	20	Wood	40	3,2	2,2	15°	10° ATB	285.040.10H	33
250	25,4	Garden	20	2,2	1,4	15°	10°_ATB	298.250.20	24
250	30	Multi-Rip	20+4	3,2	2,2	65	10°_ATB	279.020.10M	9
250	30	Abrasive Materials	16	2,8	1,8	15°	5° ATB	286.016.10M	11
250	30	Portable Machines	24	2,8	1,8	20°	10° ATB	290.250.24M	11
250	30	Wood	40	3,2	2,2	15°	10° ATB	285.040.10M	12
250	30	Wood	48	3,2	2,2	15°	10° ATB	285.048.10M	12
250	30	Wood	60	3,2	2,2	10°	15° ATB	285.060.10M	12, 34
250	30	Wood	80	3,2	2,2	5°	15° ATB	285.080.10M	13
250	30	Wood	80	3	2,5	10°	20°_ATB	285.580.10M	13
250	30	Wood	40	3,2	2,2	15°	10° ATB	285.640.10M	14
250	30	Wood	60	3,2	2,2	10°	15° ATB	285.660.10M	14
250	30	Two-Sided Melamine	80	3,2	2,2	5°	15° ATB	285.680.10M	14
250	30	Two-Sided Melamine	80	3,2	2,2	-2°	40° ATB	283.080.10M	15
250	30	Two-Sided Melamine	80	3,2	2,2	-2°	38° ATB	283.680.10M	15
250	30	Two-Sided Melamine	80	3,2	2,2	15°	1FTG+4ATB	274.080.10M	16
250	30	Two-Sided Melamine	48	3,2	2,2	-6°	HDF	287.049.10M	16
250	30	Two-Sided Melamine	48	3,2	2,2	10°	HDF	287.648.10M	17
250	30	Two-Sided Melamine	48	3,2	2,2	10°	HDF	287.048.10M	17
250	30	Two-Sided Melamine	80	3,2	2,2	5°	TCG	281.680.10M	18
250	30	Two-Sided Melamine	78	3,2	2,2	10°	FFT	295.078.10M	18
250	30	Portable Machines	60	3,2	2,2	10°	TCG	281.060.10M	19
250	30	Portable Machines	80	3,2	2,2	10°	TCG	281.080.10M	19
250	30	Two-Sided Melamine	60	3,2	2,2	-3°	FFT	281.061.10M	19
250	30	Two-Sided Melamine	81	3,2	2,2	-3°	FFT	281.081.10M	19
250	30	Two-Sided Melamine	48	3,2	2,2	10°	45° TCG	237.048.10M	20
250	30	Portable Machines	60	3,2	2,2	10°	TCG	281.060.10M	21
250	30	Portable Machines	80	3,2	2,2	10°	TCG	281.080.10M	21
250	30	Aluminium	80	3,2	2,5	-6°_Neg.	TCG	297.080.10M	25
250	30	Metal	72	2,2	1,8	10°	8° FWF	226.572.10M	26
250	30	Corian®	72	3,2	2,5	0°	MTCG	223.072.10M	27
250	30	Corian®	80	2,8	2,2	-3°	MATB	222.080.10M	27
250	30	Portable Machines	24	2,4	1,6	20°	10° ATB + 8° Shear	271.250.24M	28
250	30	Portable Machines	42	2,4	1,6	18°	10° ATB + 8° Shear	271.250.42M	28
250	30	Portable Machines	60	2,4	1,6	15°	10° ATB + 8° Shear	272.250.60M	29
250	30	Portable Machines	80	2,4	1,6	12°	10° ATB + 8° Shear	273.250.80M	29

www.dahm.no

Saw Blade Index

CMT ORANGE TOOLS™

D mm	B mm	APPLICATION	Z	K mm	P mm	α	β	ORDER NO.	PAGE
250	30	Abrasive Materials	16	2,4	1,8	12°	TCG	236.250.16M	31
250	30	Portable Machines	24	2,8	1,8	20°	10°_ATB	290.250.24M	31
250	30	Portable Machines	40	2,6	1,8	15°	10° ATB	K25040M-X05	32
250	30	Wood	24	2,6	1,8	20°	10° ATB	K25024M	32
250	30	Wood	40	2,6	1,8	15°	10° ATB	K25040M	32
250	30	Wood	40	3,2	2,2	15°	10° ATB	285.040.10M	33
250	32	Aluminium	80	3,2	2,5	5°	TCG	284.080.10P	24
250	32	Aluminium	80	3,2	2,5	-6°_Neg.	TCG	297.080.10P	25
250	35	Wood	40	3,2	2,2	15°	10° ATB	285.040.10R	12
250	35	Wood	60	3,2	2,2	10°	15° ATB	285.060.10R	12
250	35	Wood	80	3,2	2,2	5°	15° ATB	285.080.10R	13
250	70	Multi-Rip	20+4	3,2	2,2	65	10°_ATB	279.020.10V	9
250	70	Multi-Rip	20+4	2,7	1,8	18°	10° ATB	280.020.10V	10
250	80	Multi-Rip	20+4	3,2	2,2	65	10°_ATB	279.020.10W	9
250	80	Multi-Rip	20+4	2,7	1,8	18°	10° ATB	280.020.10W	10
254	15,87	Metal	48	2,2	1,8	0°	8° FWF	226.048.10	26
254	15,87	Metal	60	2,2	1,8	0°	8° FWF	226.060.10	26
254	15,87	Metal	72	2,2	1,8	10°	8° FWF	226.572.10	26
254	15,87	Abrasive Materials	6	2,2	1,6	12°	TCG	236.006.10	31
254	30	Wood	48	2,4	1,8	- 5° Neg.	15° ATB	294.048.10M	12
254	30	Wood	60	2,4	1,8	- 5° Neg.	15° ATB	294.060.10M	12
254	30	Aluminium	80	3,2	2,5	-5°_Neg.	TCG	297.081.10M	25
254	30	Metal	60	2,2	1,8	0°	8° FWF	226.060.10M	26
260	30	Wood	48	2,8	1,8	15°	10° ATB	285.048.11M	12
260	30	Wood	60	2,8	1,8	10°	15° ATB	285.060.11M	12, 34
260	30	Wood	60	2,5	1,8	- 5° Neg.	15° ATB	294.060.11M	12
260	30	Aluminium	80	2,8	2,2	-6°_Neg.	TCG	297.080.11M	25
260	30	Portable Machines	28	2,8	1,8	20°	10°_ATB	290.260.28M	31
260	30	Wood	48	2,8	1,8	15°	10° ATB	285.048.11M	33
270	30	Portable Machines	28	2,8	1,8	20°	10° ATB	290.270.28M	11
270	30	Wood	42	2,8	1,8	15°	15° ATB	291.270.42M	12
270	30	Wood	28	2,8	1,8	20°	10°_ATB	290.270.28M	31
270	30	Portable Machines	42	2,8	1,8	15°	15°_ATB	291.270.42M	33
275	20	Wood	42	3,2	2,2	15°	10° ATB	285.042.11H	12
280	30	Wood	64	2,8	1,8	10°	15° ATB	295.064.11M	12
280	30	Aluminium	64	3,2	2,5	-6°_Neg.	TCG	297.064.11M	25
300	20	Wood	48	3,2	2,2	15°	10° ATB	285.048.12H	12
300	30	Multi-Rip	24+4	3,2	2,2	80	10°_ATB	279.024.12M	9
300	30	Multi-Rip	28	3,2	2,2	18°	10°_ATB	278.028.12M	9
300	30	Multi-Rip	24+4	4	2,8	18°	10°_ATB	277.024.12M	10
300	30	Abrasive Materials	20	2,8	1,8	15°	5° ATB	286.020.12M	11
300	30	Abrasive Materials	48	3,2	2,2	15°	10° ATB	286.048.12M	11
300	30	Wood	24	3,2	2,2	20°	10° ATB	293.024.12M	11
300	30	Wood	36	3,2	2,2	15°	10° ATB	285.036.12M	12
300	30	Wood	48	3,2	2,2	15°	10° ATB	285.048.12M	12
300	30	Wood	60	3,2	2,2	15°	10° ATB	285.060.12M	12
300	30	Wood	72	3,2	2,2	10°	15° ATB	285.072.12M	12
300	30	Wood	96	3,2	2,2	5°	15° ATB	285.096.12M	13
300	30	Wood	96	3	2,5	10°	20°_ATB	285.596.12M	13
300	30	Wood	48	3,2	2,2	15°	10° ATB	285.648.12M	14
300	30	Wood	72	3,2	2,2	10°	15° ATB	285.672.12M	14
300	30	Two-Sided Melamine	96	3,2	2,2	5°	15° ATB	285.696.12M	14
300	30	Two-Sided Melamine	96	3,2	2,2	2°	40° ATB	283.096.12M	15
300	30	Two-Sided Melamine	96	3,2	2,2	2°	38° ATB	283.696.12M	15
300	30	Two-Sided Melamine	100	3,2	2,2	15°	1FTG+4ATB	274.100.12M	16
300	30	Two-Sided Melamine	72	3,2	2,2	10°	TCG	281.672.12M	18
300	30	Two-Sided Melamine	96	3,2	2,2	5°	TCG	281.696.12M	18
300	30	Two-Sided Melamine	96	3,2	2,2	10°	FFT	295.096.12M	18
300	30	Portable Machines	72	3,2	2,2	10°	TCG	281.072.12M	19
300	30	Portable Machines	96	3,2	2,2	10°	TCG	281.096.12M	19
300	30	Two-Sided Melamine	72	3,2	2,2	-3°	FFT	281.073.12M	19
300	30	Two-Sided Melamine	96	3,2	2,2	-3°	FFT	281.097.12M	19
300	30	Two-Sided Melamine	60	3,2	2,2	10°	45° TCG	237.060.12M	20
300	30	Two-Sided Melamine	96	3,2	2,2	15°	45° TCG	237.096.12M	20
300	30	Two-Sided Melamine	60	4,4	3,2	16°	TCG	282.060.12M	21
300	30	Two-Sided Melamine	72	3,2	2,2	10°	TCG	281.072.12M	21
300	30	Two-Sided Melamine	96	3,2	2,2	10°	TCG	281.096.12M	21
300	30	Aluminium	96	3,2	2,5	-6°_Neg.	TCG	297.096.12M	25
300	30	Metal	80	2,2	1,8	10°	8° FWF	226.580.12M	26
300	30	Corian®	84	3,2	2,5	0°	MTCG	223.084.12M	27
300	30	Corian®	96	2,8	2,2	-3°	MATB	222.096.12M	27
300	30	Portable Machines	24	2,6	1,8	22°	10° ATB + 8° Shear	271.300.24M	28

www.dahm.no

Saw Blade Index

D mm	B mm	APPLICATION	Z	K mm	P mm	α	β	ORDER NO.	PAGE
300	30	Portable Machines	48	2,6	1,8	18°	10° ATB + 8° Shear	271.300.48M	28
300	30	Portable Machines	72	2,6	1,8	15°	10° ATB + 8° Shear	272.300.72M	29
300	30	Portable Machines	96	2,6	1,8	12°	10° ATB + 8° Shear	273.300.96M	29
300	30	Abrasive Materials	20	2,4	1,8	12°	TCG	236.300.20M	31
300	32	Aluminium	96	3,2	2,5	5°	TCG	284.096.12P	24
300	32	Aluminium	96	3,2	2,5	-6°_Neg.	TCG	297.096.12P	25
300	35	Wood	24	3,2	2,2	20°	10° ATB	293.024.12R	11
300	35	Wood	48	3,2	2,2	15°	10° ATB	285.048.12R	12
300	35	Wood	72	3,2	2,2	10°	15° ATB	285.072.12R	12
300	35	Wood	96	3,2	2,2	5°	15° ATB	285.096.12R	13
300	50	Panel Sizing	48	4,3-5,5	3,2	10°	CO+FTG	288.300.48T	22
300	60	Multi-Rip	24+4	3,2	2,2	80	10°_ATB	279.024.12U	9
300	65	Panel Sizing	72	4,3-5,5	3,2	10°	CO+FTG	288.300.72J	22
300	70	Multi-Rip	24+4	3,2	2,2	80	10°_ATB	279.024.12V	9
300	70	Multi-Rip	28	3,2	2,2	18°	10°_ATB	278.028.12V	9
300	70	Multi-Rip	24+4	2,7	1,8	18°	10° ATB	280.024.12V	10
300	70	Multi-Rip	24+4	4	2,8	18°	10°_ATB	277.024.12V	10
300	75	Two-Sided Melamine	60	4,4	3,2	16°	TCG	282.060.12X	21
300	80	Multi-Rip	24+4	3,2	2,2	80	10°_ATB	279.024.12W	9
300	80	Multi-Rip	24+4	2,7	1,8	18°	10° ATB	280.024.12W	10
300	80	Multi-Rip	24+4	4	2,8	18°	10°_ATB	277.024.12W	10
300	80	Two-Sided Melamine	60	4,4	3,2	16°	TCG	282.060.12W	21
303	30	Two-Sided Melamine	60	3,2	2,2	-6°	HDF	287.061.12M	16
303	30	Two-Sided Melamine	60	3,2	2,2	10°	HDF	287.660.12M	17
303	30	Two-Sided Melamine	60	3,2	2,2	10°	HDF	287.060.12M	17
305	25,4	Metal	60	2,2	1,8	0°	8° FWF	226.060.12	26
305	25,4	Metal	80	2,2	1,8	0°	8° FWF	226.080.12	26
305	25,4	Metal	80	2,2	1,8	10°	8° FWF	226.580.12	26
305	25,4	Abrasive Materials	8	2,2	1,6	12°	TCG	236.008.12	31
305	30	Wood	28	2,8	1,8	20°	10° ATB	293.028.22M	11
305	30	Wood	54	2,8	1,8	-5° Neg.	15° ATB	294.054.22M	12
305	30	Wood	72	3,2	2,2	10°	15° ATB	285.072.22M	13
305	30	Wood	72	3,2	2,2	-5° Neg.	15° ATB	294.072.22M	13
305	30	Aluminium	96	3,2	2,5	-6° Neg.	TCG	297.096.13M	25
305	30	Metal	80	2,2	1,8	0°	8° FWF	226.080.12M	26
305	30	Wood	40	2,8	2	-5°	10° ATB	K30540M	32
305	30	Wood	60	2,8	2	-5°	10° ATB	K30560M	32
315	30	Abrasive Materials	24	3,2	2,2	15°	5° ATB	286.024.13M	11
315	30	Wood	28	3,2	2,2	20°	10° ATB	293.028.12M	11
315	30	Wood	36	3,2	1,8	15°	5° ATB	285.036.13M	11
315	30	Wood	54	3,2	2,2	15°	10° ATB	294.054.12M	12
315	30	Wood	72	3,2	2,2	10°	15° ATB	285.072.13M	13
315	30	Aluminium	96	3,2	2,5	-6° Neg.	TCG	297.096.23M	25
320	65	Two-Sided Melamine	60	4,4	3,2	16°	TCG	Y282.060.13J	21
320	65	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.13J	21
330	30	Aluminium	96	3,2	2,5	-6°_Neg.	TCG	297.096.33M	25
330	32	Aluminium	96	3,2	2,5	-6°_Neg.	TCG	297.096.33P	25
350	30	Multi-Rip	28+4	3,5	2,5	105	10°_ATB	279.028.14M	9
350	30	Multi-Rip	36	3,5	2,5	18°	10°_ATB	278.036.14M	9
350	30	Multi-Rip	24+6	4,2	2,8	18°	10°_ATB	277.024.14M	10
350	30	Abrasive Materials	24	3,2	2,2	15°	5° ATB	286.024.14M	11
350	30	Wood	28	3,5	2,5	20°	10° ATB	293.028.14M	11
350	30	Wood	54	3,5	2,5	15°	10° ATB	285.054.14M	12
350	30	Wood	72	3,5	2,5	15°	10° ATB	285.072.14M	12
350	30	Wood	84	3,5	2,5	10°	15° ATB	285.084.14M	12
350	30	Wood	108	3,5	2,5	5°	15° ATB	285.108.14M	13
350	30	Wood	54	3,5	2,5	15°	10° ATB	285.654.14M	14
350	30	Wood	84	3,5	2,5	10°	15° ATB	285.684.14M	14
350	30	Two-Sided Melamine	108	3,5	2,5	5°	15° ATB	285.708.14M	14
350	30	Two-Sided Melamine	108	3,5	2,5	5°	40° ATB	283.108.14M	15
350	30	Two-Sided Melamine	108	3,5	2,5	5°	TCG	281.708.14M	18
350	30	Two-Sided Melamine	108	3,5	2,5	10°	FFT	295.108.14M	18
350	30	Portable Machines	84	3,5	2,5	10°	TCG	281.084.14M	19
350	30	Portable Machines	84	3,5	2,5	10°	TCG	281.684.14M	18
350	30	Portable Machines	108	3,5	2,5	10°	TCG	281.108.14M	19
350	30	Two-Sided Melamine	72	3,5	2,4	15°	45° TCG	237.072.14M	20
350	30	Two-Sided Melamine	54	4,4	3,2	16°	TCG	282.054.14M	21
350	30	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.14M	21
350	30	Two-Sided Melamine	108	3,5	2,5	10°	TCG	281.108.14M	21
350	30	Aluminium	108	3,2	2,5	-6°_Neg.	TCG	297.108.14M	25
350	32	Aluminium	92	3,2	2,5	5°	TCG	284.092.14P	24
350	32	Aluminium	108	3,2	2,5	5°	TCG	284.108.14P	24

www.dahm.no

Saw Blade Index


CMT ORANGE TOOLS™

D mm	B mm	APPLICATION	Z	K mm	P mm	α	β	ORDER NO.	PAGE
350	32	Aluminium	108	3,2	2,5	-6°_Neg.	TCG	297.108.14P	25
350	35	Wood	28	3,5	2,5	20°	10° ATB	293.028.14R	11
350	35	Wood	54	3,5	2,5	15°	10° ATB	285.054.14R	12
350	35	Wood	84	3,5	2,5	10°	15° ATB	285.084.14R	12
350	35	Wood	108	3,5	2,5	5°	15° ATB	285.108.14R	13
350	50	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.14T	21
350	60	Multi-Rip	28+4	3,5	2,5	105	10°_ATB	279.028.14U	9
350	60	Two-Sided Melamine	72	4,4	3,2	16°	TCG	Y282.072.14U	21
350	70	Multi-Rip	28+4	3,5	2,5	105	10°_ATB	279.028.14V	9
350	70	Multi-Rip	36	3,5	2,5	18°	10°_ATB	278.036.14V	9
350	70	Multi-Rip	24+6	4,2	2,8	18°	10°_ATB	277.024.14V	10
350	75	Two-Sided Melamine	54	4,4	3,2	16°	TCG	282.054.14X	21
350	75	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.14X	21
350	80	Multi-Rip	28+4	3,5	2,5	105	10°_ATB	279.028.14W	9
350	80	Two-Sided Melamine	54	4,4	3,2	16°	TCG	282.054.14W	21
350	80	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.14W	21
355	25,4	Metal	72	2,2	1,8	0°	8° FWF	226.072.14	26
355	25,4	Metal	90	2,2	1,8	0°	8° FWF	226.090.14	26
355	25,4	Metal	90	2,2	1,8	10°	8° FWF	226.590.14	26
355	30	Two-Sided Melamine	72	4,4	3,2	16°	TCG	S282.03556	21
355	30	Metal	90	2,2	1,8	0°	8° FWF	226.090.14M	26
355	30	Metal	90	2,2	1,8	10°	8° FWF	226.590.14M	26
355	65	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.14J2	21
380	60	Two-Sided Melamine	72	4,8	3,5	16°	TCG	282.072.15U	21
380	80	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.15W	21
400	30	Multi-Rip	28+6	4	2,8	120	10°_ATB	279.028.16M	9
400	30	Abrasive Materials	28	3,2	2,2	15°	5° ATB	286.028.16M	11
400	30	Wood	36	3,5	2,5	20°	10° ATB	285.036.16M	11
400	30	Wood	48	3,5	2,5	20°	10° ATB	285.048.16M	12
400	30	Wood	60	3,5	2,5	10°	15° ATB	285.060.16M	12
400	30	Wood	60	3,5	2,5	15°	10° ATB	285.660.16M	14
400	30	Two-Sided Melamine	60	4,4	3,2	16°	TCG	282.060.16M	21
400	30	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.16M	21
400	30	Wood	96	3,5	2,5	10°	15° ATB	285.096.16M	13
400	30	Wood	96	3,5	2,5	10°	15° ATB	285.696.16M	14
400	30	Wood	120	3,5	2,5	10°	15° ATB	285.120.16M	13
400	30	Aluminium	120	3,8	3,2	-6° Neg.	TCG	297.120.16M	25
400	32	Aluminium	96	3,8	3,2	5°	TCG	284.096.16P	24
400	32	Aluminium	108	3,8	3,2	-6° Neg.	TCG	297.108.16P	25
400	60	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.16U	21
400	70	Multi-Rip	28+6	4	2,8	120	10°_ATB	279.028.16V	9
400	75	Two-Sided Melamine	60	4,4	3,2	16°	TCG	282.060.16X	21
400	75	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.16X	21
400	80	Two-Sided Melamine	60	4,4	3,2	16°	TCG	282.060.16W	21
400	80	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.16W	21
420	32	Aluminium	96	3,8	3,2	5°	TCG	284.096.17P	24
430	75	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.17X	21
430	80	Two-Sided Melamine	72	4,4	3,2	16°	TCG	282.072.17W2	21
450	30	Abrasive Materials	32	3,8	2,8	15°	5° ATB	286.032.18M	11
450	30	Wood	36	3,8	2,8	20°	10° ATB	285.036.18M	11
450	30	Wood	54	3,8	2,8	15°	15° ATB	285.054.18M	12
450	30	Wood	66	3,8	2,8	10°	15° ATB	285.066.18M	12
450	30	Aluminium	140	3,8	3,2	-6° Neg.	TCG	Y297.140.18M	25
450	32	Aluminium	108	3,8	3,2	5°	TCG	284.108.18P	24
450	32	Aluminium	108	3,8	3,2	-6° Neg.	TCG	297.108.18P	25
450	60	Two-Sided Melamine	72	4,8	3,5	16°	TCG	282.072.18U	21
450	80	Two-Sided Melamine	72	4,8	3,5	16°	TCG	282.072.18W2	21
500	30	Abrasive Materials	36	3,8	2,8	15°	5° ATB	286.036.20M	11
500	30	Wood	44	4	2,8	20°	10° ATB	285.044.20M	11
500	30	Wood	60	3,8	2,8	15°	15° ATB	285.060.20M	12
500	30	Wood	72	3,8	2,8	10°	15° ATB	285.072.20M	12
500	32	Aluminium	120	4	3,2	5°	TCG	284.120.20P	24
500	32	Aluminium	120	4	3,2	-6°_Neg.	TCG	297.120.20P	25
500	60	Two-Sided Melamine	72	4,8	3,5	16°	TCG	282.072.20U	21
500	80	Two-Sided Melamine	72	4,8	3,5	16°	TCG	Y282.072.20W	21
550	30	Abrasive Materials	40	4,2	3,2	15°	5°_ATB	286.040.22M	11
550	30	Wood	60	4,2	3,2	10°	15° ATB	285.060.22M	12
550	30	Wood	96	4,2	3,2	10°	15° ATB	285.096.22M	12
550	100	Two-Sided Melamine	72	5,2	3,5	16°	TCG	282.072.22A	21
600	30	Abrasive Materials	40	4,2	3,2	15°	5° ATB	286.040.24M	11
600	30	Wood	66	4,2	3,2	10°	15° ATB	285.066.24M	12
700	30	Abrasive Materials	46	4,4	3,2	15°	5° ATB	286.046.28M	11
700	30	Wood	72	4,4	3,2	10°	15° ATB	285.072.28M	12

www.dahm.no

QUALITY MATERIALS FOR OUTSTANDING PERFORMANCE

Produced by following state-of-the-art processes and by using high-tech machines, these jig saw blades have been specifically designed for precise cuts on soft & hardwood, plywood, OSB, laminates, plastics, HPL, multiplex panels, metals, ferrous & non-ferrous materials, aluminium, fiberglass and also stainless steel. These are made of four different materials.



What else? Geometry is important!

HCS

HCS (High Carbon Steel)
For use when cutting softwood, wood fiberboard and soft plastic.

BIM


BIM (Bimetal)
Suitable for use in hardwood, abrasive wooden and harder materials such as non-ferrous and ferrous metals. This special bond of HCS and HSS fits the most diverse needs. Resistant to shank breakage thanks to its flexibility, this material lasts much longer than HCS and HSS. An excellent value for your money.

HSS


HSS (High Speed Steel)
For use when cutting harder materials, such as metals, aluminium and non-ferrous metals.

HW


Tungsten Carbide Tipped
Use for cutting fibre cement panel, plasterboard, MDF, GRP (Fiberglass), Eternit®.



Milled & Side Set Teeth
Jig saw blades featuring this kind of geometry feature a quick rough cut into soft/hardwood, aluminium, plastic and non-ferrous metals.



Milled & Wavy Set Teeth
Suitable for fine straight cuts into plywood, soft steel, aluminium, non-ferrous metals and plastic.



Ground & Side Set Teeth
To be used for quick cuts in wood.



Ground & Taper Ground Teeth
This geometry delivers fine and clear cuts in wood and plastic.

// Wood

// Wood & Metal

// Metal

// Special

THE RIGHT BLADE FOR THE BEST RESULTS!

Quick reference charts and pictograms help you choose the right blade for your application.

www.dahm.no

Guide to Choosing the Most Suitable Jig Saw Blade

CMT ORANGE TOOLS™

Series	Material	Thickness mm	Line	Fine Straight	Coarse Straight	Fine Curve	Coarse Curve	Page
WOOD	Softwood	1,5~15	Fine			JT101AO		50
		2~15	Basic			JT119BO		49
		3~65	Fine, Splinter-Free	JT234X				51
		3~30	Fine	JT101B				50
		3~30	Fine, Splinter-Free	JT101BR				50
		4~60	Basic		JT111C			49
		5~60	Fast		JT144D		JT244D - JT244DDC	49
		5~100	Fast		JT344D			50
		7~55	Fine	JT101D				51
		7~65	Fine	JT301CD				51
	Hardwood	1,5~15	Fine			JT101AO		50
		3~30	Fine	JT101B				50
		3~30	Fine, Splinter-Free	JT101BR				50
		3~65	Fine, Splinter-Free	JT234X				51
		5~60	Fast		JT144D		JT244D - JT244DDC	49
		5~100	Fast		JT344D			50
		7~55	Fine	JT101D				51
		7~65	Fine	JT301CD				51
	OSB	2~15	Basic			JT119BO		49
		3~30	Fine	JT101B				50
		4~60	Basic		JT111C			49
		5~60	Fast		JT144D		JT244D - JT244DDC	49
		7~55	Fine	JT101D				51
	Plywood	1,5~15	Fine			JT101AO		50
		2~15	Basic			JT119BO		49
		3~30	Fine	JT101B				50
		3~30	Fine, Splinter-Free	JT101BR				50
		3~65	Fine, Splinter-Free	JT234X				51
		4~60	Basic		JT111C			49
		5~60	Fast		JT144D		JT244D - JT244DDC	49
		5~100	Fast		JT344D			50
		7~55	Fine	JT101D				51
	Construction Wood	<30	Fine	JT101B				50
		3~65	Fine, Splinter-Free	JT234X				51
		<100	Fast		JT344D			50
		<135	Fast		JT744D			50
	Chipboard	2~15	Basic			JT119BO		49
		3~30	Fine	JT101B		JT101AO		50
		3~65	Fine, Splinter-Free	JT234X				51
		4~60	Basic		JT111C			49
		5~60	Fast		JT144D		JT244D - JT244DDC	49
	Laminated panels Kitchen Tops Worktops	1,5~15	Fine			JT101AO		50
		1,5~15	Fine, Long Life	JT101BIF				51
		3~30	Fine	JT101B				50
		3~30	Fine, Splinter-Free	JT101BR				50
		3~65	Fine, Splinter-Free	JT234X				51
METAL	Sheet metals	1~3	Basic	JT118A		JT218A		52
		1,5~10	Fast, Long life	JT123X				52
		2,5~6	Basic	JT118B				52
	Aluminium, non-ferrous	<30	Fast	JT127D				52
		1,5~10	Fast	JT123X				52
	Pipes	<30	Fast	JT123X				52
	Inox Sheets	1,5~3	Fast	JT123X				52
	Sandwich Material	<120	Fast, Flexible	JT718BF				52
PLASTIC	GRP (Fiberglass)	<30	Fast	JT127D				52
	Plastic (PP, PE, PVC, PA, PS)	<30	Fine	JT101D				51
		<30	Fast	JT123X				52
		7~65	Fine	JT301CD				51
SPECIAL	Plasterboard	5~50	Special		JT141HM			51
		5~80	Special		JT341HM			51
	GRP (Fiberglass)	<80	Special		JT341HM			51
	Fibre cement boards	5~50	Special		JT141HM			51
		5~80	Special		JT341HM			51

www.dahm.no

JT119BO





Curve cuts on softwood (2 ~ 15mm), plywood, OSB.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	50	76	2	**JT119BO-5**



JT111C





Fast coarse cuts on softwood (4 ~ 60mm), plywood, OSB.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	75	100	3	**JT111C-5**




JT144D





Very fast cuts, straight and coarse, on hard/soft woods (5 ~ 60mm), plywood, OSB. Plunge cutting.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	75	100	4	**JT144D-5**
25	75	100	4	**JT144D-25**
100	75	100	4	**JT144D-100**




JT244D





Fast, curve, coarse cut on soft and hardwood from 5mm to 60mm, plywood, OSB. Plunge cutting.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	75	100	4	**JT244D-5**



JT244DDC








Fast, curve, coarse cut on soft and hardwood from 5mm to 60mm, plywood, OSB. Plunge cutting. Special “DUO” (double) cut for fast curve.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	75	100	4	**JT244DDC-5**



www.dahm.no

Jig Saw Blades

JT344D





Very fast cuts, straight and coarse on thick construction timber, hard/soft woods (5 ~ 100mm), plywood, OSB.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	110	132	4	**JT344D-5**




JT744D






Very fast cuts, straight and coarse on thick construction timber, hard/soft woods (5 ~ 135mm) and sandwich material.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
3	155	180	4	**JT744D-3**




JT101AO






Curved cuts, fine finishing on both sides of surface on hard/soft woods, plywood, chipboard, MDF, double sided laminates (1,5 ~ 15mm).

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	50	76	1,4	**JT101AO-5**




JT101B






Fine straight cuts on hard/soft woods, plywood, OSB and plastics (3 ~ 30mm). Plunge cutting.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	75	100	2,5	**JT101B-5**
25	75	100	2,5	**JT101B-25**



JT101BR





Straight cuts, fine finishing on surfaces, hard/soft woods, plywood, OSB, laminated panels, plastics (3 ~ 30mm). Reverse tooth.


Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	75	100	2,5	**JT101BR-5**
25	75	100	2,5	**JT101BR-25**



www.dahm.no


JT101D






Good straight cuts on hard/soft woods, plywood, OSB, plastics (7 ~ 55mm). Plunge cutting.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	75	100	4	**JT101D-5**




JT301CD






Straight cuts, fine finishing, on hard/soft woods, plywood, laminates, plastics (7 ~ 65mm).

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	90	116	3	**JT301CD-5**



JT234X





Extra-clean splinter-free straight cuts on hard/soft woods, plywood, OSB, laminates (3 ~ 65mm).

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	90	116	2-3	**JT234X-5**



JT101BIF





Splinter-free cuts. For all laminates, HPL and multiplex panels (1,5 ~ 15mm).

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	58	83	1,7	**JT101BIF-5**



JT141HM





Plasterboard, fibre cement boards (<50mm). Glass fibre reinforced plastic/epoxy (5 ~ 20mm), Eternit®, MDF, HDF.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	75	100	4,3	**JT141HM-3**




JT341HM





Plasterboard, fibre cement boards (<80mm). Glass fibre reinforced plastic/epoxy (5 ~ 50mm), Eternit®, MDF, HDF.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	110	132	4,3	**JT341HM-3**



www.dahm.no

JT118A

METAL · MILLED & WAVY SET TEETH · GREAT VALUE · BASIC CUT · HSS

JT118A — CMT ORANGE TOOLS — HSS // METAL

Straight cuts on thin sheet metals, ferrous and non-ferrous (1 ~ 3mm).

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	50	76	1,2	**JT118A-5**



JT218A

METAL · MILLED & WAVY SET TEETH · GREAT VALUE · BASIC CUT · HSS

JT218A — CMT ORANGE TOOLS — HSS // METAL

Curve cuts on thin sheet metals, ferrous and non-ferrous (1 ~ 3mm).

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	50	76	1,2	**JT218A-5**



JT118B

METAL · MILLED & WAVY SET TEETH · GREAT VALUE · BASIC CUT · HSS

JT118B — CMT ORANGE TOOLS — HSS // METAL

Straight cuts on medium-thick metals, ferrous and non-ferrous (2,5 ~ 6mm).

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	50	76	2	**JT118B-5**



JT123X

METAL · MILLED & SIDE SET TEETH · LONG LIFE · FAST CUT · HSS

JT123X — CMT ORANGE TOOLS — HSS // Progressive // METAL

Straight cuts on thin to thick sheet metals (1,5 ~ 10mm), pipes, profiles in plastic and aluminium (diameter <30mm), stainless steel (1,5 ~ 3mm).

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	75	100	1,2-2,6	**JT123X-5**




JT127D

METAL · MILLED & SIDE SET TEETH · FAST CUT · HSS

JT127D — CMT ORANGE TOOLS — HSS // Special // ALU

Special for aluminium, thin to thick (3 ~ 15mm), pipes + profiles, (diameter <30mm) as well as plastic and fiberglass.

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
5	75	100	3	**JT127D-5**



JT718BF


new

METAL · MILLED & WAVY SET TEETH · LONG LIFE · BIM

JT718BF — CMT ORANGE TOOLS — BIM // Flexible // METAL-SANDWICH

Special for sandwich material (<120mm).

Pack Quantity	l mm	L mm	TS Tooth spacing mm	ORDER NO. T shank
3	160	185	1,8	**JT718BF-3**



www.dahm.no

QUALITY MATERIALS FOR MAXIMUM PRODUCTIVITY

Produced by following state-of-the-art processes, using high-tech machines and premium quality raw materials, these sabre saw blades have been specifically designed to ensure maximum lifetime and performance in all materials.

new



The importance of geometry

GROUND & TAPER GROUND TEETH

Easily cut construction wood, plywood, framing lumber and plastic.

MILLED & SIDE SET TEETH

For quick and Xtreme cuts into soft or hardwood, aluminium, plastic, ferrous and non-ferrous metal.

MILLED & WAVY SET TEETH

For fine and precise cuts into thin and thick metal, pipe, open and closed profiles.

HCS — **High Carbon Steel**
Use for cutting wood and plastic.


BIM — **Bi-Metal with 8% Cobalt**
Premium bi-metal with 8% cobalt provides Xtreme results in performance and lifetime when cutting metal, nail embedded wood and plastic.

HW — **Tungsten Carbide Tipped**
Use for cutting fiber cement board, brick and porous concrete.

THE RIGHT BLADE FOR THE BEST RESULTS!

Quick reference charts and pictograms help you choose the right blade for your application.

- // Wood
- /// Wood & Metal
- // Metal
- // Special



NON-STICK ORANGE SHIELD COATING

Non-Stick Orange Shield Coating
Keeps the blade running cool, reduces pitch build up and protects against corrosion. Ideal for all types of wood including wet lumber.

Sabre Saw Blades Application Chart

new

CMT ORANGE TOOLS™

Series	Material	Material Thickness mm	Line	L	Fine Straight	Coarse Straight	Curve	Fine Angle Cut	Flush Cut	Thin & Thick	Demolition	TPI	Page
WOOD	**Coarse wood (free of nails)**	<100	Basic			JS617K	JS617K					3	56
	Pruning green wood	<175	Basic			JS1111K						3	56
	Coolant: dry	<190	Top			JS1531L						5	56
	MAX RPM 2500	<250	Basic			JS1617K						3	56
	Construction wood	<100	Top	150	JS644D		JS644D					6	56
	Coolant: dry	<150	Progressive	200	JS2345X					JS2345X		6~10	57
	MAX RPM 2500	<150	Pallet	200	JS725VFR			JS725VFR		JS725VFR	JS725VFR	8~12	57
	Boards	<60	Top	150	JS644D		JS644D					6	56
	Coolant: dry	<60	Progressive	200	JS2345X					JS2345		6~10	57
	MAX RPM 2500	<60	Pallet	200	JS725VFR			JS725VFR		JS725VFR		8~12	57
	Wooden wall cutout	<100	Top	150	JS644D		JS644D					6	56
	Coolant: dry	<150	Progressive	200	JS2345X					JS2345X		6~10	57
	MAX RPM 2500	<150	Pallet	200	JS725VFR			JS725VFR		JS725VFR	JS725VFR	8~12	57
		<190	Top	240		JS1531L						5	56
	Plastic	<100	Top	150	JS644D		JS644D					6	56
	Coolant: water MAX RPM 500	<150	Progressive	200	JS2345X					JS2345X		6~10	57
WOOD & METAL	**Wood with nails/metal**	<100	Flexible	150	JS922HF							10	57
	Coolant: dry	<100	Flexible	150	JS922VF							10~14	58
	MAX RPM 2500	<100	Heavy	150	JS641HM	JS611DF	JS711DF					6	58,60
		<100	Heavy	150		JS610VF		JS610VF			JS610VF	5~8	59
		<150	Progressive	200		JS3456XF				JS3456XF		6~12	57
		<150	Pallet	200	JS725VFR			JS725VFR		JS725VFR	JS725VFR	8~12	57
		<175	Flexible	225	JS1122HF				JS1122HF			10	57
		<175	Flexible	225	JS1122VF				JS1122HF			10~14	58
		<175	Heavy	225		JS1111DF						6	59
		<175	Heavy	225		JS1110VF		JS1110VF			JS1110VF	5~8	59
		<250	Flexible	300	JS1222VF				JS1222VF			10~14	58
		<250	Heavy	300		JS1210VF		JS1210VF			JS1210VF	5~8	59
		<250	Heavy	300		JS1411DF						6	59
	Pallets	<100	Flexible	150	JS922HF	JS641HM						10	57,60
	Coolant: dry	<150	Pallet	200	JS725VFR			JS725VFR		JS725VFR	JS725VFR	8~12	57
	MAX RPM 2500	<175	Flexible	225	JS1122HF				JS1122HF			10	57
	Wood, chipboard	<100	Heavy	150		JS611DF	JS711DF					6	58
	Coolant: dry	<100	Heavy	150		JS610VF		JS610VF			JS610VF	5~8	59
	MAX RPM 2500	<150	Progressive	200		JS3456XF				JS3456XF		6~12	57
		<150	Pallet	200	JS725VFR			JS725VFR		JS725VFR	JS725VFR	8~12	57
		<175	Heavy	225		JS1111DF						6	59
		<175	Heavy	225		JS1110VF		JS1110VF			JS1110VF	5~8	59
		<250	Heavy	300		JS1210VF		JS1210VF			JS1210VF	5~8	59
		<250	Heavy	300		JS1411DF						6	59
	Sheet metals	3~10	Flexible	150	JS922VF							10~14	58
	Coolant: cutting oil	3~10	Flexible	225	JS1122VF				JS1122HF			10~14	58
	MAX RPM 500~2000	3~10	Flexible	300	JS1222VF				JS1222HF			10~14	58
		3~18	Progressive	200		JS3456XF				JS3456XF		6~12	57
	Pipes, profiles	<100	Flexible	150	JS922VF							10~14	58
	Coolant: cutting oil	<150	Progressive	200		JS3456XF				JS3456XF		6~12	57
	MAX RPM 1500	<175	Flexible	225	JS1122VF				JS1122HF			10~14	58
		<250	Flexible	300	JS1222VF				JS1222VF			10~14	58
	Plastic, pipes, profiles	<100	Heavy	150		JS611DF	JS711DF					6	58
	Coolant: water	<150	Progressive	200		JS3456XF				JS3456XF		6~12	57
	MAX RPM 500	<175	Heavy	225		JS1111DF						6	59
		<250	Heavy	300		JS1411DF						6	59
	Glass fiber reinforced	<50	Heavy	150		JS611DF	JS711DF					6	58
	plastic/epoxy	<60	Heavy	300		JS1411DF						6	59
	Coolant: water	<60	Heavy	150		JS610VF		JS610VF			JS610VF	5~8	59
	MAX RPM 500	<60	Heavy	225		JS1111DF						6	59
		<60	Heavy	225		JS1110VF		JS1110VF			JS1110VF	5~8	59
		<100	Flexible	150	JS922VF	JS641HM						10~14	58,60
		<150	Progressive	200		JS3456XF				JS3456XF		6~12	57
		<175	Flexible	225	JS1122VF				JS1122HF			10~14	58
		<250	Flexible	300	JS1222VF				JS1222VF			10~14	58
		<250	Heavy	300		JS1210VF		JS1210VF			JS1210VF	5~8	59

Tip: Using a lubricant can extend blade lifetime up to 500%.

www.dahm.no

Sabre Saw Blades Application Chart

new

CMT ORANGE TOOLS™

Series	Material	Material Thickness (mm)	Line	L	Fine Straight	Coarse Straight	Curve	Fine Angle Cut	Flush Cut	Thin & Thick	Demolition	TPI	Page
METAL	**Sheet, perforated metals, (thin & thick)** Coolant: cutting oil MAX RPM 500~2000	0,7~3	Flexible	150	JS922AF							24	60
		0,7~3	Flexible	225	JS1122AF				JS1122AF			24	60
		1~8	Progressive	150	JS123XF					JS123XF		8~14	61
		1,5~4	Flexible	150	JS922EF							18	60
		1,5~4	Flexible	225	JS1122EF				JS1122EF			18	60
		2~10	Heavy	150	JS925VF						JS925VF	10~14	61
		2~10	Heavy	200	JS1025VF						JS1025VF	10~14	61
		2~10	Heavy	225	JS1125VF						JS1125VF	10~14	61
		2~10	Heavy	300	JS1225VF						JS1225VF	10~14	62
		3~8	Flexible	150	JS922BF							14	61
		3~8	Flexible	225	JS1122BF				JS1122BF			14	61
		4~12	Heavy	150		JS920CF		JS920CF			JS920CF	9	62
		4~12	Heavy	225		JS1120CF		JS1120CF			JS1120CF	9	62
	Pipes, profiles, thin-walled (open & closed) Coolant: cutting oil MAX RPM 500~2000	<100	Flexible	150	JS922AF							24	60
		<100	Flexible	150	JS922EF							18	60
		<100	Progressive	150	JS123XF					JS123XF		8~14	61
		<100	Heavy	150	JS925VF						JS925VF	10~14	61
		<150	Heavy	200	JS1025VF						JS1025VF	10~14	61
		<175	Flexible	225	JS1122AF				JS1122AF			24	60
		<175	Flexible	225	JS1122EF				JS1122EF			18	60
		<175	Heavy	225	JS1125VF						JS1125VF	10~14	61
		<250	Heavy	300	JS1225VF						JS1225VF	10~14	62
	Pipes, profiles, thick-walled (open & closed) Coolant: cutting oil MAX RPM 500~2000	<100	Flexible	150	JS922BF							14	61
		<100	Progressive	150	JS123XF					JS123XF		8~14	61
		<100	Heavy	150	JS925VF						JS925VF	10~14	61
		<100	Heavy	150		JS920CF		JS920CF			JS920CF	9	62
		<150	Heavy	200	JS1025VF						JS1025VF	10~14	61
		<175	Flexible	225	JS1122BF				JS1122BF			14	61
		<175	Heavy	225	JS1125VF						JS1125VF	10~14	61
		<175	Heavy	225		JS1120CF		JS1120VF			JS1120CF	9	62
		<250	Heavy	300	JS1225VF						JS1225VF	10~14	62
	Pipes, profiles (solid) Coolant: cutting oil MAX RPM 500~2000	<100	Progressive	150	JS123XF					JS123XF		8~14	61
		<100	Flexible	150	JS922BF							14	61
		<100	Heavy	150		JS920CF		JS920CF			JS920CF	9	62
		<175	Flexible	225	JS1122BF					JS1122BF		14	61
		<175	Heavy	225		JS1120CF		JS1120CF			JS1120CF	9	62
SPECIAL	**Plasterboard**	<100	Heavy	150	JS641HM	JS611DF	JS711DF					6	58,60
	Fibre Cement panels	<215	Special	305		JS1243HM		JS1243HM				2	62
		<365	Special	455		JS2243HM		JS2243HM				2	62
	Porous concrete, red brick	<215	Special	305		JS1243HM		JS1243HM				2	62
		<365	Special	455		JS2243HM		JS2243HM				2	62

Tip: Using a lubricant can extend blade lifetime up to 500%.

BLADES LINE DESCRIPTION

Different lines help you choose the ideal blade for optimal results!

BASIC: Cost effective

FLEXIBLE: Breakproof, long lifetime


PROGRESSIVE: Fast cutting through thin and thick material

TOP: Fast and efficient

HEAVY: Sturdy and precise

1/2" UNIVERSAL SHANK


Fits: AEG, B&D, Bosch, DeWalt, Fein, Flex, Hilti, Makita, Metabo, Milwaukee, Porter Cable, Ridgid, Rothenberger, Ryobi, Skil.



BLADES SHAPES & THICKNESS


Sabre Saw Blades can be manufactured in many various shapes and thickness. Shape and thickness are adjusted to fit the application and required flexibility. Demanding applications such as cutting tube/pipe require thick blades, while less demanding applications require narrower blades.
Blade shapes are divided into three categories below:

1. Universal shape




Universal blades are for general use. Their even width guarantees good cutting stability and excellent control. This enables straight edge cutting through many different materials.

2. Sloped shape



Sloped blades are commonly used for cutting wood and for demolition applications. Their narrow tip allows for plunge and curve cutting. This shape is rarely used for metal, since the tip does not have the strength required for this application.

3. Scroll shape



Scroll blades are especially used for curve cutting. The narrower the blade, the smaller the radius it can cut.

www.dahm.no

Sabre Saw Blades

new

CMT ORANGE TOOLS™

JS617K

WOOD | MILLED & SIDE SET TEETH | GREAT VALUE | BASIC CUT | HCS



Cuts coarse wood, free of nails (<100mm), pruning green wood (diameter <100mm), excellent for curved and plunge cutting.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	19	1,25	8,5	3	**JS617K-5**



JS1111K

WOOD | MILLED & SIDE SET TEETH | GREAT VALUE | BASIC CUT | HCS



Coarse wood, free of nails (<175mm), firewood (diameter <175mm).

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	225	205	19	1,25	8,5	3	**JS1111K-5**



JS1617K

WOOD | MILLED & SIDE SET TEETH | GREAT VALUE | BASIC CUT | HCS



Coarse wood, free of nails (<250mm), pruning green wood (diameter <250mm).

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	300	280	19	1,25	8,5	3	**JS1617K-5**



JS644D

WOOD | GROUND & TAPER GROUND TEETH | FINE CUT | HCS




Cuts construction wood (<100mm), wooden wall (<100mm), boards: chipboard, MDF (6-60mm), plywood, plastic (<100mm), excellent for plunge cuts.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	19	1,25	4,3	6	**JS644D-5**



JS1531L

WOOD | GROUND & TAPER GROUND TEETH | FAST CUT | HCS



Coarse wood, free of nails (<190mm), pruning green wood (diameter <190mm), firewood (diameter <190mm).

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	240	220	19	1,50	5	5	**JS1531L-5**



www.dahm.no

new

CMT ORANGE TOOLS

JS2345X

WOOD | GROUND & TAPER GROUND TEETH | EASY CUT | FINE CUT | HCS



Cuts construction wood (<150mm), boards: chipboard, MDF (6-60mm), plywood, plastic (<150mm), wooden wall (<150mm). Effortless fine cutting.

Pack Quantity	L mm	l mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	200	180	19	1,25	2,4-4	6-10	**JS2345X-5**

Fine Straight | Construction | Wooden wall cutout | Boards | PVC Plastic | THIN & THICK | <150mm

JS922HF

WOOD&METAL | MILLED & SIDE SET TEETH | LONG LIFE | BIM



For pallet repair, wood with nails/metal (<100mm), sheet metal, pipe, aluminium profiles (3-12mm).

Pack Quantity	L mm	l mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	19	0,90	2,5	10	**JS922HF-5**

Fine Straight | Pallets | Wood with nails | Sheet Metal | Pipes | ALU Aluminium | <100mm

JS1122HF

WOOD&METAL | MILLED & SIDE SET TEETH | LONG LIFE | BIM



For pallet repair, wood with nails/metal (<175mm), sheet metal, pipe, aluminium profiles (3-12mm), flexible flush cut.

Pack Quantity	L mm	l mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	225	205	19	0,90	2,5	10	**JS1122HF-5**
20	225	205	19	0,90	2,5	10	**JS1122HF-20**

Flush cut | Pallets | Wood with nails | Sheet Metal | Pipes | ALU Aluminium | <175mm

JS3456XF

WOOD&METAL | MILLED & SIDE SET TEETH | XTREME CUT | LONG LIFE | FAST CUT | BIM



Cuts wood with nails/metal, chipboard (<150mm), sheet metal, aluminium profiles (3-18mm), glass fiber reinforced plastic/epoxy (<150mm).

Pack Quantity	L mm	l mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	200	180	19	1,25	2,1-4,3	6-12	**JS3456XF-5**

Coarse Straight | Wood with nails | Boards | Sheet Metal | Epoxy | THIN & THICK | <150mm

JS725VFR

WOOD&METAL | MILLED & SIDE SET TEETH | DEMOLITION | EASY CUT | LONG LIFE | BIM



Special saw blade for pallet repairs. Cutting depth 150mm. Optimized saw blade dimensions for low vibration.

Pack Quantity	L mm	l mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	200	180	19	1,27	2,1-3,2	8-12	**JS725VFR-5**
20	200	180	19	1,27	2,1-3,2	8-12	**JS725VFR-20**

Fine Straight | Accurate angle cut | Pallets | Wood with nails | Wooden wall cutout | THIN & THICK | <150mm

www.dahm.no

Sabre Saw Blades

new

CMT ORANGE TOOLS™

JS922VF

WOOD&METAL · MILLED & SIDE SET TEETH · EASY CUT · LONG LIFE · BIM



Cuts wood with nails/metal (<100mm), sheet metal, pipe, aluminium profiles (3-10mm), glass fiber reinforced plastic/epoxy (<100mm).

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	19	0,90	1,8-2,6	10-14	**JS922VF-5**



JS1122VF

WOOD&METAL · MILLED & SIDE SET TEETH · EASY CUT · LONG LIFE · BIM



Cuts wood with nails/metal (<175mm), sheet metal, aluminium profiles (3-10mm), glass fiber reinforced plastic/epoxy (<175mm), flexible flush cut.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	225	205	19	0,90	1,8-2,6	10-14	**JS1122VF-5**



JS1222VF

WOOD&METAL · MILLED & SIDE SET TEETH · EASY CUT · LONG LIFE · BIM



Cuts wood with nails/metal (<250mm), sheet metal, aluminium profiles (3-10mm), glass fiber reinforced plastic/epoxy (<250mm), flexible flush cut.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	300	280	19	0,90	1,8-2,6	10-14	**JS1222VF-5**



JS611DF

WOOD&METAL · MILLED & SIDE SET TEETH · EASY CUT · LONG LIFE · BIM




Cuts wood with nails/metal, chipboard (<100mm), plastic profiles (<100mm), glass fiber reinforced plastic/epoxy (<50mm), window frames: wood and metal, plasterboard, excellent for plunge cuts.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	19	1,25	4,3	6	**JS611DF-5**




JS711DF

WOOD&METAL · MILLED & SIDE SET TEETH · EASY CUT · LONG LIFE · BIM



Cuts wood with nails/metal, chipboard (<100mm), glass fiber reinforced plastic/epoxy (<50mm), plasterboard, excellent for curved cuts.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	12	1,25	4,3	6	**JS711DF-5**



www.dahm.no

new

CMT ORANGE TOOLS


JS1111DF

WOOD&METAL | MILLED & SIDE SET TEETH | EASY CUT | LONG LIFE | BIM



Cuts wood with nails/metal, chipboard (<175mm), plastic profiles (diameter <175mm), glass fiber reinforced plastic/epoxy (<50mm).

Pack Quantity	L mm	l mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	225	205	19	1,25	4,3	6	**JS1111DF-5**




JS1411DF

WOOD&METAL | MILLED & SIDE SET TEETH | EASY CUT | LONG LIFE | BIM



Cuts wood with nails/metal, chipboard (<250mm), glass fiber reinforced plastic/epoxy (<60mm).

Pack Quantity	L mm	l mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	300	280	19	1,25	4,3	6	**JS1411DF-5**




JS610VF

WOOD&METAL | MILLED & SIDE SET TEETH | DEMOLITION | XTREME CUT | BIM



Cuts wood with nails/metal, wood, chipboard (<100mm), glass fiber reinforced plastic/epoxy and solid (<100mm), wall cut-outs: wood and metal (<100mm). Excellent for rescue/demolition work.

Pack Quantity	L mm	l mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	22	1,60	3,2-5	5-8	**JS610VF-5**




JS1110VF

WOOD&METAL | MILLED & SIDE SET TEETH | DEMOLITION | XTREME CUT | BIM



Cuts wood with nails/metal, wood, chipboard (<175mm), glass fiber reinforced plastic/epoxy, and solid (<175mm), wall cut-outs: wood and metal (<175mm). Excellent for rescue/demolition work.

Pack Quantity	L mm	l mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	225	205	22	1,60	3,2-5	5-8	**JS1110VF-5**




JS1210VF

WOOD&METAL | MILLED & SIDE SET TEETH | DEMOLITION | XTREME CUT | BIM



Cuts wood with nails/metal, wood, chipboard (<250mm), glass fiber reinforced plastic/epoxy (<250mm), wall cut-outs: wood and metal (<250mm). Excellent for rescue/demolition work.

Pack Quantity	L mm	l mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	300	280	22	1,60	3,2-5	5-8	**JS1210VF-5**



www.dahm.no

Sabre Saw Blades

new

CMT ORANGE TOOLS™

JS641HM

SPECIAL | GROUND & SIDE SET TEETH | EASY CUT | FINE CUT | EXTRA LONG LIFE | HW



Cuts porous concrete, red brick, fibre cement, plasterboard, glass fibre reinforced plastic/epoxy (<100mm), wood & nails, Eternit®, MDF.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
2	150	130	19	1,25	4,3	6	JS641HM-2



JS922AF

METAL | MILLED & WAVY SET TEETH | EASY CUT | FINE CUT | LONG LIFE | BIM



Cuts thin sheet metal (0,7-3mm), fine pipe and profiles (diameter <100mm), effortless fine cuts.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	19	0,90	1	24	JS922AF-5



JS1122AF

METAL | MILLED & WAVY SET TEETH | EASY CUT | FINE CUT | LONG LIFE | BIM



Cuts thin sheet metal (0,7-3mm), fine pipe and profiles (diameter <175mm), effortless fine cuts and flexible flush cuts.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	225	205	19	0,90	1	24	JS1122AF-5



JS922EF

METAL | MILLED & WAVY SET TEETH | LONG LIFE | BIM



Cuts thin sheet metal (1,5-4mm), pipe and profiles (diameter <100mm).

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	19	0,90	1,4	18	JS922EF-5
20	150	130	19	0,90	1,4	18	JS922EF-20



JS1122EF

METAL | MILLED & WAVY SET TEETH | LONG LIFE | BIM



Cuts thin sheet metal (1,5-4mm), pipe and profiles (diameter <175mm), flexible flush cuts.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	225	205	19	0,90	1,4	18	JS1122EF-5
20	225	205	19	0,90	1,4	18	JS1122EF-20



www.dahm.no

new

CMT ORANGE TOOLS™

JS922BF



METAL | MILLED & WAVY SET TEETH | LONG LIFE | FAST CUT | BIM

Cuts thick sheet metal (3-8mm), solid pipe and profiles (diameter <100mm), quick cutting.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	19	0,90	1,8	14	**JS922BF-5**
20	150	130	19	0,90	1,8	14	**JS922BF-20**



JS1122BF



METAL | MILLED & WAVY SET TEETH | LONG LIFE | FAST CUT | BIM

Cuts thick sheet metal (3-8mm), solid pipe and profiles (diameter <175mm), flexible flush cuts, quick cutting.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	225	205	19	0,90	1,8	14	**JS1122BF-5**
20	225	205	19	0,90	1,8	14	**JS1122BF-20**



JS123XF



METAL | MILLED & SIDE SET TEETH | LONG LIFE | FAST CUT | BIM

Cuts thin to thick sheet metal (1-8mm) and thin to thick profiles (diameter <100mm).

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	19	0,90	1,8-3,2	8-14	**JS123XF-5**



JS925VF



METAL | MILLED & SIDE SET TEETH | DEMOLITION | EASY CUT | LONG LIFE | BIM

Cuts medium-thick to thick sheet metal (2-10mm), thin and thick-walled pipe and profiles (<100mm). Ideal for demolition work in metal. Effortless, fine cutting.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	19	1,25	1,8-2,6	10-14	**JS925VF-5**



JS1025VF



METAL | MILLED & SIDE SET TEETH | DEMOLITION | EASY CUT | LONG LIFE | BIM

Cuts medium-thick to thick sheet metal (2-10mm), thin and thick-walled pipe and profiles (<150mm). Ideal for demolition work in metal. Effortless, fine cutting.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	200	180	19	1,25	1,8-2,6	10-14	**JS1025VF-5**



JS1125VF



METAL | MILLED & SIDE SET TEETH | DEMOLITION | EASY CUT | LONG LIFE | BIM

Cuts medium-thick to thick sheet metal (2-10mm), thin and thick-walled pipe and profiles (<175mm). Ideal for demolition work in metal. Effortless, fine cutting.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	225	205	19	1,25	1,8-2,6	10-14	**JS1125VF-5**



www.dahm.no

Sabre Saw Blades

new

CMT ORANGE TOOLS™


JS1225VF

METAL · MILLED & SIDE SET TEETH · DEMOLITION · EASY CUT · LONG LIFE · BIM



Cuts medium-thick to thick sheet metal (2-10mm), thin and thick-walled pipe and profiles (<250mm). Ideal for demolition work in metal. Effortless, fine cutting.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	300	280	19	1,25	1,8-2,6	10-14	JS1225VF-5



JS920CF

METAL · MILLED & SIDE SET TEETH · DEMOLITION · XTREME CUT · LONG LIFE · BIM



Cuts thick sheet metal (4-12mm), thick-walled pipe, solid pipe and profiles (<100mm). Ideal for pipe cutting, for rescue/demolition work. Powerful, coarse cutting.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	150	130	22	1,60	2,9	9	JS920CF-5



JS1120CF

METAL · MILLED & SIDE SET TEETH · DEMOLITION · XTREME CUT · LONG LIFE · BIM




Cuts thick sheet metal (4-12mm), thick-walled pipe, solid pipe and profiles (<175mm). Ideal for pipe cutting, for rescue/demolition work. Powerful, coarse cutting.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
5	225	205	22	1,60	2,9	9	JS1120CF-5
20	225	205	22	1,60	2,9	9	JS1120CF-20




JS1243HM

SPECIAL · LONG LIFE · FAST CUT · HW



Cuts medium-sized brick up to a material thickness of 215mm.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
1	305	250	50	1,50	12,7	2	JS1243HM




JS2243HM

SPECIAL · LONG LIFE · FAST CUT · HW



Cuts large brick up to a material thickness of 365mm.

Pack Quantity	L mm	I mm	H mm	K mm	TS mm	TPI	ORDER NO. Universal shank
1	455	400	50	1,50	12,7	2	JS2243HM



www.dahm.no



Tools for Multi-Cutters

PRODUCTS	PAGE
Plunge and Flush-Cut for Wood	65-66
Radial saw blade for Wood	66
Plunge and Flush-Cut for Wood and Metal	67-68
Radial saw blade for Wood & Metal	69
Scraper for all Materials	69-70
Radial saw blade for Masonry	70-71
Rasp for Masonry	71
Segment saw blade for Masonry	71
Grout and mortar remover for Masonry	72
Polishing Fleece	72
Sandpaper for Wood	72
CMT11 Oscillating Multi-Tools 	315





MULTI MATERIALS



APPLICATIONS

- GRINDING · SAWING
- JOINT OPENING
- PLASTIC CUTTING
- CARPET REMOVAL
- PLUNGE CUTTING
- WOOD CUTTING
- CUTTING LAMINATE SHEETS
- TUBE LENGTH TRIMMING
- NAIL CUTTING

MAXIMIZING YOUR WORK PERFORMANCE



HCS

High Carbon Steel
for cutting wood and plastic.



BIM

Bi-Metal with 8% Cobalt
for cutting metal, nail embedded wood and plastic.



BIM TiN

Bi-Metal with 8% Cobalt with Titanium coating
for cutting metal, nail embedded wood and plastic, providing extreme performance and 30% longer lifetime.



HW

Tungsten Carbide Tipped
for cutting wood, screws and nails, fiber cement board, plasterboard, plastic, sheet metal, copper, aluminium and stainless steel with double lifetime.

Stainless steel arbor
protects your tools against corrosion and rust and guarantee precise work and optimum power transfer.

Blueing coating
protects your tools against corrosion and rust and will not dirty cutting profile.

Reinforced tool mount
reduces vibrations, guarantee more control and precise cuts.



CARBIDE GRIT

Tungsten Carbide Grit Coated
for routing joints and grooves, smaller cutouts, routing recesses in several materials, from tiles, plasterboard, porous concretes, construction materials, epoxy and glass fibre.



GRIT

Diamond Grit Coated
for routing joints and grooves, smaller cutouts, routing recesses in several materials, from tiles, plasterboard, porous concretes, construction materials, epoxy and glass fibre providing extreme performance and longer lifetime.

www.dahm.no


new

CMT ORANGE TOOLS™

THE RIGHT BLADE FOR THE BEST RESULTS!

Quick reference charts and pictograms help you choose the right blade for your application.

WOOD



WOOD&METAL




MULTI-MAT




MASONRY




CMT Universal arbor fits directly onto almost all different commercially available multitools






This tool mount also enables the accessory to be repositioned in 30-degree steps.


Arbor for Fein® SuperCut and Festool® Vecturo





This tool mount also enables the accessory to be repositioned in 30-degree steps.

OMA31



Universal Adapters

Hardwearing universal adaptor allowing your CMT to attach multi-tool blades that do not have matching shanks.
Fits snugly and does not slip.
Ideal for Bosch, Chicago, Craftsman, Dremel, Fein, Makita, Milwaukee, Mastercraft, Ozito, Aeg, Ridgid, Rockwell, Smart, Worx.

Pack Quantity	ORDER NO.
2 in clamshell	**OMA31-X2**

www.dahm.no

new

CMT ORANGE TOOLS™


OMM01 / OMS01

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





10mm Plunge and Flush-Cut for Wood



Features: HCS with hardened teeth.


Material: for wood, blockboard, chipboard, plastic, pipes and profiles.

Application: wide range of applications: installing a ventilation grille, cutting a recess in furniture elements to enable access to a mains socket, adjustment work in wood like sawing recesses for locks and fitting, window and door hardware.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	10	28	18	**OMM01-X1**	**OMS01-X1**


OMM02 / OMS02

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





22mm Plunge and Flush-Cut for Wood



Features: HCS with hardened teeth.

Material: for wood, blockboard, chipboard, plastic, pipes and profiles.

Application: wide range of applications: installing a ventilation grille, cutting a recess in furniture elements to enable access to a mains socket, flush-cutting wooden components to length (like dowels and tenons), window and door hardware.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	22	48	18	**OMM02-X1**	**OMS02-X1**
5 in clamshell	22	48	18	**OMM02-X5**	**OMS02-X5**


OMM03 / OMS03

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





28mm Plunge and Flush-Cut for Wood



Features: HCS with hardened teeth.


Material: for wood, blockboard, chipboard, plastic, pipes and profiles.

Application: wide range of applications: installing a ventilation grille, cutting a recess in furniture elements to enable access to a mains socket, flush-cutting wooden components to length (like dowels and tenons), window and door hardware.


Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	28	48	18	**OMM03-X1**	**OMS03-X1**

OMM04 / OMS04

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo








Japan Toothing

34mm Precision Cut, Japan toothing for Wood



Features: HCS with "Japanese" double-row pattern, hardened teeth.

Material: for wood, timber, blockboard, chipboard.

Application: ground and side set teeth for precision, clean, quick cutting into soft wood and timber. This tooth pattern with its longer teeth allows you to start cutting from a precise point by standing the blade on its corner and lowering it into the wood.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	34	40	14	**OMM04-X1**	**OMS04-X1**
5 in clamshell	34	40	14	**OMM04-X5**	**OMS04-X5**
50 in masterpack	34	40	14	**OMM04-X50**	**OMS04-X50**


www.dahm.no

new

CMT ORANGE TOOLS™

OMM05 / OMS05


OMM05 Universal arbor



OMS05 Arbor for Fein® SuperCut Festool® Vecturo



34mm Extra-Long Life Plunge and Flush-Cut for Wood



Features: Bimetal with 8% Cobalt teeth guarantee extra-long life.


Material: for wood, blockboard, chipboard, plastic, pipes and profiles.


Application: wide range of applications: installing a ventilation grille, cutting a recess in furniture elements to enable access to a mains socket, flush-cutting wooden components to length (like dowels and tenons), window and door hardware.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	34	40	18	**OMM05-X1**	**OMS05-X1**
5 in clamshell	34	40	18	**OMM05-X5**	**OMS05-X5**
50 in masterpack	34	40	18	**OMM05-X50**	**OMS05-X50**

OMM06 / OMS06

OMM06 Universal arbor






Japan Toothing

OMS06 Arbor for Fein® SuperCut Festool® Vecturo



68mm Precision Cut, Japan toothing for Wood



Features: HCS with "Japanese" double-row pattern, hardened teeth.


Material: for wood, timber, blockboard, chipboard.

Application: ground and side-set teeth for precision, clean, quick cutting into soft wood and timber. This tooth pattern with its longer teeth allows you to start cutting from a precise point by standing the blade on its corner and lowering it into the wood. Ideal width for creating long flat horizontal cuts like: door jambs and skirting board.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	68	40	14	**OMM06-X1**	**OMS06-X1**
5 in clamshell	68	40	14	**OMM06-X5**	**OMS06-X5**
50 in masterpack	68	40	14	**OMM06-X50**	**OMS06-X50**

OMM07 / OMS07


OMM07 Universal arbor



OMS07 Arbor for Fein® SuperCut Festool® Vecturo



68mm Extra-Long Life Plunge and Flush-Cut for Wood



Features: Bimetal with 8% Cobalt teeth guarantee extra-long life.


Material: for wood, blockboard, chipboard, plastic, pipes and profiles.

Application: wide range of applications: installing a ventilation grille, cutting a recess in furniture elements to enable access to a mains socket, flush-cutting wooden components to length (like dowels and tenons), window and door hardware.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	68	40	18	**OMM07-X1**	**OMS07-X1**
5 in clamshell	68	40	18	**OMM07-X5**	**OMS07-X5**
50 in masterpack	68	40	18	**OMM07-X50**	**OMS07-X50**

OMM08 / OMS08


OMM08 Universal arbor



OMS08 Arbor for Fein® SuperCut Festool® Vecturo



87mm Radial Saw Blade for Wood



Features: HCS with hardened teeth.

Material: for wood, blockboard, chipboard, plastic, pipes and profiles.

Application: wide range of applications: installing a ventilation grille, cutting a recess in furniture elements to enable access to a mains socket, flush-cutting wooden components to length (like dowels and tenons). Cutting a plastic pipe (PVC) to length.

Pack Quantity	W mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	87	18	**OMM08-X1**	**OMS08-X1**

www.dahm.no

new

CMT ORANGE TOOLS™

OMM09 / OMS09

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





10mm Plunge and Flush-Cut for Wood & Metal

WOOD&METAL — MILLED & SIDE SET TEETH — BIM

Hard/Soft wood · PVC Plastic · ALU Aluminium · Sheet Metal · Non-Ferrous Metals

FEATURES: Bimetal with 8% Cobalt teeth.


MATERIAL: for wood, chipboard, plastic, sheet metal, copper and aluminium pipes and profiles.

APPLICATION: wide range of applications: flush-cutting a nail in wood, adjustment work on non-ferrous profiles, plunge-cutting in plasterboard.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	10	28	18	**OMM09-X1**	**OMS09-X1**
5 in clamshell	10	28	18	**OMM09-X5**	**OMS09-X5**
50 in masterpack	10	28	18	**OMM09-X50**	**OMS09-X50**

OMM10 / OMS10

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





22mm Plunge and Flush-Cut for Wood & Metal

WOOD&METAL — MILLED & SIDE SET TEETH — BIM

Hard/Soft wood · PVC Plastic · ALU Aluminium · Sheet Metal · Non-Ferrous Metals

FEATURES: Bimetal with 8% Cobalt teeth.


MATERIAL: for wood, plasterboard, plastic, sheet metal, copper and aluminium pipes and profiles.

APPLICATION: wide range of applications: flush-cutting a nail in wood, cutting copper pipes, plunge-cutting in plasterboard.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	22	48	18	**OMM10-X1**	**OMS10-X1**
5 in clamshell	22	48	18	**OMM10-X5**	**OMS10-X5**
50 in masterpack	22	48	18	**OMM10-X50**	**OMS10-X50**

OMM11 / OMS11

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





28mm Plunge and Flush-Cut for Wood & Metal

WOOD&METAL — MILLED & SIDE SET TEETH — BIM

Hard/Soft wood · PVC Plastic · ALU Aluminium · Sheet Metal · Non-Ferrous Metals

FEATURES: Bimetal with 8% Cobalt teeth.


MATERIAL: for wood, plasterboard, plastic, sheet metal, copper and aluminium pipes and profiles.

APPLICATION: wide range of applications: flush-cutting a nail in wood, cutting copper pipes and aluminium profiles, plunge-cutting in plasterboard.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	28	48	18	**OMM11-X1**	**OMS11-X1**
5 in clamshell	28	48	18	**OMM11-X5**	**OMS11-X5**
50 in masterpack	28	48	18	**OMM11-X50**	**OMS11-X50**

OMM12 / OMS12

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





32mm Plunge and Flush-Cut for Wood & Metal

WOOD&METAL — MILLED & SIDE SET TEETH — BIM

Hard/Soft wood · PVC Plastic · ALU Aluminium · Sheet Metal · Non-Ferrous Metals

FEATURES: Bimetal with 8% Cobalt teeth.

MATERIAL: for wood, plasterboard, plastic, sheet metal, copper and aluminium pipes and profiles.

APPLICATION: wide range of applications: flush-cutting a nail in wood, cutting copper pipes and aluminium profiles, plunge-cutting in plasterboard.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	32	40	18	**OMM12-X1**	**OMS12-X1**
5 in clamshell	32	40	18	**OMM12-X5**	**OMS12-X5**
50 in masterpack	32	40	18	**OMM12-X50**	**OMS12-X50**

www.dahm.no

new

CMT ORANGE TOOLS™

OMM13 / OMS13

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





32mm Extra-Long Life Plunge & Flush-Cut for Wood & Metal

WOOD&METAL · MILLED & SIDE SET TEETH · BIM TiN · Hard/Soft wood · PVC Plastic · ALU Aluminium · Sheet Metal · Non-Ferrous Metals · 130% LONGER LIFE · LONG LIFE

FEATURES: TiN Coated Bimetal with 8% Cobalt teeth.


MATERIAL: for wood and nails, plasterboard, plastic, sheet metal, copper and aluminium pipes and profiles.

APPLICATION: wide range of applications: flush-cutting a nail in wood, cutting copper pipes and aluminium profiles, plunge-cutting in plasterboard. Tooth strip coated with titanium nitride for 30% longer life.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	32	40	18	**OMM13-X1**	**OMS13-X1**
5 in clamshell	32	40	18	**OMM13-X5**	**OMS13-X5**
50 in masterpack	32	40	18	**OMM13-X50**	**OMS13-X50**

OMM14 / OMS14

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





35mm Extra-Long Life Plunge & Flush-Cut for Wood & Metal

WOOD&METAL · HW · Hard/Soft wood · PVC Plastic · ALU Aluminium · Sheet Metal · Non-Ferrous Metals · 2X LONGER LIFE · LONG LIFE

FEATURES: High Quality carbide teeth.


MATERIAL: for wood, hardened screws and nails, plasterboard, plastic, sheet metal, copper, aluminium and stainless steel.

APPLICATION: wide range of applications: cutting hardened screws/nails, Cutting stainless steel like kitchen front covers, plunge cuts in severely abrasive materials like fiberglass.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	35	40	20	**OMM14-X1**	**OMS14-X1**

OMM15 / OMS15

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





45mm Plunge and Flush-Cut for Wood & Metal

WOOD&METAL · MILLED & SIDE SET TEETH · BIM · Hard/Soft wood · PVC Plastic · ALU Aluminium · Sheet Metal · Non-Ferrous Metals

FEATURES: Bimetal with 8% Cobalt teeth.


MATERIAL: for wood, plasterboard, plastic, sheet metal, copper and aluminium pipes and profiles.

APPLICATION: wide range of applications: flush-cutting a nail, cutting copper pipes and aluminium profiles, plunge-cutting in plasterboard.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	45	48	18	**OMM15-X1**	**OMS15-X1**
5 in clamshell	45	48	18	**OMM15-X5**	**OMS15-X5**
50 in masterpack	45	48	18	**OMM15-X50**	**OMS15-X50**

OMM16 / OMS16

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





45mm Extra-Long Life Plunge & Flush-Cut for Wood & Metal

WOOD&METAL · MILLED & SIDE SET TEETH · BIM TiN · Hard/Soft wood · PVC Plastic · ALU Aluminium · Sheet Metal · Non-Ferrous Metals · 130% LONGER LIFE · LONG LIFE

FEATURES: TiN Coated Bimetal with 8% Cobalt teeth.

MATERIAL: for wood and nails, plasterboard, plastic, sheet metal, copper and aluminium pipes and profiles.

APPLICATION: wide range of applications: flush-cutting a nail, cutting copper pipes and aluminium profiles, plunge-cutting in plasterboard. Tooth strip coated with titanium nitride for 30% longer life.

Pack Quantity	W mm	I mm	TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	45	48	18	**OMM16-X1**	**OMS16-X1**
5 in clamshell	45	48	18	**OMM16-X5**	**OMS16-X5**
50 in masterpack	45	48	18	**OMM16-X50**	**OMS16-X50**


www.dahm.no

new

CMT ORANGE TOOLS™

OMM17 / OMS17

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





87mm Radial Saw Blade for Wood & Metal

WOOD&METAL BIM

Hard/Soft wood · PVC Plastic · ALU Aluminium · Sheet Metal · Non-Ferrous Metals · LONG LIFE

FEATURES: Bimetal with 8% Cobalt teeth.


MATERIAL: for wood, veneered panels, plastic and laminated panels, sheet metal, copper and aluminium pipes and profiles.

APPLICATION: wide range of applications: flush-cutting a nail, cutting a door frame, laminate/parquet, cutting aluminium profiles, plunge-cutting.

Pack Quantity	W mm		TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	87		20	**OMM17-X1**	**OMS17-X1**

OMM18 / OMS18

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





87mm Extra-Long Life Radial Saw Blade for Wood & Metal

WOOD&METAL BIM TiN

Hard/Soft wood · PVC Plastic · ALU Aluminium · Sheet Metal · Cu Zn Non-ferrous metals · 130% LONGER LIFE · LONG LIFE

FEATURES: TiN Coated Bimetal with 8% Cobalt teeth.


MATERIAL: for wood, plasterboard and fibercement boards, sheet metal, copper and aluminium pipes and profiles.

APPLICATION: wide range of applications: plunge-cutting in plasterboard, cutting smaller aluminium mouldings to length, cutting recesses in epoxy/glass fibre like dashboard in a boat.

Pack Quantity	W mm		TPI	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	87		20	**OMM18-X1**	**OMS18-X1**

OMM19 / OMS19

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





52mm Rigid Scraper for all Materials

MULTI-MAT · Sharp blade · HL

FEATURES: HL rigid scraper.

APPLICATION: wide range of applications: removing mortar or tile adhesive, removing mortar and concrete residues, removing hard, brittle carpet adhesive residues.

Pack Quantity	W mm	I mm		ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	52	26		**OMM19-X1**	**OMS19-X1**
5 in clamshell	52	26		**OMM19-X5**	**OMS19-X5**

OMM20 / OMS20

Universal arbor / Arbor for Fein® SuperCut Festool® Vecturo





52mm Flexible Scraper for all Materials

MULTI-MAT · Sharp blade · HL

FEATURES: HL flexible scraper.

APPLICATION: wide range of applications: removing soft carpet adhesive residues, removing paint residues, removing silicone joints.

Pack Quantity	W mm	I mm		ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	52	45		**OMM20-X1**	**OMS20-X1**
5 in clamshell	52	45		**OMM20-X5**	**OMS20-X5**

www.dahm.no

new

CMT ORANGE TOOLS™

OMM21 / OMS21

OMM21 Universal arbor



OMS21 Arbor for Fein® SuperCut Festool® Vecturo



28mm Sharp Corner Scraper for all Materials

MULTI-MAT · Sharp blade · HL


Features: HL sharp corner scraper.

Application: wide range of applications: cutting soft expansion joints, cutting window putty like sealing compound, cutting insulation materials.

Pack Quantity	W mm	I mm	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	28	50	**OMM21-X1**	**OMS21-X1**
5 in clamshell	28	50	**OMM21-X5**	**OMS21-X5**
50 in masterpack	28	50	**OMM21-X50**	**OMS21-X50**

OMM22 / OMS22

OMM22 Universal arbor



OMS22 Arbor for Fein® SuperCut Festool® Vecturo



87mm Carbide Grit Radial Saw Blade

MASONRY · CARBIDE GRIT · Ceramic · Porous concrete · Stone

Features: Carbide Grit.


Material: radial saw blade for tiles, plasterboard, porous concretes and similar construction materials.

Application: wide range of applications: routing joints on wall and floor tiles, smaller cutouts in soft wall tiles, routing grooves in porous concrete, for laying concealed cables and pipes.

Pack Quantity	W mm	K mm	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	87	2,2	**OMM22-X1**	**OMS22-X1**

OMM23 / OMS23

OMM23 Universal arbor



OMS23 Arbor for Fein® SuperCut Festool® Vecturo



87mm Diamond Coated Extra-Long Life Radial Saw Blade

MASONRY · GRIT · Ceramic · Porous concrete · Stone · Glass · LONG LIFE

Features: Diamond coated for extended lifetime.

Material: radial saw blade for tiles, plasterboard, porous concretes, construction materials, epoxy and glass fibre.

Application: wide range of applications: routing joints on wall and floor tiles, smaller cutouts in soft wall tiles, routing recesses in epoxy/glass fibre reinforced plastic like in a boat's hull, routing joints on wall tiles.


Pack Quantity	W mm	K mm	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	87	1,6	**OMM23-X1**	**OMS23-X1**
25 in masterpack	87	1,6	**OMM23-X25**	**OMS23-X25**

OMM24 / OMS24

OMM24 Universal arbor



OMS24 Arbor for Fein® SuperCut Festool® Vecturo



65mm Carbide Grit Radial Saw Blade

MASONRY · CARBIDE GRIT · Ceramic · Porous concrete · Stone

Features: Carbide Grit.

Material: radial saw blade for tiles, plasterboard, porous concretes and similar construction materials.

Application: wide range of applications: routing joints on wall and floor tiles, smaller cutouts in soft wall tiles, routing grooves in porous concrete, for laying concealed cables and pipes.

Pack Quantity	W mm	K mm	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	65	1,6	**OMM24-X1**	**OMS24-X1**

www.dahm.no

new

CMT ORANGE TOOLS™

OMM27

Universal arbor



OMS27

Arbor for Fein® SuperCut Festool® Vecturo



65mm Diamond Coated Extra-Long Life Radial Saw Blade

MASONRY · GRIT · Ceramic · Porous concrete · Stone · Glass · LONG LIFE

Features: Diamond coated for extended lifetime.

Material: radial saw blade for tiles, plasterboard, porous concretes, construction materials, epoxy and glass fibre.

Application: wide range of applications: routing joints on wall and floor tiles, smaller cutouts in soft wall tiles, routing recesses in epoxy/glass fibre reinforced plastic like in a boat's hull, routing joints on wall tiles.

Pack Quantity	W mm	K mm	ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	65	2	**OMM27-X1**	**OMS27-X1**

OMM26

Universal arbor



35mm Double-Face Carbide Grit Fingertip Rasp

MASONRY · CARBIDE GRIT · Ceramic · Porous concrete · Stone

Features: Carbide Grit coated on both sides.

Material: Fingertip Rasp for tiles, plasterboard, porous concretes, construction materials, wood, carpets.

Application: wide range of applications: removing mortar or tile adhesive, removing carpet adhesive residues, rasping wood for rough adjustment, rough grinding of filler, tile adhesives, concrete, stone and wood.

Pack Quantity	W mm		ORDER NO. Universal arbor
1 in clamshell	35		**OMM26-X1**

OMM25

Universal arbor



80mm Carbide Grit Delta Rasp

MASONRY · CARBIDE GRIT · Ceramic · Porous concrete · Stone

Features: Carbide Grit.

Material: Delta Rasp for tiles, plasterboard, porous concretes, construction materials, wood, carpets.

Application: wide range of applications: removing mortar or tile adhesive, removing carpet adhesive residues, rasping wood for rough adjustment, rough grinding of filler, tile adhesives, concrete, stone and wood.

Pack Quantity	W mm		ORDER NO. Universal arbor
1 in clamshell	80		**OMM25-X1**

OMM28

Universal arbor



57mm Diamond coated Extra-Long Life Segment Saw Blade

MASONRY · GRIT · Ceramic · Porous concrete · Stone · Glass · LONG LIFE

Features: Diamond coated for extended lifetime.

Material: Segment saw blade for tiles, marble, epoxy resins.

Application: wide range of applications: remove tough grout from between tiled surfaces. Efficient shape allows aggressive grinding without damaging the tile. Cutting out marble and trass concrete joints. Also for sinking ducts in plaster, brick, pumice and honeycomb stone as well as autoclave aerated concrete. Long-lasting blades are designed specifically for harder grouts.

Pack Quantity	W mm	K mm	ORDER NO. Universal arbor
1 in clamshell	57	2	**OMM28-X1**
25 in masterpack	57	2	**OMM28-X25**

www.dahm.no

new

CMT ORANGE TOOLS™

OMM29

Universal arbor



OMS29

Arbor for Fein® SuperCut Festool® Vecturo



65mm Carbide Grit Grout and Mortar Remover

MASONRY CARBIDE GRIT

Ceramic · Porous concrete · Stone

Features: Carbide Grit.

Material: Grout and Mortar remover for tiles, concrete, stone.

Application: wide range of applications: routing grout, rasping away mortar or tile adhesive, remove joints, tiles, all with one extra long life tool. Suitable for removing carpet residues from a mineral surface. The special design allows access into 90° corners.

Pack Quantity	W mm		ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	65		**OMM29-X1**	**OMS29-X1**

OMM30

Universal arbor



OMS30

Arbor for Fein® SuperCut Festool® Vecturo



93mm Delta Sanding Pad, perforated


MULTI-MAT Velcro®

Features: perforated Sanding pad with micro Velcro®-type fastening system. Quick, easy sanding sheet changes.

Application: perfectly sanded surfaces for all conditions of material with the comprehensive range of sanding sheets.

Pack Quantity	W mm		ORDER NO. Universal arbor	ORDER NO. Arbor for Fein® SuperCut
1 in clamshell	93		**OMM30-X1**	**OMS30-X1**

OMA30000



93mm Delta Polishing Fleece, perforated

MULTI-MAT Velcro®


Glass · Hard/Soft wood · Sheet Metal

Features: Delta Polishing Fleece with micro Velcro®-type to be use with our sku # OMM30 and # OMS30.

Application: wide range of applications: suitable for bringing out the grain of the wood (rustic look), de-rusting of metal and matte sanding of varnishes, removing dirt and deposits without altering the workpiece surface.

Pack Quantity	W mm		ORDER NO.
4 in clamshell	93		**OMA30000-X4**

OMA30



93mm Aluminium-Oxide Delta Sandpaper for Wood, perforated

WOOD Velcro®


Construction · Plywood · Hard/Soft wood

Features: Delta Sandpaper with micro Velcro®-type to be used with our sku # OMM30 and # OMS30.

Application: wide range of applications: suitable for sanding all types of wood, chipboard, plywood, construction boards, for pre-sanding of rough, uneven beams and boards. Best results achieved with dust extractor. Aluminium-Oxide abrasive grain and full resin bond guarantee high abrasion performance.

Pack Quantity	W mm	Grit	ORDER NO.
10 in clamshell	93	40	**OMA30040-X10**
10 in clamshell	93	60	**OMA30060-X10**
10 in clamshell	93	80	**OMA30080-X10**
10 in clamshell	93	100	**OMA30100-X10**
10 in clamshell	93	120	**OMA30120-X10**
10 in clamshell	93	180	**OMA30180-X10**
10 in clamshell	93	240	**OMA30240-X10**

www.dahm.no



Tools with Bore & Knives

PRODUCTS	PAGE
Rabbeting Cutter Heads	74-75
3 piece Adjustable Grooving Set	76-77
Planing & Jointing Spiral Cutter Heads	78
2 piece Adjustable Rounding & Chamfering Set	79
Chamfer Cutter Heads	80-81
Multiradius Roundover Cutter Heads	82~84
Jointing Cutter Heads	85~87
Panel Cutter Heads	88~92
Cutter Heads for Universal Knives & Sets	93~95
Profile Knives & Limiters	96~109
Blank Knives & Limiters (to be sharpened)	110
Bore Reducers	110
HS Corrugated Back Moulder Knives	111
Magnetic Knife Setting Jigs	111
Planer & Jointer Knives	112
HWM Reversible Knives for Portable Planers	113
HWM Reversible Knives	114~116

www.dahm.no



694.100


INSERT CARBIDE | MAN | Z2 | V4

These cutter heads have been designed for:
- rabbeting from top and from bottom
- jointing
- grooving


For use on spindle moulder machines, double-end tenoner and edging machines.
Perfect on all materials, but better results are achieved using chipboard, MDF, wood composites, plastic materials and laminates.
Improved design with shear angle.

TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 universal HWM straight knives 50x12x1,5mm [Z2].
- 4 universal HWM scoring knives 14x14x2mm [V4].
- Tools for manual feed (MAN).
- Pins for automatic positioning of the knives.

Supplied in a solid plastic box.




Drawings are 1:1 scale



D mm	B mm	I mm	Z	RPM	ORDER NO.	Spare parts						
100	19,05	51	2+4	7500~12500	**694.100.19**	790.140.00	990.093.00	991.073.00	790.500.00	695.999.46	990.064.00	991.064.00
100	30	51	2+4	7500~12500	**694.100.30**	790.140.00	990.093.00	991.073.00	790.500.00	695.999.46	990.064.00	991.064.00
100	31,75	51	2+4	7500~12500	**694.100.31**	790.140.00	990.093.00	991.073.00	790.500.00	695.999.46	990.064.00	991.064.00
100	35	51	2+4	7500~12500	**694.100.35**	790.140.00	990.093.00	991.073.00	790.500.00	695.999.46	990.064.00	991.064.00
125	40	51	2+4	6100~10000	**694.125.40**	790.140.00	990.093.00	991.073.00	790.500.00	695.999.46	990.064.00	991.064.00
125	50	51	2+4	6100~10000	**694.125.50**	790.140.00	990.093.00	991.073.00	790.500.00	695.999.46	990.064.00	991.064.00

www.dahm.no





694.020


INSERT CARBIDE | MAN | Z2 | V2


These cutter heads have been designed for:
- rabbeting from top and from bottom
- jointing
- grooving
- 40mm SP profile knives

For use on spindle moulder machines, double-end tenoners and edging machines.
Perfect on all materials, but better results are achieved on chipboard, MDF, wood composites, plastic materials and laminates.


TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 universal HWM straight knives 40x12x1,5mm [Z2].
- 2 universal HWM scoring knives 14x14x2mm [V2].
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.


Supplied in a solid plastic box.






To use with all 40mm profile knives
(see from page 96 to page 105)







D mm	B mm	I mm	Z	RPM	ORDER NO.	Spare parts						
100	30	40	2+2	7500~12500	**694.020.30**	790.140.00	990.093.00	991.073.00	790.400.00	693.999.01	990.065.00	991.064.00
100	31,75	40	2+2	7500~12500	**694.020.31**	790.140.00	990.093.00	991.073.00	790.400.00	693.999.01	990.065.00	991.064.00
125	35	40	2+2	7500~12500	**694.020.35**	790.140.00	990.093.00	991.073.00	790.400.00	693.999.01	990.065.00	991.064.00
125	40	40	2+2	7500~12500	**694.020.40**	790.140.00	990.093.00	991.073.00	790.400.00	693.999.01	990.065.00	991.064.00
125	50	40	2+2	7500~12500	**694.020.50**	790.140.00	990.093.00	991.073.00	790.400.00	693.999.01	990.065.00	991.064.00

Spare parts
691.192 Pair of limiters 40x4mm
695.020.01 Indexable knife edge block 38x4x15mm

www.dahm.no

3 piece Adjustable Grooving Sets



694.001


INSERT CARBIDE | MAN | Z4 | V4


These cutter heads are the ideal tools to create precision slots and grooves on material 4 to 15mm deep. These sets include:
- 2 cutter heads type (A) [Z4 + V4]
- 1 cutter head type (B) [Z2]
- 12 spacer rings from 0,1 to 2mm


For use on your spindle moulder machines, double-end tenoner and shaper machines.
Perfect grooving on all materials, but ideal on solid wood, plywood and laminated panels.

Technical details:
- Super-strength steel body.
- 2 HWM Knives 7,65x12x1,5mm [Z2].
- 4 HWM Knives 18x18x1,5mm [Z4].
- 4 HWM Knives 14x14x1,2mm [V4].
- Tools for manual feed (MAN).
- Pins for automatic positioning of the knives.

Supplied in a solid plastic box.







Drawings are 1:1 scale

D mm	B mm	Z + V	RPM	ORDER NO.	Spare parts			
140	30	4+4	5500~9500	**694.001.30**	790.181.00	790.140.10	790.076.00	695.998.21
140	31,75	4+4	5500~9500	**694.001.31**	790.181.00	790.140.10	790.076.00	695.998.22
140	35	4+4	5500~9500	**694.001.35**	790.181.00	790.140.10	790.076.00	695.998.23
160	40	4+4	4800~8300	**694.001.40**	790.181.00	790.140.10	790.076.00	695.998.24N
160	50	4+4	4800~8300	**694.001.50**	790.181.00	790.140.10	790.076.00	695.998.25N

Spare parts

For cutter heads (A)
990.079.00 M4x3,2mm Torx screws
991.069.00 T9 Torx key
695.996.02 M4 (Ø12x1,7mm) threaded ring
695.996.01 M4 (Ø10x1,6mm) threaded ring

For cutter heads (B)
695.999.07 7x11x9,5mm wedge for knives
990.063.00 M5x18mm screw
991.072.00 T20 Torx key

www.dahm.no



694.021 - 694.022


INSERT CARBIDE | MAN | Z4 | V4

These cutter heads are the ideal tools to create precision slots and grooves on material from 14 to 39mm deep. These sets include:
- 1 cutter head type (A) [Z2 + V2]
- 1 cutter head type (B) [Z2 + V2]
- spacer rings set


For use on spindle moulder machines, double-end tenoners and shaper machines. Perfect grooving on all materials, but ideal on solid wood, plywood and laminated panels.

TECHNICAL DETAILS:
- Super-strength hard aluminium alloy body.
- 694.021: 8 HWM Knives 13,6x13,6x2mm.
- 694.022: 8 HWM Knives 19,5x12x1,5mm.
- 4 HWM Scoring knives 14x14x2mm.
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.

Supplied in a solid plastic box.



Drawings are 1:1 scale



D mm	I mm	B mm	T1 mm	Z	RPM	ORDER NO.	Spare parts				
150	14-28	30	59	4+4	5000~8000	**694.021.30**	790.136.00	990.093.00			695.998.41
150	14-28	31,75	44	4+4	5000~8000	**694.021.31**	790.136.00	990.093.00			695.998.42
150	14-28	35	44	4+4	5000~8000	**694.021.35**	790.136.00	990.093.00			695.998.43
150	14-28	40	44	4+4	5000~8000	**694.021.40**	790.136.00	990.093.00			695.998.44
160	14-28	50	44	4+4	5000~8000	**694.021.50**	790.136.00	990.093.00			695.998.45
170	20-39	30	54	4+4	4400~7400	**694.022.30**	790.140.00	990.093.00	790.195.12	990.094.00	695.998.46
170	20-39	31,75	54	4+4	4400~7400	**694.022.31**	790.140.00	990.093.00	790.195.12	990.094.00	695.998.47
170	20-39	35	54	4+4	4400~7400	**694.022.35**	790.140.00	990.093.00	790.195.12	990.094.00	695.998.48
170	20-39	40	54	4+4	4400~7400	**694.022.40**	790.140.00	990.093.00	790.195.12	990.094.00	695.998.49
170	20-39	50	59	4+4	4400~7400	**694.022.50**	790.140.00	990.093.00	790.195.12	990.094.00	695.998.50

Spare parts
991.072.00 T20 Torx key
991.073.00 T25 Torx key

www.dahm.no




694.019

These new cutter heads have been designed for planing and jointing on soft or hard wood and wooden boards on spindle moulder machines. Ideal for routing our curved elements by using a bearing guide (sold separately) and a template.

TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 12 HWM Knives 14x14x2mm [Z2] with 4 spiral indexing.
- Tools for manual feed (MAN).

Supplied in a plastic twistpack.




Optional bearing

D mm	I mm	B mm	Z	RPM	ORDER NO.	Spare parts		
62	80	30	12	8000~12000	**694.019.30**	790.140.00	990.093.00	991.073.00
62	80	35	12	8000~12000	**694.019.35**	790.140.00	990.093.00	991.073.00
80	80	40	12	8000~12000	**694.019.40**	790.140.00	990.093.00	991.073.00
80	80	50	12	8000~12000	**694.019.50**	790.140.00	990.093.00	991.073.00

Optional


791.051.00	30x62x16mm bearing
791.052.00	35x62x14mm bearing
791.054.00	40x80x18mm bearing
791.053.00	50x80x16mm bearing

Optional



Note: Ideal for routing out curved elements by using an bearing guide (sold separately) and a template.
In order to achieve an extra-fine finish, you can order the optional knife 790.140.20.

www.dahm.no



694.005


INSERT CARBIDE | MAN | Z2+2

Innovative design, simple assembly and numerous possibilities. The CMT adjustable rounding and chamfering sets consist of two pieces, which are very easy to set up on your splindle moulder machine, allowing you to profile on solid wood and man-made boards (with or without coating). It supports five different knives for rounding over both top and bottom edges in one single pass with radius 2,3,4,5 or 6mm, and for 45° chamfering on material from 18mm to 50mm thick. The improved design with shear angle guarantees perfect finishing! For use on spindle moulder machines and double-end tenorers.

TECHNICAL DETAILS:

- Hard aluminium alloy body with high resistance to tensile and yield stress.
- One pair of HWM top knives radius 4mm and 45° chamfer (20x20,5x2mm) [Z2].
- One pair of HWM bottom knives radius 4mm and 45° chamfer (20x20,5x2mm) [Z2].
- Two HWM knives 50x12x1,5mm.
- Set of 21 spacer rings from 0,1 to 3mm.
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.

Supplied in a solid plastic box.



D mm	B mm	Z	RPM	ORDER NO.	Spare parts 17x11x9,5mm	46x11x9,5mm		
139	30	2+2	5500~9400	**694.005.30**	695.999.17	695.999.46	990.064.00	695.998.11
139	31,75	2+2	5500~9400	**694.005.31**	695.999.17	695.999.46	990.064.00	695.998.12
139	35	2+2	5500~9400	**694.005.35**	695.999.17	695.999.46	990.064.00	695.998.13
139	40	2+2	5500~9400	**694.005.40**	695.999.17	695.999.46	990.064.00	695.998.14
139	50	2+2	5500~9400	**694.005.50**	695.999.17	695.999.46	990.064.00	695.998.15

Spare parts

695.005.A4	R=4+45° pair of knives for roundover/chamfer (top)
695.005.B4	R=4+45° pair of knives for roundover/chamfer (bottom)
790.500.00	50x12x1,5mm knives
991.064.00	4mm hex key
991.067.00	3mm hex key

Optional

695.005.A2	R=2+45° pair of knives for roundover/chamfer (top)
695.005.A3	R=3+45° pair of knives for roundover/chamfer (top)
695.005.A5	R=5+45° pair of knives for roundover/chamfer (top)
695.005.A6	R=6+45° pair of knives for roundover/chamfer (top)
695.005.B2	R=2+45° pair of knives for roundover/chamfer (bottom)
695.005.B3	R=3+45° pair of knives for roundover/chamfer (bottom)
695.005.B5	R=5+45° pair of knives for roundover/chamfer (bottom)
695.005.B6	R=6+45° pair of knives for roundover/chamfer (bottom)

www.dahm.no





694.002


CMT chamfer cutter heads carry out clean accurate bevels and joints for excellent edge work. For use on spindle moulder machines, double-end tenoner and shaper machines. Perfect on all materials, but ideal on solid wood, veneer, panel and plastic-coated materials.

TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM Knives 50x12x1,5mm [Z2].
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.

Supplied in a solid plastic box.







Drawing is 1:1 scale

D mm	B mm	Z	RPM	ORDER NO.	Spare parts			
150	30	2	5100~8800	**694.002.30**	790.500.00	695.999.42	990.064.00	991.064.00
150	31,75	2	5100~8800	**694.002.31**	790.500.00	695.999.42	990.064.00	991.064.00
150	35	2	5100~8800	**694.002.35**	790.500.00	695.999.42	990.064.00	991.064.00
150	40	2	5100~8800	**694.002.40**	790.500.00	695.999.42	990.064.00	991.064.00
160	50	2	4800~8300	**694.002.50**	790.500.00	695.999.42	990.064.00	991.064.00

www.dahm.no

Adjustable Chamfer Cutter Heads with Positive Stop




INSERT CARBIDE | MAN | Z2

694.018

These new adjustable chamfer cutter heads carry out precise cuts, accurate bevels and joints on wooden boards and solid timber. For use on spindle moulder machines, double-end tenoner and shaper machines.

TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM Knives 40x12x1,5mm [Z2].
- Tools for manual feed (MAN).
- Positive lock hold of HWM knives, swivel bodies infinitely adjustable on both sides from 0 to 45°, with positive stop every 7,5° step, thanks to the special built-in geared mechanism.


Supplied in a solid plastic box.



D mm	l mm	B mm	Z	D_Max 45° mm	RPM	ORDER NO.	Spare parts			
120	40	30	2	140	7000~9000	**694.018.30**	695.018.01	790.400.00	990.094.00	991.072.00
120	40	35	2	140	7000~9000	**694.018.35**	695.018.01	790.400.00	990.094.00	991.072.00
145	40	40	2	165	4800~7200	**694.018.40**	695.018.01	790.400.00	990.094.00	991.072.00
145	40	50	2	165	4800~7200	**694.018.50**	695.018.01	790.400.00	990.094.00	991.072.00

Spare parts **991.065.00** 5mm hex key

Professional Adjustable Chamfer Cutter Heads with Gear Box




INSERT CARBIDE | MAN | Z2

694.017

These new professional adjustable chamfer cutter heads carry out precise cuts, accurate bevels and joints on wooden boards and solid timber. For use on spindle moulder machines, double-end tenoner and shaper machines.

TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM knives (50x12x1,5mm) [Z2].
- Tools for manual feed (MAN).
- Positive lock hold of HWM knives.
- Swivel bodies infinitely adjustable on both sides from +90° to -90°, thanks to the special built-in geared mechanism.

Supplied in a solid plastic box.



D mm	l mm	B mm	Z	D_Max 45° mm	RPM	ORDER NO.	Spare parts				
160	50	30	2	183	4800~6000	**694.017.30**	695.017.01	790.500.00	695.999.48	990.106.00	991.067.00
160	50	35	2	183	4800~6000	**694.017.35**	695.017.01	790.500.00	695.999.48	990.106.00	991.067.00
160	50	50	2	183	4800~6000	**694.017.50**	695.017.01	790.500.00	695.999.48	990.106.00	991.067.00

Spare parts **991.081.00** 4mm hex key

www.dahm.no

Multiradius Roundover Cutter Heads



694.003


INSERT CARBIDE · MAN · Z2

Innovative cutter heads supporting three different knives for making six radius roundover profiles. Standard cutter heads are sold with knives featuring 5 and 10mm radii; two more knife sets are available for radii 4-8mm and 3-6mm. For use on spindle moulder machines, double-end tenoner and shaper machines. Perfect for all materials, but ideal on solid wood and panel materials.


TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM knives radius 5/10mm (25x24,8x2mm) [Z2].
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.

Supplied in a solid plastic box.


Standard — Pair of knives **695.003.05**



Optional



Pair of knives **695.003.04**



Drawings are 1:1 scale

Pair of knives **695.003.03**

D mm	B mm	Z	RPM	ORDER NO.	Spare parts x2			
113	30	2	6700~11000	**694.003.30**	695.003.05	695.999.22	990.064.00	991.064.00
113	31,75	2	6700~11000	**694.003.31**	695.003.05	695.999.22	990.064.00	991.064.00
113	35	2	6700~11000	**694.003.35**	695.003.05	695.999.22	990.064.00	991.064.00
128	40	2	5900~9700	**694.003.40**	695.003.05	695.999.22	990.064.00	991.064.00
128	50	2	5900~9700	**694.003.50**	695.003.05	695.999.22	990.064.00	991.064.00

Optional
695.003.04 R=4/8mm (25x24,8x2mm) pair of profiled knives
695.003.03 R=3/6mm (25x24,8x2mm) pair of profiled knives

www.dahm.no



694.004

INSERT CARBIDE | MAN | Z2

Innovative cutter heads supporting two different knives for making four radius roundover profiles. Standard cutter heads are sold with knives featuring radii 15 and 20mm; one more knife set is available for radii 12-18mm. For use on spindle moulder machines, double-end tenorer and shaper machines. Perfect on all materials, but ideal on solid wood and panel materials.


TECHNICAL DETAILS:

- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM knives radius 15/20mm (45x34,5x2mm) [Z2].
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.


Supplied in a solid plastic box.

Standard

Pair of knives **695.004.15**



Optional



Drawings are 1:1 scale

Pair of knives **695.004.12**

D mm	B mm	Z	RPM	ORDER NO.	Spare parts x2			
132	30	2	5700~9500	**694.004.30**	695.004.15	695.999.42	990.064.00	991.064.00
132	31,75	2	5700~9500	**694.004.31**	695.004.15	695.999.42	990.064.00	991.064.00
132	35	2	5700~9500	**694.004.35**	695.004.15	695.999.42	990.064.00	991.064.00
147	40	2	5100~8500	**694.004.40**	695.004.15	695.999.42	990.064.00	991.064.00
147	50	2	5100~8500	**694.004.50**	695.004.15	695.999.42	990.064.00	991.064.00

Optional **695.004.12** R=12/18mm (45x34,5x2mm) pair of profiled knives

www.dahm.no



694.007


INSERT CARBIDE | MAN | Z2

These cutter heads are perfect for making furniture, doors and drawer fronts simply and stylishly by giving them a final touch with a CMT cove bit. It is also used for making perfect roundover profiles, drop leaf counters and table tops. You can use three different knives for carrying out roundover and cove profiles with radius 10, 12 and 15mm. For use on spindle moulder machines, double-end tenoner and shaper machines. Perfect on all materials, but ideal on solid wood and panel materials.


TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM knives radius 10mm (34,8x29,3x2mm) [Z2].
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.

Supplied in a solid plastic box.

Standard — Pair of knives **695.007.10**




Optional — Pair of knives **695.007.12** — Pair of knives **695.007.15**



D mm	B mm	Z	RPM	ORDER NO.	Spare parts x2			
121	30	2	6300~10500	**694.007.30**	695.007.10	695.999.31	990.064.00	991.064.00
121	31,75	2	6300~10500	**694.007.31**	695.007.10	695.999.31	990.064.00	991.064.00
121	35	2	6300~10500	**694.007.35**	695.007.10	695.999.31	990.064.00	991.064.00
136	40	2	5600~9300	**694.007.40**	695.007.10	695.999.31	990.064.00	991.064.00
136	50	2	5600~9300	**694.007.50**	695.007.10	695.999.31	990.064.00	991.064.00

Optional
695.007.12 R=12mm (34,8x29,3x2mm) pair of roundover/cove knives
695.007.15 R=15mm (34,8x29,3x2mm) pair of roundover/cove knives

www.dahm.no




694.008


INSERT CARBIDE | MAN | Z2

The professional CMT finger joint cutter heads allow for making the most incredibly strong side-to-side joints on all wood types and composites. The tightness of the joint and the maximum glue surface make the joint itself stronger than an unworked piece of wood, in stock with maximum 47mm in thickness. Ideal for molding manufactuers and furniture makers.
For use on spindle moulder machines, double-end tenoner and shaper machines. Perfect on all materials, but ideal on solid wood and panel materials.

TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM knives 49,6x11,9x1,5mm [Z2].
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.

Supplied in a solid plastic box.





Drawing is 1:1 scale

D mm	B mm	Z	RPM	ORDER NO.	Spare parts x2			
105	30	2	7300~11500	**694.008.30**	695.008.01	695.999.49	990.066.00	991.067.00
105	31,75	2	7300~11500	**694.008.31**	695.008.01	695.999.49	990.066.00	991.067.00
105	35	2	7300~11500	**694.008.35**	695.008.01	695.999.49	990.066.00	991.067.00
105	40	2	7300~11500	**694.008.40**	695.008.01	695.999.49	990.066.00	991.067.00
105	50	2	7300~11500	**694.008.50**	695.008.01	695.999.49	990.066.00	991.067.00

Optional

695.998.2630	Ø50x2,6x30mm guide ring
695.998.2631	Ø50x2,6x31,75mm guide ring
695.998.2635	Ø55x2,6x35mm guide ring
695.998.2640	Ø60x2,6x40mm guide ring
695.998.2650	Ø70x2,6x50mm guide ring

www.dahm.no

Reverse Glue Joint Cutter Heads




694.009


INSERT CARBIDE | MAN | Z2

The most unique and important feature of these CMT cutter heads is the capacity to produce almost indestructible glue joints quickly and accurately. Ideal for shaping wide dimension panels, doors and furniture pieces. By accurately centering the cutter head to the wood, the upper and lower vertical cutting edges will cut equal proportions. Simply run one side of the panel, turn the panel over, and then run the opposite side - you will produce perfectly harmonized reverse cuts matching up to make flawless joints. Excellent results on most materials, but ideal on solid wood, coated and uncoated man-made materials.

TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM knives 40x18x2mm [Z2].
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.

Supplied in a solid plastic box.





D mm	B mm	Z	RPM	ORDER NO.	Spare parts x2			
100	30	2	7500~12500	**694.009.30**	695.009.01	695.999.38	990.064.00	991.064.00
100	31,75	2	7500~12500	**694.009.31**	695.009.01	695.999.38	990.064.00	991.064.00
100	35	2	7500~12500	**694.009.35**	695.009.01	695.999.38	990.064.00	991.064.00
120	40	2	6400~10500	**694.009.40**	695.009.01	695.999.38	990.064.00	991.064.00
120	50	2	6400~10500	**694.009.50**	695.009.01	695.999.38	990.064.00	991.064.00

www.dahm.no



694.011


INSERT CARBIDE | MAN | Z2


CMT's lock miter cutter heads are ideal for milling miter joints in stock with maximum 28mm in thickness. Create boxes, stretcher bars, frames and any assortment of right angle or parallel joint projects. Two easy steps to produce perfect fitting 45° miter joints: first, position your workpiece horizontally, then vertically. Also, create parallel glue joints in two steps: place your workpiece horizontally, internal side facing down, and then turn it facing up. For use on spindle moulder and shaper machines. Perfect on all materials, but ideal on solid wood and panels.


TECHNICAL DETAILS:

- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM knives 43x23x2mm [Z2].
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.

Supplied in a solid plastic box.








D mm	B mm	Z	RPM	ORDER NO.	Spare parts x2			
140	30	2	5500~9500	**694.011.30**	695.011.01	695.999.42	990.064.00	991.064.00
140	31,75	2	5500~9500	**694.011.31**	695.011.01	695.999.42	990.064.00	991.064.00
140	35	2	5500~9500	**694.011.35**	695.011.01	695.999.42	990.064.00	991.064.00
140	40	2	5500~9500	**694.011.40**	695.011.01	695.999.42	990.064.00	991.064.00
150	50	2	5100~8800	**694.011.50**	695.011.01	695.999.42	990.064.00	991.064.00

www.dahm.no

Raised Panel Cutter Heads

new

CMT ORANGE TOOLS




694.012

INSERT CARBIDE | MAN | Z2


These new CMT cutter heads will allow you to make classic raised panels on furniture, interior and cabinet doors. One exceptional tool that will let you make up to 6 different profiles by exploiting both the included and the optional knives. A practical and economical solution. We recommend multiple passes for safe and accurate finishing. For use on spindle moulders. Perfect on all materials, but ideal on solid wood and panels.

TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM Knives type (A) 50x25x2mm [Z2].
- Tools for manual feed (MAN)
- Pins for the automatic positioning of the knives.


Supplied in a solid plastic box.





Standard Pair of knives **695.012A**





Optional


Pair of knives **695.012B**


Pair of knives **695.012C**


Pair of knives **695.012D**


Pair of knives **695.012E**


Pair of knives **695.012G**

Drawings are 1:1 scale

D mm	I mm	B mm	Z	RPM	ORDER NO.	Spare parts x2		
180	25	30	2	4200 ~ 7000	**694.012.30**	695.012A	990.107.00	991.067.00
180	25	35	2	4200 ~ 7000	**694.012.35**	695.012A	990.107.00	991.067.00
180	25	40	2	4200 ~ 7000	**694.012.40**	695.012A	990.107.00	991.067.00
180	25	50	2	4200 ~ 7000	**694.012.50**	695.012A	990.107.00	991.067.00

Optional

695.012B 50x25x2mm pair of knives type (B)
695.012C 50x25x2mm pair of knives type (C)
695.012D 50x25x2mm pair of knives type (D)
695.012E 50x25x2mm pair of knives type (E)
695.012G 50x25x2mm pair of knives type (G)

www.dahm.no





694.013


We offer a traditional approach to panel construction with these CMT raised panel cutter heads. Make classic raised panels on furniture, interior and cabinet doors on solid wood and wooden boards, and achieve three different profiles by adjusting the cutting depth. We recommend multiple passes for safe and accurate finishing. For use on spindle moulders. Perfect on all materials, but ideal on solid wood and panels.

TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM Knives type (A) 19,8x11,9x1,5mm [Z2].
- 2 HWM Knives type (B) 60x11,9x1,5mm [Z2].
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.

Supplied in a solid plastic box.







Drawings are 1:1 scale

D mm	B mm	Z	RPM	ORDER NO.	Spare parts x2	16x11x9,5mm	x2	53x11x9,5mm	
183	30	2+2	4100~7000	**694.013.30**	695.013.A1	695.999.16	695.013.A2	695.999.53	990.066.00
183	31,75	2+2	4100~7000	**694.013.31**	695.013.A1	695.999.16	695.013.A2	695.999.53	990.066.00
183	35	2+2	4100~7000	**694.013.35**	695.013.A1	695.999.16	695.013.A2	695.999.53	990.066.00
200	40	2+2	3800~6400	**694.013.40**	695.013.A1	695.999.16	695.013.A2	695.999.53	990.066.00
200	50	2+2	3800~6400	**694.013.50**	695.013.A1	695.999.16	695.013.A2	695.999.53	990.066.00

Spare parts **991.083.00** 3x90x135mm hex key

www.dahm.no

Profile & Counter Profile Cutter Head Sets



694.015


INSERT CARBIDE · MAN · Z2 · V4


These versatile sets were designed to make furniture and doors on soft and hardwood. It allows the insertion of five different knives to produce the most popular and classical profiles. The adjustable cutter, included in the set, can also be used individually to carry out grooves between 8mm 15mm thick. For use on spindle moulders. Perfect on solid wood and panels maximum 48mm (1-7/8") in thickness.


Technical details:


- Hard aluminium alloy body with high resistance to tensile and yield stress for cutter heads (1 & 2).
- Super-strength steel body for cutter head (3).
- 2 HWM knives type (A1) 25x29,8x2mm [Z2].
- 2 HWM knives type (A2) 25x29,8x2mm [Z2].
- 4 HWM knives 7,65x12x1,5mm [Z4].
- 4 HWM knives 14x14x2m for heads type (1 & 2).
- 12 spacer rings from 0,1 to 3mm for heads type (1 & 2).
- 12 spacer rings from 0,1 to 2mm for heads type (3).
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.

Supplied in a solid plastic box.









D mm	B mm	Z + V	RPM	ORDER NO.	Spare parts 9		10.6
132	30	2+2	5700~9500	**694.015.30**	695.998.01	695.998.21	695.998.30
132	31,75	2+2	5700~9500	**694.015.31**	695.998.02	695.998.22	695.998.31
132	35	2+2	5700~9500	**694.015.35**	695.998.03	695.998.23	695.998.35
147	40	2+2	5100~8500	**694.015.40**	695.998.04	695.998.24	695.998.40
147	50	2+2	5100~8500	**694.015.50**	695.998.05	695.998.25	

Spare parts

Head type (1)

695.015.A1 25x29,8x2mm HWM pair of knives (A1)
695.015.B1 25x29,8x2mm HWM pair of knives (B1)
695.015.C1 25x29,8x2mm HWM pair of knives (C1)
695.015.D1 25x29,8x2mm HWM pair of knives (D1)
695.015.E1 25x29,8x2mm HWM pair of knives (E1)
695.999.23 23x11x9,5mm wedge for knives
990.066.00 M6x16mm screw
991.067.00 3mm hex key

Head type (2)

695.015.A2 25x29,8x2mm HWM pair of knives (A2)
695.015.B2 25x29,8x2mm HWM pair of knives (B2)
695.015.C2 25x29,8x2mm HWM pair of knives (C2)
695.015.D2 25x29,8x2mm HWM pair of knives (D2)
695.015.E2 25x29,8x2mm HWM pair of knives (E2)
695.999.24 23x11x9,5mm wedge for knives
990.066.00 M6x16mm screws
991.067.00 3mm hex key


Head type (3)


790.076.00 7,65x12x1,5mm HWM knives
695.999.07 6,8x11x9,5mm wedge for knives
990.063.00 M5x18mm screw
991.072.00 T20 hex key
790.140.00 14x14x2mm HWM Knives
990.080.00 M5x6,5mm screw
991.073.00 T25 hex key

www.dahm.no

Standard

Pair of knives **695.015.A1** - Pair of knives **695.015.A2**







Drawings are 1:1 scale


Optional


Pair of knives **695.015.B1**
Pair of knives **695.015.B2**







Pair of knives **695.015.C1**
Pair of knives **695.015.C2**







Pair of knives **695.015.D1**
Pair of knives **695.015.D2**






Pair of knives **695.015.E1**
Pair of knives **695.015.E2**





Drawings are 1:1 scale

www.dahm.no



694.014


INSERT CARBIDE · MAN · Z2


These are unique products made by combining two cutter heads, ideal for making furniture doors and drawers. By adjusting the height of the head it is possible to cut two perfectly fitted profiles with out wasting time or effort to move the fence or replace the tool. Save money by purchasing one single head and improve your production's efficiency. For use on spindle moulders. Perfect on hardwood and panels with thickness between 22mm and 25mm.

TECHNICAL DETAILS:
- Hard aluminium alloy body with high resistance to tensile and yield stress.
- 2 HWM Knives type (A) 40x24,5x2mm [Z2].
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.

Supplied in a solid plastic box.


Standard — Pair of knives **695.014A**






Drawing is 1:1 scale

Optional — Pair of knives **695.014B** — Pair of knives **695.014C**



Pair of knives **695.014D**



Drawings are 1:1 scale

D mm	B mm	Z	RPM	ORDER NO.	Spare parts x2			
120	30	2	6400~10500	**694.014.30**	695.014A	695.999.39	990.066.00	991.067.00
120	31,75	2	6400~10500	**694.014.31**	695.014A	695.999.39	990.066.00	991.067.00
120	35	2	6400~10500	**694.014.35**	695.014A	695.999.39	990.066.00	991.067.00
120	40	2	6400~10500	**694.014.40**	695.014A	695.999.39	990.066.00	991.067.00
130	50	2	5900~9700	**694.014.50**	695.014A	695.999.39	990.066.00	991.067.00

Optional
695.014B 40x24,5x2mm pair of knives type (B)
695.014C 40x24,5x2mm pair of knives type (C)
695.014D 40x24,5x2mm pair of knives type (D)

www.dahm.no




692


SP · MEC · Z2


CMT cutter heads guarantee excellent performance for all your projects. For use on all types of moulder and spindle moulder machines.

TECHNICAL DETAILS:
- Hard aluminium or steel alloy cutter head without limiters, highly resistant to tensile and yield stress.
- Pair of universal straight knives included.
- Tools for mechanical feed (MEC).
- Pins for the automatic positioning of the knives.
- Possibility to use knives with a height of 40mm or 50mm (order no. 690).

Supplied in a solid plastic box to contain up to 12 couples of knives.







D mm	I mm	B mm	RPM	ORDER NO. Steel body	ORDER NO. Alumimium body	Spare parts		
78	40	19,05	7000~9000		**692.078.19***	692.999.01	990.064.00	991.064.00
78	40	30	7000~9000		**692.078.30***	692.999.01	990.064.00	991.064.00
100	40-50	25,4	5500~8400		**692.100.26**	692.999.01	990.064.00	991.064.00
100	40-50	30	5500~8400	**692.101.30**	**692.100.30**	692.999.01	990.064.00	991.064.00
100	40-50	31,75	5500~8400		**692.100.31**	692.999.01	990.064.00	991.064.00
100	40-50	35	5500~8400	**692.101.35**	**692.100.35**	692.999.01	990.064.00	991.064.00
120	40-50	50	4800~7400	**692.121.50**	**692.120.50**	692.999.01	990.064.00	991.064.00

*For safety reasons we recommend the use of knives with a 40mm height only.

Cutter Heads with Limiters



693


SP · MAN · Z2


CMT cutter heads guarantee excellent performance for all your projects. For use on all types of moulder and spindle moulder machines.


TECHNICAL DETAILS:
- Hard aluminium or steel alloy cutter head without limiters, highly resistant to tensile and yield stress.
- Pair of universal straight knives included.
- Tools for manual feed (MAN).
- Pins for the automatic positioning of the knives.
- Possibility to use knives with a height of 40mm or 50mm (order no. 690) and limiters (order no. 691).

Made in compliance with the European Regulation EN 847-1

Supplied in a solid plastic box to contain up to 12 couples of knives.








D mm	I mm	B mm	RPM	ORDER NO. Steel body	ORDER NO. Alumimium body	Spare parts		
78	40	30	7000~9000	**693.078.30**		693.999.01	990.065.00	991.064.00
100	40-50	30	5500~8400	**693.101.30**	**693.100.30**	693.999.01	990.065.00	991.064.00
100	40-50	31,75	5500~8400		**693.100.31**	693.999.01	990.065.00	991.064.00
100	40-50	35	5500~8400	**693.101.35**	**693.100.35**	693.999.01	990.065.00	991.064.00
120	40-50	50	4800~7400	**693.121.50**	**693.120.50**	693.999.01	990.065.00	991.064.00

www.dahm.no






692

SP MEC Z2


These sets are ideal for the professional woodworker for making joints and frames and include 3 essential profiles to produce kitchen doors. The cutter heads included in the sets allow the insertion of knives with a height of either 40mm or 50mm. Both cutter head and knives are stored in solid plastic cases to prevent damage.

These sets include:
- 1 cutter head in hard aluminium alloy with pins for the automatic positioning of the knives.
- 13 pairs of knives with a cutting height of 40mm.



D mm	I mm	B mm	RPM	ORDER NO.	Spare parts		
78	40	19,05	7000~9000	**692.013.09**	692.999.01	990.064.00	991.064.00
78	40	30	7000~9000	**692.013.01**	692.999.01	990.064.00	991.064.00
100	40	25,4	5500~8400	**692.013.10**	692.999.01	990.064.00	991.064.00
100	40	30	5500~8400	**692.013.02**	692.999.01	990.064.00	991.064.00
100	40	31,75	5500~8400	**692.013.11**	692.999.01	990.064.00	991.064.00
100	40	35	5500~8400	**692.013.03**	692.999.01	990.064.00	991.064.00
120	40	50	4800~7400	**692.013.04**	692.999.01	990.064.00	991.064.00






692

SP MEC Z2

These sets are ideal for the professional woodworker and include 13 profile knives for making joints, frames, multiple profiles, moldings and chamfers. The cutter head included in the sets allow the insertion of knives with a height of either 40mm or 50mm. Both cutter head and knives are stored in solid plastic cases to prevent damage.

These sets include:
- 1 cutter head in hard aluminium alloy with pins for the automatic positioning of the knives.
- 13 pairs of knives with a cutting height of 40mm.



D mm	I mm	B mm	RPM	ORDER NO.	Spare parts		
78	40	19,05	7000~9000	**692.013.12**	692.999.01	990.064.00	991.064.00
78	40	30	7000~9000	**692.013.05**	692.999.01	990.064.00	991.064.00
100	40	25,4	5500~8400	**692.013.13**	692.999.01	990.064.00	991.064.00
100	40	30	5500~8400	**692.013.06**	692.999.01	990.064.00	991.064.00
100	40	31,75	5500~8400	**692.013.14**	692.999.01	990.064.00	991.064.00
100	40	35	5500~8400	**692.013.07**	692.999.01	990.064.00	991.064.00
120	40	50	4800~7400	**692.013.08**	692.999.01	990.064.00	991.064.00


www.dahm.no




693

SP MAN Z2

The professional woodworker now has the chance to make kitchen doors with a horizontal profile and male-and-female joints with two pairs of cutters. In fact, along with 7 profiled knives these sets also contain a specially designed cutter head that allows the insertion of knives with a height of either 40mm or 50mm, and safety limiters produced in compliance with the European Regulation EN 847-1. Both cutter head and knives are stored in solid plastic cases to prevent damage.



These sets include:
- 1 cutter head in hard aluminium alloy allowing the insertion of straight knives, limiters and pins for the automatic positioning of the knives.
- 7 pairs of knives with 40mm of cutting.
- 7 pairs of relative limiters.




D mm	I mm	B mm	RPM	ORDER NO.	Spare parts		
100	40	30	5500~8400	**693.013.01**	693.999.01	990.065.00	991.064.00
100	40	35	5500~8400	**693.013.02**	693.999.01	990.065.00	991.064.00
120	40	50	4800~7400	**693.013.03**	693.999.01	990.065.00	991.064.00




693

SP MAN Z2

CMT has designed this sets containing 7 profiled knives and a cutter head for making joints, frames and chamfers. The cutter heads allow the insertion of knives with a height of either 40mm or 50mm and safety limiters produced in compliance with the European Regulation EN 847-1. Both cutter head and knives are stored in solid plastic cases to prevent damage.



These sets include:
- 1 cutter head in hard aluminium alloy allowing the insertion of straight knives, limiters and pins for the automatic positioning of the knives.
- 7 pairs of knives with 40mm of cutting.
- 7 pairs of relative limiters.



D mm	I mm	B mm	RPM	ORDER NO.	Spare parts		
100	40	30	5500~8400	**693.013.04**	693.999.01	990.065.00	991.064.00
100	40	35	5500~8400	**693.013.05**	693.999.01	990.065.00	991.064.00
120	40	50	4800~7400	**693.013.06**	693.999.01	990.065.00	991.064.00


www.dahm.no

Profile Knives & Limiters


Cutting length=40mm Thickness=4mm

CMT ORANGE TOOLS


SP




Pair of Knives	690.000
Pair of Limiters	691.000




Pair of Knives	690.001
Pair of Limiters	691.001




Pair of Knives	690.002
Pair of Limiters	691.002




Pair of Knives	690.003
Pair of Limiters	691.003




Pair of Knives	690.004
Pair of Limiters	691.004




Pair of Knives	690.005
Pair of Limiters	691.005




Pair of Knives	690.006
Pair of Limiters	691.006




Pair of Knives	690.007
Pair of Limiters	691.007




Pair of Knives	690.008
Pair of Limiters	691.008




Pair of Knives	690.009
Pair of Limiters	691.009




Pair of Knives	690.010
Pair of Limiters	691.010




Pair of Knives	690.011
Pair of Limiters	691.011



Pair of Knives	690.012
Pair of Limiters	691.012



Pair of Knives	690.013
Pair of Limiters	691.013



Pair of Knives	690.014
Pair of Limiters	691.014


Note: all knives & limiters available only in pairs

Drawings are 1:2 scale


Dimensions in mm.

www.dahm.no


SP




Pair of Knives	690.015
Pair of Limiters	691.015




Pair of Knives	690.016
Pair of Limiters	691.016




Pair of Knives	690.017
Pair of Limiters	691.017




Pair of Knives	690.018
Pair of Limiters	691.018




Pair of Knives	690.019
Pair of Limiters	691.019




Pair of Knives	690.020
Pair of Limiters	691.020




Pair of Knives	690.021
Pair of Limiters	691.021




Pair of Knives	690.022
Pair of Limiters	691.022




Pair of Knives	690.023
Pair of Limiters	691.023




Pair of Knives	690.024
Pair of Limiters	691.024




Pair of Knives	690.025
Pair of Limiters	691.025




Pair of Knives	690.026
Pair of Limiters	691.026



Pair of Knives	690.027
Pair of Limiters	691.027



Pair of Knives	690.028
Pair of Limiters	691.028



Pair of Knives	690.029
Pair of Limiters	691.029

Note: all knives & limiters available only in pairs

Drawings are 1:2 scale

Dimensions in mm.


www.dahm.no

Profile Knives & Limiters


Cutting length=40mm Thickness=4mm

CMT ORANGE TOOLS™


SP




Pair of Knives	690.030
Pair of Limiters	691.030




Pair of Knives	690.031
Pair of Limiters	691.031




Pair of Knives	690.032
Pair of Limiters	691.032




Pair of knives	690.033
Pair of limiters	691.033




Pair of Knives	690.034
Pair of Limiters	691.034




Pair of Knives	690.035
Pair of Limiters	691.035




Pair of Knives	690.036
Pair of Limiters	691.036




Pair of Knives	690.037
Pair of Limiters	691.037




Pair of Knives	690.038
Pair of Limiters	691.038




Pair of Knives	690.039
Pair of Limiters	691.039




Pair of Knives	690.040
Pair of Limiters	691.040




Pair of Knives	690.041
Pair of Limiters	691.041



Pair of Knives	690.042
Pair of Limiters	691.042



Pair of Knives	690.043
Pair of Limiters	691.043



Pair of Knives	690.044
Pair of Limiters	691.044


Note: all knives & limiters available only in pairs

Drawings are 1:2 scale


Dimensions in mm.

www.dahm.no


SP




Pair of Knives	690.045
Pair of Limiters	691.045




Pair of Knives	690.046
Pair of Limiters	691.046




Pair of Knives	690.047
Pair of Limiters	691.047




Pair of Knives	690.048
Pair of Limiters	691.048




Pair of Knives	690.049
Pair of Limiters	691.049




Pair of Knives	690.050
Pair of Limiters	691.050




Pair of Knives	690.051
Pair of Limiters	691.051




Pair of Knives	690.052
Pair of Limiters	691.052




Pair of Knives	690.053
Pair of Limiters	691.053




Pair of Knives	690.054
Pair of Limiters	691.054




Pair of Knives	690.055
Pair of Limiters	691.055




Pair of Knives	690.056
Pair of Limiters	691.056



Pair of Knives	690.057
Pair of Limiters	691.057



Pair of knives	690.058
Pair of limiters	691.058



Pair of knives	690.059
Pair of limiters	691.059

Note: all knives & limiters available only in pairs

Drawings are 1:2 scale

Dimensions in mm.


www.dahm.no

Profile Knives & Limiters


Cutting length=40mm Thickness=4mm

CMT ORANGE TOOLS™


SP




Pair of Knives	690.060
Pair of Limiters	691.060




Pair of Knives	690.061
Pair of Limiters	691.061




Pair of Knives	690.062
Pair of Limiters	691.062




Pair of Knives	690.063
Pair of Limiters	691.063




Pair of Knives	690.064
Pair of Limiters	691.064




Pair of Knives	690.065
Pair of Limiters	691.065




Pair of Knives	690.066
Pair of Limiters	691.066




Pair of Knives	690.067
Pair of Limiters	691.067




Pair of Knives	690.068
Pair of Limiters	691.068




Pair of Knives	690.069
Pair of Limiters	691.069




Pair of Knives	690.070
Pair of Limiters	691.070




Pair of Knives	690.071
Pair of Limiters	691.071



Pair of Knives	690.072
Pair of Limiters	691.072



Pair of Knives	690.073
Pair of Limiters	691.073



Pair of Knives	690.074
Pair of Limiters	691.074


Note: all knives & limiters available only in pairs

Drawings are 1:2 scale


Dimensions in mm.

www.dahm.no


SP




Pair of Knives	690.075
Pair of Limiters	691.075




Pair of Knives	690.076
Pair of Limiters	691.076




Pair of Knives	690.077
Pair of Limiters	691.077




Pair of Knives	690.078
Pair of Limiters	691.078




Pair of Knives	690.079
Pair of Limiters	691.079




Pair of Knives	690.080
Pair of Limiters	691.080




Pair of knives	690.081
Pair of limiters	691.081




Pair of Knives	690.082
Pair of Limiters	691.082




Pair of Knives	690.083
Pair of Limiters	691.083




Pair of Knives	690.084
Pair of Limiters	691.084




Pair of Knives	690.085
Pair of Limiters	691.085




Pair of Knives	690.086
Pair of Limiters	691.086



Pair of Knives	690.087
Pair of Limiters	691.087



Pair of Knives	690.088
Pair of Limiters	691.088



Pair of Knives	690.089
Pair of Limiters	691.089

Note: all knives & limiters available only in pairs

Drawings are 1:2 scale

Dimensions in mm.


www.dahm.no

Profile Knives & Limiters


Cutting length=40mm Thickness=4mm

CMT ORANGE TOOLS


SP




Pair of Knives	690.090
Pair of Limiters	691.090




Pair of Knives	690.091
Pair of Limiters	691.091




Pair of Knives	690.092
Pair of Limiters	691.092




Pair of Knives	690.093
Pair of Limiters	691.093




Pair of Knives	690.094
Pair of Limiters	691.094




Pair of Knives	690.095
Pair of Limiters	691.095




Pair of Knives	690.096
Pair of Limiters	691.096




Pair of Knives	690.097
Pair of Limiters	691.097




Pair of Knives	690.098
Pair of Limiters	691.098




Pair of Knives	690.099
Pair of Limiters	691.099




Pair of Knives	690.100
Pair of Limiters	691.100




Pair of Knives	690.101
Pair of Limiters	691.101



Pair of Knives	690.102
Pair of Limiters	691.102



Pair of Knives	690.103
Pair of Limiters	691.103



Pair of Knives	690.104
Pair of Limiters	691.104


Note: all knives & limiters available only in pairs

Drawings are 1:2 scale


Dimensions in mm.

www.dahm.no


SP




Pair of Knives	690.105
Pair of Limiters	691.105




Pair of Knives	690.106
Pair of Limiters	691.106




Pair of Knives	690.107
Pair of Limiters	691.107




Pair of Knives	690.108
Pair of Limiters	691.108




Pair of Knives	690.109
Pair of Limiters	691.109




Pair of Knives	690.110
Pair of Limiters	691.110




Pair of Knives	690.111
Pair of Limiters	691.111




Pair of Knives	690.112
Pair of Limiters	691.112




Pair of Knives	690.113
Pair of Limiters	691.113




Pair of Knives	690.114
Pair of Limiters	691.114




Pair of Knives	690.115
Pair of Limiters	691.115




Pair of Knives	690.116
Pair of Limiters	691.116



Pair of Knives	690.117
Pair of Limiters	691.117



Pair of Knives	690.118
Pair of Limiters	691.118



Pair of Knives	690.119
Pair of Limiters	691.119

Note: all knives & limiters available only in pairs

Drawings are 1:2 scale

Dimensions in mm.


www.dahm.no

Profile Knives & Limiters


Cutting length=40mm Thickness=4mm

CMT ORANGE TOOLS™


SP




Pair of Knives	690.120
Pair of Limiters	691.120




Pair of Knives	690.121
Pair of Limiters	691.121




Pair of Knives	690.122
Pair of Limiters	691.122




Pair of Knives	690.123
Pair of Limiters	691.123




Pair of Knives	690.124
Pair of Limiters	691.124




Pair of Knives	690.125
Pair of Limiters	691.125




Pair of Knives	690.126
Pair of Limiters	691.126




Pair of Knives	690.127
Pair of Limiters	691.127




Pair of Knives	690.128
Pair of Limiters	691.128




Pair of Knives	690.129
Pair of Limiters	691.129




Pair of Knives	690.130
Pair of Limiters	691.130




Pair of Knives	690.131
Pair of Limiters	691.131



Pair of Knives	690.132
Pair of Limiters	691.132



Pair of Knives	690.133
Pair of Limiters	691.133



Pair of Knives	690.134
Pair of Limiters	691.134


Note: all knives & limiters available only in pairs

Drawings are 1:2 scale


Dimensions in mm.

www.dahm.no


SP




Pair of Knives	690.135
Pair of Limiters	691.135




Pair of Knives	690.170
Pair of Limiters	691.170




Pair of Knives	690.171
Pair of Limiters	691.171




Pair of Knives	690.172
Pair of Limiters	691.172




Pair of Knives	690.173
Pair of Limiters	691.173




Pair of Knives	690.174
Pair of Limiters	691.174




Pair of Knives	690.175
Pair of Limiters	691.175



Pair of Knives	690.176
Pair of Limiters	691.176




Pair of Knives	690.177
Pair of Limiters	691.177




Pair of Knives	690.192
Pair of Limiters	691.192


Profile Knives & Limiters
Cutting length=50mm Thickness=4mm




Pair of Knives	690.500
Pair of Limiters	691.500



Pair of Knives	690.501
Pair of Limiters	691.501



Pair of Knives	690.502
Pair of Limiters	691.502



Pair of Knives	690.503
Pair of Limiters	691.503

Note: all knives & limiters available only in pairs

Drawings are 1:2 scale

Dimensions in mm.


www.dahm.no

Profile Knives & Limiters


Cutting length=50mm Thickness=4mm

CMT ORANGE TOOLS


SP




Pair of Knives	690.504
Pair of Limiters	691.504




Pair of Knives	690.505
Pair of Limiters	691.505




Pair of Knives	690.506
Pair of Limiters	691.506




Pair of Knives	690.507
Pair of Limiters	691.507




Pair of Knives	690.508
Pair of Limiters	691.508




Pair of Knives	690.509
Pair of Limiters	691.509




Pair of Knives	690.510
Pair of Limiters	691.510




Pair of Knives	690.511
Pair of Limiters	691.511




Pair of Knives	690.512
Pair of Limiters	691.512




Pair of Knives	690.513
Pair of Limiters	691.513




Pair of Knives	690.514
Pair of Limiters	691.514




Pair of Knives	690.515
Pair of Limiters	691.515



Pair of Knives	690.516
Pair of Limiters	691.516



Pair of Knives	690.517
Pair of Limiters	691.517




Pair of Knives	690.518
Pair of Limiters	691.518

Note: all knives & limiters available only in pairs


Drawings are 1:2 scale

Dimensions in mm.

www.dahm.no




Pair of Knives	690.519
Pair of Limiters	691.519




Pair of Knives	690.520
Pair of Limiters	691.520


SP




Pair of Knives	690.522
Pair of Limiters	691.522




Pair of Knives	690.523
Pair of Limiters	691.523




Pair of Knives	690.524
Pair of Limiters	691.524




Pair of Knives	690.541
Pair of Limiters	691.541




Pair of Knives	690.542
Pair of Limiters	691.542




Pair of Knives	690.543
Pair of Limiters	691.543




Pair of Knives	690.544
Pair of Limiters	691.544




Pair of Knives	690.545
Pair of Limiters	691.545




Pair of Knives	690.546
Pair of Limiters	691.546




Pair of Knives	690.547
Pair of Limiters	691.547



Pair of knives	690.548
Pair of limiters	691.548



Pair of Knives	690.549
Pair of Limiters	691.549



Pair of Knives	690.550
Pair of Limiters	691.550

Note: all knives & limiters available only in pairs

Drawings are 1:2 scale

Dimensions in mm.


www.dahm.no

Profile Knives & Limiters


Cutting length=50mm Thickness=4mm

CMT ORANGE TOOLS™


SP




Pair of Knives	690.551
Pair of Limiters	691.551




Pair of Knives	690.552
Pair of Limiters	691.552




Pair of Knives	690.553
Pair of Limiters	691.553




Pair of Knives	690.554
Pair of Limiters	691.554




Pair of Knives	690.555
Pair of Limiters	691.555




Pair of Knives	690.556
Pair of Limiters	691.556




Pair of Knives	690.557
Pair of Limiters	691.557




Pair of Knives	690.558
Pair of Limiters	691.558




Pair of Knives	690.559
Pair of Limiters	691.559




Pair of Knives	690.560
Pair of Limiters	691.560




Pair of Knives	690.561
Pair of Limiters	691.561




Pair of Knives	690.562
Pair of Limiters	691.562



Pair of Knives	690.563
Pair of Limiters	691.563



Pair of Knives	690.564
Pair of Limiters	691.564




Pair of Knives	690.565
Pair of Limiters	691.565

Note: all knives & limiters available only in pairs


Drawings are 1:2 scale

Dimensions in mm.

www.dahm.no




Pair of Knives	690.566
Pair of Limiters	691.566




Pair of Knives	690.567
Pair of Limiters	691.567


SP




Pair of Knives	690.568
Pair of Limiters	691.568




Pair of Knives	690.569
Pair of Limiters	691.569




Pair of Knives	690.570
Pair of Limiters	691.570




Pair of Knives	690.571
Pair of Limiters	691.571




Pair of knives	690.572
Pair of Limiters	691.572




Pair of Knives	690.573
Pair of Limiters	691.573




Pair of Knives	690.574
Pair of Limiters	691.574




Pair of Knives	690.575
Pair of Limiters	691.575




Pair of Knives	690.576
Pair of Limiters	691.576




Pair of Knives	690.577
Pair of Limiters	691.577



Pair of Knives	690.578
Pair of Limiters	691.578



Pair of Knives	690.579
Pair of Limiters	691.579



Pair of Knives	690.580
Pair of Limiters	691.580

Note: all knives & limiters available only in pairs


Drawings are 1:2 scale

Dimensions in mm.

www.dahm.no

Blank Knives & Limiters (to be sharpened)

CMT ORANGE TOOLS™




690-691

SP HS

DESCRIPTION	I mm	LB mm	L mm	Max mm	ORDER NO. SP	ORDER NO. HS
Pair of knives	40	32,5	44,5	18	**690.193**	**690.193H** new
Pair of knives	50	34	46	20	**690.599**	**690.599H** new
Pair of blank limiters	38	16	28	2	**691.190**	new
Pair of blank limiters	38	24	36	10	**691.192**	new
Pair of blank limiters	38	32,5	44,5	18	**691.193**	
Pair of blank limiters	48	34	46	20	**691.599**	

Pair of Bore Reducers




699

D mm	B mm	ORDER NO.	D mm	B mm	ORDER NO.
19,05	12,7	**699.019.13**	35	31,75	**699.035.31**
25,4	19,05	**699.026.19**	40	30	**699.040.30**
30	19,05	**699.030.19**	40	32	**699.040.32**
30	25,4	**699.030.26**	40	35	**699.040.35**
31,75	19,05	**699.031.19**	50	30	**699.050.30**
31,75	25,4	**699.031.26**	50	32	**699.050.32**
31,75	30	**699.031.30**	50	35	**699.050.35**
35	30	**699.035.30**	50	40	**699.050.40**
35	32	**699.035.32**			

For use only paired.

Chucks & “ER20” Collets for Spindle Moulder Machine



796


S mm	B mm	L mm	ORDER NO.
M12x1,75	3 ~ 12,7	43	**796.122.00**
M14x2	3 ~ 12,7	43	**796.142.00**
M16x2	3 ~ 12,7	43	**796.162.00**

Spare parts **992.483.03** M25x1,5mm clamping nut
991.483.00 “ER20” key

TECHNICAL DETAILS:
Super strength steel.
Precisely machined for accuracy.

Collet not included.

“ER20” Precision Collets for 796.122/142/162 Items




184

B mm	ORDER NO.	B mm	ORDER NO.
3	**184.030.20**	8	**184.080.20**
5	**184.050.20**	10	**184.100.20**
6	**184.060.20**	12	**184.120.20**
6,35	**184.064.20**	12,7	**184.127.20**

www.dahm.no

HS Corrugated Back Moulder Knives



IN QUADROPACK PACKAGING

793

HS


L mm	H mm	K mm	Knives pieces for each set	ORDER NO. HS
40	50	8	4	793.040.50
40	60	8	4	793.040.60
40	70	8	4	793.040.70
60	50	8	4	793.060.50
60	60	8	4	793.060.60
60	70	8	4	793.060.70
80	50	8	4	793.080.50
80	60	8	4	793.080.60
80	70	8	4	793.080.70
100	50	8	4	793.100.50
100	60	8	4	793.100.60
100	70	8	4	793.100.70
120	50	8	4	793.120.50
120	60	8	4	793.120.60
120	70	8	4	793.120.70
130	60	8	4	793.130.60
130	70	8	4	793.130.70
650	40	8	4	793.650.40
650	50	8	4	793.650.50
650	60	8	4	793.650.60
650	70	8	4	793.650.70

REMARK: *special dimensions available on request.*

MATERIAL	HS
Dry softwood	●
Wet softwood	●
Dry hardwood	●
Wet hardwood	○

● **Suitable**
○ **Party suitable**

TECHNICAL DETAILS:
Corrugated back moulder knives for profile cutter heads with precise positioning, angle 60°, pitch 1,6mm.



Set of 2 Magnetic Knife Setting Jigs

CMT792

Insert your knives into the tool holders and align them perfectly with this set! Perfect micro adjustments on will guarantee excellent cutting performance!

1. **MAGNETIC STOP**
2. **JOINTS WITH MAGNETIC CONNECTORS**
3. **LOCK SCREW**








Supplied in a solid wooden box

2 setup possibilities




Positioning on the tool holder body with detection of the knife position.

Direct positioning on both the planer table and the tool holder body with detection of the knife position.

www.dahm.no

Planer & Jointer Knives

CMT ORANGE TOOLS



IN QUADROPACK PACKAGING

792


SP HS HW

L mm	H mm	K mm	KNIVES pieces for each set	ORDER NO. SP	ORDER NO. HS	ORDER NO. HW
120	30	3	2		792.120.30	
130	30	3	2	792.131.30	792.130.30	792.132.30
150	30	3	2		792.150.30	
180	30	3	2	792.181.30	792.180.30	792.182.30
200	30	3	2	792.201.30	792.200.30	
210	30	3	2	792.211.30	792.210.30	
230	30	3	2	792.231.30	792.230.30	792.232.30
250	30	3	2	792.251.30	792.250.30	792.252.30
260	30	3	2	792.261.30	792.260.30	792.262.30
300	30	3	2	792.301.30	792.300.30	792.302.30
310	30	3	2	792.311.30	792.310.30	792.312.30
350	30	3	2	792.351.30	792.350.30	792.352.30
400	30	3	2	792.401.30	792.400.30	792.402.30
410	30	3	2	792.411.30	792.410.30	792.412.30
430	30	3	2	792.431.30	792.430.30	792.432.30
450	30	3	2	792.451.30	792.450.30	792.452.30
500	30	3	2	792.501.30	792.500.30	792.502.30
510	30	3	2	792.511.30	792.510.30	792.512.30
520	30	3	2	792.521.30	792.520.30	792.522.30
530	30	3	2	792.531.30	792.530.30	792.532.30
600	30	3	2	792.601.30	792.600.30	792.602.30
610	30	3	2	792.611.30	792.610.30	792.612.30
630	30	3	2	792.631.30	792.630.30	792.632.30
640	30	3	2		792.640.30	
710	30	3	2		792.710.30	
810	30	3	2	792.811.30	792.810.30	792.812.30
1050	30	3	2	792.998.30	792.997.30	792.999.30
300	35	3	2		792.300.35	
310	35	3	2	792.311.35		
350	35	3	2	792.351.35	792.350.35	
400	35	3	2	792.401.35	792.400.35	
410	35	3	2	792.411.35	792.410.35	
430	35	3	2		792.430.35	
450	35	3	2	792.451.35	792.450.35	
500	35	3	2	792.501.35	792.500.35	
510	35	3	2	792.511.35	792.510.35	
520	35	3	2	792.521.35	792.520.35	
530	35	3	2	792.531.35	792.530.35	
550	35	3	2	792.551.35	792.550.35	new
600	35	3	2	792.601.35	792.600.35	
610	35	3	2	792.611.35	792.610.35	
630	35	3	2	792.631.35	792.630.35	
650	35	3	2	792.651.35	792.650.35	new
710	35	3	2		792.710.35	
810	35	3	2	792.811.35	792.810.35	
820	35	3	2	792.821.35		
1050	35	3	2	792.998.35	792.997.35	

MATERIAL	SP	HS	HW
Dry softwood	○	●	
Wet softwood	○	○	
Dry hardwood	○	●	●
Wet hardwood	○	●	○
Chipboard			○
MDF			○
Glulam		○	●
Solid surface			○

● **Suitable**
○ **Party suitable**

REMARK: *special dimensions available on request.*
The mirror finish on HW knives produces both razor sharp and extremely durable cutting edges.




www.dahm.no


CMT ORANGE TOOLS

795


HPS


TERSA







CENTROSTAR
CENTROFIX
QUICKFIX





CENTROLOCK





2 KNIVES FOR EACH SET

TERSA				CENTROSTAR, CENTROFIX, QUICKFIX				CENTROLOCK			
L mm	H mm	K mm	ORDER NO.	L mm	H mm	K mm	ORDER NO.	L mm	H mm	K mm	ORDER NO.
								20	16	3	795.020.16*
80	10	2,3	795.080.10*					80	16	3	795.080.16*
100	10	2,3	795.100.10	100	12	2,7	795.100.12*				
110	10	2,3	795.110.10	110	12	2,7	795.110.12*				
120	10	2,3	795.120.10	120	12	2,7	795.120.12				
130	10	2,3	795.130.10	130	12	2,7	795.130.12	130	16	3	795.130.16
150	10	2,3	795.150.10	150	12	2,7	795.150.12	150	16	3	795.150.16
				160	12	2,7	795.160.12*				
170	10	2,3	795.170.10	170	12	2,7	795.170.12*	170	16	3	795.170.16
180	10	2,3	795.180.10	180	12	2,7	795.180.12	180	16	3	795.180.16
				190	12	2,7	795.190.12*	190	16	3	795.190.16
				200	12	2,7	795.200.12*				
210	10	2,3	795.210.10					210	16	3	795.210.16
				220	12	2,7	795.220.12*				
230	10	2,3	795.230.10	230	12	2,7	795.230.12	230	16	3	795.230.16
								235	16	3	795.235.16*
				240	12	2,7	795.240.12	240	16	3	795.240.16
250	10	2,3	795.250.10								
260	10	2,3	795.260.10					260	16	3	795.260.16
				270	12	2,7	795.270.12*	270	16	3	795.270.16
				280	12	2,7	795.280.12*				
300	10	2,3	795.300.10								
310	10	2,3	795.310.10	310	12	2,7	795.310.12	310	16	3	795.310.16
330	10	2,3	795.330.10*								
350	10	2,3	795.350.10	350	12	2,7	795.350.12*				
				360	12	2,7	795.360.12*				
400	10	2,3	795.400.10	400	12	2,7	795.400.12				
410	10	2,3	795.410.10	410	12	2,7	795.410.12				
420	10	2,3	795.420.10	420	12	2,7	795.420.12*				
430	10	2,3	795.430.10	430	12	2,7	795.430.12*				
450	10	2,3	795.450.10	450	12	2,7	795.450.12*				
500	10	2,3	795.500.10								
510	10	2,3	795.510.10	510	12	2,7	795.510.12				
520	10	2,3	795.520.10	520	12	2,7	795.520.12				
530	10	2,3	795.530.10	530	12	2,7	795.530.12*				
540	10	2,3	795.540.10								
610	10	2,3	795.610.10	610	12	2,7	795.610.12				
				620	12	2,7	795.620.12				
630	10	2,3	795.630.10	630	12	2,7	795.630.12				
635	10	2,3	795.635.10								
640	10	2,3	795.640.10	640	12	2,7	795.640.12				
650	10	2,3	795.650.10	650	12	2,7	795.650.12*				
710	10	2,3	795.710.10	710	12	2,7	795.710.12*				
				810	12	2,7	795.810.12*				
860	10	2,3	795.860.10*								
910	10	2,3	795.910.10*								
930	10	2,3	795.930.10	930	12	2,7	795.930.12*	930	16	3	795.930.16

*While supplies last

MATERIAL	GOOD	EXCELLENT
Dry Softwood		●
Wet Softwood		●
Dry Hardwood		●
Wet Hardwood		●
Exotic Hardwood	●	

TECHNICAL DETAILS:

HPS® was especially developed for the woodworking industry. The Thyssen-Krupp heat treatment division developed a special heat treatment system in a modern high vacuum oven which gives this steel its special attributes and renters it an out standing alternative to HSS steels. The main advantages are:


- superb wear resistance
- maximum level of toughness
- resistance to softening
- easy to profile
- long lasting tested

Test result: Wood=Oak, Spinadle speed=6000 rpm, feed=24 meter/min
= Result HPS® 17500 meters.
= Result HSS 10000 meters.

www.dahm.no

HWM Reversible Knives


CMT ORANGE TOOLS™



790 Standard Reversible Knives 2 Cutting Edges


HWM

L mm	H mm	K mm	A	ORDER NO. F1730	S2020	U2300	N2550
7,5	12	1,5	35°	790.075.00			
7,65	12	1,5	35°	790.076.00			
9,6	12	1,5	35°	790.096.00			
15	12	1,5	35°	790.150.00			
19,5	12	1,5	4/35°	790.195.12			
20	12	1,5	35°	790.200.00	790.200.02	790.200.03	




790 Standard Reversible Knives 2 Cutting Edges

L mm	H mm	K mm	A	ORDER NO. F1730	S2020	U2300	N2550
24,7	12	1,5	35°	790.250.00			
30	12	1,5	35°	790.300.00	790.300.02	790.300.03	790.300.04
30	12	1,5	45°		790.300.20		
40	12	1,5	35°	790.400.00	790.400.02	790.400.03	
50	12	1,5	35°	790.500.00	790.500.02	790.500.03	790.500.04
60	12	1,5	35°	790.600.00		790.600.03	




790 Standard Reversible Knives 4 Cutting Edges

L mm	H mm	K mm	A	ORDER NO. F1730	S2020	U2300	N2550
29,5	9	1,5	35°	790.295.09			
29,5	12	1,5	35°	790.295.12			
39,5	9	1,5	35°	790.395.09			
39,5	12	1,5	35°	790.395.12			
49,5	9	1,5	35°	790.495.09			
49,5	12	1,5	35°	790.495.12			




790 Standard Reversible Knives 4 Cutting Edges

L mm	H mm	K mm	A	ORDER NO. F1730	S2020	U2300	N2550
28,3	12	1,5	35°	790.283.12			
48,3	12	1,5	35°	790.483.12			




790 Standard Reversible Knives 4 Cutting Edges

L mm	H mm	K mm	A	ORDER NO. F1730	S2020	U2300	N2550
20	4,1	1,1	35°	790.200.01			
30	5,5	1,1	35°	790.300.01			
50	5,5	1,1	35°	790.500.01			



790 Standard Reversible Knives 4 Cutting Edges


L mm	H mm	K mm	A	ORDER NO. F1730	S2020	U2300	N2550
12	12	1,5	35°	790.120.00	790.120.02	790.120.03	
13,6	13,6	2	30°	790.136.00			
14	14	1,2	30°	790.140.10			
14	14	2	30°	790.140.00		790.140.03	
14	14	2	30°		790.140.02		



790 Standard Reversible Knives 4 Cutting Edges


L mm	H mm	K mm	A	ORDER NO. F1730	S2020	U2300	N2550
14	14	2	R/30°	790.140.20			

www.dahm.no




790 Standard Reversible Knives 4 Cutting Edges

L mm	H mm	K mm	A	ORDER NO. F1730	S2020	U2300	N2550
50	9	1,5	35°	**790.500.09**			




790 Standard Reversible Knives 2 Cutting Edges

L mm	H mm	K mm	A	ORDER NO. F1730	S2020	U2300	N2550
20	12	1,5	35°	**790.201.00**			
30	12	1,5	35°	**790.301.00**			
50	12	1,5	35°	**790.501.00**			




790 Standard Reversible Knives 4 Cutting Edges

L mm	H mm	K mm	ORDER NO. F1730	S2020	U2300	N2550
18	18	1,95	**790.181.00**			
18	18	2,45	**790.182.00**			




790 Standard Reversible Knives 30°

L mm	H mm	K mm	A	ORDER NO. F1730	S2020	U2300	N2550
22	19	2	30°		**790.220.02**		



790 Edge Rounding/Chamfering Reversible Knives

L mm	H mm	K mm	R mm	A	ORDER NO. F1730	S2020	U2300	N2550
16	22	5	1,5		**790.161.00**			
16	22	5	2		**790.162.00**			
16	22	5	3		**790.163.00**			
16	22	5		45°	**790.160.00**			



790 Profiled Rounding Reversible Knives 4 Cutting Edges

L mm	H mm	K mm	R mm	A	ORDER NO. F1730	S2020	U2300	N2550
19,5	9	1,5	2	35°	**790.020.00**			
19,5	9	1,5	3	35°	**790.030.00**			
19,5	9	1,5	5	35°	**790.050.00**			
24	12	1,5	6,4	35°	**790.064.00**			
24	12	1,5	8	35°	**790.080.00**			

MATERIAL	F1730	S2020	U2300	N2550
Dry softwood	●			
Wet softwood	●			
Dry hardwood	●	●		
Wet hardwood	●	●		
Chipboard		●	●	●
MDF		●	●	●
HDF			●	●
Solid surface				●

● **Suitable**

TECHNICAL DETAILS:

F1730 Hardness (HV10): 1.760 - Transverse rupture strength (N/mm²): 2.100

S2020 Hardness (HV10): 1.680 - Transverse rupture strength (N/mm²): 3.700

U2300 Hardness (HV10): 2.300 - Transverse rupture strength (N/mm²): 3.500

N2550 Hardness (HV10): 2.550 - Transverse rupture strength (N/mm²): 3.200

All knives are supplied in a 10 pc. case.






www.dahm.no

HWM Reversible Knives for Portable Planers

CMT ORANGE TOOLS™










10-pcs. case



2-pcs. blister case
(790.755/790.780/790.806/790.805/790.820)

790

HWM

L mm	H mm	K mm	MACHINE	MODEL MACHINE	ORDER NO. 2 pcs. blister case	ORDER NO. 10 pcs. blister case
56,0	5,5	1,1	Adler			**790.560.00**
60,0	5,5	1,1	Wegoma			**790.600.01**
75,5	5,5	1,1	Aeg	HTH75	**790.755**	**790.755.00**
			Black & Decker	DN75, 750SR, 600K		
			Bosch	0590, P400, 1590,1591		
			Festo	REP75		
			Haffner	FH222		
			Holz-Her	2223, 2286, 2320		
			Kress	Jet-Star 6701, 6702		
			Mafell	HU75		
			Metabo	6375		
			Scheer	MH75/3, MH80		
			Skil	98H		
78,0	5,5	1,1	Virutex		**790.780**	**790.780.00**
80,5	5,9	1,2	Elu	MFF40, MFF80, MFF81, MFF81EK, PF161	**790.806**	**790.805.00**
80,5	5,5	1,1	Elu	MFF80	**790.805**	**790.805.01**
			Aeg			
			Bosch			
			Haffner			
82,0	5,5	1,1	Aeg	EH82, EH825, EH822, EH450, EH700, EH82-1, H500, H750, EH700R	**790.820**	**790.820.00**
			Black & Decker	DN76		
			Bosch	PHO 100/150, PHO 200/300 4387, PHO 2-82/3-82, Gustav, HO0882		
			Casals	CE82		
			DeWalt	DW678, DW678EK, DW680		
			Elu	HH15, HH40, HH40K, HH40EK		
			Fein	HS2151		
			Felisatti	TP282		
			Haffner	FH224		
			Hitachi	F20, F20A, FP20A, P20V, P20SA		
			Holz-Her	2321, 2322		
			Legna	R82, G82		
			Mafell	EHU82, MHU82		
			Makita	1001, 1100, 1125B, 1900B, 1901, 1923B, 1923H, 1923HO		
			Metabo	4382, 8382, 0882, 0883, E0983		
			Perless	HHB82B		
			Peugeot	RA400, 82RAC, RA82CS, BR82 BRA1-82, BRA3-82, RA1082CA		
			Ryobi	L1323-A		
			Skil	H92, H94, H95, H96, H97 1506, 1510		
			Stayer	980B		
92,0	5,5	1,2	Aeg Hitachi Ryobi	450 F30A, FU30 L120N, L150N, L1205N, L1323		**790.920.00**
102,0	5,5	1,1	Aeg	HB750, EH102, HBE800		**790.992.00**

Technical details:

- Order no. ISO:	K40
- Hardness (HV10):	1.400
- Transverse rupture strength (N/mm²):	2.600

Application:

Softwood	Good
Hardwood	Suitable
Plywood	Suitable

www.dahm.no




Router Bits & Sets

PRODUCTS	PAGE
Straight & Spiral Bits	122~131
Trimmer & Profiler Bits	132~143
Rebater Bits	144~146
Slotting & Grooving Bits	147~151
Jointing Bits	152~159
Dovetail Bits	160~162
Lettering, "V" Groove & Chamfer Bits	163~168
Drawer Pull & Radius Bits	169~172
Ovolo & Rounding Over Bits	172~174
Bead & Ogee Bits	175~183
Molding Bits	183~188
Panel Bits	188~194
Solid Surface Bits	195~201
Router Bit Sets	202~213

www.dahm.no

BUILDING THE WORLD'S FINEST CUTTING TOOLS

We built our foundations - and our reputation for high quality - on the craftsman-like manufacturing of boring bits and router bits. Times have changed and technology has completely altered the way things are done, and in this regard CMT is no exception. Our facilities have been newly renovated and our equipment today represents the most advanced technology available on the market, but we still make and will continue to make routers and boring bits with all the skill and care that we always have.




DESIGN

We engineer each tool with as purpose in mind. Years of developing high performance tools means that many of our top-selling tools are tried and true, the result of continuously perfecting each design, but we don't stop there. New materials, new profiles and new methods of working keep emerging. At CMT, we want to stay on the cutting edge of what's new in the industry so our technical department constantly evaluates current market developments and, by using state of the art software and years of experience, designs tools that are worthy of the CMT brand.

MATERIALS

Essentially, the main components of a router bit are just two: steel and carbide. If either of these is less than the best, the tool we make will show it. We've researched steel and carbide since the beginning, and found exactly what we were looking for:

Superior Steel. All our steel comes from right above the border, in Switzerland, where they use an exclusive hot drawing process to forge the solid bar stock we use to manufacture our router bit shanks and bodies. The result is steel that is superior in strength and exceptionally resistant to fatigue and abrasion.






www.dahm.no

High-Grade Tungsten Carbide. If steel is what gives our tools strength, carbide is what gives them intelligence. The capacity of the carbide tip to cut precisely and to last a long time is critical for the performance of any tool, so at CMT we use only premium micrograin carbide from Luxembourg to make the tips for our router bits.

MANUFACTURING

Turning, Milling and Cutting. Our biggest investment in recent years has been in upgrading production. Today, all machinery at CMT is fully automated. CNC machines run by specially trained operators who make sure that the shanks and bodies of our router bits and boring bits are accurate and perfectly balanced.



Heat Forged Steel Bodies for Large Diameter Bits. No router bits are exactly the same, sometimes not even in the way they are made. Certain bits require a few more steps than others, like heat forging the steel of larger diameter bits before turning it down into precise bit bodies. This extra step produces a radial grain orientation which gives large diameter bits extra strength and durability.

Brazing. We have pioneered the art of brazing. Not only does our unique custom-designed computerized brazing equipment help eliminate the inconsistencies found in old fashioned hand brazing, but our silver-copper-silver brazing 'sandwich' provides a tight bond between the steel and the carbide, with a shock absorbing effect to protect the carbide tips when cutting harder woods.

Specially Formulated Carbide for Specific Applications. You have to cut every kind material, so we make sure that our carbide tips can handle each individual job. This means specially formulating the carbide of each tool so that the compositions vary from being super hard (for tough cutting jobs like laminates) to being less hard (to absorb the impact when cutting large profiles) and everything in between.

Grinding and Sharpening. The final step in the production process is no different from the rest: sharpening and grinding are done to extreme precision on multi-axis CNC machines. Each bevel and angle is ground or sharpened to the micron, to produce a cutting edge that is both razor sharp yet extremely durable.



680°C in seconds - and the brazing is complete.

QUALITY CONTROL

In even the most carefully done task, there's always room for error. However at CMT, we take measures to prevent even this. We always manually check the quality of our tools at each step of the manufacturing process, and we still make test cuts with rail & stile bits to make sure the cut fits. However, now we also use a fully automatic measuring process that measures every dimension of the tool without actually coming into contact with it, to make sure that the tool measurements are accurate and that the profiles conform precisely to technical specifications. We also use this system to gauge the wear and tear on the CNC machines.



CMT's fully automatic measuring system.

www.dahm.no

WHAT'S THE SECRET TO FLAWLESS EDGE PROFILES WITH NO REWORK?

WOOD® Magazine Best Overall 1994 Wood's Choice Router Bits

CMT Overall Rating 10!
Top Performing Router Bits



MULTI-AXIS GRINDING CREATES A 3X LONGER LASTING MIRROR FINISH

Each cutting edge is precisely sharpened to the micron, in order to produce a cutting angle, which is razor sharp, yet extremely durable.

ANTI-KICKBACK DESIGN

Controls depth of cut and minimizes the chance of kickback, reducing your risk of injury.

SINTERHIP HI-DENSITY INDUSTRIAL CHROME CARBIDE™

SINTERHIP HI-DENSITY INDUSTRIAL CHROME CARBIDE™

New process called SinterHIP (Hot Isostatic Pressing), helps prevent material failure and increases cutting life.

TRI-METAL BRAZING

Our Silver-Copper-Silver brazing protects the carbide tip when cutting harder wood or wood composites and reduces the chance of failed welds.

NON-STICK ORANGE SHIELD COATING™

NON-STICK ORANGE SHIELD COATING™

Prevents bit from heating up, reduces pitch build-up, protects against corrosion and provides a longer bit life.



Deluxe packaging


HQ STEEL

SUPERIOR HIGH-STRENGTH STEEL

We use high-quality, solid bar stock sourced from Switzerland, which provides exceptional resistance to fatigue and abrasion.


www.dahm.no

Solid Carbide Spiral Bits





Due to their spiral cutting edge which stays in continuous contact with the workpiece, these bits give a smooth, chatter-free cutting action, unlike conventional bits which have intermittent contact with the workpiece. Unsurpassed for cleaner cuts in ordinary or difficult materials, softwood, hardwood, plywood, composites etc. This new range of spiral bits with 6 - 8 - 12mm and 6,35 - 12,7mm shanks allow them to be used with a C.N.C. router and hand-routers.

Test check yourself the extraordinary quality-price ratio of these bits!



Drawing is 1:1 scale






190 Upcut & Downcut Spiral

HWM | Z2+2 | Z3+3 | RH

D mm	I mm	I1 mm	L mm	Z	ORDER NO. S=Ø8mm	ORDER NO. S=Ø9,52mm	ORDER NO. S=Ø10mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
8	32	7	80	2+2	**190.080.11**				
9,52	28,6	7	76,2	2+2		**190.504.11**			
10	32	7	80	2+2			**190.100.11**		
10	42	7	90	2+2			**190.101.11**		
new 12	42	7	90	2+2				**190.120.11**	
12	52	7	100	2+2				**190.121.11**	
new 12,7	25,4	16	76,2	2+2					**190.505.11**
12,7	28,6	16	76,2	2+2					**190.506.11**
12,7	34,9	16	88,9	2+2					**190.507.11**
12,7	41,3	16	101,6	2+2					**190.508.11**
Up & Downcut Mortising Bits									
9,52	22,2	4,8	76,2	2+2		**190.513.11**			
9,52	25,4	5,2	76,2	3+3		**190.813.11**			
12	25,4	5,2	83	3+3				**190.320.11**	
12,7	22,2	5,2	76,2	2+2					**190.515.11**
12,7	34,9	5,2	88,9	2+2					**190.517.11**





198 Upcut

HWM | Z1 | RH

D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
3,18	12,7	50,8		**198.001.11**			
4,76	15,87	50,8		**198.005.11**			
6	22	60	**198.060.11**				
6,35	19,05	50,8		**198.007.11**			
6,35	25,4	63,5		**198.008.11**			
8	22	70			**198.080.11**		
new 8	32	80			**198.081.11**		
12	32	83				**198.120.11**	

www.dahm.no






191 Upcut Spiral

HWM Z2 RH

D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
3	12	60	**191.630.11**		**191.830.11**		
3,18	12,7	50,8		**191.001.11**			
3,5	12	60	**191.635.11**				
3,97	12,7	50,8		**191.003.11**			
4	15	60	**191.640.11**		**191.840.11**		
4,76	19,05	50,8		**191.005.11**			
5	17	60	**191.650.11**		**191.850.11**		
6	27	70	**191.060.11**		**191.860.11**		
6,35	19,05	50,8		**191.007.11**			
6,35	25,4	63,5		**191.008.11**			
7	32	80			**191.870.11**		
7,94	25,4	76,2					**191.501.11**
8	22	70			**191.080.11**		
8	32	80			**191.081.11**		
8	42	90			**191.082.11**		
9	32	83				**191.890.11**	
9,53	31,75	76,2					**191.503.11**
10	32	80			**191.800.11**		
10	32	83				**191.900.11**	
10	42	90				**191.901.11**	
12	35	83			**191.820.11**	**191.120.11**	
12	42	90				**191.121.11**	
12	52	100				**191.122.11**	
12,7	31,75	76,2					**191.505.11**
12,7	38,1	88,9					**191.506.11**
12,7	50,8	101,6					**191.507.11**





192 Downcut Spiral


HWM Z2 RH


D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
3	12	60	**192.630.11**		**192.830.11**		
3,18	12,7	50,8		**192.001.11**			
3,97	12,7	50,8		**192.003.11**			
4	15	60	**192.640.11**		**192.840.11**		
4,76	19,05	50,8		**192.005.11**			
5	17	60	**192.650.11**		**192.850.11**		
6	27	70	**192.060.11**		**192.860.11**		
6,35	19,05	50,8		**192.007.11**			
6,35	25,4	63,5		**192.008.11**			
7,94	25,4	76,2					**192.501.11**
8	22	70			**192.080.11**		
8	32	80			**192.081.11**		
8	42	90			**192.082.11**		
9,53	31,75	76,2					**192.503.11**
10	32	80			**192.800.11**		
10	32	83				**192.900.11**	
12	35	83			**192.820.11**	**192.120.11**	
12,7	31,75	76,2					**192.505.11**
12,7	38,1	88,9					**192.506.11**
12,7	50,8	101,6					**192.507.11**

www.dahm.no

Straight Bits with Centre Tip

CMT ORANGE TOOLS





Drawing is 1:1 scale

174-177

HW HWM Z2+1 RH

These industrial straight bits are made a from of stainless steel specifically created to support hard work on route machines and CNC routers.
The cutting plunging edge allows you to execute any kind of drilling and trimming jobs on soft and hardwood, wood composites and also plastic and laminated materials.

Application: used for drilling, grooving or jointing solid wood and wood composites. Can be used on machining centres, CNC routers and hand-held routers equipped with chucks or adaptors.

Plunge Centre Tip

This particolar kind of cutting plunging edge allows long-lasting performance on drilling operations.




D mm	I mm	L mm	ORDER NO. S=Ø12mm
10	35	90	**177.100.11**
12	35	90	**177.120.11**
12	50	100	**177.121.11**
14	35	90	**177.140.11**
16	35	90	**177.160.11**
16	60	110	**177.161.11**
18	35	90	**177.180.11**
18	60	110	**177.181.11**
20	35	90	**177.200.11**
22	35	90	**177.220.11**
24	35	90	**177.240.11**
25	35	90	**177.250.11**
26	35	90	**177.260.11**
28	35	90	**177.280.11**
30	35	90	**177.300.11**
35	35	90	**177.350.11**

• **HWM**

D mm	I mm	L mm	ORDER NO. S=Ø8mm
• 3	10	55	**174.030.11**
• 4	10	55	**174.040.11**
• 5	12	55	**174.050.11**
• 6	14	55	**174.060.11**
• 7	20	55	**174.070.11**
8	20	55	**174.080.11**
8	30	70	**174.081.11**
8	40	90	**174.082.11**
9	20	55	**174.090.11**
10	20	60	**174.100.11**
10	30	70	**174.102.11**
10	40	90	**174.101.11**
11	20	60	**174.110.11**
12	20	60	**174.120.11**
12	30	70	**174.122.11**
12	40	90	**174.121.11**
13	20	60	**174.130.11**
14	20	60	**174.140.11**
14	30	70	**174.142.11**
14	40	90	**174.141.11**
15	20	60	**174.150.11**
16	20	70	**174.160.11**
16	30	70	**174.162.11**
16	40	90	**174.161.11**
18	20	70	**174.180.11**
18	30	70	**174.181.11**
18	40	80	**174.182.11**
19	20	70	**174.190.11**
20	20	70	**174.200.11**
20	30	70	**174.201.11**
20	40	90	**174.202.11**
22	20	70	**174.220.11**
22	30	70	**174.221.11**
22	40	90	**174.222.11**
24	20	70	**174.240.11**
24	30	70	**174.241.11**
24	40	90	**174.242.11**
25	20	70	**174.250.11**
26	20	70	**174.260.11**
26	30	70	**174.261.11**
28	20	70	**174.280.11**
28	30	70	**174.281.11**
29	20	70	**174.290.11**
30	20	70	**174.300.11**

www.dahm.no






7/8/912

HW HWM Z2 RH


SAFETY PRECAUTIONS: never use damaged or worn bits. Always work at the recommended proper feed rate without forcing the bit. Pay particular attention when making the initial cut with a small diameter bit.
For best results when working with small diameter bits, make the cut in more than one pass.

The sharpened cutting edge top on 9mm diameter bits and larger allows for short plunging operations.





Masterpack



Drawing is 1:1 scale


D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
• 3	11	60	**712.030.11**				
• 3,2	12,7	50,8		**812.032.11**			
• 4	12	60	**712.040.11**				
• 5	18	60	**712.050.11**				
• 6	25,4	60	**712.060.11**	**812.060.11**	**912.060.11**		
• 6,35	25,4	60		**812.064.11**			
• 8	31,7	60	**712.080.11**	**812.080.11**	**912.080.11**		
• 8	31,7	75				**912.580.11**	
9	31,7	75				**912.590.11**	
9,5	31,7	63,5		**812.095.11**			
9,5	31,7	73					**812.595.11**
10	31,7	60	**712.100.11**	**812.100.11**	**912.100.11**		
10	31,7	70					**812.600.11**
10	31,7	74				**912.600.11**	
11,1	31,7	82,5					**812.611.11**
12	31,7	60	**712.120.11**	**812.120.11**	**912.120.11**		
12	31,7	70					**812.620.11**
12	38,1	95				**912.621.11**	**812.621.11**
12	50,8	108				**912.622.11**	
12,7	31,7	70		**812.127.11**	**912.127.11**		
12,7	38,1	95					**812.627.11**
12,7	50,8	108					**812.628.11**
12,7	63,5	111					**812.629.11**
14	31,7	60	**712.140.11**	**812.140.11**	**912.140.11**		
14	31,7	70				**912.640.11**	
15	31,7	66	**712.150.11**	**812.150.11**	**912.150.11**		
15	31,7	70				**912.650.11**	
15,8	31,7	70		**812.158.11**			
16	31,7	66	**712.160.11**	**812.160.11**	**912.160.11**		
16	31,7	70				**912.660.11**	**812.660.11**
18	38,1	80				**912.681.11**	
19	38,1	82,5				**912.690.11**	**812.690.11**
19	50,8	92				**912.691.11**	**812.691.11**
20	38,1	80				**912.701.11**	
22	38,1	80				**912.721.11**	
10 pc. masterpack							
12,7	50,8	108					**812.628.11-X10**

• **HWM**

www.dahm.no

Straight Bits

CMT ORANGE TOOLS™




7/8/911

HW HWM Z1 Z2 RH


If you are looking to get the most out of your time and money through more efficient production, but want nothing less than a beautiful clean edge on your finished piece, then you definitely must include CMT straight bits in your collection. These razor-sharp, double-faced cutters perfectly synthesize the characteristics and advantages that define quality CMT products. Made of special Fatigue Proof® steel and micrograin carbide, our straight bits can withstand even the heaviest work load and still give you a smooth, precise cut every time. You also get exceptional chip ejection to allow cleaner and more constant cutting. The surface of all CMT bits is protected with our trademark orange non-stick PTFE coating to help keep the bit from collecting resin, pitch and other residue.
Every bit is submitted to strict quality tests to guarantee perfect cutting tolerance, balance and concentricity. CMT bits allow production on an industrial scale using a variety of plywood, composites and natural woods.
CMT produces 91 types of straight bits in a wide range of diameters so you can find exactly what you want.

The sharpened cutting edge top on 9mm diameter bits and larger allows for short plunging operations.







Drawing is 1:1 scale




Biscuit joint using bit #7/8/911.040.11




Mortise and tenon




Rabbet




Right-angle joint



Union



Tongue and groove joint



Box joint

Plywood Groove Set




811

HW HWM Z2 RH

Our plywood groove bits are designed specifically for routing grooves and dadoes for joints in plywood. That means they match the true thickness of plywood, producing tight, accurate joints. Use our 18,2mm bit for 19mm plywood, 12,3mm bit for 12,7mm plywood and our 6mm for 6,35mm ply. No gaps or sloppy joints, guaranteed.
These money-saving 3-bit sets are available with 12,7mm or 6,35 shanks.

Example shown in 12,7mm thick plywood

This joint is made with the CMT 12,3mm straight bit in 12,7mm plywood. Notice the precise fit - no gaps.



This joint is made with a regular 12,7mm straight bit in 12,7mm plywood. Notice the extra space and ill fitting joint.

DESCRIPTION		ORDER NO. S=Ø**6,35**mm	ORDER NO. S=Ø**12,7**mm
Plywood Groove Set	(Ø6 - Ø12,3 - Ø18,2mm)	**811.001.11**	**811.501.11**

www.dahm.no

Straight Bits, Short Series

CMT ORANGE TOOLS™

D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
• 2*	4	45	**711.020.11**	**811.020.11**			
• 3	8	45	**711.030.11**	**811.030.11**			
• 3	8	50			**911.030.11**		
• 3	8	58,3				**911.530.11**	
• 3,2	9,5	45		**811.032.11**			
• 4	10	58,3				**911.540.11**	
• 4	10	45	**711.040.11**	**811.040.11**			
• 4	10	50			**911.040.11**		
• 4,75	12,7	50,8		**811.047.11**			
• 5	12	50	**711.050.11**	**811.050.11**	**911.050.11**		
• 5	12	58,3				**911.550.11**	
• 6	16	50	**711.060.11**	**811.060.11**	**911.060.11**		
• 6	19	63,5				**911.560.11**	**811.560.11**
• 6,35	19	50,8		**811.064.11**			
• 6,35	19	57,2		**811.065.11**			
• 6,35	19	63,5					**811.564.11**
• 7	18	49	**711.070.11**	**811.070.11**	**911.070.11**		
• 7	18	63,5				**911.570.11**	
• 7,6	20	50			**911.076.11**		
• 8	20	50	**711.080.11**	**811.080.11**	**911.080.11**		
• 8	25,4	70		**811.081.11**			
• 8	25,4	70					**811.581.11**
9	20	48	**711.090.11**		**911.090.11**		
9,5	19	50,8		**811.095.11**			
9,5	25,4	63,5		**811.096.11**			
9,5	25,4	66,7					**811.595.11**
10	20	48	**711.100.11**	**811.100.11**	**911.100.11**		
10	25,4	63,5					**811.600.11**
11	20	48	**711.110.11**		**911.110.11**		
12	20	50	**711.120.11**	**811.120.11**	**911.120.11**		
12	25,4	63,5				**911.620.11**	**811.620.11**
12,3	25,4	57,2		**811.123.11**			
12,3	25,4	63,5					**811.623.11**
12,7	19	57,2		**811.127.11**			
12,7	25,4	66,7					**811.627.11**
12,7	31,7	82,5					**811.628.11**
13	20	57	**711.130.11**		**911.130.11**		
14	20	50	**711.140.11**	**811.140.11**	**911.140.11**		
14,2	14,2	57,2		**811.142.11**			
15	20	57,2	**711.150.11**	**811.150.11**	**911.150.11**		
15,8	19	66,7		**811.158.11**			
15,8	25,4	63,5					**811.660.11**
16	20	57,2	**711.160.11**	**811.160.11**	**911.160.11**		
16	25,4	63,5					**811.661.11**
17	20	50	**711.170.11**				
18	20	50	**711.180.11**	**811.180.11**	**911.180.11**		
18,2	25,4	57,2		**811.182.11**			
18,2	25,4	63,5					**811.682.11**
19	20	57,2	**711.190.11**	**811.191.11**	**911.190.11**		
19	25,4	63,5					**811.690.11**
20	20	50	**711.200.11**	**811.200.11**	**911.200.11**		
22	20	57,2	**711.220.11**	**811.220.11**	**911.220.11**		
24	20	50	**711.240.11**		**911.240.11**		
25	20	50	**711.250.11**		**911.250.11**		
25,4	19	50,8		**811.254.11**			
25,4	31,7	76,2					**811.754.11**
28,5	31,7	76,2					**811.785.11**
10 pc. masterpack							
9,5	25,4	63,5					**811.096.11-X10**


• HWM
*** Z1**



Masterpack

www.dahm.no






170-171-180-181


HW Z2+1 RH

D mm	I mm	L mm		ORDER NO. S=M12x1	
6	18	60		**170.060.11**	
8	23	60		**170.080.11**	
10	23	60		**170.100.11**	
11	23	60		**170.110.11**	
12	23	60		**170.120.11**	
14	23	60		**170.140.11**	
15	25	60		**170.150.11**	
16	25	60		**170.160.11**	
18	25	60		**170.180.11**	
20	25	60		**170.200.11**	
22	25	60		**170.220.11**	
24	25	60		**170.240.11**	
25	25	60		**170.250.11**	
26	25	60		**170.260.11**	
28	25	60		**170.280.11**	
30	25	60		**170.300.11**	
35	25	60		**170.350.11**	
8	35	67		**171.080.11**	
10	35	67		**171.100.11**	
12	35	67		**171.120.11**	
14	35	67		**171.140.11**	
16	35	67		**171.160.11**	
18	35	67		**171.180.11**	
20	35	67		**171.200.11**	
22	35	67		**171.220.11**	
12	45	77		**180.120.11**	
16	45	77		**180.160.11**	
18	45	77		**180.180.11**	
20	45	77		**180.200.11**	
16	60	92		**181.160.11**	
20	60	92		**181.200.11**	

TECHNICAL DETAILS:
- Super strength steel
- 2 HW alternating precision ground cutting edges [Z2+1]

APPLICATION: ideal for cutting openings for electrical boxes and similar operations in solid wood, wood composites, plastics and laminates. Can be used on machining centres, CNC routers and hand-held routers equipped with chucks or adaptors.






173-182

HW Z2+1 RH

D mm	I mm	L mm		ORDER NO. S=M10	
6	14	50		**173.060.11**	
8	20	52		**173.080.11**	
10	22	52		**173.100.11**	
12	22	52		**173.120.11**	
14	25	52		**173.140.11**	
15	25	52		**173.150.11**	
16	25	52		**173.160.11**	
18	25	52		**173.180.11**	
20	25	52		**173.200.11**	
22	25	52		**173.220.11**	
25	25	52		**173.250.11**	
30	25	52		**173.300.11**	
8	35	67		**182.080.11**	
10	35	67		**182.100.11**	
12	35	67		**182.120.11**	
14	35	67		**182.140.11**	
16	45	77		**182.160.11**	
18	45	77		**182.180.11**	
20	45	77		**182.200.11**	

www.cmtutensili.com
www.dahm.no

5%co HS Spiral Bits for Aluminium Positive Single Flute



Suggested
MAX RPM 12.000

188


HS Z1 RH

D mm	I mm		L mm		ORDER NO. S=Ø8mm
3	12		60		**188.030.51**
4	12		60		**188.040.51**
4	40		100		**188.041.51**
5	14		60		**188.050.51**
5	40		100		**188.051.51**
6	14		60		**188.060.51**
6	40		100		**188.061.51**
7	14		60		**188.070.51**
8	14		80		**188.080.51**
8	40		100		**188.081.51**
9	14		80		**188.090.51**
10	14		80		**188.100.51**
12	14		80		**188.120.51**

TECHNICAL DETAILS:
- 5%co premium solid HS
- 1 upcut spiral cutting edge
- Upward chip ejection

APPLICATION: these tools feature a single flute design allowing both efficient and effective carving on all types of aluminium. The final result? Higher flexibility than traditional bits, enhanced productivity and high quality finishing.

5%co HS Spiral Bits for Aluminium Positive Single Flute for High Cutting Depth



Suggested
MAX RPM 12.000

189

HS Z1 RH


D mm	I mm	I_1 mm	L mm	S mm	ORDER NO.
4	46	16	90	8	**189.040.51**
5	35	18	80	8	**189.050.51**
5	35	14	120	8	**189.051.51**
5	55	16	90	8	**189.052.51**
6	45	16	90	8	**189.060.51**
8	68	14	100	8	**189.080.51**
8	55	14	80	8	**189.081.51**
10	95	14	120	10	**189.100.51**
10	70	30	100	10	**189.101.51**

TECHNICAL DETAILS:
- 5%co premium solid HS
- 1 upcut spiral cutting edge
- Upward chip ejection

APPLICATION: these tools feature a single flute design allowing both efficient and effective carving on all types of aluminium. The final result? Higher flexibility than traditional bits, enhanced productivity and high quality finishing.

www.dahm.no

Straight Router Bits with Insert Knives





651-652

INSERT CARBIDE Z1 RH 2X LONGER LIFE

Straight router bit with one replaceable mini knife and fixing wedge. Radial and axial groove for better and safe knife insertion. For finishing, routing and grooving in board materials (DTD laminated, MDF and hardwood). For use on portable routers or CNC machining centres.

Drawings are 1:1 scale





D mm	I mm	L mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
8	20	60	**651.079.11**				790.200.01	651.999.01	990.070.00	991.063.00
8	20	60		**651.080.11**			790.200.01	651.999.01	990.070.00	991.063.00
8	20	67			**651.081.11**	**651.681.11**	790.200.01	651.999.01	990.070.00	991.063.00
9,5	30	70	**651.095.11**				790.300.01	651.999.02	990.071.00	991.063.00
9,5	30	80				**651.695.11**	790.300.01	651.999.02	990.071.00	991.063.00
10	30	70		**651.100.11**			790.300.01	651.999.02	990.071.00	991.063.00
10	30	80			**651.101.11**	**651.701.11**	790.300.01	651.999.02	990.071.00	991.063.00
12	30	70		**651.120.11**			790.300.01	651.999.02	990.071.00	991.063.00
12	30	80			**651.121.11**	**651.721.11**	790.300.01	651.999.02	990.071.00	991.063.00
12	50	103			**652.121.11**	**652.621.11**	790.500.01	651.999.03	990.016.00	991.060.00
12,7	30	70	**651.127.11**				790.300.01	651.999.02	990.071.00	991.063.00
12,7	30	80				**651.727.11**	790.300.01	651.999.02	990.071.00	991.063.00
12,7	50	103				**652.628.11**	790.500.01	651.999.03	990.016.00	991.060.00
14	30	73		**651.140.11**			790.300.01	651.999.02	990.071.00	991.063.00


Straight Router Bits with Insert Knives for Laminates



652

INSERT CARBIDE Z1 RH 2X LONGER LIFE

Straight trimmer bits with one replaceable knife fixed by Torx screw.
For economical specialist applications requiring low down-time.
The 29,5x9x1,5mm knives provide a 40mm cutting lenght when operating in multiple passes.
For routing, trimming and grooving on board materials (laminated chipboards, worktop panels and MDF).
For use on portable routers.



Drawings are 1:1 scale

D mm	I mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
12	29,5	79	**652.120.11**			790.295.09	990.072.00	991.061.00
12	39,5	90	**652.122.11**			790.395.09	990.072.00	991.061.00
12,7	29,5	89			**652.627.11**	790.295.09	990.072.00	991.061.00
14	50	96		**652.141.11**		790.500.09	990.072.00	991.061.00
16	50	96		**652.161.11**		790.500.09	990.072.00	991.061.00


www.dahm.no



653

INSERT CARBIDE | Z1+1 | RH | 2X LONGER LIFE

Straight router bits with a replaceable plunging knife and side knife fixed by a special Torx screw.
The tool bodies are precisely balanced. For finishing, routing, plunging and grooving on board materials (laminated chipboards and MDF) and hardwood. For use on portable routers or CNC machining centres.




Drawings are 1:1 scale

D mm	I mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	ORDER NO. S=Ø20mm	Spare parts					
15,8	28,3	92			**653.158.11**		790.283.12	990.074.00	990.075.00	790.075.00	990.072.00	991.061.00
15,8	48,3	112			**653.159.11**		790.483.12	990.074.00	990.075.00	790.075.00	990.072.00	991.061.00
16	28,3	82	**653.160.11**				790.283.12	990.074.00	990.075.00	790.075.00	990.072.00	991.061.00
16	28,3	92		**653.161.11**		**653.661.11**	790.283.12	990.074.00	990.075.00	790.075.00	990.072.00	991.061.00
16	48,3	111,5		**653.162.11**		**653.662.11**	790.483.12	990.074.00	990.075.00	790.075.00	990.072.00	991.061.00
18	48,3	111,5				**653.681.11**	790.483.12	990.074.00	990.075.00	790.075.00	990.072.00	991.061.00
20	48,3	111,5				**653.701.11**	790.483.12	990.074.00	990.075.00	790.096.00	990.072.00	991.061.00

Straight Router Bits with Insert Knives



655




Drawing is 1:1 scale

654



INSERT CARBIDE | Z2 | RH | 2X LONGER LIFE


Straight router bit with two replaceable knives fixed by special Torx screws.
Their blades are sharpened on the top with 3° angle for better plunging operations.



Drawings are 1:1 scale

D mm	I mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	ORDER NO. S=Ø20mm	Spare parts		
16	28,3	76	**654.160.11**				790.283.12	990.073.00	991.061.00
16	28,3	87		**654.161.11**	**654.661.11**		790.283.12	990.073.00	991.061.00
16	48,3	105		**654.162.11**		**654.662.11**	790.483.12	990.073.00	991.061.00
19	12	45	**655.190.11**				790.120.00	990.075.00	991.061.00


www.dahm.no




7/8/901B

HW Z2 RH


Equipped with thick carbide tips and negative shear angle design, CMT mortising bits guarantee you flawe less performance. Mortise perfect hinges with no splintered edges or rough bottoms.They also make an easy job on both natural wood and wood composites. Fit most popular mortising jigs. The CMT mortising bit with top bearing guide is the perfect bit for sign making or any kind of template work.



Example of usage of a CMT mortising bit to fit a hinge.



Drawings are 1:1 scale



7/8/901



D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
12,7	6,35	41		**801.128.11**			
12,7	19	54	**701.127.11**	**801.127.11**	**901.127.11**		
12,7	19	60				**901.627.11**	**801.627.11**
15,8	19	57		**801.158.11**			
16	19	54	**701.160.11**		**901.160.11**		
18	16	48	**701.180.11**		**901.180.11**		
19	19	54	**701.190.11**	**801.190.11**	**901.190.11**		
19	19	57					**801.690.11**
20	16	48	**701.200.11**		**901.200.11**		
31,7	5,7	63					**801.818.11**
31,7	12,7	48		**801.317.11**			
31,7	12,7	54				**901.817.11**	**801.817.11**
With Top Bearing							
12,7	6,35	41		**801.128.11B**			
12,7	19	54		**801.127.11B**			
15,8	19	57		**801.158.11B**			
16	19	54			**901.160.11B**		
19	19	54	**701.190.11B**				
19	19	54		**801.190.11B**			
31,7	5,7	63					**801.818.11B**
31,7	12,7	54					**801.817.11B**


Spare parts




791.010.00	541.001.00	991.056.00
791.010.00	541.001.00	991.056.00
791.009.00	541.001.00	991.056.00
791.025.00	541.004.00	991.056.00
791.007.00	541.003.00	991.056.00
791.004.00	541.001.00	991.056.00
791.015.00	541.002.00	991.056.00
791.015.00	541.002.00	991.056.00

www.dahm.no

Hinge Recesser Bits





Drawing is 1:1 scale


7/902

HW Z2 RH

CMT hinge recesser bits are ideal for shallow lateral routing cuts such as recessing hinges.

SHOP TIPS: corners will require final square with a hand or a corner chisel.

Ideal for hinge recessing




The special construction allows good chip clearance and plunging.



D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø8mm
12	12	38	**702.120.11**	**902.120.11**
13	12	38	**702.130.11**	**902.130.11**
14	12	38	**702.140.11**	**902.140.11**
15	12	38	**702.150.11**	**902.150.11**
16	12	38	**702.160.11**	**902.160.11**
18	12	38	**702.180.11**	**902.180.11**
20	11	38	**702.200.11**	**902.200.11**
22	11	38	**702.220.11**	**902.220.11**
23	11	38	**702.230.11**	**902.230.11**
24	11	38	**702.240.11**	**902.240.11**
25	11	38	**702.250.11**	**902.250.11**

Dado & Planer Bits

852B







852

HW Z2 RH

Constructed with thick carbide tips and downward shear angle design, CMT mortising bits give you flawless performance. The negative shear angle of the cutting edges pushes the wood fibers down as they cut, allowing you to rout perfect hinge mortises with no splintered edges or rough bottoms. They also make an easy job on both natural wood and wood composites. We offer bits to fit the most popular mortising jigs.





Drawings are 1:1 scale


D mm	I mm	L mm	ORDER NO. S=Ø6,35mm		ORDER NO. S=Ø12,7mm	
19	9,5	57	**852.001.11**			
19	9,5	63,5			**852.501.11**	
25,4	9,5	57			**852.502.11**	
31,7	15,8	70			**852.503.11**	
38,1	15,8	70			**852.504.11**	
With Top Bearing						
19	9,5	57	**852.001.11B**			
19	9,5	63,5			**852.501.11B**	
31,7	15,8	70			**852.503.11B**	
38,1	15,8	70			**852.504.11B**	

Spare parts



791.004.00	541.001.00	991.056.00
791.011.00	541.002.00	991.056.00
791.015.00	541.002.00	991.056.00
791.020.00	541.002.00	991.056.00

www.dahm.no




7/8/911B


HW Z2 RH


Whether you're a full time professional or a part time woodworking enthusiast, discover the unlimited possibilities of template routing with a CMT pattern bit. Pair up these double fluted bits with your choice of template to produce cabinet and furniture pieces, signs, toys and any other creative projects.
Carbide tipped to last longer, CMT pattern bits are equipped with top bearing for working with the bearing above the wood piece.
This gives you a clear view of what you are routing so you can work confidently and accurately.

Safety tips: make sure your router is in top condition. The template must be securely fastened to the workpiece. When choosing a bit, carefully consider the thickness of the template and all the implications of the cut. Opt for the shortest bit possible for the project you are working on.



811.081.11B





Drawings are 1:1 scale

7/8/912B



D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
8	25,4	70		811.081.11B				791.010.00	541.001.00	991.056.00
12,7	19	57,2		811.127.11B				791.010.00	541.001.00	991.056.00
13	20	57	711.130.11B					791.023.00	541.003.00	991.056.00
14,2	14,2	57,2		811.142.11B				791.009.00	541.001.00	991.056.00
15	20	57	711.150.11B					791.024.00	541.003.00	991.056.00
15,8	12,7	58		811.159.11B				791.009.00	541.001.00	991.056.00
15,8	19	66,5		811.158.11B				791.009.00	541.001.00	991.056.00
16	20	57			911.160.11B			791.025.00	541.004.00	991.056.00
19	20	57	711.190.11B					791.007.00	541.003.00	991.056.00
19	20	57,2		811.191.11B				791.004.00	541.001.00	991.056.00
19	25,4	63,5					811.690.11B	791.011.00	541.002.00	991.056.00
22	20	57			911.220.11B			791.005.00	541.004.00	991.056.00
22,2	25,4	66,5					811.222.11B*	791.021.00	541.006.00	991.056.00
Long Series										
12,7	31,7	70		812.127.11B				791.010.00	541.001.00	991.056.00
15	31,7	66,5	712.150.11B					791.024.00	541.003.00	991.056.00
15,8	31,7	70		812.158.11B				791.009.00	541.001.00	991.056.00
16	31,7	66,5			912.160.11B			791.025.00	541.004.00	991.056.00
19	38,1	82,5				912.690.11B		791.011.00	541.005.00	991.056.00
19	38,1	82,5					812.690.11B	791.011.00	541.002.00	991.056.00
19	50,8	92				912.691.11B		791.011.00	541.005.00	991.056.00
19	50,8	92					812.691.11B	791.011.00	541.002.00	991.056.00

This item requires a slightly larger bearing than its cutting diameter
***Ø9,5mm shanks with Ø9,5/12,7mm bushings (799.001.00)**

www.dahm.no


Pattern Router Bits with Insert Knives



652B

INSERT CARBIDE | Z1 | RH | 2X LONGER LIFE

Straight router bits with a replaceable knife fixed by a Torx screw. For economical specialist applications requiring low downtime. They are equipped with top bearing for template use. For routing, trimming and grooving in board materials (laminated chipboards, worktop panels, MDF).
For use on portable routers.



Drawing is 1:1 scale

D mm	I mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts					
19	49,5	100	**652.690.11B**	**652.691.11B**	790.495.09	990.072.00	991.061.00	791.011.00	541.002.00	991.056.00


Pattern Router Bits with Insert Knives for Laminates



656

INSERT CARBIDE | Z2 | RH | 2X LONGER LIFE

This bit type is equipped with top bearing for template use. For finishing, routing and grooving in board materials (laminated chipboards, MDF) and hardwood. For use on portable routers or CNC machining centres.



Drawings are 1:1 scale

D mm	I mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts					
16	35	80	**656.160.11**			790.283.12	990.076.00	991.061.00	791.025.00	541.004.00	991.056.00
19	28,3	69	**656.190.11**			790.283.12	990.075.00	991.061.00	791.034.00	541.004.00	991.056.00
19	28,3	79			**656.691.11**	790.283.12	990.075.00	991.061.00	791.011.00	541.002.00	991.056.00
19	48,3	100		**656.692.11**	**656.693.11**	790.483.12	990.075.00	991.061.00	791.011.00	541.002.00	991.056.00

www.dahm.no

Weatherseal Bits




7/813.001



191.635



711.031




712.030
712.040
812.032


HWM Z2 RH

Make your house more energy efficient by insulating old doors and windows. A CMT Weatherseal bit is the perfect bit to re-groove door and window frames to accommodate wind blocking inserts. Made of solid carbide for strength and endurance.


Special economical double-sided design lets you save money by offering two tips in one bit; with the same features as the one-sided weatherseal bit. Only available with a 3mm (1/8") cutting diametre.



Drawings are 1:1 scale




7/813.001.11



D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm
3	8	70	**711.031.11**	
3	11	60	**712.030.11**	
3,2	12,7	50,8		**812.032.11**
3,5	10	60	**191.635.11**	
4	12	60	**712.040.11**	
3,5	8	70	**713.001.11**	
3,5	8	63,5		**813.001.11**

Combination Trimmer Bits




7/8/921

HW Z2 α RH

Work to your highest standards with the CMT combination trimmer bits. Now you can cut, trim and bevel all laminates without changing the bits. Achieve great results in straigth or angled cuts on both soft and hardwood. Three popular sizes, each with carbide-tipped cutting edges for efficient bevel and straight trimming.


Notice: these bits must be used with an edge, separate guide or fence.



Drawings are 1:1 scale

A	D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm		
0° - 22°	12	12,7	44,5	**721.022.11**	**821.022.11**			
0° - 30°	12	12,7	44,5	**721.030.11**	**821.030.11**	**921.030.11**		
0° - 45°	12	12,7	44,5	**721.045.11**	**821.045.11**			

www.dahm.no



742.095
842.095

743.060
843.063

843.064

7/842 - 7/843


HWM Z1 RH

Work to your highest standards with CMT combination trimmer bits. Now you can cut, trim and bevel all laminate without changing the bits. Achieve great results in straigth or angled cuts on both soft and hardwood. Three popular sizes, each with carbide-tipped cutting edges for efficient bevel and straight trimming.

NOTICE: these bits must be used with an edge, separate guide or fence.




Masterpack



Drawings are 1:1 scale

A	D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm
0°	6	9,5	38,1	**742.095.11**	
0°	6,35	9,5	38,1		**842.095.11**
7°	4,5 - 6	6	38,1	**743.060.11**	
7°	4,76 - 6,35	6,35	38,1		**843.063.11**
0° - 10°	6,35	9,5	38,1		**843.064.11**
50 pc. masterpack					
0°	6,35	9,5	38,1		842.095.11-X50
7°	4,76 - 6,35	6,35	38,1		843.063.11-X50

Combination Trimmer Bits



809.022
809.025
7/909.260
7/910.260

7/907 - 7/8/909 - 7/910

HW Z2 Z3 RH

Using CMT's combination flush and bevel trim bits is the easiest and most precise way to execute perfect fine supere finishing on laminates. No bit changing is necessary to achieve a large variety of angles; simply lower the bit cutting depth for perfect right angle cuts, or raise it for creating rounded off edges on both soft and hardwood.

These bits include a ball bearing guide for easy template work and for guaranteeing the protection of your workpiece.
Also, they feature two flutes for smoother cutting and are perfect for rounding off table legs and other soft areas on furniture pieces that may be easily damaged.




7/907.210





7/809.016




809.023
Z3









Drawings are 1:1 scale


A	D mm	I mm	L mm	Z	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm
0° - 25°	19 - 24,5	16 (10+6)	56,5	2	**707.210.11**		**907.210.11**
new 15°	18,6	11	57	2	**709.016.11**	**809.016.11**	
22°	12,7	7,8	47,6	2		**809.022.11**	
new 22°	17,5	9,5	51	3		**809.023.11**	
25°	19,05	10	52,4	2		**809.025.11**	
30°	27	9	55	2	**709.260.11**		**909.260.11**
45°	27	5,5	51,5	2	**710.260.11**		**910.260.11**

Spare parts

	791.007.00	990.004.00	991.062.00
990.422.00	791.044.00	990.058.00	991.057.00
	791.035.00	990.062.00	991.060.00
990.422.00	791.002.00	990.058.00	991.057.00
990.422.00	791.002.00	990.058.00	991.057.00
990.423.00	791.018.00	990.058.00	991.057.00
990.423.00	791.018.00	990.058.00	991.057.00

www.dahm.no

Flush Trim Bits






8/906.227.11
Z3


7/8/906

HW HWM Z2 Z3 RH

We have designed a series of truly indispensable bits available in a wide range of sizes for your woodworking needs and the most difficult projects. For precision work on laminates or quick template work with excellent finishing.

Shop tips: these bits are excellent for making through mortises. Use a straight bit (#711.130.11) to groove the through mortise area, then use the drill bit (#517.130.31) to bore a through hole at the end of the groove. Turn the workpiece over to end the mortise. Use the flush trim bit with a cutting length slightly longer than the fillet, following the groove made on the opposite side of the workpiece with the ball bearing guide.





Drawing is 1:1 scale



Masterpack

• **HWM**

I mm	D mm	L mm	α	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
•25,4	6,35	63,5	0°	**706.064.11**	**806.064.11**				791.035.00		990.060.00	541.008.00
12,7	9,5	55,5	0°	**706.096.11**	**806.096.11**	**906.096.11**			791.002.00	990.422.00	990.058.00	
12,7	12,7	57,8	-5°	**706.128.11**	**806.128.11**	**906.128.11**			791.003.00	990.423.00	990.058.00	
12,7	12,7	70,6	-5°				**906.628.11**	**806.628.11**	791.003.00	990.423.00	990.058.00	
16	19	57,1	-5°	**706.190.11**		**906.190.11**			791.007.00		990.004.00	
25,4	9,5	68,2	0°	**706.095.11**	**806.095.11**	**906.095.11**			791.002.00	990.422.00	990.058.00	
25,4	12,7	70,7	-3°	**706.127.11**	**806.127.11**	**906.127.11**			791.003.00	990.423.00	990.058.00	
25,4	12,7	71	0°		**806.227.11**	**906.227.11**			791.003.00	990.423.00	990.058.00	
25,4	12,7	86,6	-3°				**906.627.11**	**806.627.11**	791.003.00	990.423.00	990.058.00	
38,1	12,7	94	0°				**906.629.11**	**806.629.11**	791.003.00	990.423.00	990.058.00	
50,8	12,7	104	0°				**906.630.11**	**806.630.11**	791.003.00	990.423.00	990.058.00	
10 pc. masterpack												
25,4	9,5	68,2	0°		806.095.11-X10							
25,4	12,7	70,7	-3°		806.127.11-X10			806.627.11-X10				
38,1	12,7	94	0°					806.629.11-X10				

Spare parts

991.055.00	0,9mm hex key for screw (990.060.00)
991.057.00	3/32" hex key for screw (990.058.00)
991.062.00	2,5mm hex key for screw (990.004.00)

Flush Trim Bit Set




806

HW Z2 RH

Indispensable in any shop, the new 3 piece flush trim bit set gives you the option to trim laminates or do template work conveniently.

Set contains:
806.095.11 - 806.096.11 - 806.191.11.



Drawings are 1:1 scale

DESCRIPTION	BITS SIZES mm	ORDER NO. S=Ø6,35mm
Flush Trim Bit Set	9,5x12,7 - 9,5x25,4 - 19x25	**806.001.11**

www.dahm.no

Super-Duty Flush Trim Bits





7/8/906

HW | α | Z2 | RH

These new super duty bits represent the finest in the extensive line of CMT flush trim bits with ball bearing guides. A negative shear angle cutting edge and 19mm cutting diameter set CMT flush trim bits apart from standard bits. Work quickly and safely to get superior finishing with absolute minimal chipping.

SAFETY TIPS: dust and chips from laminate materials are hazardous to your health and safety. Always wear a dust mask and eye protection when routing.






Drawings are 1:1 scale



I mm	D mm	L mm	α	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
25,4	19	73,9	-5°	**706.191.11**	**806.191.11**	**906.191.11**			791.004.00	541.550.00	990.058.00
25,4	19	86,5	-5°				**906.691.11**	**806.691.11**	791.004.00	541.550.00	990.058.00
38,1	19	92,9	-3°				**906.692.11**	**806.692.11**	791.004.00	541.550.00	990.058.00
50,8	19	109,5	-3°				**906.690.11**	**806.690.11**	791.004.00	541.550.00	990.058.00

Spare parts **991.057.00** 3/32" hex key for screw (990.058.00)


DP Flush Trim Bits for Laminates




7/8/906 XTREME

DP | LONG LIFE | Z2 | RH

These new super duty DP (polycrystalline diamond) bits represent the ultimate in the extensive line of CMT flush trim bits. Investing in CMT DP flush trim bits to save time and money, as they last at least 40 times longer than conventional carbide tipped flush trim bits.






Drawing is 1:1 scale

40X LONGER LIFE THAN CARBIDE

I mm	D mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	Spare parts			
11	12,7	58,1	**706.128.61**	**806.128.61**	**906.128.61**	990.423.00	791.003.00	990.058.00	991.057.00

www.dahm.no


Double-Bearing Spiral Flush Trim Bits




190B-191B-192B

HWM Z2 Z2+2 RH

The new CMT solid carbide spiral flush trim bits are manufactured with a special super-micrograin formulation that has increased hardness with a higher transverse rupture point. Combined with a spiral cutting angle, the new CMT solid carbide spiral flush trim bits with double bearing allow cabinet makers to shear wood and wood products cleanly, providing more efficient chip ejection than standard flush trim bits. In production settings these new bits will run cooler and the edges will stay sharper, last longer and increase your shop productivity.




Drawing is 1:1 scale



I mm	D mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts	
Z2+2 Upcut & Downcut Spiral Bit								
42	12,7	114			**190.127.11B**	**190.508.11B**	791.010.00	541.301.00
Z2 Upcut Spiral Bit								
25,4	6,35	76,2	**191.064.11B**	**191.008.11B**			791.035.00	541.350.00
31,7	12,7	89				**191.505.11B**	791.010.00	541.301.00
50,8	12,7	114			**191.127.11B**	**191.507.11B**	791.010.00	541.301.00
Z2 Downcut Spiral Bit								
31,7	12,7	89				**192.505.11B**	791.010.00	541.301.00
50,8	12,7	114			**192.127.11B**	**192.507.11B**	791.010.00	541.301.00

3-in-1 Flush Trim Bits for MDF/Laminate



7/8/907

HW Z2 RH

3 in 1 new flush trim bits with Delrin® Triangular bearings are your best partner for laminate trimming. In fact, it solves three of the most common problems that occur when flush trimming:

1) The anti-stick properties of the Delrin® bearing greatly reduces the likelihood of freezing of the bearing from glue.
2) The extended guide surface of the new Delrin® bearing will perfectly match the work surface without scratching like a steel bearing would. The Delrin® bearing also guarantees maximum stability.
3) The shear angle cutting edge reduces the need for filing. 3-in-1 bits are ideal on plastic laminates as well as aluminium laminates!


3-in-1 bits are ideal on plastic laminates as well as aluminium laminates!


NON BLOCKING

Patent No. D628,218

- Extended guide surface
- Non-freezing
- Non-scratch surface







Drawing is 1:1 scale


Perfect trimming with conical edges!

Thanks to the innovative conical edges of this bit, you will always get perfect cuts even after re-sharpening. In fact, the most common problem you have with standard flush trim bits is the undersized diameter after re-sharpening which leaves a mark on the material; with the new CMT construction you could re-sharpen up to six times without any problem. Just remember to adjust your bit up or down as per the illustration.



I mm	D mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm	Spare parts			
12,7	12,7	54,2	**707.128.11**	**807.128.11**	**907.128.11**		990.422.00	791.042.00	990.058.00	991.057.00
15,87	19	59,3	**707.190.11**	**807.190.11**	**907.190.11**		990.423.00	791.043.00	990.058.00	991.057.00
15,87	19	65,7				**807.690.11**	990.423.00	791.043.00	990.058.00	991.057.00


www.dahm.no



657.9

INSERT CARBIDE | Z2 | RH | 2X LONGER LIFE

Flush trim bits with two replaceable knives fixed by special Torx screws.
The 2-sided blades can create extra new edges.
Guided flush trim bits type 657.1 are equipped with ball bearing guides.



Drawings are 1:1 scale

657.1




I mm	D mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
12	19	57	**657.194.11**	**657.192.11**	**657.190.11**			790.120.00	990.075.00	991.061.00	791.007.00
30	19	76	**657.195.11**					790.300.00	990.075.00	991.061.00	791.007.00
30	19	85			**657.191.11**			790.300.00	990.075.00	991.061.00	791.007.00
30	19	87					**657.692.11**	790.300.00	990.075.00	991.061.00	791.007.00
50	19	112				**657.991.11**	**657.992.11**	790.500.00	990.075.00	991.061.00	791.007.00

Spare parts

990.410.00	Ø4,2/Ø9mm shield for M4 screws
990.052.00	M4x6mm TCEI screws
991.067.00	3mm hex key
541.514.00	Ø6,4mm shield


FILE-FREE Flush Trim Bits for Laminate



8/907

HW | Z2 | RH

This bit is perfect for ensuring smooth flawless results on your laminate surfaces after flush trimming.
Sharp edges are easily trimmed away, leaving your surfaces nice and smooth to the touch. No further filing is needed!



Drawings are 1:1 scale

D mm	I mm	R mm	L mm		ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	Spare parts			
12,7	9,5	0,4	52		**807.004.11**	**907.004.11**	990.422.00	791.002.00	990.058.00	991.057.00
12,7	9,5	1,6	52		**807.015.11**	**907.015.11**	990.422.00	791.002.00	990.058.00	991.057.00

www.dahm.no


Pattern/Flush Trim Bits with Insert Knives




657B

INSERT CARBIDE | Z2 | RH | 2X LONGER LIFE

Flush trim bit combined with pattern bit fixed by special Torx screws. The blades are 2 sided sharpened and can provide extra new edges. Guided flush trim bits type 657 are equipped with top and bottom ball bearing guides.
For flush and finishing operations.





Drawing is 1:1 scale


I mm	D mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
new 30	19	90	**657.191.11B**		
new 30	19	90			**657.692.11B**
50	19	110		**657.993.11B**	**657.994.11B**
new 60	19	120		**657.995.11B**	**657.996.11B**

Spare parts

790.300.00	990.075.00	791.007.00	990.052.00	791.034.00	541.004.00
790.300.00	990.075.00	791.007.00	990.052.00	791.011.00	541.002.00
790.500.00	990.075.00	791.007.00	990.052.00	791.011.00	541.002.00
790.600.00	990.075.00	791.007.00	990.052.00	791.011.00	541.002.00

Spare parts

990.410.00 Ø4,2/Ø9mm shield for M4 screws
991.067.00 3mm hex key
991.061.00 T15 Torx key
991.056.00 1,5mm hex key




Flush Trim Router Bits with Double Bearing

806/906B

HW | α | Z2 | RH

These new innovative two-flute router bits are equipped with a double bearing and feature a down shear design, which allows for clean smooth cuts on many materials.
Therefore, it is no longer necessary to flip or move your tool if you need to ride it from either direction to the other side of your workpiece. You will benefit from this tool especially when routing curved elements along or against the grain.




Drawings are 1:1 scale

I mm	D mm	L mm	α	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
25,4	19	86,5	-5°	**906.691.11B**	
25,4	19	86,5	-5°		**806.691.11B**
50,8	19	109,5	-3°	**906.690.11B**	
50,8	19	109,5	-3°		**806.690.11B**

Spare parts

791.004.00	541.550.00	990.058.00	991.057.00	791.011.00	541.005.00
791.004.00	541.550.00	990.058.00	991.057.00	791.011.00	541.002.00
791.004.00	541.550.00	990.058.00	991.057.00	791.011.00	541.005.00
791.004.00	541.550.00	990.058.00	991.057.00	791.011.00	541.002.00

www.dahm.no




7/8/916

HW | HWM | Z1 | Z1+1 | Z2 | RH

716.061


How much time do you end up spending making openings in paneling, drywall, siding, doors or windows? With the CMT panel pilot bit, the job just got quicker. The point plunges smoothly and easily and the carbide edges cut clean and fast. All of this adds up to accurate cuts in less time and with less effort - great for trimming Formica®, veneer and other laminates.

Safety Tips: always use extra caution when working near electrical outlets and boxes - always disconnect the current. Make sure the bit does not go so deep as to cut the wires.






Masterpack




A unique and time saving bit, the CMT Double Panel Pilot Bit is perfect for making openings and slots in veneers and laminates. The lower portion of the cutting edge is located under the bearing and allows you to cut on both sides of the material. Durable carbide tipped cutters are spaced 12mm apart and each cutter can work in stock up to 18mm thick.



• HWM

D mm	I mm	L mm	Z	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
6	19	64	1	**716.060.11**				
•6	19	60	1	**716.060.21**				
•6	18+18	70	1+1	**716.061.11**				
6,35	19	64	1		**816.064.11**			
8	19	64	1			**916.080.11**		
9,53	25,4	78	2		**816.095.11**			
12	31,7	102	2				**916.627.11**	
12,7	31,7	102	2					**816.627.11**
10 pc. masterpack								
12,7	31,7	102	2					**816.627.11-X10**




Panel Pilot Bits with Guide

7/8/953

HW | Z2 | RH

An absolutely indispensable bit for making cabinets. CMT Flush and V-Groove bits allow you to make cabinet front frames in 25mm stock that fit perfectly with the sides. The added V-cutter feature makes a decorative groove along the hinge joint to hide the seam.

Shop Tip: For best results, leave less than 3mm overhang on cabinet front frames for easier routing.



Drawing is 1:1 scale

d mm	D mm	I mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
12,7	19	25,4	**753.001.11**	**853.001.11**	**953.001.11**	**953.501.11**	**853.501.11**

Spare parts



990.423.00 | 791.003.00 | 990.058.00 | 991.057.00

www.dahm.no


The CMT Grand Rabbet Set




8/935.503


HW | α | Z2 | RH

"The Grand Rabbet" by CMT is an investment that shows your commitment to quality. This CMT product will deliver years of reliable service under normal use. For safe and trouble-free results please observe the following instructions and safety precautions.
The complete kit (item code 835-935.503.11), will enable you to produce 17 different rabbet sizes including rabbets for under-size plywood applications.
For rabbet sizes over 12,7mm (1/2"), make the cuts in several shallow passes until the desired depth is achieved.
Available in 12mm and 12,7mm shanks.






Collar order no.
799.517.00




8/935.990

Drawings are 1:1 scale


With bushings




Order no. 791.705.00




Order no. 791.706.00



Without bushings



Order no. 791.707.00



DESCRIPTION	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
The CMT Grand Rabbet Set (Ø50,8x22,2mm)	**935.503.11**	**835.503.11**
Set contains: The Grand Rabbet (bit only) with bushing Ø19mm	**935.990.11**	**835.990.11**
5 pcs. Bushing kits for bearing (H=1,6 - 3,2 - 6,35 - 9,5 - 12,7mm rabbets)		**791.705.00**
5 pcs. Bushing kits for bearing (H=4,7 - 8 - 11,1 - 14,3 - 17,5mm rabbets)		**791.706.00**
5 pcs. Bushing kits for bearing (H=6 - 9,1 - 11,9 - 15 - 18,2mm rabbets)		**791.707.00**
Bushing Ø50,8mm		**799.517.00**
Kit with screw, shields and keys		**990.452.00**


www.dahm.no



7/8/935

HW | α | Z2 | RH

CMT carbide-faced rabbeting bits are fast and accurate - you can quickly produce inset doors and drawer fronts, make strong rabbet joints, mill perfect tongue and groove joints or any number of other jobs usually time consuming and difficult.
You can even re-groove old window frames to fit insulated glass panes with the extra long CMT 19mm (3/4“) rabbeting bit.
Other possibilities are illustrated below and on the following pages. Look at our slot cutters and round over bits for ideas on how to put extra finishing touches on all your grooving and rabbeting projects.




Drawings are 1:1 scale

H mm	D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
9,5	31,7	12,7	58,4	**735.317.11**	**835.317.11**	**935.317.11**			990.423.00	791.003.00	990.058.00
9,5	31,7	12,7	61,2				**935.817.11**	**835.817.11**	990.423.00	791.003.00	990.058.00
9,5	31,7	19	64,8	**735.318.11**		**935.318.11**			990.423.00	791.003.00	990.058.00
12,7	34,9	12,7	59,4	**735.350.11**	**835.350.11**	**935.350.11**	**935.850.11**	**835.850.11**	990.422.00	791.002.00	990.058.00
12,7	34,9	19	65,8				**935.851.11**	**835.851.11**	990.422.00	791.002.00	990.058.00
15,8	50,8	22,2	77,8				**935.990.11**	**835.990.11**	990.408.00	791.010.00	990.058.00

Spare parts

991.057.00 3/32” hex key
799.503.00 19,05mm bushings
541.514.00 2mm spacer (8/935.990.11)

Rabbeting Sets



7/8/935.001

HW | α | Z2 | RH

CMT rabbeting sets allow you to make a limitless number of cuts by adjusting the cutting height on your router and changing the bearing on the bit.




791.703.00




BE SURE to keep the black bearing washer right side up to correspond with the bearing rotation when re-assembling the bearing. Improper re-assembly can cause the screw to come loose. Each set comes complete with one rabbeting bit and six interchangeable ball bearing guides.

Drawings are 1:1 scale



H mm	D mm	I mm		ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
0-12,7	34,9	12,7		**735.001.11**	**835.001.11**	**935.001.11**	**935.501.11**	**835.501.11**
0-12,7	34,9	19					**935.502.11**	**835.502.11**

Rabbeting Bits with Insert Knives




660

INSERT CARBIDE Z2 RH 4X LONGER LIFE

Rabbeting bits with two replaceable knives fixed by special Torx screws.
The blades are sharpenend on 4-sidesand increase efficiency when working with board materials.
Rabbeting bits are equipped with ball bearing guides for rabbeting width H= 9,5mm.
You can also choose bearings for rabbeting width 12,7 - 11,1 - 8 - 6,35 - 3,2 - 0mm.
For chipboards, hard wood or MDF. For use on portable routers.


Drawings are 1:1 scale

Standard



with bearing **791.018.00**

Optional



with bearing **791.016.00** | with bearing **791.014.00** | with bearing **791.017.00**

with bearing **791.019.00** | with bearing **791.003.00** | with bearing **791.002.00**

Spare parts 990.463.00 Kit with screw, shield and key

H mm	D mm	I mm	L mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm
9,5	34,9	12	55	**660.351.11**	**660.350.11**	
9,5	34,9	12	65			**660.851.11**


Spare parts

790.120.00	990.075.00	991.061.00	791.018.00
790.120.00	990.075.00	991.061.00	791.018.00

Spare parts

990.400.00	Ø3.2/Ø7mm shield for M3 screw
541.552.00	Ø3.25/Ø15.8mm shield for M3 screw
990.051.00	M3x6mm TCEI screws
990.053.00	M3x10mm TCEI screws
990.054.00	M3x16mm TCEI screws
991.062.00	Hex key 2,5mm


Grand Rabbeting Bits with Insert Knives





660.9

INSERT CARBIDE Z2 RH 2X LONGER LIFE


"The Grand Rabbet" by CMT is an investment that shows your commitment to quality. This CMT product will deliver years of reliable service under normal use. The collar sets (791.705.00-791.706.00-791.707.00) will enable you to produce 17 different rabbet sizes including rabbets for under-sized plywood applications. For rabbet sizes over 12,7mm (1/2"), make the cuts in several shallow passes until the desired depth is achieved. Available in 12mm and 12,7mm shanks.







Collar order no.
799.517.00



Drawing is 1:1 scale

H mm	D mm	I mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
16	50,8	28,3	87	**660.990.11**	**660.991.11**

Spare parts

790.283.12	990.075.00	991.061.00	791.010.00


Spare parts

541.514.00	Ø6,4mm stop collar
799.503.00	Ø19,05mm bushings
990.410.00	Ø4.2/Ø9mm shield for M4 screw
990.052.00	M4x6mm TCEI screw
991.067.00	3mm hex key
990.469.00	Kit screw, shield and key

Optional:

799.517.00	Bushing for flush trim Ø50,8mm
791.705.00	5 pcs. bushing set (H=1,6-3,2-6,35-9,5-12,7mm rabbets)
791.706.00	5 pcs. bushing set (H=4,7-8-11,1-14,3-17,5mm rabbets)
791.707.00	5 pcs. bushing set (H=6-9,1-11,9-15-18,2mm rabbets)

www.dahm.no




7/8/950.001


HW Z1 RH


With the CMT keyhole bit you can make holes that keep your frames, plaques or any wall hanging perfectly straight and attached to the wall.
The bit bores an entry hole in the wood, then proceeds to cut a 4,8mm hole and finishes by boring a larger opening under the surface. The perfect way to securely mount wall hangings on screws and nails.

Safety Tips: Be sure the workpiece is securely fastened to the router table or work bench.

Shop Tips: Recommended for use with a plunge router.








Drawing is 1:1 scale


D mm	d mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
9,5	4,8	11	54	**750.001.11**	**850.001.11**	**950.001.11**	**950.501.11**	**850.501.11**

T-Slot Bits




8/950.6

HW Z2 Z1+1 RH




8/950.603




8/950.601

Drawings are 1:1 scale



950.604




8/950.602

D mm	d mm	I mm	L mm	Z				ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
28	11	13,5	56,3	2				**950.603.11**	**850.603.11**
30	9,5	17,5	60,3	2				**950.601.11**	**850.601.11**
32	8,7-15	20	66	1+1				**950.604.11**	
34,9	12,7	22,2	63,5	2				**950.602.11**	**850.602.11**

www.dahm.no

Screw Slot Bits




913.101.11
813.601.11


8/913

HW Z2 RH

Any large panel or table top should be secured in a way that allows it to expand or contract without splitting.
These screw-slot bits let you create screw slots so that panels can be held in place but are able to slide back and forth without splitting the wood or breaking the screw securing them.




Drawing is 1:1 scale






913.201.11
813.701.11



D mm	d mm	l_1 mm	I mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm
11,1	4,36	12,7	20,6	63,5	**913.201.11**	**813.701.11**
12,7	4,36	13,9	24,2	63,5	**913.101.11**	**813.601.11**


Flooring Router Bits



822.023B - 822.024B


HW Z2 RH

CMT now offers you these industrial quality carbide-tipped router bits for flooring and inlay applications. They easily and smoothly run through solid and timber wood while cutting edges and remain even sharp after several passes. 822.024.11B item number also features rounded edges to produce 3,2mm (1/8") radius inlays. These bits are equipped with a stop collar and a bearing.




822.023.11B

Drawings are 1:1 scale



822.024.11B






D mm	I mm	H mm	R mm	L mm	ORDER NO. S=Ø6,35mm
31,75	6,35	9,5		47,6	**822.023.11B**
31,75	6,35	9,5	3,2	47,6	**822.024.11B**

Spare parts

791.010.00	541.001.00	990.005.00	991.056.00
791.010.00	541.001.00	990.005.00	991.056.00

www.dahm.no

Three Wing Slot Cutter Set



8/900.506


HW Z3 RH

Create slots, grooves and rabbets in materials from 3,2mm to 18mm in depth by using the adjustable CMT Three Wing slot cutter set. See chart below for details on spacing and correct cutter combinations. Ideal for biscuit joints and milling perfect tongue and groove joints.
This set includes:
- 4 carbide tipped cutters 3,2mm, 4mm, 4,8mm, 6,4mm
- 1 arbor 12mm or 12,7mm
- 1 ball bearing (22mm) for 12,7mm cut
- 17 shims: (8x0,1mm - 4x0,5mm - 3x1mm and 2x4mm)

SAFETY TIPS: never use the slot cutter set without shims between the cutters.
The distance between the cutters can vary from 1mm to 1,7mm. A shim must also be positioned between the ball bearing and the cutters.


SHOP TIPS: the bearings kit 791.711.00 makes 6,35mm and 9,5mm cutting depths.

NOTE: The carbide edges of the cutters should never touch; arrange the shims as illustrated below. Use only the thicknesses provided in the set. Be sure all cutters are assembled in the proper right rotational direction below. Looking down the arbor the cutters will turn clockwise.



Cutter combinations	Cutter height mm		mm
A	3,2		
B	4		
C	4,8		
D	6,4		
A + B	6,4	a	7,1
A + C	7,2	a	7,9
A + D	8,8	a	9,5
B + C	8	a	8,7
B + D	9,6	a	10,3
C + D	10,4	a	11,1
A + B + C	10,4	a	11,8
A + B + D	11,9	a	13,3
A + C + D	12,7	a	14,1
B + C + D	13,5	a	14,9
A + B + C + D	15,9	a	18

Use shims to adjust cut width: MIN.1mm - MAX 1,7mm




I mm	D mm	H mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
3,2-18	47,6	12,8	81	**900.506.11**		924.128.00	791.005.00	990.020.00
3,2-18	47,6	12,8	81		**800.506.11**	824.128.00	791.005.00	990.020.00

Spare parts
541.515.00 0,1mm spacer
541.517.00 0,5mm spacer
541.518.00 1mm spaceer
541.501.00 4mm spacer

Optional:
791.711.00 Kit with two 28,5mm and 34,9mm bearing for slot cutter


Tongue & Groove Set



8/900.626

HW Z3 RH

Make tongue and groove joints without the complicated process of taking apart and reassembling bits. The new CMT tongue and groove set gives you one bit to groove the slot and a separate bit to mill the tongue. Or use your imagination and put them to work individually on other projects. Makes tongue and groove cuts in wood up to 19mm thickness.




Drawings are 1:1 scale

Profile	I mm	D mm	H mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
A+B	19	47,6	12,8	71	**900.126.11**			924.083.00	791.005.00	822.364.11	990.020.00
A+B	19	47,6	12,8	71		**900.626.11**		924.131.00	791.005.00	822.364.11	990.020.00
A+B	19	47,6	12,8	71			**800.626.11**	824.131.00	791.005.00	822.364.11	990.020.00
A	19	47,6	12,8	71			**800.626.11M**	824.131.00	791.005.00	822.364.11	990.020.00

Spare parts
541.515.00 0,1mm spacer
541.516.00 0,3mm spacer
541.517.00 0,5mm spacer
541.518.00 1mm spacer
541.500.00 3mm spacer

www.dahm.no





7/8/922A/B

HW Z3 RH

Uses for the CMT three wing slot cutter are almost infinite. Cut slots and grooves for splines, biscuits, T-molding or tongue and groove joints.
Every cutter features anti-kickback design, micrograin carbide tips and CMT is trademark orange non-stick PTFE coating. CMT slot cutters are available as a blade only or with your choice of a 6, 8, 12, 6,35 or 12,7mm diameter arbor which includes a 22mm diameter bearing for a cutting depth of up to 12,7mm.

NOTE: For biscuit joints, use l=4mm slot cutter.








Drawing is 1:1 scale

l mm	P mm	D mm	H mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
1,5	1,07	47,6	12,8	**722.315.11A**		**922.315.11A**	**922.315.11B**	
1,6	1,07	47,6	12,8		**822.316.11A**			**822.316.11B**
2	1,27	47,6	12,8	**722.320.11A**	**822.320.11A**	**922.320.11A**	**922.320.11B**	**822.320.11B**
2,4	1,27	47,6	12,8		**822.324.11A**			**822.324.11B**
2,5	1,27	47,6	12,8	**722.325.11A**		**922.325.11A**	**922.325.11B**	
3	1,27	47,6	12,8	**722.330.11A**		**922.330.11A**	**922.330.11B**	
3,2	1,27	47,6	12,8		**822.332.11A**			**822.332.11B**
3,5	2,07	47,6	12,8	**722.335.11A**		**922.335.11A**	**922.335.11B**	
4	2,07	47,6	12,8	**722.340.11A**	**822.340.11A**	**922.340.11A**	**922.340.11B**	**822.340.11B**
4,8	2,86	47,6	12,8		**822.348.11A**			**822.348.11B**
5	2,86	47,6	12,8	**722.350.11A**		**922.350.11A**	**922.350.11B**	
6	4,45	47,6	12,8	**722.360.11A**	**822.360.11A**	**922.360.11A**	**922.360.11B**	**822.360.11B**
6,4	4,45	47,6	12,8		**822.364.11A**			**822.364.11B**

These three wing carbide tipped Slot Cutters feature anti-kickback three wing blade design and CMT's trademark orange P.T.F.E. Industrial Coating.
All cutters feature an 8mm bore that fits CMT's arbors (items 7/8/924).








l mm	P mm	D mm	B mm	ORDER NO.
1,5	1,07	47,6	8	**822.315.11**
1,6	1,07	47,6	8	**822.316.11**
1,8	1,27	47,6	8	**822.318.11**
2	1,27	47,6	8	**822.320.11**
2,2	1,27	47,6	8	**822.322.11**
2,4	1,27	47,6	8	**822.324.11**
2,5	1,27	47,6	8	**822.325.11**
2,8	1,27	47,6	8	**822.328.11**
3	1,27	47,6	8	**822.330.11**
3,2	1,27	47,6	8	**822.332.11**
3,5	2,07	47,6	8	**822.335.11**
4	2,07	47,6	8	**822.340.11**
4,8	2,86	47,6	8	**822.348.11**
5	2,86	47,6	8	**822.350.11**
6	4,45	47,6	8	**822.360.11**
6,4	4,45	47,6	8	**822.364.11**

DESCRIPTION	L1 mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
1 Slot cutter arbor without bearing	26	61	**724.060.00**	**824.064.00**	**924.080.00**		
1 Slot cutter arbor without bearing	26	67,5				**924.120.00**	**824.127.00**
2 Slot cutter arbor with bearing	26	61	**724.060.10**	**824.064.10**	**924.080.10**		
2 Slot cutter arbor with bearing	26	67,5				**924.120.10**	**824.127.10**
Slot cutter arbor without bearing, long series	40	86			**924.083.00**		
Slot cutter arbor with bearing, long series	40	86			**924.083.10**		

Spare parts

791.005.00 Ø8-22mm bearing
541.501.00 4mm spacer
541.500.00 3mm spacer
541.518.00 1mm spacer
990.020.00 M8 nut


www.dahm.no




923A - 823B

HW Z3 RH

The uses of this bit are infinite: not only can you rout grooves and rabbets, but you can even T or dovetail joints on wood panels. Each bit has three carbide tipped cutters and has an orange coloured PTFE coating, it features anti-kickback design too. The 22mm bearing is included for a cutting depth of 12,8mm. The bit and the slot cutter are also available separately.






Drawing is 1:1 scale

I mm	P mm	D mm	H mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm
3	1,27	47,6	12,8	58	**923.330.11A**	
3,2	1,27	47,6	12,8	57,5		**823.332.11B**
4	2,07	47,6	12,8	58,3	**923.340.11A**	**823.340.11B**
5	2,86	47,6	12,8	63	**923.350.11A**	
6,4	4,45	47,6	12,8	60,7		**823.364.11B**


823



Bore 45°

These three wing carbide tipped slot cutters feature anti-kickback three wing blade design and CMT's trademark orange PTFE Industrial Coating.
All cutters feature an 8mm bore that fits CMT's arbors (items 7/8/924).

I mm	P mm	D mm	B mm	ORDER NO.
3	1,27	47,6	8	**823.330.11**
3,2	1,27	47,6	8	**823.332.11**
4	2,07	47,6	8	**823.340.11**
5	2,86	47,6	8	**823.350.11**
6,4	4,45	47,6	8	**823.364.11**




7/8/924



with stop collar



Assembly Illustration



DESCRIPTION	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm
1 Slot cutter arbor without bearing without stop collar	**724.061.00**	**824.061.00**	**924.081.00**	**824.121.00**
1 Slot cutter arbor with bearing and stop collar	**724.061.10**	**824.061.10**	**924.081.10**	**824.121.10**
2 Slot cutter arbor without bearing			**924.082.00**	**824.122.00**
2 Slot cutter arbor with bearing			**924.082.10**	**824.122.10**

Spare parts

791.012.00 Ø8-22mm bearing
541.001.00 Stop collar for Ø6,35mm shanks
541.002.00 Stop collar for Ø12,7mm shanks
791.013.00 Ø12,7-22mm bearing
541.003.00 Stop collar for Ø6mm shanks
541.004.00 Stop collar for Ø8mm shanks

541.515.00 0,1mm spacer
541.516.00 0,3mm spacer
541.517.00 0,5mm spacer
541.518.00 1mm spacer
990.055.00 M5x12mm TSPEI screw
991.067.00 3mm hex key

www.dahm.no

Flute & Bead Set


CMT ORANGE TOOLS™


HW Z2 RH

8/955.701

This perfectly mated CMT set is ideal for making canoe slats and hot tub enclosures. Featuring tungsten carbide, the bits' cutting edges stay sharp after cutting large amounts of stock, and the anti-kickback design lets you work safely.

Use both the flute and the bead bits for 6,35mm (1/4") slats as shown below.





Drawings are 1:1 scale




R mm	D mm					ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
3,2	38					955.701.11	855.701.11


Lock Miter Set


HW α Z2 RH

8/955


Now you don't have to fight with those awkward clamps on your 22,5° projects. Use this pair of bits to produce octagonal shaped boxes and popular corner cabinetry like corner cabinets for kitchens, entertainment centres, kitchen islands and corner hutches. This 22,5° Lock Miter set provides a strong tight joint when you want to join wood at 45° angles.
Biscuits and splines are time-consuming to make and difficult to clamp. CMT's matched pair of cutters makes set-up easy. Height adjustment is not critical with this matched pair; simply adjust your fence so the top edge of the work piece intersects the angle of the bit where it meets the fence. After your joints are machined they can be glued and assembled and simply clamped by using strapping tape.








Drawings are 1:1 scale



D mm	I mm	A	T1 mm	L mm		ORDER NO. S=Ø8mm		ORDER NO. S=Ø12,7mm
37,3	22,2	22.5°	9,5 ÷ 19	60,3		955.005.11		855.505.11

www.dahm.no





HW | Z2 | RH


CMT lock miter bits are ideal for milling miter joints in 28,5mm stock. A quick and easy way to accurately create boxes, stretcher bars, frames and any assortment of right angle or parallel joint projects.


To produce perfectly fitting miter joints, lay one piece with the inside face-down on the work table and the wood centred to the bit. Mill as shown in step 1 of the illustration below. Mill the second piece with the inside face placed vertical to the bit and fence, as shown in step 2.

To mill sturdy parallel glue joints follow step 1 shown in the illustration with the inside face of the workpiece laid flat on the table and centred to the bit. To make the second part, lay the workpiece flat on the table and centred to the bit. Mill with the inside face-up.











8/955.503




Drawings are 1:1 scale

For miter and parallel glue joints using 19mm board




Nr. 1: Rout one piece with the inside face flat on the router table. Be sure the cut is centred to the stock.



Nr. 2: Rout the second piece with the inside face vertical to the fence.

D mm	I mm	A	T_1 mm	L mm			ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
70	31,7	45°	15 ÷ 28,5	69,9			**955.503.11**	**855.503.11**
50,8	22,2	45°	9,5 ÷ 19	60,3			**955.504.11**	**855.504.11**

www.dahm.no




8/955.501


HW Z2 RH

The most unique and important characteristic of this CMT bit is its capacity to produce an almost indestructible glue joint quickly and without error. Ideal for routing wide dimension panels, doors and furniture pieces. By accurately centering the bit to the wood, the upper and lower vertical cutting edges of the bit will cut equal proportions. Simply run one edge of the panel, turn the panel over, and then run the opposite edge - you will produce perfectly harmonized reverse cuts that match up to make flawless joints.


Shop tips: When glueing, apply enough pressure to securely seal the joint. Insufficient pressure results in a weak joint and excessive pressure will distort the wood.



Drawings are 1:1 scale




Example using a 19mm board



To accurately centre the wood to the bit: Adjust the bit according to the thickness of the wood you are cutting. Line up the cut edge of the wood to the centre point of the bit as illustrated in the enlarged drawing. The upper and lower vertical cutting edges of the bit are in proportion and at an equal distance from the centre point of the bit. Run one cut edge of the wood, turn the piece over and run the other edge for exact reverse cuts that match up perfectly. Assemble the reverse cut pairs together for beautiful, strong joints.

D mm	I mm	T1 mm	L mm				ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
44,4	32	15 - 30	70,1				**955.501.11**	**855.501.11**

www.dahm.no




855.508 - 955.008
7/8/955.002 - 8/955.502

HW | Z2 | RH


The key to success when constructing quality drawers is in the quality of the drawer lock bit you use. With CMT drawer lock bits you can make strong, perfectly fitted joints quickly and easily.
As illustrated below, mill the drawer front with the inside face-down on the work table.
Mill the sides of the drawer with the inside face placed vertical to the bit and fence, and perpendicular to the table.
These bits are to be used on router tables only. Do not use on hand-held routers.




8/955.002-502




Drawing is 1:1 scale




855.508
955.008





Drawing is 1:1 scale





Overhang
for drawer stop





D mm	T1 min. mm	T1 max. mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
25,4	9,5	15,87	12,7	54			**955.008.11**		**855.508.11**
31,7	15,87	25,4	12,7	44,5	**755.002.11**	**855.002.11**	**955.002.11**		
50,8	15,87	25,4	12,7	50,8				**955.502.11**	**855.502.11**

www.dahm.no


Window Sash Set

CMT ORANGE TOOLS™

HW Z2 RH

8/955.801

CMT designed this set so you can create window sashes that are as beautiful as they are functional. As an additional feature, the CMT window sash set will also mill perfectly matched jowed 35mm rail and stile parts for custom made doors. Like all CMT quality bits, this set includes our anti-kickback design feature and our trademark non-stick orange coating. Made of Fatigue Proof® steel with carbide-faced cutting edges for longer life. Each set contains one 38mm bit and one 35mm bit designed for cutting 35mm stock.




d mm	l mm	L mm		D mm	l mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
35	35	84		38	17,5	56	**955.801.11**	**855.801.11**	791.012.00	822.004.11	541.518.00	990.020.00

Step-By-Step Window Sash Construction


CMT set makes it easy!

In our step-by-step example for window sash construction, we used the following:
- CMT Window Sash Set (item #855.801.11)
- stiles cut 35mm thick
- rails cut 35mm thick
- scrap stock

The CMT Window Sash Set was designed ideally for the construction of windows in 35mm stock, however variations as narrow as 28mm can be used. Stock thicker than 35mm exceeds the milling range of the cutter. Remember to adjust your measurements and cutting depths according to the wood thickness you use. We suggest making a trial joint in scrap stock according to the following steps before milling all of the cope and stick profiles.





STEP 1 - Measurements and making the tenons
The ideal thickness of the stiles when using the CMT sash set is 35mm. The desired width of the stiles will determine the length you need to make your tenons, while the length of the stile will represent the desired full height of the sash. When cutting the rails to length, make sure to add the length of the two tenons to the overall length of the rail. The length of the tenons should be at least half the width of the stile. Mill 16mm measuring from the front face of the stock using a table saw, radial saw or router as shown in illustration 1. This measurement remains invariable since it is calculated to the height of the CMT sash routers. The width of the tenon is 6mm. Rotate the stock and mill the other side. As per our example, the second milling will be 13mm but this measurement will vary if you are using thinner stock.



STEP 2 - Making the cope profile on rails, sash bar and muntins
To make the cope profile, place the rail face front down on the router table with the tenon flush to the bit as shown in illustration 2. Adjust the fence so the bit mills 6,35mm deeper than the tenon. To mill the sash bar and the muntins (cross bars), position front face down on the router table and mill without changing the height of the bit.


STEP 3 - Making the stick profile on rails, stile, sash bar and muntins
To mill the stick profile along the inside edges of all sash parts, place the already milled cope profile front face down on the router table and adjust the sash bit so that the lower edge of the top cutter will exactly touch the upper edge of the tenon as shown in need to 3 illustrations. With the rail still face down on the table, turn it so the inside edge of the rail is touching the bit and mill the stick profile. Mill the inside edges of the stiles and mill both edges of the front face of the sash bar and muntins. To cut the slots for the tenons, measure 16mm from the front face of the stiles and rout with a table saw.





www.dahm.no


Ovolo Sash Bits




8/955.3


HW | Z2 | RH

These bits allow you to make true divided light doors for fine furniture and cabinets as well as sash bar windows, and stile and rail constructions.
The glazing bar ovolo bits are bearing-guided to enable curved frames to be moulded.
Cove bits can be used to produce easy-to-pull drawer handles.





Drawings are 1:1 scale




D mm	I mm	R mm	L mm	Profile	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm
25	19	10	50,8	A	**855.307.11M**	**955.307.11M**
22	19	10	50,8	B	**855.307.11F**	**955.307.11F**
28	19	10	61,2	C	**855.308.11F**	**955.308.11F**

Spare parts




990.423.00 791.003.00 990.058.00 991.057.00


Ovolo Sash Set



955.302 - 855.802

HW | Z2 | RH





Drawings are 1:1 scale

d mm	D mm	I mm	R mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm
30	31,7	12	6,35	**955.302.11**	**855.802.11**


Spare parts



990.423.00 791.003.00 990.058.00 991.057.00 791.011.00 541.002.00

Spare parts **991.056.00** 1,5mm hex key


Finger Joint Bit



8/900.616

HW Z3 RH

This router allows you to carry out accurate and functional finger joints in a much easier way. Without any adjustment you will be able to work woods with different thicknesses as indicated in the drawing.
The bearing allows you to reach a 9,5mm cutting depth.
For further cutting depths you need to use a fence.



Drawing is 1:1 scale

T1 mm	D mm	H mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
12 - 40	47,6	9,5	97	**900.616.11**	
12 - 40	47,6	9,5	97		**800.616.11**

Spare parts

924.130.00	791.027.00	822.340.11	990.020.00
824.130.00	791.027.00	822.340.11	990.020.00


Spare parts

541.515.00 0,1mm spacer
541.519.00 5,8mm spacer
990.403.00 1,6mm washer
990.459.00 Kit with spacers

Optional

791.020.00 Ø38,1mm bearing (for depth 4,75mm)
791.029.00 Ø34,9mm bearing (for depth 6,35mm)
791.015.00 Ø31,7mm bearing (for depth 8mm)
791.011.00 Ø19mm bearing (for depth 14,3mm)


Professional Finger Joint Bit



8/900.606

HW Z2 RH

This versatile CMT finger joint bit lets you make one of the most incredibly strong side-to-side or end-to-end joints in all wood and wood composites.
The tightness of the accurately cut joint and the maximum glue surface create a joint that is actually stronger than an unworked piece of wood.
CMT's professional finger joint features two flute design, carbide teeth and six removable cutters so you can make joints in a wide range of stock thicknesses, from 12,7mm to 36mm. Ideal for moulding manufacturers and furniture makers.



Drawing is 1:1 scale

T1 mm	D mm	H mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
12,7 - 36	47,6	5,5	97	**900.606.11**	
12,7 - 36	47,6	5,5	97		**800.606.11**

Spare parts


924.129.00	791.028.00	822.005.11	822.006.11	990.022.00
824.129.00	791.028.00	822.005.11	822.006.11	990.022.00

Spare parts


541.511.00 3mm spacer
541.512.00 2mm spacer
541.513.00 0,1mm spacer
990.458.00 Kit with spacer

www.dahm.no

V-Tongue & Groove Set




8/955.506



HW | Z2 | RH

If the standard selection of moulding and mill work you find in today's lumber shops isn't satisfactory to your woodworking tastes, then consider CMT's moulding system instead. With these bits, you can make dozens of elaborate profiles by combining two or more passes. Avoid the average and create your own mouldings. Some initial suggestions are illustrated below.

SAFETY TIPS: use these bits with a fence. The profiles shown below are milled from heavy stock then refined to the desired shape.




Drawing is 1:1 scale

D mm	T1 mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts 8mm	4mm	19mm	22mm	
44,4	19÷25,4	**955.506.11**	**855.506.11**	822.013.11	822.014.11	791.011.00	791.005.00	990.020.00

Spare parts

541.515.00 0,1mm spacer
541.516.00 0,3mm spacer
541.517.00 0,5mm spacer
990.407.00 Shield


Edge Banding Bits Set



8/955.510

HW | Z2 | RH

This is a great set to create cost-effective jet attractive and durable edge to your cabinet doors. Use 1/2" or 1" thick panels in plywood or MDF and create your own edge banding from the wood of your choice.Easy to use: just center each cutter on the stock and make the cut; glue together the two pieces and flush trim it after assembly if necessary. The set features a 60° tongue & groove for a large surface area for glue.



Drawing is 1:1 scale


D mm	I mm	A	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
40	25,4	30°	74,5	**955.510.11**	**855.510.11**	990.423.00	791.018.00	990.058.00	991.057.00

www.dahm.no

Dovetail Bits

CMT ORANGE TOOLS™

HW | HWM | α | Z2 | RH



7/818B





7/8/918

The beautifully crafted dovetail joint is a classic that appeals to both professionals and novices alike. Admired for its attractiveness in box and exposed joint projects, the dovetail is remarkably strong and functional.
CMT dovetail bits are available in 25 different sizes so you can stretch your creativity to the limit.
See the illustrations on the next page for dovetail joinery possibilities.
CMT dovetail bits are designed to fit all popular jigs including Leigh, Keller, JoinTECH and Omnijig systems. You are sure to find the bit you are looking for in our vast selection of cutting sizes and angles.
Check the overall length of the bit before placing an order to be sure you get the size you need - CMT makes bits specifically to fit on jigs and routers that require a longer shank length.


Shop Tips: two passes are recommended when routing dovetails with a template. Check that the dovetails have been cut through completely and smoothly before removing the workpiece.
For even easier routing and less stress on your dovetail bit, run the first pass with a straight bit. Use a dovetail on your router table equipped with a fence to achieve difficult chamfer angles.

Safety Tips: if a dovetail bit jams while working, adjust the position of the bit in the collet and make sure the cutting depth is correct. Do not lift the router out of the template.







Drawings are 1:1 scale



Drawings are 1:1 scale

Fit Manufacturer/Model	ORDER NO.	
CMT-Enlock10	718.098.11B	818.098.11B
CMT-Enlock15	718.127.11B	818.128.11B
CMT300	718.127.11	818.128.11
	918.127.11	818.628.11






Manufacturer/Model FIT HOFFMANN KEYS	ORDER NO.	
W1 L=16mm	718.053.11	818.053.11
W2L=17,5mm	718.079.11	818.079.11
W3 L=19mm	718.093.11	818.093.11
W4 L=25mm	918.167.11	

www.dahm.no


7/8/918 - 7/818B



A few of the beautiful dovetail joints you can produce using CMT bits



Joint are ready in no time at all!



D mm	I mm	L mm	A	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
• 6	8,3	60	7,5°	**718.060.11**				
• 6,35	6,35	50,8	8°		**818.065.11**			
• 6,35	8,3	63,5	7,5°		**818.064.11**			**818.564.11**
• 8	9,5	54	8°		**818.081.11**			
• 8	9,5	52,5	9°		**818.080.11**			
• 8	9,5	63,5	9°					**818.580.11**
9,5	9,5	52,5	9°	**718.095.11**	**818.096.11**	**918.095.11**		
9,5	9,5	63,5	9°					**818.596.11**
• 9,5	9,5	60,3	14°		**818.098.11**			
• 9,5	12,7	60,3	8°		**818.097.11**			
11,1	15,9	60,3	8°		**818.111.11**			
12,7	10,3	60,3	18°		**818.132.11**			
12,7	12,7	52,4	14°	**718.127.11**	**818.128.11**	**918.127.11**		
12,7	12,7	63,5	14°					**818.628.11**
12,7	12,7	62	14°		**818.130.11**			
12,7	16	60,3	10°		**818.133.11**			
12,7	20,6	69,8	8°		**818.129.11**	**918.129.11**		
13,5	19,05	61,5	7°					**818.635.11**
14,2	9,5	50,8	14°		**818.142.11**			
15,8	22	60,3	7°	**718.158.11**	**818.158.11**	**918.158.11**		
15,8	22	66,7	7°				**918.658.11**	**818.658.11**
17,4	25,4	77,6	8°					**818.674.11**
19	19	77,6	14°					**818.691.11**
19	22	60,3	7°	**718.190.11**	**818.190.11**	**918.190.11**		
19	22	66,7	7°				**918.690.11**	**818.690.11**
19	22	60,3	14°		**818.191.11**			
20,6	31,7	84,1	8°					**818.706.11**
With Top Bearing								
8,73	10,3	58	7°		**818.087.11B**			
• 9,5	9,5	60,3	14°	**718.098.11B**	**818.098.11B**			
11,1	19	66,7	7°		**818.113.11B**			
12,7	12,7	52,4	14°	**718.127.11B**	**818.128.11B**			
14,2	9,5	50,8	14°		**818.142.11B**			
With Top Bearing (shank Ø9,5mm)								
15,8	25,4	68,3	7°			**818.159.11B**		
Fit Hoffmann Keys								
• 5,5	4	43	17°	**718.053.11**	**818.053.11**			
• 8	6	43	18°	**718.079.11**	**818.079.11**			
• 9,5	7,3	43	19°	**718.093.11**	**818.093.11**			
16,7	12,5	49	20°			**918.167.11**		

7/8/918




Spare parts		
		
791.009.00	541.001.00	
791.010.00	541.001.00	
791.009.00	541.001.00	
791.010.00	541.001.00	
791.010.00	541.001.00	
791.021.00	541.006.00	

Spare parts

990.005.00 M3x3mm TSEI screw
991.056.00 1,5mm hex key

• **HWM**

9° Dovetail Cutters




522


HW | Z1 | RH

D mm	I mm	L mm	A	S mm	ORDER NO. Right-hand rotation
14	18	60	9°	12	**522.140.11**

Technical details:
- Super strength steel
- 1 HW precision ground cutting edge [Z1]



Drawing is 1:1 scale




523

HW | Z2 | RH


D mm	I mm	L mm	A	S mm	ORDER NO. Right-hand rotation
14	16	60	9°	10	**523.140.11**

Technical details:
- Super strength steel
- 2 HW precision ground cutting edges [Z2]



Drawing is 1:1 scale

15° Dovetail Cutter with Insert Knives for Roof-Frames



664

INSERT CARBIDE | Z2 | RH | 2X LONGER LIFE

D mm	I mm	L mm	A	S mm	ORDER NO. Right-hand rotation
39,5	31,5	65,5	15°	M12x1	**664.395.11**


Technical details:
- Super strength steel
- 2 HWM precision insert knives [Z2]

Spare parts



790.315.00	990.078.00	991.061.00

Application:
This cutter allows you to assemble roof-frames by dovetailing.



Drawing is 1:1 scale

www.dahm.no

60° Lettering Bit



8/949B


7/8/949



HW Z2 RH

The ideal bit for routing signs. CMT designed this bit with a 60° curved profile, a 3,2mm (1/8") radius and a flattened bottom to make relief letter-making easy and accurate.
This exclusive design allows you to efficiently level off the area around the base of the letter and bevel the letter edges to eliminate aggravating splintering.
Try our 60° lettering bit with top bearing guide to get even more precise decorative effects.


Drawings are 1:1 scale



D mm	I mm	A	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm		ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
25,4	19	60°	50,8	**749.001.11**	**849.001.11**						
28	19	60°	63,5				**949.502.11**				
28,5	19	60°	63,5					**849.501.11**			
With Top Bearing											
28	19	60°	63,5				**949.502.11B**		791.026.00	541.005.00	991.056.00
28,5	19	60°	63,5					**849.501.11B**	791.027.00	541.002.00	991.056.00

Spare parts **990.005.00** M3x3mm STEI screw

Bowl & Tray Bits



7/851B




7/8/951

HW Z2 RH

This CMT bit is ideal for making bowls, trays, boxes, cutting boards or any other specialty or craft item. The round corner of the bit shapes the inner radius while the sides and bottom create the smooth flat surfaces. Makes pattern work quick and easy. For best results on jobs where accuracy is a priority, we recommend using our top bearing bowl and tray bits shown at the bottom of this page. Bowl and Tray bits with top bearings are great for pattern work.
Use them to create raised sign lettering, trays and a variety of other items.


Drawings are 1:1 scale



D mm	I mm	R mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
11,1	12,7	3,2	45,5		**851.001.11**						
19	16	6,4	54	**751.002.11**	**851.002.11**	**951.002.11**					
19	16	6,4	60,4				**951.501.11**	**851.501.11**			
31,7	16	6,4	60,4				**951.502.11**	**851.502.11**			
With Top Bearing											
19	16	6,4	54	**751.002.11B**					791.007.00	541.003.00	991.056.00
19	16	6,4	54		**851.002.11B**				791.004.00	541.001.00	991.056.00
19	16	6,4	60,4					**851.501.11B**	791.011.00	541.002.00	991.056.00
31,7	16	6,4	60,4				**951.502.11B**	**851.502.11B**	791.015.00	541.002.00	991.056.00

Spare parts **990.005.00** M3x3mm STEI screw


www.dahm.no




7/8/915

HW HWM Z2 RH

These double cutting edge CMT bits offer an almost endless range of woodworking possibilities. Make clean, perfect cuts in panels, drawer fronts or even plasterboard panels; chamfer edges or engrave beautiful lettering.



Drawings are 1:1 scale



• HWM

D mm	I mm	A	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
• 6	8	90°	38,1	**715.060.11**		**915.060.11**		
• 6,35	8	90°	38,1		**815.064.11**			
9,5	12,7	90°	44,5	**715.095.11**	**815.095.11**	**915.095.11**		
12,7	12,7	90°	44,5	**715.127.11**	**815.127.11**	**915.127.11**		
16	12,7	90°	52,8			**915.160.11**		
16	12,7	90°	63,5				**915.660.11**	**815.660.11**
19	16	90°	55,5	**715.190.11**				
19	16	90°	63,5				**915.690.11**	**815.690.11**
31,7	19	90°	63,5			**915.317.11**	**915.817.11**	**815.817.11**
38	28,5	90°	63,5			**915.380.11**		
38	28,5	90°	70					**815.880.11**




7/8/915B

HW Z2 RH

In addition, CMT has versatile top bearing bits that allow for several template options of your choice (see series 715B-815B-915B). Like all CMT bits, they are made of super strength Fatigue Proof® steel with carbide-tipped cutting edges and are coated with our trademark orange PTFE non-stick coating. These bits are ideal for routing signs, or almost any project that is suitable for accurate template routing.

Tips: V-grooving bits can perfectly chamfer 45°. Two tools in one!




Drawings are 1:1 scale

D mm	I mm	L mm	A	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm		ORDER NO. S=Ø12,7mm	Spare parts		
12,7	12,7	44,5	90°		**815.127.11B**				791.010.00	541.001.00	991.056.00
16	12,7	52,8	90°			**915.160.11B**			791.025.00	541.004.00	991.056.00
19	16	55,5	90°	**715.190.11B**					791.007.00	541.003.00	991.056.00
19	16	63,5	90°					**815.690.11B**	791.011.00	541.002.00	991.056.00

Spare parts 990.005.00 M3x3mm STEI screw


www.cmtutensili.com
www.dahm.no



915

HW Z2 RH


ALUCOBOND® plus composite panels can be shaped using a very simple processing method. The technique, called the routing and folding method, enables a fabricator to produce shapes of various kinds and sizes.
A V-shaped groove is routed on the reverse side of the ALUCOBOND® plus composite panel using a "V" groove router bit. A thin layer of the core material should be left at the base of the groove, i.e. on the inside of the outer cover sheet. The untouched outer cover sheet can now be bent manually, giving an exact and clean folding line which follows the routed groove. The outer radius of the folded edge depends on the shape of the groove and its depth.
We recommend that the routing be done using a CNC machining centre, a portable sheet milling machine or a hand router. The routing and folding method can be used for ALUCOBOND® plus composite panels with all available standard surface finishes. The advantages of this unique technique are:
- Low investment cost
- Simple fabrication technique
- Folding can be done on site, saving transportation costs
- Low-cost fabrication of shaped components, wall cladding, roof edgings, column cladding, flashings, etc.
- Flexibility in creating shapes
- Very cost effective
- Shapes are not limited by machine capacity.



Drawings are 1:1 scale

	D mm	I mm	A	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm		
new	18	7,4	90°	60	**715.001.11**	**815.001.11**	**915.001.11**		
new	18	3,3	135°	60	**715.002.11**	**815.002.11**	**915.002.11**		

Laser Point Bit






7/858.002

7/8/958


HW HWM Z1 Z2 Z3 RH

This new bit lets you make delicate grooves and incisions with laser precision. Make one of a kind effects with single run 30° bevel edges. Three super sharp cutting edges and this perfectly balanced bit allow you to work with superior accuracy with no risk of burning. Raise the bit and produce a delicate fine point incision, or work the whole 12,7mm diameter to render bold highlighted lettering. Super strong steel shank and micrograin carbide cutting edges guarantee long lasting performance.



Drawing is 1:1 scale






• **HWM**

	D mm	I mm	A	Z	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm		ORDER NO. S=Ø12,7mm
	• 6	9	35°	1	50	**758.002.11**				
	• 6,35	9,5	35°	1	50,8		**858.002.11**			
	12,7	11	60°	3	57,2	**758.001.11**	**858.001.11**	**958.001.11**		
	12,7	11	60°	3	60,3					**858.501.11**
new	12,7	10	60°	2	50,8		**858.003.11**	**958.003.11**		

www.dahm.no

V-Grooving & Signmaking Router Bits with indexable knives (90°)

CMT ORANGE TOOLS





665

INSERT CARBIDE | Z1 | RH | 4X LONGER LIFE

These bits have been designed for signmaking and lettering. When the insert shows signs of wear, you can simply rotate it to exploit the other cutting edges. A locking screw secures, the insert tightly for safety and high cutting accuracy.

TECHNICAL DETAILS:
- Super strength steel.
- 1 HW precision insert knife [Z1].






Drawing is 1:1 scale

A	D mm	I mm	L mm		ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm		Spare parts		
90°	17	8,5	53		**665.171.11**	**665.170.11**		790.120.00	990.075.00	991.061.00


Stepped Rebate Router Bit



965

HW | α | Z2 | RH


Router bit featuring 2 carbide-tipped cutting edges for producing double rebates on wood and wood composites. Designed for accepting library/bookcase shelving strips or for accommodating hardware into your window slots.



Drawing is 1:1 scale

d mm	D mm	I mm	L mm			ORDER NO. S=Ø8mm		
new 12,3	16,3	16	80			**965.122.11**		
12,7	19	15,9	50,8			**965.121.11**		


www.dahm.no



703/4/5 - 903/4/5

HW | α | Z2 | RH


From a gently beveled edge to decorative chamfers in a variety of materials, CMT offers smooth results.



Drawings are 1:1 scale

A	D mm	I mm	L mm	ORDER NO. S=Ø6mm		ORDER NO. S=Ø8mm		
15°	24	14	46	**703.240.11**		**903.240.11**		
30°	26	12,7	44,5	**704.240.11**		**904.240.11**		
45°	25	8	41	**705.240.11**		**905.240.11**		


Chamfer Bits with Insert Knives



659

INSERT CARBIDE | Z2 | RH | 4X LONGER LIFE

Bevel and Chamfer trim bits with two replaceable knives fixed by special Torx screws. The knives are sharpened on all 4-sided sharpened and provide three extra new edges. Guided bevel and chamfer trim bits type 659 are equipped with the ball bearing guides. Type 658 is unguided. For specialist applications requiring economy of replaceable tips. For precision work on laminates, MDF or for quick rounded edges in hard wood. For use on portable Routers or CNC machining centers.



Drawings are 1:1 scale

658




A	D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm	Spare parts		
45°	29	8	52	**658.047.11**		**658.045.11**		790.120.00	990.075.00	
22°	25	11	65	**659.024.11**	**659.023.11**	**659.022.11**		790.120.00	990.075.00	791.006.00
30°	28	10	66	**659.032.11**	**659.031.11**	**659.030.11**		790.120.00	990.075.00	791.006.00
45°	29	8	60	**659.047.11**	**659.046.11**	**659.045.11**		790.120.00	990.075.00	791.022.00
45°	29	8	68				**659.646.11**	790.120.00	990.075.00	791.022.00

Spare parts

990.400.00	Ø3.2/Ø7mm shield for M3 screw
990.051.00	M3x6mm TCEI screw
991.062.00	2,5mm hex key
991.061.00	T15 Torx key

www.dahm.no


Chamfer Bits



7/8/936 - 8/957

HW | Z2 | RH

CMT chamfer bits can cut clean, accurate bevels and chamfers and are great for edge work or for making perfectly aligned multi-sided containers, boxes and other decorative projects.
See illustration below for examples. Can be used for working larger scale projects such as beams and columns with excellent results.



Drawings are 1:1 scale

A	D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
15°	19	11,5	54,9	**736.130.11**	**836.130.11**	**936.130.11**			990.423.00	791.003.00	990.058.00	991.057.00
25°	22,2	10	54,9	**736.190.11**	**836.190.11**	**936.190.11**			990.423.00	791.003.00	990.058.00	991.057.00
45°	31,7	9,5	53	**736.280.11**	**836.280.11**	**936.280.11**			990.423.00	791.003.00	990.058.00	991.057.00
45°	45	18	60,2	**736.420.11**	**836.420.11**	**936.420.11**			990.423.00	791.003.00	990.058.00	991.057.00
45°	45	18	66,5				**936.920.11**	**836.920.11**	990.423.00	791.003.00	990.058.00	991.057.00
45°	65	26	76,7				**936.950.11**	**836.950.11**	990.423.00	791.003.00	990.058.00	991.057.00
11,25°	21,5	22	71,1				**957.504.11**	**857.504.11**	990.423.00	791.003.00	990.058.00	991.057.00
15°	24,5	22	71,1				**957.503.11**	**857.503.11**	990.423.00	791.003.00	990.058.00	991.057.00
22,5°	31	22	71,1				**957.502.11**	**857.502.11**	990.423.00	791.003.00	990.058.00	991.057.00
30°	38,5	22	71,1				**957.501.11**	**857.501.11**	990.423.00	791.003.00	990.058.00	991.057.00


Chamfer Set

836

HW | Z2 | RH

Build beautiful planters, boxes and other multi-sided pieces with this handy set. Why cut imperfect angles on your table saw when it's so much easier and accurate to use the CMT Chamfer set? Our solution to accurate polygon construction includes 5 anti-kickback, carbide tipped bits in the most popular angles - 11-1/4°, 15°, 22-1/2°, 30° and 45°. No polygon project is too difficult. Available with 12,7mm shank.






Drawings are 1:1 scale

DESCRIPTION	ORDER NO. S=Ø12,7mm
Chamfer Set	**836.501.11**

www.dahm.no



7/8/914B


7/8/914



HWM | HW | α | Z2 | RH

Personalize your doors, drawer fronts, panels or any surface you choose with your own signature motif. CMT round nose bits in solid carbide or with carbide tipped flutes let you create engraving in any wood or wood product. We offer a complete selection of diameters and cutting depths so you can achieve the effects you want. Mounted on your router table, you can work materials up to 31,7mm in depth.
For even more elaborate decorations, we also offer top bearing bits - use your own template with one of these bits to produce truly unique doors and drawer fronts.
A favourite item for professional sign makers, craft makers and hobbyists.

Shop Tips: more than one pass is recommended when making cove edges. To prevent splintering, begin with a shallow initial pass and deepen gradually.



R mm	D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
• 1,6	3,2	9,5	50,8	**714.032.11**	**814.032.11**	**914.032.11**		
• 1,6	3,2	12,7	50,8		**199.001.11**			
• 3	6	12,7	50,8	**714.060.11**		**914.060.11**		
• 3	6	27	70	**199.060.11**				
• 3,2	6,4	12,7	50,8		**814.064.11**			
• 3,2	6,4	25,4	63,5		**199.008.11**			
• 3,2	6,4	15,9	63,5					**814.564.11**
• 4	8	32	80			**199.081.11**		
4,75	9,5	6,4	50,8	**714.095.11**	**814.095.11**	**914.095.11**		
4,75	9,5	25,4	66,7					**814.595.11**
• 6	12	35	80				**199.120.11**	
6,35	12,7	9,5	50,8	**714.127.11**	**814.127.11**	**914.127.11**		
6,35	12,7	31,7	73				**914.627.11**	**814.627.11**
• 6,35	12,7	31,7	76,2					**199.505.11**
8	15,8	9,5	50,8	**714.160.11**	**814.160.11**	**914.160.11**		
8	15,8	31,7	73					**814.660.11**
9,5	19	11,3	50,8	**714.190.11**	**814.190.11**	**914.190.11**		
9,5	19	25	63,5			**914.191.11**		
9,5	19	31,7	73				**914.690.11**	**814.690.11**
new 11	22	25,4	63,5			**914.221.11**		
12,7	25,4	16	73			**914.254.11**		
12,7	25,4	31,7	73				**914.754.11**	**814.754.11**
16	31,7	18,5	58,8				**914.817.11**	**814.817.11**
new 19,05	38,1	31,7	69,8				**914.880.11**	**814.880.11**
new 25,4	50,8	31,7	69,8				**914.990.11**	**814.990.11**
With Top Bearing								
6,35	12,7	9,5	50,8		**814.127.11B**			
8	15,8	9,5	50,8		**814.160.11B**			
8	15,8	9,5	50,8			**914.160.11B**		
9,5	19	11,3	50,8	**714.190.11B**				
9,5	19	11,3	50,8		**814.190.11B**			
9,5	19	31,7	73					**814.690.11B**

Spare parts 990.005.00 M3x3mm TSEI screw



199

Spare parts



791.010.00	541.001.00	991.056.00
791.009.00	541.001.00	991.056.00
791.025.00	541.004.00	991.056.00
791.007.00	541.003.00	991.056.00
791.004.00	541.001.00	991.056.00
791.011.00	541.002.00	991.056.00

• HWM

www.dahm.no


Ball Milling



8/968

HW | α | Z2 | RH

Cut channels for pipes or cables in one single pass using CMT's ball end bits.
Reduce the stress on the bits by cutting a first groove with a straight bit.



Drawings are 1:1 scale

R mm	D mm	I mm	L mm			ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
6,35	12,7	11	57,15			**968.127.11**		**868.627.11**
7,94	15,88	14,2	60,3			**968.158.11**		**868.658.11**
9,52	19,05	17,4	63,5			**968.190.11**		**868.690.11**
12,7	25,4	23,5	70				**968.754.11**	**868.754.11**

Round Nose Set




814


HW | α | HWM | Z2 | RH

Each of these sets include 3 of the most widely used CMT Round Nose bits. These solid carbide or carbide tipped bits are perfect for sign making, engraving, or adding flutes and veins to doors or drawer fronts. Available in 6,35mm and 12,7mm shanks.

Drawings are 1:1 scale

814.001.11






814.501.11

DESCRIPTION	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø12,7mm
Round Nose Set	**814.001.11**	**814.501.11**


www.dahm.no




7/8/937

HW · α · Z2 · RH


Make simple or elegant furniture, doors and drawer fonts by adding a final touch with CMT cove bits. Join them together with a CMT roundover bit and make perfectly fitting rule joints, ideal for drop leaf counter and table tops. These bits feature anti-kickback design, carbide-tipped cutting edges, Fatigue Proof® steel body and PTFE non-stick coating.



CMT's carbide tipped cove bits are a perfect match for the roundover bits on the next page. That means they're the ideal way to produce rule joints for your drop leaf tables.



8/937.955.11



Drawings are 1:1 scale

R mm	D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
4,75	22,2	12,7	54,9	**737.190.11**	**837.190.11**	**937.190.11**			990.423.00	791.003.00	990.058.00	991.057.00
4,75	22,2	12,7	61,2				**937.690.11**	**837.690.11**	990.423.00	791.003.00	990.058.00	991.057.00
6,35	25,4	12,7	54,9	**737.222.11**	**837.222.11**	**937.222.11**			990.423.00	791.003.00	990.058.00	991.057.00
6,35	25,4	12,7	61,2				**937.722.11**	**837.722.11**	990.423.00	791.003.00	990.058.00	991.057.00
8	28,7	12,7	54,2	**737.254.11**	**837.254.11**	**937.254.11**			990.423.00	791.003.00	990.058.00	991.057.00
8	28,7	12,7	60,5				**937.754.11**	**837.754.11**	990.423.00	791.003.00	990.058.00	991.057.00
9,5	31,7	12,7	54,2	**737.286.11**	**837.286.11**	**937.286.11**			990.423.00	791.003.00	990.058.00	991.057.00
9,5	31,7	12,7	60,5				**937.786.11**	**837.786.11**	990.423.00	791.003.00	990.058.00	991.057.00
12,7	38,1	15,5	57,7	**737.350.11**	**837.350.11**	**937.350.11**			990.423.00	791.003.00	990.058.00	991.057.00
12,7	38,1	15,5	64				**937.850.11**	**837.850.11**	990.423.00	791.003.00	990.058.00	991.057.00
16	44,5	18,5	67				**937.950.11**	**837.950.11**	990.423.00	791.003.00	990.058.00	991.057.00
19	50,8	22,2	70,7				**937.951.11**	**837.951.11**	990.423.00	791.003.00	990.058.00	991.057.00
14,3-35	50,8	12,7	61,2				**937.955.11**	**837.955.11**	990.423.00	791.003.00	990.058.00	991.057.00


Cove Bit Set



837

HW · α · Z2 · RH

See simple furniture, doors and drawer fronts transform into elegant pieces by giving them a final touch with a CMT Cove Bit. Pair them up with CMT Roundover Bits and make beautiful rule joints to create drop leaf counter and table tops.
Anti-kickback design and thick carbide tips for long lasting performance.
Available with a 12,7mm or 6,35mm shank. Cove radii are 6,35mm, 9,5mm and 12,7mm.




Drawings are 1:1 scale

DESCRIPTION	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø12,7mm
Cove Bit Set	**837.001.11**	**837.501.11**

www.dahm.no

Cavetto Edge Mould Bits





7/8/963 - 7/8/964

HW | α | Z2 | RH

The cavetto bit cuts beautiful, traditional profiles, but you may also use just a portion of the bit to cut a more simple and cleaner cove edge. This bit adds a special touch to furniture pieces by making traditional cove profiles with top and bottom fillet grooves in any kind of wood and wood composites.

IMPORTANT: always assemble the black bearing heat shield with the raised side up when changing the bearing. Improper assembly will cause the screw to come loose and the bearing to fall off when routing.






Drawings are 1:1 scale

R mm	D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
4,8	25,4	11,5	54,6	**763.048.11**	**863.048.11**	**963.048.11**		
4,8	25,4	11,5	60,9				**963.548.11**	**863.548.11**
8	31,7	14,3	56,9	**763.080.11**	**863.080.11**	**963.080.11**		
8	31,7	14,3	63				**963.580.11**	**863.580.11**
4,8	25,4	11,5	52,8	**764.048.11**	**864.048.11**	**964.048.11**		
4,8	25,4	11,5	59,1				**964.548.11**	**864.548.11**
8	31,7	14,3	55,1	**764.080.11**	**864.080.11**	**964.080.11**		
8	31,7	14,3	61				**964.580.11**	**864.580.11**

Spare parts

990.423.00	791.003.00	990.058.00	991.057.00
990.423.00	791.003.00	990.058.00	991.057.00
990.423.00	791.003.00	990.058.00	991.057.00
990.423.00	791.003.00	990.058.00	991.057.00
990.422.00	791.002.00	990.058.00	991.057.00
990.422.00	791.002.00	990.058.00	991.057.00
990.422.00	791.002.00	990.058.00	991.057.00
990.422.00	791.002.00	990.058.00	991.057.00

Ovolo Bits




7/8/927

HW | α | Z2 | RH

CMT put the work capacity of several different bits all into one. The perfect bit for furniture makers, the CMT ovolo allows you to make beautiful beadwork, edgework and veins. Use these bits on automated router systems or with a fence to produce a wide variety of single and double bead profiles and roundovers like those illustrated below by simply adjusting the height or depth of the cut.


SAFETY TIPS: pay particular attention to never rush the job when using a large profile bit. Mill pieces with a fence mounted on the work table to insure maximum protection.



Drawings are 1:1 scale

R mm	D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
4	19	12	43,8	**727.040.11**		**927.040.11**		
5	21	12	43,8	**727.050.11**	**827.050.11**	**927.050.11**		
6	23	12	43,8	**727.060.11**	**827.060.11**	**927.060.11**		
6	23	12	50,1					**827.560.11**
8	28,6	12,7	44,5	**727.080.11**		**927.080.11**		
9,5	31,7	15,8	47,6	**727.095.11**	**827.095.11**	**927.095.11**		
9,5	31,7	15,8	54				**927.595.11**	**827.595.11**
12,7	38,1	19	50,8		**827.127.11**			
12,7	38,1	19	57,1				**927.627.11**	**827.627.11**
16	44,5	22,2	60,3				**927.660.11**	**827.660.11**
19	50,8	25,4	63,5				**927.690.11**	**827.690.11**
22,2	57,1	28,5	66,6				**927.722.11**	**827.722.11**
25,4	63,5	33,3	71,4				**927.754.11**	**827.754.11**

www.dahm.no




7/8/939

HW | Z2 | RH


Beading bits are similar to the roundover profile, but a smaller bearing produces a delicate inset at the base of the cut, giving you an extra decorative option. For a beading profile (code 7/8/939) simply change the bearing **(791.002.00)** on your roundover bits (code 7/8/938).

Drawings are 1:1 scale



***Use only on router table**


R mm	D mm	I mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
1,6	15,9	12,7	**739.160.11**	**839.160.11**	**939.160.11**			990.422.00	791.002.00	990.058.00	991.057.00
2	16,7	12,7			**939.167.11**			990.422.00	791.002.00	990.058.00	991.057.00
3	18,7	12,7			**939.187.11**			990.422.00	791.002.00	990.058.00	991.057.00
3,2	19,1	12,7	**739.190.11**	**839.190.11**	**939.190.11**			990.422.00	791.002.00	990.058.00	991.057.00
4,75	22,2	12,7	**739.222.11**	**839.222.11**	**939.222.11**			990.422.00	791.002.00	990.058.00	991.057.00
6,35	25,4	12,7	**739.254.11**	**839.254.11**	**939.254.11**	**939.754.11**	**839.754.11**	990.422.00	791.002.00	990.058.00	991.057.00
8	28,6	12,7	**739.285.11**	**839.285.11**	**939.285.11**			990.422.00	791.002.00	990.058.00	991.057.00
9,5	31,7	16	**739.317.11**	**839.317.11**	**939.317.11**	**939.817.11**	**839.817.11**	990.422.00	791.002.00	990.058.00	991.057.00
12,7	38,1	19	**739.380.11**	**839.380.11**	**939.380.11**	**939.880.11**	**839.880.11**	990.422.00	791.002.00	990.058.00	991.057.00
16	44,5	22		**839.445.11**	**939.445.11**	**939.945.11**	**839.945.11**	990.422.00	791.002.00	990.058.00	991.057.00
19	50,8	25,4				**939.990.11**	**839.990.11**	990.422.00	791.002.00	990.058.00	991.057.00
22,2	57,1	28,5				**939.991.11**	**839.991.11**	990.422.00	791.002.00	990.058.00	991.057.00
25,4	63,5	33,3				**939.992.11***	**839.992.11***	990.422.00	791.002.00	990.058.00	991.057.00



Roundover Bits with Insert Knives

661.11

Roundover bits with two replaceable knives fixed by special Torx screws. The blades are profiled on 2 sided and give increase efficiency of your work with laminates. Roundover bits type are equipped with ball bearing guides. For precision work on laminates. Radius R2 or R3 is for rounded 2mm or 3mm ABS edges. Radius R5 is for quick rounded edges in hard wood or MDF. For use on portable Routers.




Drawings are 1:1 scale

new

INSERT CARBIDE | Z2 | RH

4X LONGER LIFE





661.41

Optional

R=1mm	790.010.04
R=1,5mm	790.015.04
R=2mm	790.020.04
R=3mm	790.030.04

R mm	D mm	I mm	L mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm	Spare parts				
2	22,8	19,5	64	**661.021.11**	**661.020.11**		790.020.00		990.076.00	991.061.00	791.007.00
new 2	27		57,5	**661.021.41**	**661.020.41**			790.020.04	990.078.00	991.061.00	791.003.00
new 3	27		57,5	**661.031.41**	**661.030.41**			790.030.04	990.078.00	991.061.00	791.003.00
3	24,8	19,5	64	**661.031.11**	**661.030.11**		790.030.00		990.076.00	991.061.00	791.007.00
5	28,8	19,5	64	**661.051.11**	**661.050.11**		790.050.00		990.076.00	991.061.00	791.007.00
6,35	28,5	24	67	**661.064.11**	**661.063.11**		790.064.00		990.075.00	991.061.00	791.006.00
8	31,8	24	67		**661.080.11**		790.080.00		990.075.00	991.061.00	791.006.00
8	31,8	24	77			**661.581.11**	790.080.00		990.075.00	991.061.00	791.006.00


Spare parts

990.400.00	M3 shield	990.410.00	M4 shield	990.423.00	Shield for 12,7mm bearing
990.051.00	M3x6mm TCEI screw	990.052.00	M4x6mm TCEI screw	990.058.00	1/8"x3/8"x1/2" TCEI screw
991.062.00	2,5mm hex key	991.067.00	3mm hex key	991.057.00	3/32" hex key

www.dahm.no

Roundover Bits

CMT ORANGE TOOLS



7/8/938

HW | α | Z2 | RH

The smaller bearing on the CMT Beading bits makes a delicate inset at the base of the cut, giving you the advantage of an extra decorative option.


Be Sure to keep the black bearing washer right side up to correspond with the bearing rotation when reassembling the bearing. Improper reassembly can cause the bit to unscrew. All CMT roundover bits have a 12,7mm bearing diameter with the exception of the radius 28,6mm and 31,7mm bits which have a 19mm bearing diameter. You have 13 different radii to choose from, the majority having 5 shank diameter options. All bits are made of Fatigue Proof® steel and have carbide-tipped cutting edges.

Shop Tips: the CMT 1.6mm radius roundover bit is excellent for finishing laminates. Virtually eliminates the filing required when using conventional trim bits.

Safety Tips: use caution when working with large diameter bits and make more than one pass to gradually remove stock. Pay particular attention when routing small pieces; and always rout on a router table equipped with a fence.

***Use only on router table**

Drawings are 1:1 scale



R mm	D mm	I mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
new 1	14,7	10		**838.147.11**	**938.147.11**			990.422.00	791.044.00	990.058.00	991.057.00
1,6	15,9	12,7	**738.160.11**	**838.160.11**	**938.160.11**			990.423.00	791.003.00	990.058.00	991.057.00
2	16,7	12,7	**738.167.11°**		**938.167.11°**			990.422.00	791.044.00	990.058.00	991.057.00
3	18,7	12,7	**738.187.11°**		**938.187.11°**			990.422.00	791.044.00	990.058.00	991.057.00
3,2	19,1	12,7	**738.190.11**	**838.190.11**	**938.190.11**			990.423.00	791.003.00	990.058.00	991.057.00
4,75	22,2	12,7	**738.222.11**	**838.222.11**	**938.222.11**			990.423.00	791.003.00	990.058.00	991.057.00
6,35	25,4	12,7	**738.254.11**	**838.254.11**	**938.254.11**	**938.754.11**	**838.754.11**	990.423.00	791.003.00	990.058.00	991.057.00
8	28,6	12,7	**738.285.11**	**838.285.11**	**938.285.11**			990.423.00	791.003.00	990.058.00	991.057.00
9,5	31,7	16	**738.317.11**	**838.317.11**	**938.317.11**	**938.817.11**	**838.817.11**	990.423.00	791.003.00	990.058.00	991.057.00
12,7	38,1	19	**738.380.11**	**838.380.11**	**938.380.11**	**938.880.11**	**838.880.11**	990.423.00	791.003.00	990.058.00	991.057.00
16	44,5	22		**838.445.11**	**938.445.11**	**938.945.11**	**838.945.11**	990.423.00	791.003.00	990.058.00	991.057.00
19	50,8	25,4				**938.990.11**	**838.990.11**	990.423.00	791.003.00	990.058.00	991.057.00
22,2	57,1	28,5				**938.991.11**	**838.991.11**	990.423.00	791.003.00	990.058.00	991.057.00
25,4	63,5	33,3				**938.992.11***	**838.992.11***	990.423.00	791.003.00	990.058.00	991.057.00
28,6	76,2	38,1				**938.993.11***	**838.993.11***	541.550.00	791.004.00	990.058.00	991.057.00
31,75	82,5	44,4				**938.994.11***	**838.994.11***	541.550.00	791.004.00	990.058.00	991.057.00
38,1	88,9	44,4				**938.996.11***	**838.996.11***	990.423.00	791.003.00	990.058.00	991.057.00

°791.044.00 Delrin® Bearing




Roundover Set

838

HW | α | Z2 | RH

CMT's roundover sets give you the maximum flexibility for all of your projects by putting the most requested diameters in one package. Available in 12,7mm and 6,35mm shanks. Roundover radii are 6,35mm, 9,5mm and 12,7mm.
These versatile bits are always in demand - the simple clean lines of a smooth roundover edge can be used in a wide variety of applications from picture frames to table and counter tops.

Drawings are 1:1 scale



DESCRIPTION	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø12,7mm
Roundover set	**838.001.11**	**838.501.11**


www.cmtutensili.com
www.dahm.no

CMT ORANGE TOOLS™

HW α Z2 RH

8/965


Enhance your doors and drawer fronts and leave your visitors amazed! The cutting edges on these ogee bits are carbide-tipped for effective, smooth and eye-catching work.



8/965.905




8/965.903
8/965.904



Drawings are 1:1 scale

D mm	d mm	R mm	I mm	L mm	Profile				ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
19	6,4	6,4	13	51	B				**965.903.11**	**865.903.11**
22	12,7	3,2	31,7	69,8	C				**965.905.11**	**865.905.11**
34,9	9,5	12,7	25	65,5	D				**965.904.11**	**865.904.11**


Decorative Ogee Bits



HW α Z2 RH

7/8/965

This new CMT bit produces a classic single or double-edged bead.
Ideal for creating a marked decorative effect on panel, door and drawer work.




Drawings are 1:1 scale

D mm	d mm	R mm	I mm	L mm	Profile	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
19	6,35	6,4	11	50,8	A	**765.001.11**	**865.001.11**	**965.001.11**	**965.501.11**	**865.501.11**
12,7	4	2	8	51	B		**865.002.11**	**965.002.11**		
19	6,35	3,2	13	68	C				**965.503.11**	**865.503.11**
25,4	9,5	3,2	9,5	49	D				**965.504.11**	**865.504.11**

www.dahm.no


Decorative Beading Bits



7/8/965

HW Z2 RH


Make subtle decorative edges with this bit! Perfect for enhancing doors and drawer fronts, it will deliver smooth and flawless results. Carbide-tipped to ensure a clean, sharp and precise cut.



Drawing is 1:1 scale

D mm	d mm	R mm	I mm	L mm	Profile	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm
10	1,3	5	10	50	A	**765.402.11**	**865.402.11**	**965.402.11**


Classical Bead Bits




7/8/965B

HW Z2 RH

This bit gives you even more decorative possibilities for panel and edge work. The bit design offers a wide flat bottom cut and a longer shank allows for a greater depth in the detail of the profile.




Drawings are 1:1 scale



D mm	R mm	I mm	L mm	Profile	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
19	3,2	12,3	54	A	**765.201.11B**					791.007.00	541.003.00	991.056.00
19	3,2	12,3	54	A		**865.201.11B**				791.004.00	541.001.00	991.056.00
28,6	4	14,3	58,8	B			**965.202.11B**			791.027.00	541.002.00	991.056.00
28,6	4	14,3	58,8	B				**965.702.11B**		791.027.00	541.005.00	991.056.00
28,6	4	14,3	58,8	B					**865.702.11B**	791.027.00	541.002.00	991.056.00
19	3,2	12,3	54	C	**765.301.11B**					791.007.00	541.003.00	991.056.00
19	3,2	12,3	54	C		**865.301.11B**				791.004.00	541.001.00	991.056.00
28,6	4	13,3	58	D			**965.302.11B**		**865.802.11B**	791.027.00	541.002.00	991.056.00
28,6	4	13,3	58	D				**965.802.11B**		791.027.00	541.005.00	991.056.00
34,9	4,76 - 6,35	18,5	66,1	E			**965.303.11B**			791.031.00	541.004.00	991.056.00
34,9	4,76 - 6,35	18,5	66,1	E					**865.803.11B**	791.029.00	541.002.00	991.056.00

Spare parts **990.005.00** M3x3mm TSEI screw

www.dahm.no




7/8/948 - 7/8/948B

HW | Z2 | RH

You will never run out of ideas with this creative bit. Add a classic touch to any edge or highlight door fronts and panels with decorative layered effects.
For even more options, try the CMT plunge ogee with bearing guide for pattern following.


For more CMT ogee profile options, choose among plunge ogee bits equiped with a top bearing.
Excellent for achieving accurate decorative work and guaranteed for long-lasting performance.



Drawings are 1:1 scale

D mm	R mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
19	4	13	51,1	**748.190.11**	**848.190.11**	**948.190.11**					
19	2,4	12	53	**748.191.11**	**848.191.11**	**948.191.11**					
31,7	4	13	58			**948.317.11**	**948.817.11**	**848.817.11**			
34,9	6,5-10	18	68				**948.850.11**	**848.850.11**			
With Top Bearing											
19	4	13	51,1	**748.190.11B**					791.007.00	541.003.00	991.056.00
19	4	13	51,1		**848.190.11B**				791.004.00	541.001.00	991.056.00
19	2,4	12	53	**748.191.11B**					791.007.00	541.003.00	991.056.00
19	2,4	12	53		**848.191.11B**				791.004.00	541.001.00	991.056.00
31,7	4	13	58			**948.317.11B**			791.015.00	541.002.00	991.056.00
31,7	4	13	58				**948.817.11B**		791.015.00	541.005.00	991.056.00
31,7	4	13	58					**848.817.11B**	791.015.00	541.002.00	991.056.00

Spare parts **990.005.00** M3x3mm TSEI screw




Decorative Ogee Bits

7/8/965

HW | Z2 | RH

This new CMT bit produces a classic single or double edged bead.
Ideal for creating a marked decorative effect on panel, door and drawer work.




Drawings are 1:1 scale

D mm	d mm	R mm	I mm	L mm	Profile	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm		
12,7	8,4	1,2	12,7	50,8	E	**765.101.11**	**865.101.11**	**965.101.11**		
19	11,1	2,4	11	50,8	F	**765.102.11**	**865.102.11**	**965.102.11**		

www.dahm.no

Roman Ogee Bits




7/8/940

HW α Z2 RH


The roman ogee may be the most popular edge treatment in woodworking, and it is certainly one of the most beautiful. This bit includes all CMT bit features and produces a perfect rendition of classic design.


SHOP TIPS: for best results, multiple passes are recommended.



Drawings are 1:1 scale

7/8/941






This bit takes the Roman Ogee a step further. The horizontal bead adds style and elegance to the traditional shape contour.

SHOP TIPS: for best results, multiple passes are recommended.

R mm	D mm	I mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
4	28,7	11,5	**740.270.11**	**840.270.11**	**940.270.11**	**940.770.11**	**840.770.11**	990.423.00	791.003.00	990.058.00	991.057.00
6,4	38,1	17,3	**740.350.11**	**840.350.11**	**940.350.11**	**940.850.11**	**840.850.11**	990.423.00	791.003.00	990.058.00	991.057.00
4	33,4	13	**741.285.11**	**841.285.11**	**941.285.11**	**941.785.11**	**841.785.11**	990.423.00	791.003.00	990.058.00	991.057.00
6,4	42,8	18,5	**741.380.11**	**841.380.11**	**941.380.11**	**941.880.11**	**841.880.11**	990.423.00	791.003.00	990.058.00	991.057.00

Classical Ogee Bits




7/8/944

HW α Z2 RH


CMT's classical ogee bits feature an inverted ogee profile, with the concave edge adjacent to the upper surface of the workpiece. A vertical bead was added to separate the curves and creates an eye-catching shape.


SHOP TIPS: for best results, multiple passes are recommended.



Drawings are 1:1 scale

7/8/945






This profile includes a horizontal bead along the bottom of the profile adding a decorative detail to the traditional ogee design.

SHOP TIPS: for best results, multiple passes are recommended.

R mm	D mm	I mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
4	28,7	13	**744.287.11**	**844.287.11**	**944.287.11**	**944.787.11**	**844.787.11**	990.423.00	791.003.00	990.058.00	991.057.00
6,4-4,8	35	18,5	**744.350.11**	**844.350.11**	**944.350.11**	**944.850.11**	**844.850.11**	990.423.00	791.003.00	990.058.00	991.057.00
4	28,7	13	**745.287.11**	**845.287.11**	**945.287.11**	**945.787.11**	**845.787.11**	990.422.00	791.002.00	990.058.00	991.057.00
6,4-4,8	35	18,5	**745.350.11**	**845.350.11**	**945.350.11**	**945.850.11**	**845.850.11**	990.422.00	791.002.00	990.058.00	991.057.00

www.dahm.no

Ogee with Fillet Bits



7/8/946

HW | Z2 | RH


Take a complete assortment of CMT ogee bits into your shop. These bits feature micrograin carbide edges, high strength steel and the trademarked orange non-stick PTFE coating.

SHOP TIPS: for best results, multiple passes are recommended.


For a more-detailed profile, this bit adds an inset bead along the lower edge of the cut.

SHOP TIPS: for best results, multiple passes are recommended.


7/8/947



Drawings are 1:1 scale



7/8/946



7/8/947

R mm	D mm	I mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
4,8-3,6	34,2	13	**746.325.11**	**846.325.11**	**946.325.11**	**946.825.11**	**846.825.11**	990.423.00	791.003.00	990.058.00	991.057.00
4,8-3,6	34,2	13	**747.325.11**	**847.325.11**	**947.325.11**	**947.825.11**	**847.825.11**	990.422.00	791.002.00	990.058.00	991.057.00

Ogee Bits



7/8/959


HW | Z2 | RH

These profiles are the mirror image of the traditional roman ogee. They add sharp defining details to the edges of cabinets and furniture, before rolling into a smooth convex shape.

SHOP TIPS: for best results, multiple passes are recommended.

These bits are identical to the 7/8/959 series with the addition of an inset bead along the lower edge.

SHOP TIPS: for best results, multiple passes are recommended.




7/8/959

7/8/960



Drawings are 1:1 scale




7/8/960

R mm	D mm	I mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
4	28,7	13	**759.040.11**	**859.040.11**	**959.040.11**	**959.540.11**	**859.540.11**	990.423.00	791.003.00	990.058.00	991.057.00
6,4	38,1	18	**759.064.11**	**859.064.11**	**959.064.11**	**959.564.11**	**859.564.11**	990.423.00	791.003.00	990.058.00	991.057.00
4	28,7	13	**760.040.11**	**860.040.11**	**960.040.11**	**960.540.11**	**860.540.11**	990.422.00	791.002.00	990.058.00	991.057.00
6,4	38,1	18	**760.064.11**	**860.064.11**	**960.064.11**	**960.564.11**	**860.564.11**	990.422.00	791.002.00	990.058.00	991.057.00

www.dahm.no


Adjustable Roundover & Bevel Router Bits



8/900.623

HW Z2 RH

These new CMT bits are ideal for making new awesome creations! Create a double 4,76mm (3/16") roundover profile, a double 45° bevel or even a mixed profile on your wood panels easily and in a cost-effective way! Interchangeable shims are included to allow for different stock thicknesses according to the board.
To be used on table-mounted routers. Do not use these bits with hand-held power tools.




Drawings are 1:1 scale

D mm	T1 mm	R mm	A	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts				
38,1	11,1 - 31,75	4,76	45°	100	**900.623.11**		924.137.00	791.037.00	822.029.11	822.030.11	990.020.11
38,1	11,1 - 31,75	4,76	45°	100		**800.623.11**	824.137.00	791.037.00	822.029.11	822.030.11	990.020.11

Spare parts

541.500.00 3mm spacer
541.515.00 0,1mm spacer
541.517.00 0,5mm spacer
541.518.00 1mm spacer
541.519.00 5,8mm spacer




Adjustable Double Roundover Router Bits

8/900.622

HW Z2 RH

Create awesome furnishing decorations with these new CMT bits! They provide a double 2mm (5/64") and 3mm (1/8") roundover profile on your wood panels easily and in a cost-effective way! Interchangeable shims are included to allow for different stock thicknesses according to the board. To be used on table-mounted routers. Do not use these bits with hand-held power tools.




Drawings are 1:1 scale


D mm	T1 mm	R mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts				
34	11,1 - 31,75	3 - 2	100	**900.622.11**		924.137.00	791.037.00	822.031.11	822.032.11	990.020.11
34	11,1 - 31,75	3 - 2	100		**800.622.11**	824.137.00	791.037.00	822.031.11	822.032.11	990.020.11

Spare parts

541.500.00 3mm spacer
541.501.00 4mm spacer
541.515.00 0,1mm spacer
541.516.00 0,3mm spacer
541.518.00 1mm spacer
541.519.00 5,8mm spacer

www.dahm.no







Drawing is 1:1 scale


8/961.6

HW Z2 RH


This new router bit designed for 19mm (3/4") thick stock is perfect for creating wainscots and panels on your walls. Simply create a 6,35mm (1/4") tongue-and-groove interlock with a CMT 8/900.626.11, then, with two passes mill an attractive traditional beadboard profile with this new bit.
Perfect for cabinets, bookcase backings, ceiling and wall paneling.







Standard with bearing Ø12,7mm (791.003.00)




Optional with Ø15,8mm bearing (791.018.00)

D mm	I mm	R mm	A	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
23,8	19,05	4	45°	67,7	**961.601.11**	**861.601.11**

Spare parts: 990.423.00 | 791.003.00 | 990.058.00 | 991.057.00

Corner Beading Bit with 45° Chamfer




954

HW α Z2 RH

An innovative bit to create beautiful edges and corner beads.

SAFETY TIPS: to be used only on CNC machines or router tables equipped with a fence.




Drawing is 1:1 scale

D mm	D1 mm	I mm	R mm	L mm		ORDER NO. S=Ø8mm
36	22	25	8	60		**954.080.11**

www.dahm.no

Bead & Bull Nose Bits

CMT ORANGE TOOLS




7/8/954

HW Z2 RH

CMT bull nose bits create beautifully finished edges on stair treads, window sills and shelves in a pass. Ad a final touch by using a cutter with a bead diameter wider than the stock thickness. CMT bull nose bits have bead diameters from 6,35mm (1/4") to 25,4mm (1") and each bit features carbide-tipped cutting edges, anti-kickback design and the orange PTFE non-stick coating trademark.


Safety tips: to be used only on router tables equipped with a fence. Do not remove the workpiece while the bit is routing.



Drawings are 1:1 scale

R mm	D mm	I1 mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
3,2	22,2	6,56	19	50,8	**754.002.11**	**854.002.11**	**954.002.11**		
3,2	22,2	6,56	19	57,2				**954.502.11**	**854.502.11**
4,75	25,4	9,85	22	54	**754.003.11**	**854.003.11**	**954.003.11**		
4,75	25,4	9,85	22	60,4				**954.503.11**	**854.503.11**
6,35	28,6	13,15	25,5	57,2	**754.004.11**	**854.004.11**	**954.004.11**		
6,35	28,6	13,15	25,5	63,5				**954.504.11**	**854.504.11**
9,5	34,9	19,71	35	73				**954.507.11**	**854.507.11**
12,7	44,5	26,3	41	79,4				**954.509.11**	**854.509.11**


Corner Beading Bits



7/8/961

HW α Z2 RH

Make beautiful traditional beads and edge beads or turn old beads into new moldings with the new CMT corner beading bits with bearing. Featuring carbide-tipped cutting edges and orange PTFE non-stick coating, these bits provide excellent results on corner beads. Run the bead twice to form a complete corner bead.




Drawings are 1:1 scale

R mm	D mm	I1 mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
3,2	22,2	6,50	15	57,7	**761.032.11**	**861.032.11**	**961.032.11**			990.423.00	791.003.00	990.058.00
3,2	22,2	6,50	15	64				**961.532.11**	**861.532.11**	990.423.00	791.003.00	990.058.00
4,75	25,4	9,68	18,6	61,2	**761.048.11**	**861.048.11**	**961.048.11**			990.423.00	791.003.00	990.058.00
4,75	25,4	9,68	18,6	67,6				**961.548.11**	**861.548.11**	990.423.00	791.003.00	990.058.00
6,35	28,6	12,86	22,2	64,8	**761.064.11**	**861.064.11**	**961.064.11**			990.423.00	791.003.00	990.058.00
6,35	28,6	12,86	22,2	71,7				**961.564.11**	**861.564.11**	990.423.00	791.003.00	990.058.00

Spare parts **991.057.00** 3/32" hex key


www.dahm.no



7/862

HW Z2 RH

The edge-fluting bearing guided bits are quick to set up and can be used for curved screens, small radius grooves, doors etc. No side fence is required. Use in a handheld or table-mounted router.




Drawings are 1:1 scale



For Top bearing version: use bearing 791.010.00 and stop collar 541.001.00 (optional)

R mm	D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	Spare parts			
3,2	19,05	6,4	57	**762.032.11**	**862.032.11**	990.423.00	791.003.00	990.058.00	991.057.00
4	20,7	8	57	**762.040.11**	**862.040.11**	990.423.00	791.003.00	990.058.00	991.057.00
5	22,7	10	57	**762.050.11**	**862.050.11**	990.423.00	791.003.00	990.058.00	991.057.00

CMT Moulding System



8/956.852


HW Z2 RH

If the standard selection of molding and mill work you find in today's lumber shops isn't satisfactory to your woodworking tastes, then look to CMT's molding system instead. With these bits, you can make dozens of elaborate profiles by combining two or more passes. Avoid the average and create your own mouldings. Some initial suggestions are illustrated below.


SAFETY TIPS: use these bits with a fence.
The profiles shown below are milled from heavy stock then refined to the desired shape.



8/956.851




Drawings are 1:1 scale



Chair rail 4 passes | Panel molding 3 passes | Base cap 3 passes | Stop 2 passes | Shoe 1 pass

Profile	D mm	I mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
A	31,7	23	61,1	**956.852.11**	**856.852.11**
B	31,7	19	57,2	**956.851.11**	**856.851.11**

www.dahm.no





8/956.8


HW | α | Z2 | RH

Create endless profiles with CMT multiprofile bits. Simply adjust the height of the bit to create classic profiles in one single pass, or make more complex decorative effects in multiple passes. The bits super-strength steel body can withstand long-lasting cutting operations, and the micrograin carbide tips remain sharp longer for superior performance. In addition these bits feature non-stick PTFE coating and anti-kickback design. To be used on tables equipped with a fence.

Safety tips: to make small moulding as shown below, cut the profile from very wide stock. Remove the excess material and work on the bigger piece to give you easier control. Keep hands far from the bit when working.







Drawings are 1:1 scale

Profile	D mm	I mm	L mm			ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
A	55,6	47	96,4			**956.802.11**	**856.802.11**
B	38,1	28	77,5			**956.801.11**	**856.801.11**

Spare parts

990.423.00	791.003.00	990.058.00	991.057.00
990.423.00	791.003.00	990.058.00	991.057.00

www.dahm.no

Why waste time searching for a particular style of frame moulding when you can just as quickly and easily make your own. With the wide range of decorative possibilities offered by CMT moulding bits, you can always create the edge profile you want, anywhere you want and any time you want. These CMT bits are made to last a lifetime - carbide-tipped cutters and solid bar stock steel shanks can withstand serious use and the baked-on non-stick PTFE coating makes sure you continuously get clean, smooth-running cuts.
Our anti-kickback feature helps guarantee you work more safely when using these wide profile bits.


SHOP TIPS: multiple pass operations require advance planning. To avoid making a mistake that could render it impossible to finish the job, carefully consider the entire cutting sequence before you begin.

SAFETY TIPS: all large diameter bits such as these should be used with caution and on router tables equipped with a fence. For best results, 1,7 KW (2-1/4 HP) routers are recommended. Routers as low-powered as 1,1 KW (1-1/2 HP) can be used if limited to shorter, shallower runs. When possible, reduce the RPMs of the router for operations requiring the use of these bits.


HW | α | Z2 | RH

Drawings are 1:1 scale


8/955.901



8/955.902



8/956.501




D mm	I mm	L mm			ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
23,8	35	83,8			**955.901.11**	**855.901.11**	990.423.00	791.003.00	990.058.00	991.057.00
27	41	90,2			**955.902.11**	**855.902.11**	990.423.00	791.003.00	990.058.00	991.057.00
47,5	28,5	77,4			**956.501.11**	**856.501.11**	990.423.00	791.003.00	990.058.00	991.057.00

www.dahm.no

Moulding Bits

CMT ORANGE TOOLS




8/967.5B

HW α Z2 RH


CMT's new moulding bits allow you to shape elegant moldings with your table saw and router. Unlike any commercially available crown mouldings, mouldings made with these bits are easy to install and create a finished appearance. After shaping the cove, you can use special router bits with inverted profiles to create different edges and complete the molding.

Drawings are 1:1 scale



R mm	D mm	I mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
4	39,05	11,5	57	**967.001.11B**	**967.501.11B**	**867.501.11B**	791.011.00	541.002.00	990.005.00	991.056.00
4	54	11,5	65,9		**967.502.11B**	**867.502.11B**	791.011.00	541.002.00	990.005.00	991.056.00
6,35	60,5	17,3	71,7		**967.503.11B**	**867.503.11B**	791.011.00	541.002.00	990.005.00	991.056.00


Moulding Bits



8/967.6B

HW α Z2 RH


CMT's moulding bits allow you to shape elegant mouldings with your table saw and router. Unlike any commercially available crown mouldings, mouldings made with these bits are easy to install and create a finished appearance. After shaping the cove, you can use special router bits with inverted profiles to create different edges and complete the molding.



Drawings are 1:1 scale

R mm	D mm	I mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
6,35	38	12,5	57	**967.101.11B**	**967.601.11B**	**867.601.11B**	791.011.00	541.002.00	990.005.00	991.056.00
8	35	13,2	57,7	**967.102.11B**	**967.602.11B**	**867.602.11B**	791.011.00	541.002.00	990.005.00	991.056.00
9,5	38	14,5	59	**967.103.11B**	**967.603.11B**	**867.603.11B**	791.011.00	541.002.00	990.005.00	991.056.00

www.dahm.no





855/955

HW Z2 RH


Why interrupt the subtle linearity of an all-wood drawer front or cabinet door with a metal knob or handle? Use a CMT finger pull bit and make a harmonious wooden handle. Choose your preference - a template profile made directly in the wood or a European-style hardwood pull as illustrated below.









Drawings are 1:1 scale








D mm	d mm	T1 mm	I mm	R mm	R1 mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
19,05	9,5	14	19,05	4,76	2,4	57,2	**955.102.11**		**855.602.11**
38,1	17	18	20,7	6	1,8	55,5	**955.103.11**		
38,1	17	18	20,7	6	1,8	61,8			**855.603.11**
47,6	24	22	28,5	6,35	3,2	66,6		**955.601.11**	**855.601.11**


Window Sill & Finger Bits




HW Z2 RH

8/955.804/805 - 8/955.804B/805B

These profiles were originally intended for shaping the edges of window sills. Now these bits are also used for creating finger pulls on the edges of doors and drawers. These bits are available with top bearings for curved template work or without bearings for straight cuts against a fence.
Recommended for router table use only.





Drawings are 1:1 scale

Spare parts




R1 mm	R mm	D mm	I mm	L mm		ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm				
5,5	9,5	31,7	25,4	73		**955.804.11**	**855.804.11**				
9,5	12,7	38,1	35	85,8		**955.805.11**	**855.805.11**				
With Top Bearing											
5,5	9,5	31,7	25,4	73		**955.804.11B**		791.015.00	541.005.00	990.005.00	991.056.00
5,5	9,5	31,7	25,4	73			**855.804.11B**	791.015.00	541.002.00	990.005.00	991.056.00
9,5	12,7	38,1	35	85,8		**955.805.11B**		791.020.00	541.005.00	990.005.00	991.056.00
9,5	12,7	38,1	35	85,8			**855.805.11B**	791.020.00	541.002.00	990.005.00	991.056.00

www.dahm.no

Table Edge & Hand Rail Bits

CMT ORANGE TOOLS

HW | α | Z2 | RH




8/956.701


Turn a small investment into a big return with these CMT bits! They give you well-proportioned smooth curves for elegant eye-catching work on your tables. CMT hand rail bits feature 30° bevel edge and 3,2mm bead that allow you to make beautiful and functional hand rails. Add a touch of class to your architectural settings!

SAFETY TIPS: these profile bits remove large amounts of stock and make consistent quantities of dust. We recommend using a vacuum to keep the work area safe.

8/956.601




8/956.702





Profile	D mm	I mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
A	63,5	19	67,9	**956.601.11**	**856.601.11**	990.423.00	791.003.00	990.058.00	991.057.00
B	35	38	87	**956.701.11**	**856.701.11**	990.423.00	791.003.00	990.058.00	991.057.00
C	31,7	38,1	87	**956.702.11**	**856.702.11**	990.423.00	791.018.00	990.058.00	991.057.00

Vertical Raised Panel Bits




8/990.6

HW | α | Z2 | RH

Mill raised panel doors and drawer fronts easily and economically just by putting a CMT vertical raised panel bit in your router* and a sturdy 90° fence on your router table. Meticulously studied, designed and crafted using the highest technology available, these bits are perfected down to the smallest detail. And just like any true craftsman, we are as proud of our work as you are of yours. Choose any of the three vertical profilee designs for the style you want.

* Recommended for use on routers with a minimum speed of 1,7 KW (2-1/4 HP). Routers as low-powered as 1,1 KW (1-1/2 HP) can be used but we suggest limiting their use to shorter, shallower runs.

SAFETY TIPS: the template must be at least 150mm and clamps should be used whenever possible. Three to five passes are recommended to safely and accurately obtain the profile you desire.



Profile	D mm	I mm	T1 mm	L mm				ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
A	38	38	15 ÷ 18	76,2				**990.601.11**	**890.601.11**
B	38	38	15 ÷ 18	76,2				**990.602.11**	**890.602.11**
C	38	38	15 ÷ 18	76,2				**990.603.11**	**890.603.11**


www.dahm.no

CMT ORANGE TOOLS


8/990

HW | α | Z2 | RH


These bits have a back-cutter which allows milling of both the front and back of the panel in the same cut. An additional 31,7mm diameter bearing promotes safety by allowing you to take two shallow passes (only for Ø89mm).










Drawings are 1:1 scale










First pass with Ø31,7mm bearing (for Ø89mm only)




Second pass with Ø16mm bearing

Profile	D mm	T1 mm	L mm		ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
								16mm	31,7mm	
A	89	19 - 20,6	78,1		**990.524.11**	**890.524.11**	822.007.11	791.025.00	791.033.00	990.020.00
B	89	19 - 25,4	78,1		**990.527.11**	**890.527.11**	822.007.11	791.025.00	791.033.00	990.020.00
A1	63,5	11,1 - 17,5	70		**990.534.11**	**890.534.11**	822.010.11	791.025.00		990.020.00
B1	63,5	11,1 - 17,5	70		**990.537.11**	**890.537.11**	822.010.11	791.025.00		990.020.00

Spare parts

541.515.00 0,1mm spacer
541.516.00 0,3mm spacer
541.518.00 1,0mm spacer
990.407.00 Shield conical

www.dahm.no




HW | Z2 | RH

8/990.5

We offer you the traditional approach to panel construction with the CMT raised panel bit. Make classic raised panel doors as shown in the profiles below.
These raised panel bits have carbide-faced cutting edges and are equipped with our anti-kickback design and orange non-stick coating to further increase your safety when working with larger diameter bits.

Safety Tips: Horizontally employed bits should be used at a lower speed, between 10,000 and 12,000 RPMs.
Three to five passes are recommended to safely and accurately obtain the profile you desire.
To be used on jigs with at least 1,7 KW (2-1/4 HP).




Drawings are 1:1 scale

Profile	D mm	I mm	L mm	T1 mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts			
A	82,5	15	63,8	15 ÷ 18		**990.501.11**	**890.501.11**	990.423.00	791.003.00	990.058.00	991.057.00
B	82,5	15	63,8	15 ÷ 18		**990.502.11**	**890.502.11**	990.423.00	791.003.00	990.058.00	991.057.00
C	82,5	15	64,6	15 ÷ 18		**990.503.11**	**890.503.11**	990.423.00	791.003.00	990.058.00	991.057.00
A2	89	15	64,6	18 ÷ 20		**990.504.11**	**890.504.11**	990.423.00	791.003.00	990.058.00	991.057.00
B2	89	15	64,6	18 ÷ 20		**990.505.11**	**890.505.11**	990.423.00	791.003.00	990.058.00	991.057.00
C2	89	15	64,6	18 ÷ 20		**990.506.11**	**890.506.11**	990.423.00	791.003.00	990.058.00	991.057.00
D	89	15	64,6	15 ÷ 20		**990.507.11**	**890.507.11**	990.423.00	791.003.00	990.058.00	991.057.00
A3	47,6	9,5	58,1	12,7 ÷ 15	**990.011.11**			990.423.00	791.003.00	990.058.00	991.057.00
B3	47,6	9,5	58,1	12,7 ÷ 15	**990.012.11**		**890.512.11**	990.423.00	791.003.00	990.058.00	991.057.00

www.dahm.no


Junior Ogee Rail & Stile Set



8/991.517

HW | Z2 | RH

These bits are designed for those special projects that require a smaller panel door. Use these bits with stock from 11,1mm to 17,4mm thick, and build doors as small as 70mm.




Drawing is 1:1 scale

D mm	T1 mm	L mm		ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts 4mm	6mm		
31,75	11 ÷ 17,4	67		**991.517.11**	**891.517.11**	822.008.11	822.009.11	791.025.00	990.020.00

Spare parts

541.515.00	0,1mm spacer
541.516.00	0,3mm spacer
541.518.00	1,0mm spacer


Rail & Stile Set



8/991.512

HW | Z2 | RH

Designed for fine furniture construction, these bits mill a delicate 4,75mm thumbnail profile in stock from 15,8mm to 20,6mm.




Drawing is 1:1 scale


D mm	T1 mm	R mm	L mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm	Spare parts 6,35mm	10,8mm		
28,7	16 ÷ 22	4,8	79,2	**991.012.11**	**891.512.11**	822.011.11	822.012.11	791.025.00	990.020.00

Spare parts

541.515.00	0,1mm spacer
541.516.00	0,3mm spacer
541.518.00	1,0mm spacer

www.dahm.no






8/991.5


HW · Z2 · RH

A well-constructed door will bear the mark of a perfect joint-clean, exact and well-crafted for strength. For this project, the CMT male-female rail and stile sets are the perfect pair. Made to our specifications they match exactly; not simply approximated like standard reversible cutters.
Choose the style of CMT rail and stile set that best suits your needs and create smooth, perfect joints in hard and soft woods with accuracy and speed. Perfect for working in stock from 18mm to 22mm. See chart and illustrations below for profile options available.

Drawings are 1:1 scale




Profile	D mm	L mm	T1 mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		0,1mm	0,3mm	0,9mm	
A	44,4	71	18 ÷ 22	**991.001.11**	**991.501.11**	**891.501.11**	822.003.11	791.012.00	541.515.00	514.516.00	990.407.00	990.020.00
B	44,4	71	18 ÷ 22		**991.502.11**	**891.502.11**	822.003.11	791.012.00	541.515.00	541.516.00	990.407.00	990.020.00
C	44,4	71	18 ÷ 22		**991.503.11**	**891.503.11**	822.003.11	791.012.00	541.515.00	541.516.00	990.407.00	990.020.00



8/991.521

HW · Z2 · RH

The most innovative bit for the construction of furniture doors and drawers. The new CMT One-Piece Rail and Stile Bit represents the union of two cutters in one bit. By simply adjusting the height of the bit, you can cut two perfectly joining profiles with no wasted time or effort moving the fence or changing the bit. Save time money by investing in a single CMT bit.
For working in stock from 18mm to 22,2mm.



Profile	D mm	L mm	T1 mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts						
A	50,87	96	18 ÷ 22		**891.521.11**	791.027.00	541.002.00	990.005.00	991.056.00	541.551.00	990.010.00	991.064.00
A	50,87	96	18 ÷ 22	**991.521.11**		791.027.00	541.005.00	990.005.00	991.056.00	541.551.00	990.010.00	991.064.00

www.cmtutensili.com
www.dahm.no

In our step-by-step example of panel door construction, we used the following:
- CMT Rail & Stile set (item #891.502.11)
- CMT Reverse Glue Joint (item #855.501.11)
- pre-cut to length stiles - 19mm thick x 57mm wide
- pre-cut to length rails - 19mm thick x 57mm wide
- panel - 16mm thick
- scrap stock

The CMT Rail & Stile set was designed ideally for the construction of panel doors from 19mm thick stock, however any variation of size up to 22mm thick can be used. Remember to adjust your measurements and cutting depths according to the wood thickness you use.




ILLUSTRATION A






ILLUSTRATION B



MILLING THE RAILS AND STILES

First make trial cuts of the cope profile (rail) and the stick profile (stile) in scrap stock and check the accuracy of the joint. This is extremely important when working at maximum thickness (22mm). Make sure your stock is flat and cut straight with square edges. Using the CMT Stile Bit shown in illustration A, place the stock front face-down on the router table and mill the stick profile in the stile and rail pieces. To mill the rails, use the CMT Rail Bit shown in illustration A, position the rails face-down on the router table and mill the cope profile on the ends. If you are milling cope and stick profiles before cutting the rails and stiles to length, be sure to make the proper calculations before cutting the rails. The stiles are the same length as the door. The rails must be calculated by the following equation (CMT standard tenon length is 22mm):
(total door width - sum of stile widths) + sum of 2 tenons = total rail length
therefore, using our example measurements listed above, for a 300mm cabinet door:
300mm - 114mm + 22mm = 208mm

ILLUSTRATION C




GLUEING UP PANELS

If the panel requires a width greater than the width of your stock, you will need to edge glue stock for the central floating panel. This is accomplished by simply using the CMT Reverse Glue Joint bit. For making a two panel glue joint, place the first panel front face-down on the router table and accurately centre the wood to the bit. Adjust the bit according to the thickness of the wood you are cutting by lining up the cut edge of the wood to the centre point of the bit as illustrated in illustration B and mill the cut edge of the wood. Place the second panel front face up and repeat the milling process. This assures you will have the best side of your stock as a front face. If a third panel is required, mill one cut edge of the piece as instructed above, turn the piece over and run the other edge. Assemble the reverse cut pairs together for beautiful, strong joints that match up perfectly.

MILLING THE FLOATING PANEL

Make trial cuts in scrap stock to create a tongue that fits snugly into the groove in the stile without forcing it. To cut your panel to size be sure to make the proper calculations, taking into account the length of the tongue. The CMT Raised Panel Bit in our example has a standard tongue length of 8mm (The New CMT Raised Panel Bit profile has a 9,5mm tongue).
Use the following equation:
(Total door length - Sum of Stile widths) + Sum of 2 Tongues = Overall Panel Length
Therefore, using our example, measurements listed above for a 600mm long cabinet door: (600 - 114) + 16mm = 502mm
And accordingly:
(Total door width - Sum of Stile widths) + Sum of 2 Tongues = Overall Panel Width.
Once the panel has been cut to proper dimensions, position the panel front face side down on the router table tongue as shown in illustration C and use the CMT Raised Panel Bit to mill the tongue. ATTENTION: this bit is capable of removing large amounts of stock. To safely and effectively produce the profile you want, we suggest making several shallow passes. It can be dangerous to try to mill the entire profile in a single run.



www.dahm.no


8/970

HW | Z2 | RH

These bits can be used for decorative work on solid wood panels and MDF materials. Use them in one pass or in combination with CMT's MDF panel bits for complex and intricate profiles. A simple approach for an elegant appearance.

Featuring large cutting diameters and available in the most popular profiles, these panel bits guarantee excellent performance.

PANEL BITS



870.501.11
970.501.11




870.502.11
970.502.11




870.503.11
970.503.11


STILE BITS




870.101.11
970.101.11




870.504.11
970.504.11




870.501.11
970.501.11




870.502.11
970.502.11




870.503.11
970.503.11



970.505.11



8/970.503.11
+
8/970.101.11




8/970.501.11
+
8/970.504.11

D mm	d mm	I mm	R mm	A	L mm		ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
25	6	8	12		39,8		**970.101.11**		**870.101.11**
50	16	14	12		52,1			**970.501.11**	**870.501.11**
50	16	17		10°	55,1			**970.502.11**	**870.502.11**
45	34	13,5	3,2 - 6,4	3°	51,6			**970.503.11**	**870.503.11**
35	12,5	9,5	3,2		47,6			**970.504.11**	**870.504.11**
new 35	13,3	8	3,2		46			**970.505.11**	

www.dahm.no


Solid Surface Rounding Over Bits



7/8/938 - 8/980.5

HW | α | Z2 | RH

Use these bits to create a traditional roundover edge on solid surface countertops. Equipped with a non-marring Delrin® bearing to protect the finished edges. For use on hand-held portable routers.




Drawings are 1:1 scale

R mm	D mm	I mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
new 1	14,7	10	51		**838.147.11**	**938.147.11**			990.422.00	791.044.00	990.058.00
2	16,7	12,7	52,5	**738.167.11**		**938.167.11**			990.422.00	791.044.00	990.058.00
3	18,7	12,7	54	**738.187.11**		**938.187.11**			990.422.00	791.044.00	990.058.00
3,2	19,05	12,7	59,5				**980.501.11**	**880.501.11**	990.422.00	791.044.00	990.058.00
6,35	25,4	12,7	59,5				**980.502.11**	**880.502.11**	990.422.00	791.044.00	990.058.00
new 8	28,7	15	62,5				**980.505.11**	**880.505.11**	990.422.00	791.044.00	990.058.00
9,5	31,75	14	61				**980.503.11**	**880.503.11**	990.422.00	791.044.00	990.058.00
12,7	38,1	19,05	66				**980.504.11**	**880.504.11**	990.422.00	791.044.00	990.058.00

Spare parts **991.057.00** 3/32" hex key


Solid Surface Decorative Edge Profile Bits



8/980.521

HW | α | Z2 | RH

Create elegant countertops with flawless results. Features a non-marring Delrin® bearing to protect the finished edges. For use on hand-held portable routers.




Drawings are 1:1 scale

D mm	I mm	R mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
66,7	41,3	8	89,8	**980.521.11**	**880.521.11**	791.046.00	990.058.00	991.057.00

www.dahm.no

Solid Surface Rounding Over Bowl Bits




8/966.601/602
8/980.541

HW α Z2 RH

These bits roundover and trim the countertop edges after the bowl is mounted. Can be used with the CMT 880.551.11 bevel cutter for a flush cut-out between the countertop and installed undermount bowl. For use on hand-held portable routers. Features a non-marring Delrin® bearing to protect the finished edges.


The special angled Delrin® sleeve on the bearing of the CMT bevel cutter lets you work without leaving marks on the workpiece. Trims and shapes all wood and wood materials. Perfect for kitchen and bathroom countertop work.


880.541.11
980.541.11



Drawings are 1:1 scale

966.601.11
866.601.11






966.602.11
866.602.11

A	D mm	T1 mm	I mm	R mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
15°	50,8	19	25,4	12,7	74,9	**966.601.11**	**866.601.11**	791.041.00	990.058.00	991.057.00
15°	50,8	25,4	31,75	12,7	81,3	**966.602.11**	**866.602.11**	791.041.00	990.058.00	991.057.00
18°	54	19	25,4	12,7	78,1	**980.541.11**	**880.541.11**	791.041.00	990.058.00	991.057.00


Solid Surface Rounding Over Bowl Bit (ogee profile)



8/980.542

HW α Z2 RH

These bits roundover and trim the countertop edges after the bowl is mounted. Can be used with the CMT 880.551.11 bevel cutter for a flush cut-out between the countertop and installed undermount bowl. For use on hand-held portable routers. Features a non-marring Delrin® bearing to protect the finished edges.




Drawing is 1:1 scale

A	D mm	T1 mm	I mm	R mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
15°	54	19	25,4	6,35-12,7	77,6	**980.542.11**	**880.542.11**	791.041.00	990.058.00	991.057.00

www.dahm.no

Solid Surface Bevel Bowl Bits




8/966.501 - 8/980.551


HW | α | Z2 | RH

These bits are designed for undermount applications joining the countertops and sink bowls with a 10 (degree) beveled edge. Can be used with the 880.541.11 and 880.542.11 for complete undermount applications. For use on hand-held routers. Features a non-marring Delrin® bearing to protect the finished edges.

Special angled Delrin® sleeve on the bearing of the CMT bevel cutter lets you work without leaving marks on the workpiece. Trims and shapes all wood and wood materials. Perfect for kitchen and bathroom counter top work.



866.501.11
966.501.11




880.551.11
980.551.11

Drawings are 1:1 scale

A	D mm	I mm	L mm		ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
15°	31,7	22,2	72		**966.501.11**	**866.501.11**	791.041.00	990.058.00	991.057.00
10°	28,5	25,4	77		**980.551.11**	**880.551.11**	791.041.00	990.058.00	991.057.00


Solid Surface Bevel Bit



8/981.521

HW | α | Z2 | RH

Edge profile bit designed to create a 15° bevel on solid surface countertops. Can also be used for European type topmount installation with sinks and bowls. For use on hand-held portable routers.



Drawings are 1:1 scale

D mm	d mm	I mm	A	L mm			ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
23	9,52	25,4	15°	63,5			**981.521.11**	**881.521.11**


www.dahm.no


Solid Surface Cut & Plug Repair Set

9/881.541

HW | Z2 | Z3 | RH

Special carbide-tipped bits for use on solid surface and repairing your ruined surfaces. To repair, create the plug with the plug cutter first, then use the other bit to easily make the hole. Your surfaces will look like new. To be used on hand-held routers or CNC machines.








D1 mm	D2 mm	I mm	A	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
47,6	63,5	20	15°	68,5-74	**981.541.11**	**881.541.11**


4-Wing Cut Out Slot Cutters for Solid Surfaces



8/922.033B

HW | Z4 | RH

Tools featuring specially formulated carbide-tipped cutting edges for cutting your solid surface undermount bowls. For use on hand-held portable routers. Bits feature a non-marring Delrin® bearing to protect your surfaces.



Drawing is 1:1 scale

D mm	I mm	H mm	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
92	6,35	27,3	82,5	**922.033.11B**	**822.033.11B**

Spare parts



541.553.00	791.047.00	541.002.00	991.056.00

www.dahm.no


Solid Surface No-Drip Bit




8/981.501

HW | α | Z2 | RH

This bit is designed to create “no-drip” edges on kitchen and vanity countertops. Designed for hand-held portable routers on applications where a guide bearing cannot be used. This one bit will cut both the outer and inner profiles creating a slightly raised edge, controlling spilled liquids.






Drawing is 1:1 scale

8/980.531


This bit is designed to create “no-drip” edges on kitchen and vanity countertops in a single pass. For use on hand-held portable routers. This one bit will cut both the outer and inner profiles creating a slightly raised edge that controls spilled liquids. Features a non-marring Delrin® bearing to protect the finished edges.



Drawing is 1:1 scale

D mm	d mm	I mm	I1 mm	R mm	L mm			ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
25,4		12,7	3,2	8	63,5			**981.501.11**	**881.501.11**			
25,4	19	22,2	15,87	8	77			**980.531.11**	**880.531.11**	791.046.00	990.058.00	991.057.00


Solid Surface Wavy Joint Bit




8/981.531

HW | Z2 | RH

These bits are ideal for making strong joints on any solid surface, thanks to a wider area for glue.




Drawings are 1:1 scale



D mm	I mm	R mm	L mm				ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
15,87	51,5	4,36	89				**981.531.11**	**881.531.11**

www.dahm.no


Solid Surface Drainboard Bits



8/981.511-512

HW | α | Z2 | RH


This bit is ideal for creating custom drainboard patterns in solid surface countertops.
For use on hand-held portable routers.



Drawings are 1:1 scale

D mm	I mm	R mm	L mm			ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
15,87	12,7	3,2	63,5			**981.511.11**	**881.511.11**
25,4	12,7	3,2	69,8			**981.512.11**	**881.512.11**

Solid Surface - Inlay Bits




8/980.511-512-513

HW | Z2 | RH


Add a decorative wood, plastic or metal inlay to solid surface countertops. Equipped with a non-marring Delrin® bearing to protect the finished edges. For use on hand-held portable routers.

Standard



Drawings are 1:1 scale

Optional



optional with bearing 791.045.00

optional with bearing 791.046.00

D mm	I mm	H mm	L mm				ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
22,2	6,35	4,76	77				**980.511.11**	**880.511.11**	791.044.00	990.058.00	991.057.00
22,2	12,7	4,76	90				**980.512.11**	**880.512.11**	791.044.00	990.058.00	991.057.00
22,2	19,05	4,76	90				**980.513.11**	**880.513.11**	791.044.00	990.058.00	991.057.00


www.dahm.no

Solid Surface Sink & Trim Bits with Delrin® Bearing

new


CMT ORANGE TOOLS™

HW LONG LIFE Z2 RH




8/980.57

Trim a sink cutout flush with the bowl in stages using these "over-hang" and flush trim bits in tandem. These "over-hang" bits are equipped with Delrin® bearings that are tapered to match the slope of the bowl's side. A first pass with the appropriate overhang bit cleans the cutout edge, leaving a very slight overhang at the underside of the counter. A pass with the flush-trim bit completes the operation. Equipped with special super micrograin carbide for longer life.



880.571.11
980.571.11

Drawings are 1:1 scale



880.572.11
980.572.11




D mm	I mm	A	L mm				ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts		
19,05	25,4		78				**980.571.11**	**880.571.11**	791.046.00	990.058.00	991.057.00
22	25,4	10°	78				**980.572.11**	**880.572.11**	791.048.00	990.058.00	991.057.00

Solid Surface Sink & Trim Bits with Insert Knives & Delrin® Bearing


new

INSERT CARBIDE LONG LIFE Z2 RH 2X LONGER LIFE




8/980.56

Trim a sink cutout flush with the bowl in stages using these "over-hang" and flush trim bits in tandem. These "over-hang" bits are equipped with Delrin® bearings that are tapered to match the slope of the bowl's side. A first pass with the appropriate overhang bit cleans the cutout edge, leaving a very slight overhang at the underside of the counter. A pass with the flush-trim bit completes the operation. Equipped with special super micrograin carbide insert knives for longer life.
The blades are 2 sided sharpened and can give extra new edges.



880.561.11
980.561.11

Drawings are 1:1 scale



880.562.11
980.562.11



D mm	I mm	A	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm	Spare parts					
19,05	30		83	**980.561.11**	**880.561.11**	790.300.03	990.075.00	991.061.00	791.046.00	990.058.00	991.057.00
22	30	10°	83	**980.562.11**	**880.562.11**	790.300.03	990.075.00	991.061.00	791.048.00	990.058.00	991.057.00


www.dahm.no




7/900.003

HW HWM α Z2 RH

Find a whole workshop in practical 26 piece router bit sets! With a wide selection of the most in demand tools, these sets include straight bits, flush trim bits, dovetail bits, cove bits, ogee bits and many more. You will have an endless choice to express your creativity! Ideal for master craftsmen, these sets are available from 6mm to 8mm shank diametres. See chart below for details.





Drawings are 1:1 scale


DESCRIPTION	ORDER NO. S=Ø6mm	ORDER NO. S=Ø8mm
26-Piece Router Bit Sets	**700.003.00**	**900.003.00**




7/8/900.001

HW HWM α Z2 RH

CMT's router bit sets are the perfect companions for the professional craftsman. These sets offer a selection of organized and ready-to-use straight and profile bits; added value for any woodworker!
Each bit is made of Fatigue Proof® steel, micrograin carbide and is coated with orange non-stick PTFE.
The bits can be safely stored in their hardwood snap lock cases.





Drawings are 1:1 scale

DESCRIPTION	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm
15-Piece Router Bit Sets	**700.001.00**	**800.001.00**	**900.001.00**

www.dahm.no


8-Piece Dovetail & Straight Bit Sets



800.500/501

HW HWM Z2 RH

Perfect for the craftsman with a creative flair, these sets contain the most frequently used bits for boxes, creative joinery and a wide range of other projects.
Safely packaged in a hardwood box to have the bits within reach.
The bits suit most popular jigs.
IDEAL FOR INCRA & JOINTECH JIGS.



Drawings are 1:1 scale

DESCRIPTION	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø12,7mm
8-Piece Dovetail & Straight Bit Sets	**800.500.11**	**800.501.11**

13-Piece Dovetail & Straight Bit Sets




800.519

HW HWM Z2 RH

Perfect for the craftsman with a creative flair, these sets contain the most frequently used bits for making boxes, creative joinery and a wide range of other projects. Safely packaged in a hardwood box to have the bits within reach. The bits suit most popular jigs.
IDEAL FOR D4 LEIGH JIGS.

Drawings are 1:1 scale



DESCRIPTION	ORDER NO. S=Ø6,35-12,7mm
13-Piece Dovetail & Straight Bit Sets	**800.519.11**

www.dahm.no

12-Piece Router Bit Set with Wooden Case




800.503

HW HWM Z2 RH


Containing 12 of CMT's most frequently used 6,35mm shank router bits featuring the finest steel and carbide, plus CMT's baked-on orange PTFE non-stick coating, this compact Italian hardwood case is beautiful and convenient for your woodworking needs. You will always have exactly what you need within reach.

Drawings are 1:1 scale



DESCRIPTION	ORDER NO. S=Ø6,35mm
12-Piece Router Bit Set with Wooden Case	**800.503.11**

13-Piece Router Bit Set with Wooden Case




800.505

HW HWM Z2 RH

Containing 13 of CMT's most frequently used 12,7mm shank router bits featuring the finest steel and carbide, plus CMT's baked-on orange PTFE non-stick coating.
The compact Italian hardwood case is beautiful and convenient for your woodworking needs. You will always have exactly what you need within reach.

Drawings are 1:1 scale



DESCRIPTION	ORDER NO. S=Ø12,7mm
13-Piece Router Bit Set with Wooden Case	**800.505.11**


www.dahm.no

6-Piece Profile Bit Set with Wooden Case



800.504

HW | α | Z2 | RH



Drawings are 1:1 scale

Containing 6 of CMT's most frequently used 12,7mm shank router bits, this compact Italian hardwood case is beautiful and convenient for your woodworking needs. All the bits contained feature the finest steel and carbide, plus CMT's baked-on orange PTFE non-stick coating.

DESCRIPTION	ORDER NO. S=Ø12,7mm
6-Piece Rrofile Bit Set with Wooden Case	800.504.11

Entry & Interior Door Router Bit Set




8/900.527


HW | α | Z2 | RH

This CMT three-piece router bit set simplifies door construction, making it easy as 1-2-3! In fact this is a multifunctional set for door and furniture makers, building entry or passage doors and any furniture tenons. The included tenon cutter produces a beefy 27mm long tenon. Coupled with the cope cutter, you can produce long and strong tenons with minimum setup. As an extra bonus, the tenon cutter can be used for furniture making requiring any tenon from 4,7mm to 16mm thick.


Entry & interior door construction
Easy as 1, 2, 3!



Step 1. Cut the tenon into the rails




Step 2. Cut the groove and door profile in pieces.



Step 3. Undercut the tenons to cope the ends of the rails.








DESCRIPTION	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
3-Piece Entry & Interior Door Router Bit Set	900.527.11	800.527.11

www.dahm.no

2-Piece Entry Door Router Bit Set




8/955.806

HW | α | Z2 | RH

These bits allow you to create tongue-and-groove joints and produce entry and passage doors with minimal effort. The bit on the left, when used in pair with the bit 800.628.11, is great for producing long and beefy tenons, whereas the other tool makes the decorating profile.

Entry & Interior Door Construction



Application 1: cut the groove and the door profile in all pieces.


Application 2: undercut the tenon to cope the ends of the rails.

D mm	I mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
44,5-48	35-44,5	**955.806.11**	**855.806.11**


Spare parts

8-22mm	up	down		0,1mm	0,3mm	3mm	
791.005.00	822.021.11A	822.021.11B	822.022.11	541.515.00	541.516.00	541.500.00	990.020.00

Tenon Cutting Router Bits



8/900.628




8/900.627

HW | Z2 | RH

If you've struggled cutting fitting tenons, here's the perfect solution for you. CMT's tenon cutting router bit will produce perfectly fitting tenons in every board you cut, even if the boards vary slightly in thickness. Simply set the distance between the cutters using the included spacers, and you can easily cut tenons from 4,76mm (3/16") to 9,5mm (3/8") thick, up to 27mm (1-1/16") long. This simple-to-use router bit takes the mystery out of achieving the excellent tenon-to-mortise fit required for high quality joinery.

Maximum speed
MAX RPM 12.000



Drawing is 1:1 scale

8-900.627

T1	Spacers (mm) 6,35mm	3,2mm	1,6mm
4,76mm	1	0	0
6,35mm	1	0	1
8mm	1	1	0
9,5mm	1	1	1

D mm	I mm	T1 mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
75	34,9	4,76-9,5	**900.627.11**	
75	34,9	4,76-9,5		**800.627.11**
75	44,5	9,5-15,8	**900.628.11**	
75	44,5	9,5-15,8		**800.628.11**

Spare parts

		0,1mm	0,3mm	1,6mm	3,2mm	6,2mm	
924.134.00	822.020.11	541.513.00	541.520.00	541.521.00	541.522.00	541.523.00	990.022.00
824.134.00	822.020.11	541.513.00	541.520.00	541.521.00	541.522.00	541.523.00	990.022.00
924.135.00	822.020.11	541.513.00	541.520.00	541.521.00	541.522.00	541.523.00	990.022.00
824.135.00	822.020.11	541.513.00	541.520.00	541.521.00	541.522.00	541.523.00	990.022.00

www.dahm.no




8/923.001

HW Z3 RH

Create slots, grooves and rabbets on all materials using the CMT slot cutter sets. Ideal for biscuit and tongue and groove joints. **These sets include 4 different bearings to allow a cutting depth of 7,95mm, 9,5mm, 12,8mm and 14,3mm.** Please refer to the chart below for applications and the correct cutter combinations.

SAFETY TIPS: never use the slot cutter sets without shims between cutters, whose distance can vary from 1mm to 1,7mm. Shims can also be positioned between the ball bearings and the cutters.

Assembly Illustration



Spare parts

H mm		ORDER NO.
14,3	8-19	791.033.00
12,7	8-22	791.005.00
9,5	8-28,5	791.030.00
8	8-31,5	791.033.00

DESCRIPTION	ORDER NO. S=Ø8mm	Spare parts 2mm	3mm	4mm	5mm	6mm				
Set	**923.001.11**	822.320.11	823.330.11	823.340.11	823.350.11	822.360.11	924.081.10	924.082.10	924.080.10	924.083.10

DESCRIPTION	ORDER NO. S=Ø12,7mm	Spare parts 1,6mm	3,2mm	4mm	4,8mm	6,4mm				
Set	**823.001.11**	822.316.11	823.332.11	823.340.11	822.348.11	822.364.11	824.121.10	824.122.10	824.127.10	824.128.10


5-Piece Straight Bit Set & Profile Bit Set

Our beautiful sets are the perfect companion for the professional craftsman. We offer three 5-piece sets with a selection of straight bits and the most popular profile router bits. These tools feature Fatigue Proof® steel, micrograin carbide and orange PTFE non-stick coating.
Safely stored in a solid plastic box to fit in your display cabinet.

HW HWM Z2 RH

8/900.005.01






DESCRIPTION	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm
5-Piece Straight Bit Set	**800.005.01**	**900.005.01**

7/900.005.03





DESCRIPTION	ORDER NO. S=Ø6mm		ORDER NO. S=Ø8mm
5-Piece Profile Bit Set	**700.005.03**		**900.005.03**

www.dahm.no

Router Bit Set with Insert Knives


CMT ORANGE TOOLS™



600.005.01

INSERT CARBIDE | Z1 | Z2 | RH | 2X LONGER LIFE

This set is the perfect companion for the professional craftsman. We offer the 5 most popular bits with knives and all necessary spare knives and Torx keys. They are perfect for working on all materials such as solid wood, wood composites, plastic and laminated materials. For use with a hand held or CNC router.



DESCRIPTION	ORDER NO. S=Ø8mm
Router Bit Set with Insert Knives	**600.005.01**

10 spare knives and 2 torx keys included


Set contains	D mm	l mm	Spare knives		ORDER NO. S=Ø8mm
Straight Router Bit with Knife	8	20	790.200.01 - 20 x 4,1 x 1,1mm		**651.080.11**
Straight Router Bit with Knife	10	30	790.300.01 - 30 x 5,5 x 1,1mm		**651.100.11**
Straight Router Bit with Knife	12	30	790.300.01 - 30 x 5,5 x 1,1mm		**651.120.11**
Straight Router Bit with Knife	14	30	790.300.01 - 30 x 5,5 x 1,1mm		**651.140.11**
Flush Trim Bit with Knife	19	30	790.300.00 - 30 x 12 x 1,5mm	791.007.00	**657.191.11**

5-Piece Spiral Bit Sets





191 Upcut




192 Downcut




191/192

HWM | Z2 | RH

CMT is proud to offer you these new sets of high quality solid tungsten carbide upcut and downcut spiral bits in the most popular diametres.
The new formulated super micrograin composition guarantees extremely sharp long-lasting cutting edges, whereas the spiral layout allows for a more efficient chip ejection. In addition, these bits stay cooler during work and are suitable for CMT's new precision machines.
Recommended for use on soft and hardwood, plywood, laminates, MDF and plastic materials.
To be used on handheld routers and CNC machines.



Drawings are 1:1 scale



DESCRIPTION		ORDER NO. S=Ø8mm	ORDER NO. S=Ø6,35-12,7mm
5-Piece upcut spiral bit sets	(Ø4 - 6 - 8 - 10 - 12mm)	**191.000.01**	
5-Piece Downcut Spiral Bit Sets	(Ø4 - 6 - 8 - 10 - 12mm)	**192.000.01**	
5-Piece upcut spiral bit sets	(Ø4,76 - 6,35 - 8 - 9,5 - 12,7mm)		**191.000.02**
5-Piece Downcut Spiral Bit Sets	(Ø4,76 - 6,35 - 8 - 9,5 - 12,7mm)		**192.000.02**

www.dahm.no

CMT's Complete Kitchen Set




HW | α | Z2 | RH


These CMT's sets aren't only a random selection of odds and ends packaged in a nice elegant box, but they are also professional kits for drawer and door makers. 3 sets to choose from, 5 different bits to suit your needs: a raised panel bit, rail and stile bits, a glue joint and a drawer lock bit. Please refer to the illustrations below for complete profile options.

Drawings are 1:1 scale


8/900.509.11



8/900.510.11



8/900.511.11




DESCRIPTION		ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
CMT's Complete Kitchen Set - Profile A	(5 HW pcs.)	**900.509.11**	**800.509.11**
CMT's Complete Kitchen Set - Profile B	(5 HW pcs.)	**900.510.11**	**800.510.11**
CMT's Complete Kitchen Set - Profile C	(5 HW pcs.)	**900.511.11**	**800.511.11**

Panalign Strips

Beautiful panel doors can be ruined by a poorly-aligned panel. Next time, slip panalign strips into the rails to keep panels perfectly centred while allowing for expansion. Unlike carpet foam, which eventually loses elasticity and ceases to work, the rubber in panalign strips is specially designed to spring back indefinitely. The rectangular shape makes the strips easy to handle. Typical doors require 4 to 8 strips each.

PNL



DESCRIPTION	DIMENSION mm	Q.TY	ORDER NO.
Panalign Strips	27x7x7mm	200	**PNL-001**

www.dahm.no


Kitchen Sets



HW α Z2 RH

Our 3 piece kitchen set includes a couple of rail and stile bits and a raised panel bit. Choose among 4 possible profiles to make panel doors easily economically.
Each bit is made from bar stock steel and the highest quality tungsten carbide, along with the trademark orange non-stick PTFE coating. Also, they all come with their protective hardwood case: perfect for keeping your bits safe, organized and within reach.

Drawings are 1:1 scale




DESCRIPTION	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
Kitchen Set - Profile A+A_2	900.513.11	800.513.11
Kitchen Set - Profile B+B_2	900.512.11	800.512.11
Kitchen Set - Profile C+C_2	900.514.11	800.514.11
Kitchen Set - Profile D+B	900.516.11	800.516.11

The Raised Panel Sets with Backcutter




8/900.518 - 8/900.522

HW α Z2 RH



8/900.517 - 8/900.521

Drawings are 1:1 scale



CMT's junior raised panel sets add intricate detail on a whole new scale! You will make frame and panel details as small as 70mm square in material as thin as 11mm. Delicate panel doors are only the beginning – use these bits with templates to add interesting arches to your work. The sets include a choice of a cove or an ogee raised panel bit and an ogee rail & stile pair. Packaged in beautiful hardwood cases.

DESCRIPTION			ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
Junior Raised Panel Sets - Profile A	(3 HW pcs.)	Ø63,5mm.	900.518.11	800.518.11
Junior Raised Panel Sets - Profile B	(3 HW pcs.)	Ø63,5mm.	900.522.11	800.522.11
Raised Panel Sets - Profile C	(3 HW pcs.)	Ø89mm.	900.517.11	800.517.11
Raised Panel Sets - Profile D	(3 HW pcs.)	Ø89mm.	900.521.11	800.521.11

www.dahm.no

The Cabinetmaking Sets



800.515 - 800.520

HW Z2 RH

Available with raised panel bits in two different profiles, these sets feature six router bits for making arched raised panel doors and professional drawer fronts.
These sets include:


OGEE RAIL & STILE BITS: these two perfectly matched tools will eliminate the frustration of setting up reversible cutters. The stile bits also feature shear angles for neater cuts.

RAISED PANEL BIT WITH BACKCUTTER: this 88,9mm diameter bit features a backcutter for milling both the front and the back on the panel in a single cut. We recommend using a 31mm diameter bearing to work safely in two shallow passes.

SUPER-DUTY FLUSH TRIM BIT: this 19mm diameter bit gives you a superior cut with minimal chipping, even on end grain.

OGEE DOOR EDGE BIT: a subtle cove followed by a subtle roundover adds an elegant touch to your door edge.


DRAWER FRONT BIT: this bit makes a mini-raised panel cut on the outside edges of your drawer fronts.



Drawings are 1:1 scale

DESCRIPTION		ORDER NO. S=Ø12,7mm
The Cabinetmaking Sets - Profile A	(6 HW pcs.)	800.515.11
The Cabinetmaking Sets - Profile B	(6 HW pcs.)	800.520.11

Small Arch Door Sets




800.524 - 900.024

HW Z2 RH

These 3-piece sets will produce beautifully raised panel doors with a classic bevelled profile. Designed for use in fine furniture making, these sets include two matched cope and stick bits to produce frames from 15,87mm to 19mm in thickness. The stick bit shapes a decorative 4,76mm thumbnail moulding along the edge of the frame.
The panel bit is designed for 12,7mm thick material. All bits are equipped with guide bearings for shaping curved work such as the small arched panel doors seen on secretaries and corner cabinetry. These sets also produce panels for small chests, lids for small boxes, or drawer fronts. Instructions included.






Drawings are 1:1 scale

DESCRIPTION		ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm
Small Arch Door Sets	(3 HW pcs.)	900.024.11	800.524.11

www.dahm.no


Divided Light Door Sets



800.525 - 900.025


HW | α | Z2 | RH

Build authentic divided light doors for fine furniture and cabinets with these 3-piece sets. They include a stuck bit to cut the decorative ovolo profile on the frame edges, a cope to shape the mating profile on the ends of the stock, and a rabbeting bit to cut the recess for the glass.
Thanks to the guide bearings, you can also create arches on curved frames.
The unique design of the cope bit allows you to use full-length tenons to create strong, authentic mortise-and-tenon joinery. As the stock is coped, the tenon passes over the bit. These sets are designed for 22,2mm wide bars such as those on corner cupboard doors.
Available in 8mm and 12,7mm shanks. Instructions included.



DESCRIPTION	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm
Divided Light Door Sets	900.025.11	800.525.11


Glass Panel Sets



8/955.803


HW | Z2 | Z3 | RH


CMT's unique stile and rail router bit sets allow you to produce glass panel doors by using a rubber panel retaines to secure the glass in a 3,2mm slot cut into the frames. These bits work the same as other CMT stile and rail sets, but they leave you with a square rabbet on the inside of your door for installing the glass panel.
Available in 12mm and 12,7mm shanks.



Glass Panel Retainers

HERE'S HOW IT WORKS:
Mill the cope and pattern cuts first, then use the slot cutter to cut the groove for the rubber panel retainer. The edge of the pattern cut will ride on the bearing of the slot cutter bit. When you cut the slot in the rails you can cut the slot the full length of the stock. When you cut the slot in the stiles you need to set up reference points to stop and start the cuts so they are hidden from view on the top and bottom of the doors.





GLAS/RTBRN




Our unique retainer strips fit perfectly in the slots created by the slot cutter bit and hold your glass securely in the frame. Sold in 762cm. lengths.

DESCRIPTION	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
Glass Panel Sets	955.803.11	855.803.11

www.dahm.no

Adjustable Shaker Router Bit Sets




8/900.624

HW Z2 RH


These new bit sets are excellent for producing adjustable tongue and groove joints with a bevel, in order to eliminate panel rattle that may occur with the production of standard cabinets. Cut precise grooves into your plywood veneered panels and make perfect rattle-free fits. To be used on table-mounted routers. Avoid using these bits in hand-held power tools.





D mm	T1 mm	A	L mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
41,2	16 - 35	18°	87	**900.624.11**	**800.624.11**

Spare parts



791.025.00 822.025.11 822.026.11 822.027.11 822.028.11 990.020.00

Spare parts

541.515.00 0,1mm spacer
541.516.00 0,3mm spacer
541.517.00 0,5mm spacer
541.518.00 1mm spacer
541.500.00 3mm spacer
541.519.00 5,8mm spacer


Adjustable Tongue & Groove Bit Set for Mission Style Cabinet Doors




8/900.625


HW Z2 RH

Exclusive CMT design which allows the perfect fix for undersized plywood panel. The tongue cutter features opposing shear angles to obtain flawless finishing on a large variety of material such as plywood, softwood and hardwood.
For use on a table-mounted router, not for handheld routers.
- Adjustable at 0.050mm (0.002") increments;
- For groove width from 5mm (13/64") to 13,5mm (17/32");
- Cut stock thickness of 12,7mm (1/2") to 31,7mm (1-1/4");
- Features micrograin carbide for longer life.









D mm	T1 mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
41,2	5,15-13,5	**900.625.11**	
41,2	5,15-13,5		**800.625.11**

Spare parts



924.136.00 791.012.00 822.025.11 822.026.11 822.027.11 822.028.11 990.020.00
824.136.00 791.012.00 822.025.11 822.026.11 822.027.11 822.028.11 990.020.00

Spare parts

541.515.00 0,1mm spacer
541.516.00 0,3mm spacer
541.517.00 0,5mm spacer
541.518.00 1mm spacer
541.500.00 3mm spacer
541.519.00 5,8mm spacer

www.dahm.no

What work parameters are best when routing?

CMT ORANGE TOOLS™

Answering the following questions will provide you with the answer!


- **What equipment are you using?** Using brand new equipment of high quality is not the same as using outdated machinery! It is important to understand that vibration is the direct result of wear and tear, which can lead to a poor quality finish. Feed rate should be chosen in order to dampen vibration, and quite often, higher feed rates are associated with better finishing results.
- **What factors influence the performance of the bit I am using?** Many factors affect performance and the ultimate finish of the workpiece: the power of the collet chuck, the rigidity and eccentricity of the couplings, conditions and quality of the collets, reverse locking system, sharpened tool edge, the dust-collection system in use and even the relative humidity of the workplace environment.
- **What bit should I use?** The number of cutting edges as well as the cutting diameter significantly affect work parameters. In general, the more cutting edges and the wider the blade diameter, the higher the feed rate.
- **What is the cutting depth I hope to carry out?** In order to increase cutting depth, it is necessary to reduce the feed rate and vice versa for shallower cuts.
- **At what speed does my machine run?** By increasing the spindle speed (rpm), the quality of the finished edge improves. However, at the same time friction also increases between the tool and the workpiece. As a result, tool longevity is compromised. Ideally, the objective is to select the slowest rotation speed possible compatible with the quality of finishing you hope to achieve.
- **What edge finish am I looking to achieve?** Coarse routing and fine routing are definitely not the same thing! You need to figure out what is more important: quality or quantity. In order to prolong the life of your cutting tool, its best to choose the highest feed rate possible best suited to achieve the finish you want.
- **Above all....what materials am I working with?** Wood is a good example of natural fiber composite. It is made up of a natural fibrous material, both elastic and flexible (cellulose: long molecular polymer chains), bound together by a very rigid substance (lignin: cross-linked polymer) as well as a compatibilizer (hemicellulose: a polysaccharide). It is an anisotropic material, that is, directionally dependent, changing with direction along the object. How many types of wood and wood derivatives are you familiar with? Remember, no two pieces of wood are the same! In fact, the same work parameters carried out on two different pieces of wood will provide two very different results.

Feed rate is dependent of several factors, like the ones mentioned above - and these are just a few examples. It is important to weigh all factors in order to select an optimum feed rate suitable for the tools and work objectives involved. CMT is synonymous with quality and to produce high quality cuts you just can't randomly shoot off a bunch of numbers. Be wary of those who provide you with random numbers.

I get it....but where do I start? *The best way to go forward is step-by-step using reliable test data.* To quickly achieve the results best suited for your specific work expectations, you can always turn to theory!
One rule of thumb, which may prove advantageous, is to use a simple gauge to measure chipload wherever possible. On the one hand, it should be noted that when chips that are too thick, breakage will occur, resulting in a poor, rough finish. On the other hand, when chips are too thin, it will negatively affect tool longevity and cause rapid wear and tear of the cutting edge because the teeth of the tool are rubbing more than removing material.
The next time you experiment, you need to properly assess the specific demands of the work involved, assess chipload measurements and try to orient yourself towards a different thickness by taking into account the aforementioned factors. Then, with the aid of the formulas listed below, proceed to establish the appropriate feed rate for your next test. This will help you to achieve better results faster and you will have the essential information you will need for the next work project.

Parameters:
V = feed rate (m/min)
Z = cutting edges
C = Chipload (mm)

Formulas:
V = (RPM x Z x C)/1000
RPM = V x 1000 /(Z x C)



Example:
with caliper take measurement of a good result chipload (C=0,2mm).

Z=2
RPM=18000

V = (RPM x Z x C)/1000 = (18000x2x0,2)/1000 = 7,2m/min

Problem Solving

PROBLEM	SOLUTIONS	INCREASE
Bad finishing	• Cutting depth • Vibrations	• Rotation speed • Dust extraction • Number of cutting edges • Clamping cutter/chuck
Cutting edge wear	• Rotation speed • Vibrations	• Cutting advancement
Cutting edge burns	• Rotation speed • Number of cutting-edges	• Feed speed
Cutting edge debris	• Cutting depth	• Rotation speed • Feed speed • Dust extraction
Vibrations	• Rotation speed • Cutting depth	• Machine firmness • Workpiece firmness
Cutter breakage	• Feed speed • Cutting depth • Vibrations	• Shank diameter • Collet clamping • Change tool material (solid carbide or Densimet®)

DECREASE

www.dahm.no



CNC Router Cutters & Chucks

PRODUCTS	PAGE
Kinetic Dust Extractor	216
Universal Assembly Supports for Chucks	216
CNC Chucks	217~220
Precision Collets	220-221
Cutter Arbor	222-223
MK2 Chucks	223
Solid Carbide Spiral Bits	224~234
CNC Straight Cutters	234~242
CNC Profiled Cutters	243~246
Slot & Mortise Bits	246~252

www.dahm.no

new

CMT ORANGE TOOLS™



KINETIC DUST EXTRACTOR


992 Removes MDF & Chipboard dust from the workpiece

RH

DESCRIPTION	D mm	ORDER NO.
Kinetic Dust Extractor for chucks with DIN6388/EOC25 collets	100	**992.101.EOC25**
Kinetic Dust Extractor for chucks with ER32 collets	100	**992.101.ER32**
Kinetic Dust Extractor for chucks with ER40 collets	100	**992.101.ER40**

Spare parts **991.284.00** C-Spanner 95-100mm






EASY TO USE!

Install & remove as a clamping nut

- Health & Safety
- Tool Performance & Cut Quality
- Tool Life & Labor Costs
- Recommended for Nesting and Routing operations
- No wasted time during work process
- Replaces the standard clamping nut
- Suitable for any collet chucks with standard router bits
- Available for ER32 - ER40 - EC025 (DIN6388) collets
- The thick ceramic coat gives to KDE an anti-corrosion, anti-friction and anti-static surface.
- Tool body in light alloy
- Better air quality
- Good performances even at low rpm: from 6,000 up to 20,000 rpm
- Material: chipboard, coated chipboard, MDF, Corian®, plasterboard, OSB, HPL.



Download Instruction

Watch the video on YouTube

Watch Video

Working WITHOUT Kinetic Dust Extractor



Working WITH Kinetic Dust Extractor



www.dahm.no

HSK Chucks for “ER40” Precision Collets



183.310


RH LH

S	DESCRIPTION	To be used with collet	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
HSK-F63	Clamping nut without bearing	ER40	**183.310.01**	**183.310.02**
HSK-F63	Clamping nut with bearing	ER40	**183.310.11***	

* Suitable for right-hand and left-hand rotation.

For Homag, Eima, IMA from 9/94, Dubus, Weeke, Biesse, SCM, Morbidelli and Masterwood machines.

ISO30 Chucks for “ER40” Precision Collets





995.200

183.201

RH

S	To be used with collet	Retaining stud mm	ORDER NO. Right-hand rotation
ISO30	ER40	Ø12-8	**183.201.01**

For Biesse machines



995.201

183.211

RH

S	To be used with collet	Retaining stud mm	ORDER NO. Right-hand rotation
ISO30	ER40	Ø13-9	**183.211.01**

For Biesse machines with Omlat engine, Bulleri, Busellato, CMS and IMA machines.



995.202

183.221

RH

S	To be used with collet	Retaining stud mm	ORDER NO. Right-hand rotation
ISO30	ER40	Ø12,8-9	**183.221.01**

For Alberti and Masterwood machines.

Clamping Nuts for Chucks with “ER40” Precision Collets



992.383

RH LH

DESCRIPTION	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
Clamping nut without bearing		
For 183.201/211/221/310 chucks	**992.383.01**	**992.383.02**
Clamping nut with bearing		
For 183.201/211/221/310 chucks	**992.383.11**	

C-spanner for “ER40” Precision Collets



991.184

DESCRIPTION	ORDER NO.
C-Spanner for “ER40” precision collet	**991.184.00**

www.dahm.no

HSK Chuck for "ER32" Precision Collets



183.300


RH LH

S	DESCRIPTION	To be used with collet	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
HSK-F63	Clamping nut without bearing	ER32	**183.300.01**	**183.300.02**
HSK-F63	Clamping nut with bearing	ER32	**183.300.11***	

*** Suitable for right-hand and left-hand rotation.**

For Homag, Eima from 9/94, Dubus, Weeke, Biesse, SCM, Morbidelli and Masterwood machines.

ISO30 Chucks for "ER32" Precision Collets





995.200

183.200

RH LH

S	To be used with collet	Retaining stud mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
ISO 30	ER32	Ø12-8		**183.200.01**	**183.200.02**

For Biesse machines.



995.201

183.210

RH LH

S	To be used with collet	Retaining stud mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
ISO 30	ER32	Ø13-9		**183.210.01**	**183.210.02**

For Biesse machines with Omlat engine, Bulleri, Busellato, CMS and IMA machines.



995.202


183.220

RH LH

S	To be used with collet	Retaining stud mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
ISO 30	ER32	Ø12,8-9		**183.220.01**	**183.220.02**

For Alberti and Masterwood machines.

ISO30 Chucks for "ER32" Precision Collets





995.250

183.250 without aluminium flange

RH LH

S	To be used with collet	Retaining stud mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
ISO 30	ER32	Ø8,5		**183.250.01**	**183.250.02**

For Morbidelli and SCM machines.

183.251 with aluminium flange already assembled Ø69,5mm.

RH LH


S	To be used with collet	Retaining stud mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
ISO 30	ER32	Ø8,5		**183.251.01**	**183.251.02**

Spare parts 992.501.00 Ø69,5mm aluminium flange*

For Morbidelli and SCM machines.

www.dahm.no

Chucks for “ER32” Precision Collets




183.000/100

RH LH

S mm	To be used with collet		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
MK2/M30x1,5	ER32		**183.000.01**	**183.000.02**
MK3/M30x1,5	ER32		**183.100.01**	

MK2/MK3 tapered shank

Chucks for “ER32” Precision Collets





995.400

183.400

RH

S mm	To be used with collet	Retaining stud		ORDER NO. Right-hand rotation	
Ø25x55	ER32	PS LEUCO		**183.400.01**	

For machines with PS Leuco system.

Clamping Nuts for Chucks with “ER32” Collets



992.183

RH LH

DESCRIPTION	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
Clamping nut without bearing		
For 183.000/100/200/250/300/400 chucks	**992.183.01**	**992.183.02**
Clamping nut with bearing		
For 183.000/100/200/250/300/400 chucks	**992.183.11**	**992.183.12**

C-Spanner for “ER32” Precision Collets




991.183

DESCRIPTION	ORDER NO.
C-Spanner for “ER32” precision collets	**991.183.00**

www.dahm.no

HSK Chuck for "DIN6388" - EOC25 Precision Collet



183.320

RH

S	DESCRIPTION	To be used with collet	ORDER NO. Right-hand rotation
HSK-F63	HSK chuck with bearing nut	EOC-25	**183.320.01***

Spare parts **992.283.11** Clamping nut with bearing

* Suitable for left-hand rotation too.

For Homag, Eima from 9/94, Dubus, Weeke, Biesse, SCM, Morbidelli & Masterwood machines.

Clamping Nuts



992.283

RH

DESCRIPTION	ORDER NO. Right-hand rotation
Clamping nut without bearing	**992.283.01**
Clamping nut with bearing	**992.283.11**

For chuck 183.320.

C-Spanner for "DIN6388" & "ER40"



991.283

DESCRIPTION	ORDER NO.
C-Spanner for USAG 58-62-65	**991.283.00**

Precision Collets "DIN6388"



185 - EOC-25

B mm	B inches	ORDER NO.	B mm	B inches	ORDER NO.
3		**185.030.00**	13	1/2	**185.130.00**
4		**185.040.00**	14		**185.140.00**
5		**185.050.00**	16	5/8	**185.160.00**
6		**185.060.00**	18		**185.180.00**
8	5/16	**185.080.00**	20		**185.200.00**
10		**185.100.00**	25		**185.250.00**
12		**185.120.00**			

REMARK: *special dimensions available on request.*



185 - EOC-16


new

B mm	B inches	ORDER NO.	B mm	B inches	ORDER NO.
6		**185.060.16**	12		**185.120.16**
8	5/16	**185.080.16**	14		**185.140.16**
10		**185.100.16**	16	5/8	**185.160.16**

REMARK: *special dimensions available on request.*

www.dahm.no

184 - ER11




B mm	ORDER NO.
2	184.020.11
3	184.030.11
4	184.040.11
5	184.050.11
6	184.060.11

TECHNICAL DETAILS:
- replaceable Std “**ER11**” collets (from 1 to 7mm)
- fit most tapered spindle noses
- +0-0,7mm wide clamping tolerance
- suitable for most conical chucks.

REMARK: *special dimensions available on request.*

184 - ER16




B mm	ORDER NO.
2	184.020.16
3	184.030.16
4	184.040.16
5	184.050.16
6	184.060.16
7	184.070.16
8	184.080.16
9	184.090.16
10	184.100.16

TECHNICAL DETAILS:
- replaceable Std “**ER16**” collets (from 1 to 10mm)
- fit most tapered spindle noses
- +0-0,7mm wide clamping tolerance
- suitable for most conical chucks.

REMARK: *special dimensions available on request.*

184 - ER20




B mm	ORDER NO.
new 2	184.020.20
3	184.030.20
new 4	184.040.20
5	184.050.20
6	184.060.20
6,35	184.064.20
new 7	184.070.20
8	184.080.20
new 9	184.090.20
10	184.100.20
new 11	184.110.20
12	184.120.20
12,7	184.127.20
new 13	184.130.20

TECHNICAL DETAILS:
- replaceable Std “**ER20**” collets (from 1 to 13mm)
- fit most tapered spindle noses
- +0-0,7mm wide clamping tolerance
- suitable for most conical chucks.

REMARK: *special dimensions available on request.*

184 - ER25



B mm	ORDER NO.
new 3	184.030.25
new 4	184.040.25
new 5	184.050.25
6	184.060.25
8	184.080.25
new 9	184.090.25
10	184.100.25
12	184.120.25
new 13	184.130.25
14	184.140.25
16	184.160.25

TECHNICAL DETAILS:
- replaceable Std “**ER25**” collets (from 1 to 16mm)
- fit most tapered spindle noses
- +0-0,7mm wide clamping tolerance
- suitable for most conical chucks.

REMARK: *special dimensions available on request.*

184 - ER32



B mm	ORDER NO.
3	184.030.00
4	184.040.00
5	184.050.00
6	184.060.00
6,35	184.065.00
7	184.070.00
8	184.080.00
new 9	184.090.00
9,52	184.095.00
10	184.100.00
new 11	184.110.00
12	184.120.00
13	184.130.00
14	184.140.00
new 15	184.150.00
16	184.160.00
new 17	184.170.00
18	184.180.00
19	184.190.00
20	184.200.00

For chucks
183.000/100/200/250/300/400

TECHNICAL DETAILS:
- replaceable Std ”**ER32**” collets (from 3 to 20mm)
- fit most tapered spindle noses
- +0-0,7mm wide clamping tolerance
- suitable for most conical chucks.

REMARK: *special dimensions available on request.*

184 - ER40



B mm	ORDER NO.
new 3	184.032.00
4	184.042.00
5	184.052.00
6	184.062.00
7	184.072.00
8	184.082.00
9,52	184.096.00
10	184.102.00
12	184.122.00
13	184.132.00
14	184.142.00
16	184.162.00
18	184.182.00
19	184.192.00
20	184.202.00
25	184.252.00

For chucks
183.201/211/221/310

TECHNICAL DETAILS:
- replaceable Std ”**ER40**” collets (from 3 to 25mm)
- fit most tapered spindle noses
- +0-0,7mm wide clamping tolerance
- suitable for most conical chucks.

REMARK: *special dimensions available on request.*

www.dahm.no

Cap Nuts for CNC Machines

CMT ORANGE TOOLS




993.0

RH LH

Internal thread				ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
Ø20x14Fx1"				**993.020.01**	**993.020.02**
M30x1,5				**993.030.01**	**993.030.02**

For machines with M33x3 threaded spindle nose.

ISO30 Retaining Studs



995.200 995.201 995.202 995.250 995.400

DESCRIPTION	D_1 mm	D_2 mm	ORDER NO.
Retaining stud for 183.200/201 "Biesse" chucks	8	12	**995.200.00**
Retaining stud for 183.210/211 "Biesse, Omlat, Bulleri, Busellato, Weeke and IMA" chucks	9	13	**995.201.00**
Retaining stud for 183.220/221 "Alberti-Masterwood" chucks	9	12,8	**995.202.00**
Retaining stud for 183.250/251 "SCM - Morbidelli" chucks	6,5	8,5	**995.250.00**
Retaining stud for "PS and Leuco" 183.400 chucks	M8		**995.400.00**

Cutter Arbor with HSK Tapered Shank



183.360

RH LH

S	d mm	D mm			ORDER NO.
HSK-F63	Ø30x100	63			**183.360.00**
new HSK-F63	Ø30x150	63			**183.360.10**
HSK-F63	Ø35x100	63			**183.361.00**
HSK-F63	Ø40x100	63			**183.362.00**

For Homag, Eima from 9/94, Dubus, Weeke, Biesse, SCM, Morbidelli and Masterwood machines.



Cutter Arbor with ISO30 Tapered Shank

183.260


RH LH


S	D mm	D_3 mm		ORDER NO.
ISO 30	Ø30x100	50		**183.260.00**

For Biesse machines.

REMARK: *special dimensions available on request.*

Spare Parts for Chucks





DESCRIPTION	ORDER NO.	DESCRIPTION	ORDER NO.
M6x25 TCEI screw	**990.098.00**	***Optional***	
Steel flange for with Ø30mm arbors - Male	**992.560.30M**	Steel flange for with Ø30mm arbors - Female	**992.560.30F**
Steel flange for with Ø35mm arbors - Male	**992.560.35M**	Steel flange for with Ø35mm arbors - Female	**992.560.35F**
Steel flange for with Ø40mm arbors - Male	**992.560.40M**	Steel flange for with Ø40mm arbors - Female	**992.560.40F**

www.dahm.no

Universal Assembly Supports for Chucks




183

DESCRIPTION	D mm	ORDER NO.
Universal assembly supports for chucks HSK-F63	63	**183-HSK**
Universal assembly supports for chucks ISO30	50	**183-ISO**


For HSK-F63 and ISO30 chucks

CMT now offers new universal assembly supports for HSK-F63 and ISO30 chucks. Thanks to the bidirectional roller bearings, which clamp the tooLeft-hand rotationolder to the flange, the system offers the highest protection to the tool taper and clamps are no longer needed.

The special bidirectional roller bearing clamps the tooLeft-hand rotationolder to the flange, offering the highest protection to the tool taper.



Saw Blade Arbor with Parallel Shank



183.410


RH LH

S mm	D mm	Pin Hole	L mm	ORDER NO.
20	30	4/M6/48	97,5	**183.410.30**

Spare parts

990.083.00	M6x10mm TCEI screw
991.067.00	3mm allen key
991.064.00	4mm allen key

Collet Chucks Clamp with MK2 Tapered Shank



123

RH LH

S			ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
MK2/Ø20x14Fx1"			**123.000.01**	**123.000.02**

Spare parts

992.123.01	Clamping nut RH
992.123.02	Clamping nut LH
991.123.00	Type 40-42 USAG c-spanner

Collets for 123 Chucks




124

D_3 mm	ORDER NO.	D_3 mm	ORDER NO.
6	**124.060.00**	10	**124.100.00**
6,35	**124.064.00**	12	**124.120.00**
8	**124.080.00**	12,7	**124.127.00**
9,5	**124.095.00**	14	**124.140.00**

www.dahm.no

Solid Carbide Up & Downcut Spiral Bits



190


HWM | Z1+1 | Z2+2 | Z3+3 | RH

D mm	I mm	I_1 mm	L mm	S mm	Z	ORDER NO. Right-hand rotation
4	15	7	50	4	1+1	**190.040.11**
5	22	8	60	5	1+1	**190.050.11**
6	22	8	60	6	1+1	**190.060.11**
8	32	7	80	8	2+2	**190.080.11**
9,52	28,6	7	76,2	9,52	2+2	**190.504.11**
10	32	7	80	10	2+2	**190.100.11**
10	42	7	90	10	2+2	**190.101.11**
12	42	7	90	12	2+2	**190.120.11**
12	52	7	100	12	2+2	**190.121.11**
12,7	25,4	16	76,2	12,7	2+2	**190.505.11**
12,7	28,6	16	76,2	12,7	2+2	**190.506.11**
12,7	34,9	16	88,9	12,7	2+2	**190.507.11**
12,7	41,3	16	101,6	12,7	2+2	**190.508.11**
16	55	24	110	16	2+2	**190.160.11**
18	55	30	110	18	2+2	**190.180.11**
...up & downcut mortising bits						
9,52	22,2	4,8	76,2	9,52	2+2	**190.513.11**
9,52	25,4	5,2	76,2	9,52	3+3	**190.813.11**
12	25	5,2	83	12	3+3	**190.320.11**
12,7	22,2	5,2	76,2	12,7	2+2	**190.515.11**
12,7	34,9	5,2	88,9	12,7	2+2	**190.517.11**

Technical details:
- Premium quality HWM.
- 2+2 spiral cutting edges [Z2+2].
- 3+3 spiral cutting edges [Z3+3].
- Provide an excellent finish on both the upper and the lower side of the workpiece.


Application:
used for cutting, copying, panel sizing and any routing application on solid wood, wood composites, plastic materials and laminates. Use a high feed speed on well-clamped workpieces. Can be used on machining centres, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.

Ø4-6mm Chipboard




24000 RPM
Correction factor for Vf:
MDF=0.8

Ø8-18mm Chipboard



18000 RPM
Correction factor for Vf:
MDF=0.8

www.dahm.no




198

HWM Z1 RH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
3	12	50	3	**198.030.11**
3,18	12,7	50,8	6,35	**198.001.11**
4	15	50	4	**198.040.11**
4,76	15,87	50,8	6,35	**198.005.11**
5	17	50	5	**198.050.11**
6	22	60	6	**198.060.11**
6,35	19,05	50,8	6,35	**198.007.11**
6,35	25,4	63,5	6,35	**198.008.11**
8	22	70	8	**198.080.11**
8	32	80	8	**198.081.11**
9,52	28,57	76,2	9,52	**198.504.11**
10	32	70	10	**198.100.11**
10	42	80	10	**198.101.11**
10	52	90	10	**198.102.11**
12	32	83	12	**198.120.11**

Ø3-12mm Plastics, laminated



16000~18000 RPM

Ø3-12mm Softwood




18000~24000 RPM
Correction factor for Vf:
Hardwood=0.9
Machining across grain=0.7
Chipboard=1.1

Technical details:
- Premium quality HWM.
- 1 spiral cutting edge [Z1].
- Provide an excellent finish on the lower side of the workpiece.
- **Upward chip ejection.**

Application:
used for cutting, copying, panel sizing and any routing applications on solid wood, wood composites, plastic materials and laminates. Use a high feed speed on well-clamped workpieces.
Can be used on machining centres, point to point machines, CNC routers and hand-held routers equipped with chucks or adaptors.

Solid Carbide Upcut Spiral Bits



197

HWM Z4 RH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
12	42	90	12	**197.121.11**
14	50	110	14	**197.140.11**
16	55	110	16	**197.160.11**
16	35	90	16	**197.161.11**
18	55	110	18	**197.180.11**
20	60	120	20	**197.200.11**
20	70	120	20	**197.201.11**

Technical details:
- Premium quality HWM.
- 4 spiral cutting edges (2 with chip-breaker) [Z2+2R].
- Max 0.1mm tooth depth.
- Provide excellent finish on the lower side of the workpiece.
- **Upward chip ejection.**


Application:
used for ripping, template routing, panel sizing and any routing application on solid wood and wood composites. Can be used on machining centres, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.



The special 4 flute design (Z2 finishing + Z2R with chipbreaker) allows high speed with excellent finish on the workpiece.

www.dahm.no

Solid Carbide Upcut Spiral Bits with Chip-Breaker



195


HWM Z3R RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
8	32	80	8	**195.081.11**	**195.081.12**
8	42	90	8	**195.082.11**	
10	32	80	10	**195.100.11**	**195.100.12**
10	42	90	10	**195.101.11**	
12	35	83	12	**195.120.11**	**195.120.12**
12	42	90	12	**195.121.11**	
12	52	100	12	**195.122.11**	
12,7	38,1	88,9	12,7	**195.506.11**	
14	58	110	14	**195.140.11**	
15,88	54	109,5	15,88	**195.509.11**	
16	55	110	16	**195.160.11**	**195.160.12**
16	35	90	16	**195.161.11**	
16	72	120	16	**195.165.11**	
18	55	110	18	**195.180.11**	
19,05	54	109,5	19,05	**195.511.11**	
20	60	120	20	**195.200.11**	**195.200.12**
20	72	120	20	**195.201.11**	
20	102	165	20	**195.202.11**	

Technical details:
- Premium quality HWM.
- 3 spiral cutting edges [Z3R].
- Chip breaker teeth.
- Max 0.3mm tooth depth.
- Provide an excellent finish on the lower side of the workpiece.
- **Upward chip ejection.**


Application:
used for ripping, template routing, panel sizing and any routing application on solid wood, or wood composites. Can be used at a high feed speed on well-clamped workpieces.
Can be used on machining centres, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.

Ø8-10mm Softwood



18000 RPM
Correction factor for Vf:
Hardwood=0.8
Chipboard without coating=1.3

Ø12-20mm Softwood



18000 RPM
Correction factor for Vf:
Hardwood=0.8
Chipboard without coating=1.3

www.dahm.no



196


HWM | Z3R | RH | LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
8	32	80	8	**196.081.11**	
10	42	90	10	**196.101.11**	
12	35	83	12	**196.120.11**	**196.120.12**
12	42	90	12	**196.121.11**	
12	52	100	12	**196.122.11**	
12,7	38,1	88,9	12,7	**196.506.11**	
14	50	110	14	**196.140.11**	
15,88	54	109,5	15,88	**196.509.11**	
16	55	110	16	**196.160.11**	**196.160.12**
18	55	110	18	**196.180.11**	
19,05	54	109,5	19,05	**196.511.11**	
20	60	120	20	**196.200.11**	**196.200.12**
20	72	120	20	**196.201.11**	

TECHNICAL DETAILS:
- Premium quality HWM.
- 3 spiral cutting edges [Z3R].
- Chip breaker teeth.
- Max 0.3mm tooth depth.
- Provide excellent finish on the upper side of the workpiece.
- **Downward chip ejection.**


APPLICATION:
used for ripping, template routing, panel sizing and any routing application on solid wood and wood composites.
Can be used on machining centres, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.

Ø8-10mm SOFTWOOD



18000 RPM
Correction factor for Vf:
Hardwood=0.8
Chipboard without coating=1.3


Ø12-20mm SOFTWOOD



18000 RPM
Correction factor for Vf:
Hardwood=0.8
Chipboard without coating=1.3

www.dahm.no

Solid Carbide Upcut Spiral Bits



193


HWM | Z3 | RH | LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
8	32	80	8	**193.081.11**	**193.081.12**
10	32	80	10	**193.100.11**	**193.100.12**
10	42	90	10	**193.101.11**	
12	35	83	12	**193.120.11**	**193.120.12**
12	42	90	12	**193.121.11**	
12	52	100	12	**193.122.11**	
14	58	110	14	**193.140.11**	
16	55	110	16	**193.160.11**	**193.160.12**
16	35	90	16	**193.161.11**	
16	72	120	16	**193.165.11**	
18	55	110	18	**193.180.11**	
20	60	120	20	**193.200.11**	**193.200.12**
20	70	120	20	**193.201.11**	

Technical details:
- Premium quality HWM.
- 3 spiral cutting edges [Z3].
- Provide an excellent finish on the lower side of the workpiece.
- **Upward chip ejection.**


Application:
used for ripping, template routing, panel sizing and any routing application on solid wood, or wood composites. Can be used at a high feed speed on well-clamped workpieces.
Can be used on machining centres, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.

Ø12-14mm Plastics, laminated




14000-18000 RPM

Ø12-20mm Softwood



18000 RPM
Cutting thickness 0.5-2mm
Correction factor for Vf:
Hardwood=0.9
Machining across grain=0.7

www.dahm.no



194


HWM | Z3 | RH | LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
10	32	80	10	**194.100.11**	
10	42	90	10	**194.101.11**	
12	35	83	12	**194.120.11**	**194.120.12**
12	42	90	12	**194.121.11**	
14	50	110	14	**194.140.11**	
16	55	110	16	**194.160.11**	**194.160.12**
16	35	90	16	**194.161.11**	
18	55	110	18	**194.180.11**	
20	60	120	20	**194.200.11**	**194.200.12**
20	72	120	20	**194.201.11**	
20	102	165	20	**194.202.11**	

TECHNICAL DETAILS:
- Premium quality HWM.
- 3 spiral cutting edges [Z3].
- Provide an excellent finish on the upper side of the workpiece.
- **Downward chip ejection.**


APPLICATION:
used for ripping, template routing, panel sizing and any routing application on solid wood, wood composites, plastic materials and laminates. Can be used at a high feed speed on small, difficult to clamp workpieces.
Can be used on machining centres, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.

Ø12-14mm PLASTICS, LAMINATED



14000-18000 RPM

Ø12-20mm SOFTWOOD




18000 RPM
Cutting thickness 0.5-2mm
Correction factor for Vf:
Hardwood=0.9
Machining across grain=0.7

www.dahm.no

Solid Carbide Upcut Spiral Bits

CMT ORANGE TOOLS




191

HWM Z2 RH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	
3	12	50	3	**191.030.11**	
3	12	60	6	**191.630.11**	
3	12	60	8	**191.830.11**	
3,18	12,7	50,8	6,35	**191.001.11**	
3,5	12	60	6	**191.635.11**	
3,97	12,7	50,8	6,35	**191.003.11**	
4	15	50	4	**191.040.11**	
4	15	60	6	**191.640.11**	
4	15	60	8	**191.840.11**	
4,76	19,05	50,8	6,35	**191.005.11**	
5	17	50	5	**191.050.11**	
5	17	60	6	**191.650.11**	
5	17	60	8	**191.850.11**	
6	27	70	6	**191.060.11**	
6	27	70	8	**191.860.11**	
6,35	19,05	50,8	6,35	**191.007.11**	
6,35	25,4	63,5	6,35	**191.008.11**	
7	32	80	8	**191.870.11**	
7,94	25,4	76,2	12,7	**191.501.11**	
8	22	70	8	**191.080.11**	
8	32	80	8	**191.081.11**	
8	42	90	8	**191.082.11**	
9	32	83	12	**191.890.11**	
9,52	31,75	76,2	12,7	**191.503.11**	
10	32	80	8	**191.800.11**	
10	32	80	10	**191.100.11**	
10	32	83	12	**191.900.11**	
10	42	90	10	**191.101.11**	
10	42	90	12	**191.901.11**	
12	35	83	8	**191.820.11**	
12	35	83	12	**191.120.11**	
12	42	90	12	**191.121.11**	
12	52	100	12	**191.122.11**	
12,7	31,75	76,2	12,7	**191.505.11**	
12,7	38,1	88,9	12,7	**191.506.11**	
12,7	50,8	101,6	12,7	**191.507.11**	
14	50	110	14	**191.140.11**	
15,88	55	109,5	15,88	**191.509.11**	
16	55	110	16	**191.160.11**	
16	35	90	16	**191.161.11**	
16	72	120	16	**191.165.11**	
19,05	55	109,5	19,05	**191.511.11**	
20	60	120	20	**191.200.11**	

Ø12-14mm Plastics,Laminated



14000~18000 RPM

Ø12-20mm Softwood



18000 RPM
Cutting thickness 0.5-2mm
Correction factor for Vf:
Hardwood=0.9
Machining across grain=0.7

Technical details:
- Premium quality HWM.
- 2 spiral cutting edges [Z2].
- Provide an excellent finish on the lower side of the workpiece.
- **Upward chip ejection.**

Application:
used for ripping, template routing, panel sizing and any routing application on solid wood, wood composites, plastic materials and laminates.
Can be used at a high feed speed on well-clamped workpieces.
Can be used on machining centres, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.

www.dahm.no




192

HWM | Z2 | RH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
3	12	50	3	**192.030.11**
3	12	60	6	**192.630.11**
3	12	60	8	**192.830.11**
3,18	12,7	50,8	6,35	**192.001.11**
3,97	12,7	50,8	6,35	**192.003.11**
4	15	50	4	**192.040.11**
4	15	60	6	**192.640.11**
4	15	60	8	**192.840.11**
4,76	19,05	50,8	6,35	**192.005.11**
5	17	50	5	**192.050.11**
5	17	60	6	**192.650.11**
5	17	60	8	**192.850.11**
6	27	70	6	**192.060.11**
6	27	70	8	**192.860.11**
6,35	19,05	50,8	6,35	**192.007.11**
6,35	25,4	63,5	6,35	**192.008.11**
7,94	25,4	76,2	12,7	**192.501.11**
8	22	70	8	**192.080.11**
8	32	80	8	**192.081.11**
8	42	90	8	**192.082.11**
9,52	31,75	76,2	12,7	**192.503.11**
10	32	80	8	**192.800.11**
10	32	80	10	**192.100.11**
10	42	90	10	**192.101.11**
10	32	83	12	**192.900.11**
12	35	83	8	**192.820.11**
12	35	83	12	**192.120.11**
12,7	31,75	76,2	12,7	**192.505.11**
12,7	38,1	88,9	12,7	**192.506.11**
12,7	50,8	101,6	12,7	**192.507.11**
14	52	110	14	**192.140.11**
16	55	110	16	**192.160.11**

Ø12-14mm PLASTICS,LAMINATED



14000-18000 RPM

Ø12-20mm SOFTWOOD




18000 RPM
Cutting thickness 0.5-2mm
Correction factor for Vf:
Hardwood=0.9
Machining across grain=0.7

TECHNICAL DETAILS:
- Premium quality HWM.
- 2 spiral edges [Z2].
- Provide an excellent finish on the upper side of the workpiece.
- **Downward chip ejection.**

APPLICATION:
used for ripping, template routing, panel sizing and any routing application on solid wood, wood composites, plastic materials and laminates.
Can be used at a high feed speed on small, difficult to clamp work pieces.
Can be used on machining centres, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.

www.dahm.no

Solid Carbide Upcut Spiral Bits for Locksets



195

HWM Z3R Z3 RH


D mm	I mm	I1 mm	L mm	S mm	ORDER NO. Right-hand rotation
With Chip-Breaker					
14	95*	45	150	14	**195.142.11**
14	125*	45	170	14	**195.144.11**
16	95*	45	150	16	**195.162.11**
16	120*	50	170	16	**195.164.11**
18	95*	45	150	18	**195.182.11**
Without Chip-Breaker					
16	95*	45	150	16	**193.162.11**

*** The maximum cutting length is achieved in 2-3 passes.**


TECHNICAL DETAILS:
- Premium quality HWM.
- 3 spiral cutting edges [Z3] and [Z3R].
- Max 0.3mm tooth depth.
- Provide an excellent finish on the lower side of the workpiece.
- Seat for seeger ring *(not included)*.
- **Upward chip ejection.**

APPLICATION:
used for ripping, template routing, panel sizing and any routing application on solid wood, or wood composites. Can be used at a high feed speed on well-clamped workpieces. Can be used on machining centres, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.


MACHINING DEEP SLOTS GUIDE



Reducing the slot cutting width by approx 0.1mm per stroke reduces the risk of breakage as the tool does not touch the side of the slot with the full length of the tool.



Solid Carbide Upcut with Spiral Bits Chip-Breaker for 60° V-Point Locksets



195.143/163

HWM Z3R RH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
14	58	110	14	**195.143.11**
16	55	110	16	**195.163.11**

Solid Carbide Upcut Spiral Bits without Chip-Breaker for 60° V-Point Locksets

191.143/163

HWM Z3 RH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
14	50	110	14	**191.143.11**
16	55	110	16	**191.163.11**

TECHNICAL DETAILS:
- Premium quality HWM.
- 3 spiral cutting edges [Z3].
- Provide an excellent finish on the lower side of the workpiece.
- **Upward chip ejection.**

APPLICATION:
used for ripping, template routing, panel sizing and any routing application on solid wood, or wood composites. Can be used at a high feed speed on well-clamped workpieces.
Can be used on machining centres, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.

www.dahm.no

Spiral Bits with Insert Knives & Chip-Breaker for Locksets



662

INSERT CARBIDE | Z2R | RH | 2X LONGER LIFE

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
16	23/95*	150	16	**662.160.11**

Spare parts


790.230.2R	23x7x1.5mm 2-RT HWM knives
790.230.3R	23x7x1.5mm 3-RT HWM knives
990.082.00	M3x4mm T9 Torx screw
991.069.00	T9 Torx key

*** The 95mm length is achieved in 4-5 passes.**


TECHNICAL DETAILS:
- Densimet® tungsten heavy metal alloys for low-vibration.
- 2 cutting edges [Z2R].
- Chip-breaker teeth.

APPLICATION:
used for ripping, template routing, panel sizing and any routing application on solid wood, or wood composites. Can be used at a high feed speed on well-clamped workpieces.
Can be used on machining centres, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.

MACHINING DEEP SLOTS GUIDE



Reducing the slot cutting width by approx 0.1mm per stroke reduces the risk of breakage as the tool does not touch the side of the slot with the full length of the tool.



Upcut Spiral Bits with Chipbreaker for Glue-Laminated Wooden Beams



195

HS | Z3R | RH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
□ 30	170	235	30	**Y195.300.51**
40	165	235	30	**195.400.51**
50	215	295	30	**195.500.51**


□ **On request**
We manufacture bits without chipbreaker, with left-hand rotation and also in custom dimensions.

TECHNICAL DETAILS:
- High speed cobalt steel.
- 3 upcut spiral cutting edges with chipbreaker [Z3R].
- Resharpenable cutters.
- Max 6000~10000 RPM.
- Maximum feed speed 2m/minute.
- **Upward chip ejection.**

APPLICATION:
used for cutting, copying, and routing on glue-laminated wooden beams.
To be inserted on Hundegger machines.

www.dahm.no

Round Nose Solid Carbide Upcut Spiral Bits



199

HWM | Z2 | RH

D mm	R mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
3,18	1,6	12,7	50,8	6,35	**199.001.11**
6	3	27	70	6	**199.060.11**
6,35	3,18	25,4	63,5	6,35	**199.008.11**
8	4	32	80	8	**199.081.11**
9,52	4,76	28,57	76,2	9,52	**199.504.11**
10	5	32	80	10	**199.100.11**
12	6	35	80	12	**199.120.11**
12,7	6,35	31,75	76,2	12,7	**199.505.11**
15,88	7,94	57,15	109,5	15,88	**199.509.11**
16	8	55	110	16	**199.160.11**
19,05	9,52	57,15	109,5	19,05	**199.511.11**

TECHNICAL DETAILS:
- Premium quality HWM.
- 2 upcut spiral cutting edges [Z2].
- Excellent finish on the lower side of the work piece.
- **Upward chip ejection.**

APPLICATION:
used for ripping, template routing, panel sizing and any routing application on solid wood, wood composites, plastic materials and laminates. Can be used at a high feed speed on well-clamped workpieces.
For use on machining centers, point-to-point boring machines, CNC routers and hand-held routers equipped with chucks or adaptors.

DP Router Cutters with Shear Angle



141


DP | Z1+1 | Z1 | RH

D mm	I mm	L mm	S mm	Z	ORDER NO. Right-hand rotation
6	8	65	12x40	1	**141.060.61**
8	12	65	12x40	1	**141.080.61**
*10	22	75	12x40	1+1	**141.101.61**

TECHNICAL DETAILS:
- Super strength steel.
- DP cutting edge.
- HW plunging tip for diagonal plunge-cutting.
- Resharpenable cutter (max 3 times).
- Max feed speed 4 m/min.

APPLICATION:
to be used on all CNC routers for jointing and sizing of solid wood and wood-based panels.

40X LONGER LIFE THAN CARBIDE



*** Z1+1 CONSTRUCTION FOR 141.101.61 ITEM**

www.dahm.no

DP Router Cutters with Shear Angle



140

DP | Z1+1 | RH


D mm	I mm	L mm	S mm	Z	ORDER NO. Right-hand rotation
10	25	72	12x40	1+1 (3 DP+1 HW)	**140.03956**
12	27	75	12x40	1+1 (3 DP+1 HW)	**140.120.61**
12	35	85	12x40	1+1 (4 DP+1 HW)	**140.121.61**
12,7	27	75	12,7x40	1+1 (3 DP+1 HW)	**140.127.61**
12,7	35	85	12,7x40	1+1 (4 DP+1 HW)	**140.128.61**
15,87	27	85	15,87x50	1+1 (3 DP+1 HW)	**140.158.61**
15,87	45	103	15,87x50	1+1 (5 DP+1 HW)	**140.159.61**
16	27	85	16x50	1+1 (3 DP+1 HW)	**140.160.61**
16	35	93	16x50	1+1 (4 DP+1 HW)	**140.161.61**
18	27	85	20x50	1+1 (3 DP+1 HW)	**140.180.61**
18	35	95	20x50	1+1 (4 DP+1 HW)	**140.181.61**
18	45	105	20x50	1+1 (5 DP+1 HW)	**140.182.61**
19,05	27	85	19,05x50	1+1 (3 DP+1 HW)	**140.190.61**
19,05	45	105	19,05x50	1+1 (5 DP+1 HW)	**140.192.61**
20	27	85	20x50	1+1 (3 DP+1 HW)	**140.200.61**
20	35	95	20x50	1+1 (4 DP+1 HW)	**140.201.61**
20	45	105	20x50	1+1 (5 DP+1 HW)	**140.202.61**
20	55	115	20x50	1+1 (6 DP+1 HW)	**140.203.61**

TECHNICAL DETAILS:
- Super strength steel.
- DP cutting edge.
- HW plunging tip for diagonal plunge-cutting (Z-axis tool entrance).
- Resharpenable cutter (max 3 times).
- Max feed speed 5 m/min.

APPLICATION:
to be used on all CNC routers for jointing, rabbeting, grooving and copying of raw material, melamine and laminates, MDF, HPL and veneered panels.

40X LONGER LIFE THAN CARBIDE

Diamond Router Cutters with 45° Shear Angle



140

DP | Z1+1 | RH

D mm	I mm	L mm	S mm	Z	ORDER NO. Right-hand rotation
20	25	85	20x50	1+1 (6 DP+1 HW)	**140.720.61**
20	35	95	20x50	1+1 (8 DP+1 HW)	**140.721.61**
20	45	105	20x50	1+1 (10 DP+1 HW)	**140.722.61**


TECHNICAL DETAILS:
- Super strength steel.
- "H4" diamond cutting edgesf featuring 45° shear angle.
- HW plunging tip for plunge cutting.
- Resharpenable cutters (max 8-9 times).
- Maximum feed speed 5m/minute.

APPLICATION:
to be used on all CNC routers for jointing, rabbeting, grooving and copying of raw material, melamine and laminates, MDF, HPL and veneered panels.

40X LONGER LIFE THAN CARBIDE

www.dahm.no

DP Router Cutters with Shear Angle



40X LONGER LIFE THAN CARBIDE

142


DP | Z2+2 | RH

D mm	I mm	L mm	S mm	Z	ORDER NO. Right-hand rotation
20	27	85	20x50	2+2 (6 DP+1 HW)	**142.200.61**
20	36	95	20x50	2+2 (8 DP+1 HW)	**142.201.61**
20	45	105	20x50	2+2 (10 DP+1 HW)	**142.202.61**
20	55	115	20x50	2+2 (12 DP+1 HW)	**142.203.61**
25	27	90	25x55	2+2 (6 DP+1 HW)	**142.250.61**
25	36	100	25x55	2+2 (8 DP+1 HW)	**142.251.61**
25	45	110	25x55	2+2 (10 DP+1 HW)	**142.252.61**
25	55	120	25x55	2+2 (12 DP+1 HW)	**142.253.61**

Technical details:
- Super strength steel.
- DP cutting edge.
- HW plunging tip for diagonal plunge-cutting (Z-axis tool entrance).
- Resharpenable cutter (max 3 times).
- Max feed speed 10 m/min.

Application:
to be used on all CNC routers for jointing, rabbeting, grooving, copying and dividing cuts of raw material, melamine and laminates, MDF, HPL and veneered panels.

Diamond Router Cutters with 20° Shear Angle



40X LONGER LIFE THAN CARBIDE

142

DP | Z2+2 | RH

D mm	I mm	L mm	S mm	Z	ORDER NO. Right-hand rotation
20	25	85	20x45	2+2 (8 DP+1 HW)	**142.720.61**
20	30	90	20x45	2+2 (10 DP+1 HW)	**142.721.61**
20	35	95	20x45	2+2 (12 DP+1 HW)	**142.722.61**
20	40	100	20x45	2+2 (14 DP+1 HW)	**142.723.61**
20	45	105	20x45	2+2 (16 DP+1 HW)	**142.724.61**
20	50	110	20x45	2+2 (18 DP+1 HW)	**142.725.61**
20	55	115	20x45	2+2 (20 DP+1 HW)	**142.726.61**

Technical details:
- Super strength steel.
- "H4" diamond cutting edgesf featuring 20° shear angle.
- HW plunging tip for diagonal plunge-cutting (Z-axis tool entrance).
- Resharpenable cutters (max 8-10 times).
- Maximum feed speed 20m/minute.

Application:
used on all CNC routers for jointing, rabbeting, grooving, copying and dividing raw material, melamine, laminated, MDF, HPL and veneered panels.

DP Router Cutters with Shear Angle for Nesting (Densimet® Tungsten Heavy Metal Alloys)

new



40X LONGER LIFE THAN CARBIDE

143

DP | Z3 | RH


D mm	I mm	L mm	S mm	Z	ORDER NO. Right-hand rotation
12	25	70	12x40	3 (9 DP)	**143.120.61**
12	31	80	12x40	3 (12 DP)	**143.121.61**

Technical details:
- Densimet® tungsten heavy metal alloys for low-vibration.
- DP cutting edge.
- Resharpenable cutter (max 6 times).
- Max feed speed 25 m/min.

Application:
to be used on all CNC routers for jointing, rabbeting, grooving, copying and dividing cuts of raw material, melamine and laminates, MDF, HPL and veneered panels.
High performance on pre-and finish-routing.

www.dahm.no

DP Spiral Router Cutters with Shear Angle



143

DP Z3 RH


	D mm	I mm	L mm	S mm	Z	ORDER NO. Right-hand rotation
new	18	25	82	20x50	3 (10 DP+1 HW)	**143.180.61**
new	18	30	87	20x50	3 (13 DP+1 HW)	**143.181.61**
new	18	35	92	20x50	3 (15 DP+1 HW)	**143.182.61**
new	20	25	82	20x50	3 (10 DP+1 HW)	**143.200.61**
new	20	30	85	20x50	3 (13 DP+1 HW)	**143.201.61**
new	20	35	92,5	20x50	3 (15 DP+1 HW)	**143.202.61**
new	20	40	97	20x50	3 (18 DP+1 HW)	**143.203.61**
new	20	45	102	20x50	3 (21 DP+1 HW)	**143.204.61**
new	20	50	106,5	20x50	3 (24 DP+1 HW)	**143.205.61**
new	20	55	111	20x50	3 (27 DP+1 HW)	**143.206.61**
new	20	60	116,5	20x50	3 (30 DP+1 HW)	**143.207.61**
new	20	65	121,5	20x50	3 (31 DP+1 HW)	**143.208.61**
	22	30	92	25x50	3 (12 DP+1 HW)	**143.220.61**
☐	22	35	97	25x50	3 (15 DP+1 HW)	**143.221.61**
	22	40	102	25x50	3 (18 DP+1 HW)	**143.222.61**
☐	22	45	107	25x50	3 (20 DP+1 HW)	**143.223.61**
	22	50	112	25x50	3 (21 DP+1 HW)	**143.224.61**
☐	22	55	117	25x50	3 (24 DP+1 HW)	**143.225.61**
	22	60	122	25x50	3 (30 DP+1 HW)	**143.226.61**
☐	22	65	127	25x50	3 (31 DP+1 HW)	**143.227.61**
☐	22	70	132	25x50	3 (36 DP+1 HW)	**143.228.61**

☐ **On request**

40X LONGER LIFE THAN CARBIDE

TECHNICAL DETAILS:
- Super strength steel.
- DP cutting edge.
- HW plunging tip for diagonal plunge-cutting (Z-axis tool entrance).
- Resharpenable cutter (max 10/12 times).
- Max feed speed 25 m/min.

Diamond Router Cutters with 40° Shear Angle



145

DP Z3 Z4 RH

	D mm	I mm	L mm	S mm	Z	ORDER NO. Right-hand rotation
☐	50	23	80	25x55	3+3 (9 DP)	**145.501.61**
☐	50	23	80	25x55	4+4 (12 DP)	**145.511.61**
☐	50	28	85	25x55	3+3 (15 DP)	**145.502.61**
☐	50	28	85	25x55	4+4 (20 DP)	**145.512.61**
☐	50	38	95	25x55	3+3 (21 DP)	**145.503.61**
☐	50	38	95	25x55	4+4 (28 DP)	**145.513.61**

☐ **On request**

TECHNICAL DETAILS:
- Super strength steel.
-"H4" diamond cutting edgesf featuring 40° shear angle.
- Resharpenable cutters (max 8-10 times).
- Maximum feed speed 30m/minute.

APPLICATION:
used on all CNC routers for jointing, rabbeting, grooving, copying and dividing raw material, melamine, laminated, MDF, HPL and veneered panels. High performance routing.

40X LONGER LIFE THAN CARBIDE

www.dahm.no

Solid Carbide Router Cutters



174


HWM | Z2+1 | RH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
3	10	55	8	**174.030.11**
4	10	55	8	**174.040.11**
5	12	55	8	**174.050.11**
6	14	55	8	**174.060.11**
7	20	55	8	**174.070.11**

Technical details:
- Premium quality HWM.
- 2 radial relief cutting edges [Z2].

Router Cutters





174


HW | Z2+1 | RH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
8	20	55	8	**174.080.11**
8	30	70	8	**174.081.11**
8	40	90	8	**174.082.11**
9	20	55	8	**174.090.11**
10	20	60	8	**174.100.11**
10	30	70	8	**174.102.11**
10	40	90	8	**174.101.11**
11	20	60	8	**174.110.11**
12	20	60	8	**174.120.11**
12	30	70	8	**174.122.11**
12	40	90	8	**174.121.11**
13	20	60	8	**174.130.11**
14	20	60	8	**174.140.11**
14	30	70	8	**174.142.11**
14	40	90	8	**174.141.11**
15	20	60	8	**174.150.11**
16	20	70	8	**174.160.11**
16	30	70	8	**174.162.11**
16	40	90	8	**174.161.11**
18	20	70	8	**174.180.11**
18	30	70	8	**174.181.11**
18	40	80	8	**174.182.11**
19	20	70	8	**174.190.11**
20	20	70	8	**174.200.11**
20	30	70	8	**174.201.11**
20	40	90	8	**174.202.11**
22	20	70	8	**174.220.11**
22	30	70	8	**174.221.11**
22	40	90	8	**174.222.11**
24	20	70	8	**174.240.11**
24	30	70	8	**174.241.11**
24	40	90	8	**174.242.11**
25	20	70	8	**174.250.11**
26	20	70	8	**174.260.11**
26	30	70	8	**174.261.11**
28	20	70	8	**174.280.11**
28	30	70	8	**174.281.11**
29	20	70	8	**174.290.11**
30	20	70	8	**174.300.11**

Technical details:
- Super strength steel.
- 2 precision ground HW cutting edges and 1 HW plunge centre tip [Z2+1].

Application:
used for drilling, grooving or jointing on solid wood and wood composites.
Can be used on machining centres, CNC routers and hand-held routers equipped with chucks or adaptors.

www.dahm.no





112

HW | HWM | Z2+1 | RH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
3	10	48	9,5	**112.030.11**
4	10	48	9,5	**112.040.11**
5	12	39	9,5	**112.050.11**
6	14	41	9,5	**112.060.11**
7	16	43	9,5	**112.070.11**
8	18	48	9,5	**112.080.11**
8	30	60	9,5	**112.081.11**
9	20	52	9,5	**112.090.11**
10*	22	52	9,5	**112.100.11**
10*	35	65	9,5	**112.101.11**
11*	26	52	9,5	**112.110.11**
12*	26	52	9,5	**112.120.11**

*** Super strength steel**
2 precision ground HW cutting edges [Z2+1]

TECHNICAL DETAILS:
- Premium quality HWM.
- 2 radial relief cutting edges [Z2+1].

Router Cutters





113


HW | Z2+1 | RH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
12	26	52	12	**113.120.11**
12	40	70	12	**113.121.11**
13	26	52	12	**113.130.11**
14	28	56	12	**113.140.11**
14	40	72	12	**113.141.11**
15	32	60	12	**113.150.11**
16	32	60	12	**113.160.11**
16	40	72	12	**113.161.11**
17	35	64	12	**113.170.11**
18	35	64	12	**113.180.11**
19	38	68	12	**113.190.11**
20	38	68	12	**113.200.11**
22	40	72	12	**113.220.11**
24	40	72	12	**113.240.11**
25	40	72	12	**113.250.11**
26	42	74	12	**113.260.11**
28	42	74	12	**113.280.11**
30	42	74	12	**113.300.11**

TECHNICAL DETAILS:
- Super strength steel.
- 2 precision ground HW cutting edges and 1 HW plunge centre tip [Z2+1].

APPLICATION:
used for grooving, jointing and routing on solid wood, wood composites, plastic materials and laminates.

www.dahm.no





175

HW | HWM | Z2+1 | RH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
• 4	10	65	10	**175.040.11**
• 5	12	65	10	**175.050.11**
• 6	14	65	10	**175.060.11**
• 7	17	65	10	**175.070.11**
8	20	65	10	**175.080.11**
10	25	70	10	**175.100.11**
12	25	70	10	**175.120.11**
14	25	70	10	**175.140.11**
15	25	70	10	**175.150.11**
16	25	70	10	**175.160.11**
18	25	70	10	**175.180.11**
20	25	70	10	**175.200.11**
22	25	70	10	**175.220.11**
24	25	70	10	**175.240.11**
25	25	70	10	**175.250.11**
26	25	70	10	**175.260.11**
30	25	70	10	**175.300.11**
35	25	70	10	**175.350.11**

• **HWM**

TECHNICAL DETAILS:
- Premium quality HWM.
- 2 radial relief cutting edges [Z2].
- 1 HW [Z1] plunge centre tip.

APPLICATION:
for grooving, jointing and routing on solid wood, wood composites, plastic materials and laminates.

176

HW | Z2+1 | RH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
10	40	87	10	**176.100.11**
12	40	87	10	**176.120.11**
14	40	87	10	**176.140.11**
15	40	87	10	**176.150.11**
16	40	87	10	**176.160.11**
18	40	87	10	**176.180.11**
20	40	87	10	**176.200.11**




177

HW | Z2+1 | RH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
10	35	90	12	**177.100.11**
12	35	90	12	**177.120.11**
12	50	100	12	**177.121.11**
14	35	90	12	**177.140.11**
16	35	90	12	**177.160.11**
16	60	110	12	**177.161.11**
18	35	90	12	**177.180.11**
18	60	110	12	**177.181.11**
20	35	90	12	**177.200.11**
22	35	90	12	**177.220.11**
24	35	90	12	**177.240.11**
25	35	90	12	**177.250.11**
26	35	90	12	**177.260.11**
28	35	90	12	**177.280.11**
30	35	90	12	**177.300.11**
35	35	90	12	**177.350.11**


TECHNICAL DETAILS:
- Super strength steel.
- 2 precision ground HW cutting edges and 1 HW plunge centre tip [Z2+1].

APPLICATION:
used for grooving, jointing and general routing operation on solid wood, wood composites, plastics and laminates. Can be used on machining centres, CNC routers and hand-held routers.



www.dahm.no

Straight Router Cutters with Insert Knives



653

INSERT CARBIDE | Z1+1 | RH | 2X LONGER LIFE

D mm	I mm	L mm	S mm	Spare knives side	Spare knives top	ORDER NO. Right-hand rotation
16	28,3	92	20	790.283.12	790.075.00	**653.661.11**
16	48,3	111,5	20	790.483.12	790.075.00	**653.662.11**
18	48,3	111,5	20	790.483.12	790.075.00	**653.681.11**
20	48,3	111,5	20	790.483.12	790.096.00	**653.701.11**

Spare parts

790.075.00	7,5x12x1,5mm knife
790.096.00	9,6x12x1,5mm knife
790.283.12	28,3x12x1,5mm knife
790.483.12	48,3x12x1,5mm knife
990.072.00	M3,5x3,5mm Torx screw
990.074.00	M4x3,5mm Torx screw
990.075.00	M4x6mm Torx screw
991.061.00	T15 Torx key

TECHNICAL DETAILS:
- Super strength steel.
- 2 cutting edges [Z1+1].

APPLICATION:
straight router bit with one replaceable plunging knife and one-sided knife fixed by special Torx screws. The body is precision balanced. For finishing and routing, plunge cutting and grooving in board materials (laminated chipboards, MDF) and hardwood.
For use on CNC machining centres.

Spoilboard Surfacing Router Cutters with Insert Knives

new



663

INSERT CARBIDE | Z3 | RH | 4X LONGER LIFE

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	Spare parts	
60	12	80	12x50	**663.004.11**	790.120.03	990.075.00
80	12	90	20x60	**663.003.11**	790.120.03	990.075.00

Spare parts


991.061.00	T15 Torx key
990.036.00	M8x25mm TE screw (only for 663.003.11)
990.020.00	Hex nut for threaded arbors M8 (only for 663.003.11)

The screw 990.036.00 and the nut 990.020.00 (on the shank) only fit item 663.003.11

TECHNICAL DETAILS:
- Super strength steel.
- 3 cutting edges [Z3].

APPLICATION:
the new router bit for CNC routers is ideal for fast removal of material over a large surface area leaving an improved finish at the bottom of the cut.
Used on soft and hardwood, particle board and MDF.
The cutter uses 4-sided inserts in super micrograin carbide.


A cost effective solution compared to brazed router bits and solid carbide spiral bits.



Drawings are 1:2 scale

www.dahm.no

Adjustable Chamfering CNC Cutter



663.201.11

INSERT CARBIDE | Z2 | RH | 2X LONGER LIFE


D mm	D_Max 45° mm	I mm	A	L mm	S mm	ORDER NO. Right-hand rotation
85	102	39,5	0°-45° - 0°+90°	92	20	**663.201.11**

Spare parts


790.395.12	39,5x12x1,5mm knife
663.999.01	38x6x12mm wedge
990.087.00	M6x8mm STEI screw (4x2mm threaded pin)
991.067.00	3mm hex key
663.999.02	Kit with 2 wedges and 1 screw for blocking rotation
990.099.00	M8x25mm TCEI screw
990.023.00	M8 (4mm) nut
991.081.00	4mm "T" hex key

TECHNICAL DETAILS: tool body in steel, two TC reversible knives in swiveling blade carriers. Cutting on periphery and both sides. Swiveling range towards top 0-45°, toward bottom 0-90°, infinitely variable adjustment according to precise scale. With positive stops at 7,5° through adjustment aide. No displacement of adjusted beveling angle when replacing blades. Righ-hand rotation.

APPLICATION:
for jointing, rebating and chamfering of solid wood and wooden boards. Suitable for CNC router machines and stationary router machine with manual or mechanical feed.



V-Groove - Folding - Signmaking CNC Router Cutters with Insert Knives



663.101.11

INSERT CARBIDE | Z1 | RH | 2X LONGER LIFE

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
52	25	100	20	**663.101.11**

Spare parts


790.360.01	36x12x1,5mm knife
990.077.00	M3,5x7mm Torx screw
991.061.00	T15 Torx key

Optional

S790.360.03	36x12x1,5mm HW-SMG replaceable knife (4 cutting edges 35°)

TECHNICAL DETAILS:
- Super Strength steel.
- 1 cutting edges [Z1].

APPLICATION:
this innovative CNC router bit offers you an endless range of possibilities for V-Groove, miter folds, signmaking, lettering and chamfer edges. The tool mounts a high grade HWM reversible knife ideal for general purpose, chipboard and plywood, but a higher quality is available for laminated and MDF material.



Drawings are 1:2 scale

www.dahm.no





616.000.01

INSERT CARBIDE | Z2 | RH

This unique system includes a tool body with 22 profile knives designed for multiple applications on your CNC routers. Ideal for MDF, laminates, veneers, plastic, wood and solid surface materials.

TECHNICAL DETAILS:
- Knives 20x20x2mm.
- We recommend re-sharpened that knives be on the profiled cutting edges.





Drawings are 1:1 scale

DESCRIPTION	S mm	ORDER NO. Right-hand rotation	Spare parts		
Complete Set for Decorating on MDF	20	**616.000.01**	616.200	990.077.00	991.061.00
Router cutter body with shank Ø20mm (insert knives not included)	20	**616.200**		990.077.00	991.061.00
new Router cutter body with shank Ø12mm (insert knives not included)	12	**616.120**		990.077.00	991.061.00

REMARK: tool body and insert knives can be sold individually.

www.dahm.no

Complete Set for MDF Doors

CMT ORANGE TOOLS



615.004.01


INSERT CARBIDE | Z2 | RH

Open some new doors with CMT. Our 4-piece set includes the most popolar profile to make MDF panel doors for kitchens and bathrooms. Each bit is made from bar stock steel and is equipped with 5 differents profile knives allowing enormous possibilities for easy and economical construction. The highest materials, the lowest tolerance in balancing and the precision in the sharpening of the knives let you obtain a smooth finish on your CNC machine.


Spare parts

991.061.00	T15 Tork key
990.073.00	M3,5x5mm Torx screw
990.075.00	M4x6mm Torx screw
990.077.00	M3,5x7mm Torx screw





Standard Profile No. 1





Drawings are 1:1 scale


DESCRIPTION		S mm	ORDER NO. Right-hand rotation
Complete Set for MDF Doors	(Profile no. 1)	20	**615.004.01**


www.dahm.no

Optional









Drawings are 1:1 scale

www.dahm.no

Universal Profile Cutter for CNC Machines

new

CMT ORANGE TOOLS



663.301.11

SP Z2 RH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
65	40-50	93	20	**663.301.11**

Spare parts


692.999.01	38x15x16mm wedge for cutter
990.068.00	M5x5mm TCEI screw
991.064.00	Hex key 4mm

Technical details:
- Super Strength steel.
- 2 cutting edges [Z2] for knives 40x4mm and 50x4mm.

Application:
for universal profiling of solid wood on CNC router machines. For cutting width 40mm and 50mm (serie 690).
Profile knives may only be ordered and used in pairs.
For router machines with mechanical feed.



To be used with SP knives serie 690 (see pages 96~109)



Profile knives cutting length=40mm (serie 690)

Profile knives cutting length=50mm (serie 690.5)

Slot & Mortise Boring Bits



163

HW Z2 RH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	
12	100	M12x1		**163.120.11**	
14	100	M12x1		**163.140.11**	
16	100	M12x1		**163.160.11**	

Technical details:
- Super strength steel.
- 2 HW precision ground cutting edges [Z2].

Application:
used for cutting mortises and slots in solid wood and wood composites. Assembled in chucks.

163

HL Z2 RH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	
12	100	M12x1		**163.120.31**	
14	100	M12x1		**163.140.31**	
16	100	M12x1		**163.160.31**	
18	100	M12x1		**163.180.31**	

Technical details:
- Long lasting cutter performance.
- 2 HL precision ground cutting edges [Z2].

Application:
used for cutting mortises and slots in solid wood and wood composites. Assembled in chucks.

www.dahm.no



164

HW Z2 V2 RH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	
18	100	M12x1		**164.180.11**	
20	100	M12x1		**164.200.11**	
22	100	M12x1		**164.220.11**	

TECHNICAL DETAILS:
- Super strength steel.
- HW cutting head with precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- 2 negatively ground spurs [V2].

APPLICATION:
used for drilling blind holes in solid wood, wood composites, plastic and laminated materials. Used on slot and mortise machines equipped with chucks.

164


HL Z2 V2 RH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	
15	100	M12x1		**164.150.31**	
18	100	M12x1		**164.180.31**	
20	100	M12x1		**164.200.31**	
24	100	M12x1		**164.240.31**	

TECHNICAL DETAILS:
- Long lasting cutter performance.
- HL cutting head with precision balanced centre point.
- 2 precision ground edges [Z2].
- 2 ground spurs [V2].

APPLICATION:
used for drilling blind holes in soft and hardwood. Used on slot and mortise machines equipped with chucks.

Slot & Mortise Boring Bits



166-167

HW Z2 V2 RH

d mm	D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
11	19	62	155	M12x1	**166.190.11**
11	22	62	155	M12x1	**166.220.11**
12	19	62	155	M12x1	**167.190.11**
12	24	62	155	M12x1	**167.240.11**

TECHNICAL DETAILS:
- Super strength steel.
- 2 HW precision ground cutting edges [Z2].
- 2 negatively ground spurs [V2].

APPLICATION:
used for drilling and cutting mortise slots in solid wood, wood composites, plastic and laminated materials.

www.dahm.no

Slot Mortising Bits with Chip-Breaker



102

HL Z2R RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
6	50	105	16	**102.060.31**	**102.060.32**
7	55	110	16	**102.070.31**	**102.070.32**
8	60	115	16	**102.080.31**	**102.080.32**
9	65	120	16	**102.090.31**	**102.090.32**
10	70	125	16	**102.100.31**	**102.100.32**
11	75	130	16	**102.110.31**	**102.110.32**
12	80	135	16	**102.120.31**	**102.120.32**
13	85	140	16	**102.130.31**	**102.130.32**
14	90	145	16	**102.140.31**	**102.140.32**
15	95	150	16	**102.150.31**	**102.150.32**
16	100	155	16	**102.160.31**	**102.160.32**
17	105	160	16	**102.170.31**	**102.170.32**
18	110	165	16	**102.180.31**	**102.180.32**
19	115	170	16	**102.190.31**	**102.190.32**
20	120	175	16	**102.200.31**	**102.200.32**
22	125	180	16	**102.220.31**	**102.220.32**
24	125	180	16	**102.240.31**	**102.240.32**


172

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
6	50	105	13	**172.060.31**	**172.060.32**
7	55	110	13	**172.070.31**	**172.070.32**
8	60	115	13	**172.080.31**	**172.080.32**
9	65	120	13	**172.090.31**	**172.090.32**
10	70	125	13	**172.100.31**	**172.100.32**
11	75	130	13	**172.110.31**	**172.110.32**
12	80	135	13	**172.120.31**	**172.120.32**
13	85	140	13	**172.130.31**	**172.130.32**
14	90	145	13	**172.140.31**	**172.140.32**
15	95	150	13	**172.150.31**	**172.150.32**
16	100	155	13	**172.160.31**	**172.160.32**
18	110	165	13	**172.180.31**	**172.180.32**
20	120	175	13	**172.200.31**	**172.200.32**

Technical details:
- Long-lasting cutting performance.
- 2 HL precision ground straight cutting edges with chip-breaker teeth [Z2R].

Application:
for cutting mortise slots in soft and hardwood. Used on machining centres equipped with chucks.

Machining Deep Slots Guide





6-Piece Mortising Bit Sets


102-172

HL Z2R RH LH

Ideal for heavy mortise jobs.
Made of super strength high speed steel and available in left-hand or right-hand rotation.
Safely packaged in a hardwood and glass box for protection, these sets are economical and a perfect addition to any workshop.

S mm	D mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
16	6-8-10-12-14-16	**102.001.00**	**102.001.10**
13	6-8-10-12-14-16	**172.001.00**	**172.001.10**

www.dahm.no



161

HS Z2R RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
6	60	120	16	**161.060.31**	**161.060.32**
8	70	130	16	**161.080.31**	**161.080.32**
10	80	140	16	**161.100.31**	**161.100.32**
12	90	150	16	**161.120.31**	**161.120.32**
14	100	160	16	**161.140.31**	**161.140.32**
16	110	170	16	**161.160.31**	**161.160.32**

160


HS Z2R RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
6	60	120	13	**160.060.31**	**160.060.32**
8	70	130	13	**160.080.31**	**160.080.32**
10	80	140	13	**160.100.31**	**160.100.32**
12	90	150	13	**160.120.31**	**160.120.32**
14	100	160	13	**160.140.31**	**160.140.32**
16	110	170	13	**160.160.31**	**160.160.32**

TECHNICAL DETAILS:
- Long-lasting cutting performance.
- 2 HS precision ground twisted cutting edges with chip-breaker teeth [Z2R].

APPLICATION:
for cutting mortise slots in soft and hardwood.
Used on machining centres equipped with chucks.
RPM 3000~5000

MACHINING DEEP SLOTS GUIDE



6-Piece Mortising Bit Sets



160-161

HS Z2R RH LH


Ideal for heavy mortise jobs.
Made of super strength high speed steel and available in left-hand or right-hand rotation.
Safely packaged in a hardwood and glass box for protection, these sets are economical and a perfect addition to any workshop.

S mm	D mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
16	6-8-10-12-14-16	**161.001.00**	**161.001.10**
13	6-8-10-12-14-16	**160.001.00**	**160.001.10**

www.dahm.no

Reciprocating Slot Mortising Bits

CMT ORANGE TOOLS



104


HL Z4 LH RH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand & Left-hand rotation
6	45	100	13	**104.060.30**
7	45	100	13	**104.070.30**
8	45	100	13	**104.080.30**
9	45	100	13	**104.090.30**
10	55	110	13	**104.100.30**
11	55	110	13	**104.110.30**
12	55	110	13	**104.120.30**
13	55	110	13	**104.130.30**
14	55	110	13	**104.140.30**
15	55	110	13	**104.150.30**
16	55	110	13	**104.160.30**

Technical details:
- Long-lasting cutting performance.
- 4 HL precision ground cutting edges [Z4].

Application:
used for cutting mortise slots in soft and hardwood.
Used on machining centres equipped with chucks.

Reciprocating Slot Mortising Bits



105


HL Z4 LH RH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand & Left-hand rotation
6	28	73	10	**105.060.30**
7	28	73	10	**105.070.30**
8	28	73	10	**105.080.30**
9	28	73	10	**105.090.30**
10	28	73	10	**105.100.30**
11	28	73	10	**105.110.30**
12	28	73	10	**105.120.30**
13	28	73	10	**105.130.30**
14	28	73	10	**105.140.30**
15	28	73	10	**105.150.30**
16	28	73	10	**105.160.30**

Technical details:
- Long-lasting cutting performance.
- 4 HL precision ground cutting edges [Z4].

Application:
used for cutting mortise slots in soft and hardwood.
Used on machining centres equipped with chucks.

www.dahm.no



103


HL Z2 LH RH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand & Left-hand rotation
6	45	100	16	**103.060.30**
7	45	100	16	**103.070.30**
8	45	100	16	**103.080.30**
9	45	100	16	**103.090.30**
10	55	110	16	**103.100.30**
11	55	110	16	**103.110.30**
12	55	110	16	**103.120.30**
13	55	110	16	**103.130.30**
14	55	110	16	**103.140.30**
15	55	110	16	**103.150.30**
16	55	110	16	**103.160.30**

TECHNICAL DETAILS:
- Long-lasting cutter performance.
- 2 HL precision ground cutting edges [Z2].

APPLICATION:
used for cutting mortise slots in soft and hardwood.
Used on machining centres equipped with chucks.

Reciprocating Slot Mortising Bits



179

HS Z2 LH RH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand & Left-hand rotation
6	45	90	13	**179.060.50**
7	50	95	13	**179.070.50**
8	50	95	13	**179.080.50**
9	55	100	13	**179.090.50**
10	60	105	13	**179.100.50**
11	65	110	13	**179.110.50**
12	70	115	13	**179.120.50**
13	75	120	13	**179.130.50**

TECHNICAL DETAILS:
- Long-lasting cutter performance.
- 2 HS precision ground cutting edges [Z2].

APPLICATION:
used for cutting mortise slots in soft and hardwood.
Used on machining centres equipped with chucks.

www.dahm.no

Reciprocating Slot Mortising Bits




106

HL | Z2 | Z4 | LH RH

D mm	I mm	L mm	S mm	Z	ORDER NO. Right-hand & Left-hand rotation
6	25	60	12	2	**106.060.30**
7	25	60	12	2	**106.070.30**
8	25	60	12	2	**106.080.30**
9	25	60	12	2	**106.090.30**
10	25	60	12	4	**106.100.30**
11	25	60	12	4	**106.110.30**
12	25	60	12	4	**106.120.30**
13	25	60	12	4	**106.130.30**
14	25	60	12	4	**106.140.30**
15	25	60	12	4	**106.150.30**

Technical details:
- Long-lasting cutter performance.
- 2 or 4 HL precision ground cutting edges [Z2-Z4].

Slot Mortising Bits



107

HL | Z3 | RH | LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
6	55	110	16	**107.060.31**	**107.060.32**
8	55	110	16	**107.080.31**	**107.080.32**
10	55	110	16	**107.100.31**	**107.100.32**
12	55	110	16	**107.120.31**	**107.120.32**
14	60	115	16	**107.140.31**	**107.140.32**
16	60	115	16	**107.160.31**	**107.160.32**
18	60	115	16	**107.180.31**	**107.180.32**
20	60	115	16	**107.200.31**	**107.200.32**

Technical details:
- Long-lasting cutter performance.
- 3 HL precision ground cutting edges [Z3].

Application:
used for cutting mortise slots in soft and hardwood.
Used in maching centres equipped with chucks.


www.dahm.no



Industrial Dowel Drills

PRODUCTS	PAGE
Adaptors	254~256
XTreme Solid Carbide Boring Bits	258-259
XTreme Boring Bits	260-261
Solid Carbide Twist Drills	262-263
2 Flute Dowel Drills	264-265
4 Flute Dowel Drills	266~268
Dowel Drills with Countersink	269
Through Hole Dowel Drills	270-271
Countersinks	272
Hinge Boring Bits	273-274
Dowel Drills with Threaded Shank	275~277

Adaptors



301

RH LH


B mm	D mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
8	16	M8		**301.080.01**	**301.080.02**
10	19,5	M8		**301.000.01**	**301.000.02**

For use on the following machines:
Nottmeyer (older models).

Spare parts



990.006.00 991.062.00



302

RH LH

B mm	D mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
8	16	M10		**302.080.01**	**302.080.02**
10	19,5	M10		**302.000.01**	**302.000.02**

For use on the following machines:
Ayen, Holzma, Knoevenagel, Mayer, Torwegge.

Spare parts



990.006.00 991.062.00



303

RH LH

B mm	D mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
8	16	M10/30°		**303.080.01**	**303.080.02**
10	19,5	M10/30°		**303.000.01**	**303.000.02**

For use on the following machines:
Alberti (older models).
Balestrini, Bilek, Busellato (older models).
Schleicher, Vitap (older models).

Spare parts



990.006.00 991.062.00



304

RH LH

B mm	D mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
8	16	M8/20° 48'		**304.080.01**	**304.080.02**
10	19,5	M8/20° 48'		**304.000.01**	**304.000.02**


For use on the following machines:
Balestrini, Bilek.

Spare parts



990.006.00 991.062.00

www.dahm.no




305

RH LH

B mm	D mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
8	16	M10/11		**305.080.01**	**305.080.02**
10	19,5	M10/11		**305.000.01**	**305.000.02**

For use on the following machines:
Biesse (older models).
Masterwood (Zangheri & Boschetti).
Morbidelli, Torwegge, Vitap (new design).
Weeke.

Spare parts
990.006.00 991.062.00



358

RH LH

B mm	D mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
8	16	M8/9		**358.080.01**	**358.080.02**
10	19,5	M8/9		**358.000.01**	**358.000.02**

For use on the following machines:
Masterwood (Zangheri & Boschetti).
Morbidelli, Nottmeyer (new design).

Spare parts
990.006.00 991.062.00



359

RH LH

B mm	D mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
10	19,5	M10		**359.000.01**	**359.000.02**

For use on the following machines:
Scheer.

Spare parts
990.006.00 991.062.00



360.001

RH LH

B mm	D mm			ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
10	20			**360.001.01**	**360.001.02**

For use on the following machines:
For Biesse machines with quick drill change attachment.

Spare parts
990.007.00 991.067.00

www.dahm.no



360.101

RH LH

B mm	D mm	ORDER NO. Right-hand & Left-hand rotation
10	18	360.101.00

For use on the following machines:
Vitap.

Spare parts
990.015.00 991.062.00



360.201

RH LH

B mm	D mm	ORDER NO. Right-hand & Left-hand rotation
10	19,25	360.201.00

For use on the following machines:
Morbidelli.

Spare parts
990.009.00 991.067.00



360.301

RH LH

B mm	D mm	ORDER NO. Right-hand & Left-hand rotation
10	19,4	360.301.00

For use on the following machines:
Masterwood, Maggi, Griggio.

Spare parts
990.015.00 991.062.00



360.401

RH LH

B mm	D mm	ORDER NO. Right-hand & Left-hand rotation
10	20	360.401.00

For use on the following machines:
Weeke.

Spare parts
990.009.00 991.067.00



990.088

RH LH


DESCRIPTION	ORDER NO. Right-hand & Left-hand rotation
Retaining screw for Weeke machines	990.088.00

www.cmtutensili.com
www.dahm.no


XTREME BORING BITS

Setting a new standard for performance and value

NEW DOWNCUT ROUND SHARPENING




EXTRA-FINE MICROGRAIN CARBIDE




Reduced boring surface for faster feed speed



STANDARD SHARPENING



STANDARD CARBIDE



Standard boring surface

The Finest Industrial Quality Micrograin Carbide

CMT makes the finest quality cutting edges. Produced by Ceratizit in Luxembourg, CMT's carbide tips are selected among many carbide grades to ensure longer endurance and higher impact resistance.

Micrograin Carbide Sharpening

Sharpening on the carbide cutting edges provides a 0,4µ/mm micrograin finish. This is processed on automated CNC machines equipped with as many as 6 axes for maximum accuracy

P.T.F.E. Coating

CMT's P.T.F.E. coating provides a non-stick surface preventing any residue accumulation on the bit body. Baked on at 420°, this unique industrial material is specifically designed to fit woodworking tool requirements.

Special Metal Shock Resistant Brazing

Micrograin carbide tips are applied with a special brazing compound. This allows a higher brazing temperature than other methods and guarantees a solid bond of every tip on every bit.

Highly-Resistant Steel Body

Our bit bodies and shanks are machined from solid bar stock steel made by Von Moos Steel in Switzerland. The main mechanical properties are:

- superior strength
- high level uniformity
- minimal distortion
- exceptional resistance to fatigue and abrasion.


Steel Shank Grinding

CMT grinds the steel shank to a micrograin finish of 0,8µ/mm. The smooth finish on the shank determines how well the drills fit into your machine.
Rough grinding results in a poor chuck grip and in a poor wobbly rotation.

www.dahm.no

Solid Carbide Dowel Drills

CMT ORANGE TOOLS




310.21/22 XTREME

HWM | LONG LIFE | Z2 | V2 | RH | LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
1,3	5	57,5	10x30	**310.013.20***	
2	12	57,5	10x27	**310.020.21**	**310.020.22**
3	9	57,5	10x35	**310.530.21**	**310.530.22**
3	18	57,5	10x25	**310.030.21**	**310.030.22**
4	20	57,5	10x25	**310.040.21**	**310.040.22**
5	22	57,5	10x27	**310.050.21**	**310.050.22**
6	22	57,5	10x25	**310.060.21**	**310.060.22**
6,35 (1/4")	22	57,5	10x25	**310.064.21**	**310.064.22**
8	22	57,5	10x25	**310.080.21**	**310.080.22**
new 10	22	57,5	10x25	**310.100.21**	**310.100.22**

*** Boring bit for panel preboring.**
Suitable for both right-hand and left-hand rotation.

Spare parts: 990.003.00 — Optional: 990.088.00




311.21/22 XTREME

HWM | LONG LIFE | Z2 | V2 | RH | LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
1,3	5	70	10x45	**311.013.20***	
2	12	70	10x40	**311.020.21**	**311.020.22**
3	18	70	10x40	**311.030.21**	**311.030.22**
4	27	70	10x28	**311.040.21**	**311.040.22**
5	30	70	10x30	**311.050.21**	**311.050.22**
6	30	70	10x30	**311.060.21**	**311.060.22**
6,35 (1/4")	30	70	10x30	**311.064.21**	**311.064.22**
8	35	70	10x25	**311.080.21**	**311.080.22**
new 10	35	70	10x25	**311.100.21**	**311.100.22**

*** Boring bit for panel preboring.**
Suitable for both right-hand and left-hand rotation.

Spare parts: 990.003.00 — Optional: 990.088.00



XTreme Sharpening

TECHNICAL DETAILS:
- Premium quality super-strength steel.
- HWM spiral portion with centre point.
- 2 cutting edges [Z2].
- 2 spiral flutes.
- 2 curved, negatively ground spurs [V2].
- Parallel shank with driving flat and adjustable screw length.

APPLICATION:
used on boring machines separately or with chucks for drilling blind holes in solid wood, wood composites, plastic and laminated materials.


Perfect for all materials and long-lasting performance!

Grinding Wheels for XTreme Sharpening




01.02


D mm	DESCRIPTION	DIMENSION mm	B mm	ORDER NO.
Ø3 a 7	Grinding wheel for resharpening	Ø125x5,5	Ø20	**01.02.0316**
Ø8 a 10	Grinding wheel for resharpening	Ø125x7	Ø20	**01.02.0317**



www.dahm.no

Solid Carbide Dowel Drills for Through Holes





XTreme Sharpening

314.21/22

HWM LONG LIFE Z2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
3	27	70	10x30	**314.030.21**	**314.030.22**
4	35	70	10x26	**314.040.21**	**314.040.22**
5	35	70	10x26	**314.050.21**	**314.050.22**
6	35	70	10x26	**314.060.21**	**314.060.22**
8	35	70	10x26	**314.080.21**	**314.080.22**
new 10	35	70	10x27	**314.100.21**	**314.100.22**

For panels with maximum 20-30mm in thickness

Spare parts 990.008.00


Optional 990.088.00

TECHNICAL DETAILS:
- Premium quality super-strength steel.
- HWM spiral portion with centre point.
- 2 precision ground cutting edges [Z2].
- Double angle.
- 2 spiral flutes.
- Parallel shank with driving flat and adjustable screw length.

APPLICATION:
used on boring machines and dowel drilling devices.
Use for drilling through holes in solid wood, wood composites, plastic and laminated materials.

Solid Carbide Dowel Drills

new



382

HWM LONG LIFE Z1 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand & Left-hand rotation
2	12	57,5	10x30	**382.2057**
2	12	70	10x42,5	**382.2070**
2,5	16	57,5	10x24	**382.2557**
2,5	16	70	10x35	**382.2570**
3	15	57,5	10x26	**382.3057**
3	25	70	10x26	**382.3070**
3,5	18	57,5	10x24	**382.3557**
3,5	18	70	10x36	**382.3570**
5	25	57,5	10x25	**382.5057**
5	35	70	10x25	**382.5070**

Spare parts 990.003.00

Optional 990.088.00

TECHNICAL DETAILS:
- Premium quality HWM.
- Cutting head with precision balanced centre point.
- 1 cutting edge [Z1].
- Parallel shank with driving flat and length adjusting screw.


APPLICATION:
for drilling blind holes on solid wood, wood composites, plastic and laminated materials. For use on machining centres, point to point machines, CNC routers and hand-held routers equipped with chucks or adaptors.

SECURITY TIPS:
these boring bits require more power compared to tradition dowel drills. The number of boring bits to be used in a single drilling unit depends on the machine power.

www.dahm.no

Dowel Drills

CMT ORANGE TOOLS



310.41/42 XTREME

HW LONG LIFE Z2 V2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	27	57,5	10x27	**310.050.41**	**310.050.42**
6	27	57,5	10x27	**310.060.41**	**310.060.42**
7	27	57,5	10x27	**310.070.41**	**310.070.42**
8	27	57,5	10x27	**310.080.41**	**310.080.42**
9	27	57,5	10x27	**310.090.41**	**310.090.42**
10	27	57,5	10x27	**310.100.41**	**310.100.42**


TECHNICAL DETAILS:
- Premium quality super-strength steel.
- Spiral portion coated with orange or black P.T.F.E.
- Extra-fine micrograin carbide spiral portion with centre point.
- 2 cutting edges [Z2].
- 2 spiral flutes.
- 2 curved, negatively ground spurs [V2].
- Parallel shank with driving flat and adjustable screw length.

Spare parts
990.003.00

Optional
990.088.00

APPLICATION:
used on boring machines separately or with chucks for drilling blind holes in solid wood, wood composites, plastic and laminated materials.

Dowel Drills



311.41/42 XTREME

HW LONG LIFE Z2 V2 RH LH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	35	70	10x30	**311.050.41**	**311.050.42**
6	35	70	10x30	**311.060.41**	**311.060.42**
7	35	70	10x30	**311.070.41**	**311.070.42**
8	35	70	10x30	**311.080.41**	**311.080.42**
9	35	70	10x30	**311.090.41**	**311.090.42**
10	35	70	10x30	**311.100.41**	**311.100.42**

TECHNICAL DETAILS:
- Premium quality super-strength steel.
- Spiral portion coated with orange or black P.T.F.E.
- Extra-fine micrograin carbide spiral portion with centre point.
- 2 cutting edges [Z2].
- 2 spiral flutes.
- 2 curved, negatively ground spurs [V2].
- Parallel shank with driving flat and adjustable screw length.

Spare parts
990.003.00

Optional
990.088.00

APPLICATION:
used on boring machines separately or with chucks for drilling blind holes in solid wood, wood composites, plastic and laminated materials.



XTreme Sharpening


Perfect for all materials and long-lasting performance!

CMT announces the new series of solid carbide boring bits, now available from their extensive industrial line. These bits are entirely made of premium quality super micrograin carbide from Ceratizit in Luxemburg.

The entire series offers several design features:
- the unique tip has curved, negatively ground spurs to produce exceptionally clear bores with no rough edges. Centre point balanced;
- the cylindrical head is bigger than traditional tips and is extremely resistant to prolonged use.

It lasts longer between sharpenings;
- the plunge edge runs all the way to the centre of the bit to reduce drilling resistance and increase production speed;
- the solid carbide construction guarantees an almost infinite number of resharpenings, and since it is a solid unit of carbide, it offers extra safety features;
- ideal for hardwood and difficult composites such as particle boards, MDF and veneered wood.
- excellent performance on high-speed boring units and CNC routers.

www.dahm.no



313.41/42

HW LONG LIFE Z2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	27	57,5	10x26	**313.050.41**	**313.050.42**
8	27	57,5	10x26	**313.080.41**	**313.080.42**

For panels with maximum 20mm in thickness


Spare parts 990.003.00

Optional 990.088.00

TECHNICAL DETAILS:
- Super-strength steel.
- Spiral portion coated with orange or black P.T.F.E.
- Extra-fine micrograin carbide spiral portion with centre point.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- Double angle.
- 2 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.

APPLICATION:
used on boring machines and dowel drilling devices. Use for drilling through holes in solid wood, wood composites, plastic and laminated materials.

Dowel Drills for Through Holes



314.41/42

HW LONG LIFE Z2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	35	70	10x26	**314.050.41**	**314.050.42**
6	35	70	10x26	**314.060.41**	**314.060.42**
7	35	70	10x26	**314.070.41**	**314.070.42**
8	35	70	10x26	**314.080.41**	**314.080.42**
10	35	70	10x26	**314.100.41**	**314.100.42**


For panels with maximum 30mm in thickness

Spare parts 990.003.00

Optional 990.088.00

TECHNICAL DETAILS:
- Super-strength steel.
- Spiral portion coated with orange or black P.T.F.E.
- Extra-fine micrograin carbide spiral portion with centre point.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- Double angle.
- 2 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.

APPLICATION:
used on boring machines and dowel drilling devices. Use for drilling through holes in solid wood, wood composites, plastic and laminated materials.



XTreme Sharpening

Perfect for all materials and long-lasting performance!


CMT announces the new series of solid carbide boring bits, now available from their extensive industrial line. These bits are entirely made of premium quality super micrograin carbide from Ceratizit in Luxemburg.

The entire series offers several design features:
- the unique tip has curved, negatively ground spurs to produce exceptionally clear bores with no rough edges. Centre point balanced;
- the cylindrical head is bigger than traditional tips and is extremely resistant to prolonged use.

It lasts longer between sharpenings;
- the plunge edge runs all the way to the centre of the bit to reduce drilling resistance and increase production speed;
- the solid carbide construction guarantees an almost infinite number of resharpenings, and since it is a solid unit of carbide, it offers extra safety features;
- ideal for hardwood and difficult composites such as particle boards, MDF and veneered wood.
- excellent performance on high-speed boring units and CNC routers.

www.dahm.no

Adaptors for Twist Drills



364

B mm	L mm	S mm		ORDER NO.	
2	38	10x20		364.020.00	
2,5	38	10x20		364.025.00	
3	38	10x20		364.030.00	
3,2	38	10x20		364.032.00	
3,5	38	10x20		364.035.00	
4	38	10x20		364.040.00	
4,5	38	10x20		364.045.00	
5	38	10x20		364.050.00	

For use with the following items: 363 HWM

Spare parts



990.001.00 991.062.00

Technical details:
- Super-strength steel.
- Quick and secure assembly on twist drills.
- Precision relief.
- Parallel shank with driving flat and length adjusting screw.

Application:
for use with twist drills with common shank and bushing diameter.
Used on boring machines equipped with adaptor chucks.

Bushings for Twist Drills



365

B mm	L mm	S mm		ORDER NO.	
2	23	10		365.020.00	
2,5	23	10		365.025.00	
3	23	10		365.030.00	
3,2	23	10		365.032.00	
3,5	23	10		365.035.00	
4	23	10		365.040.00	
4,5	23	10		365.045.00	
5	23	10		365.050.00	


For use with the following items: 363 HWM


Technical details:
- Super-strength steel.
- Shank with driving flat.
- Axial cuttings for cylindrical drill clamps.

Application:
used with spiral boring bits with shank diameters equal to the bushing diameter.
Used on boring machines equipped with adaptors.

www.dahm.no

Solid Carbide Twist Drills “V” Point Sharpening





“V” Point 120°




“V” Point 60°


363

HWM LONG LIFE Z2 RH LH

S=D mm	I mm	L mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
120° Through Holes					
2	25	50		**363.020.11**	**363.020.12**
2,5	27	55		**363.025.11**	**363.025.12**
3	27	55		**363.030.11**	**363.030.12**
3,2	27	55		**363.032.11**	**363.032.12**
3,5	27	55		**363.035.11**	**363.035.12**
4	27	55		**363.040.11**	**363.040.12**
4,5	28	60		**363.045.11**	**363.045.12**
5	28	60		**363.050.11**	**363.050.12**
60° Through Hole					
2,5	27	55	new	**363.025.41**	**363.025.42**
3	27	55	new	**363.030.41**	**363.030.42**
3,5	27	55	new	**363.035.41**	**363.035.42**
4	27	55	new	**363.040.41**	**363.040.42**

Solid Carbide Twist Drills Negatively Ground Spurs Sharpening





X-Treme Sharpening

363

HWM LONG LIFE Z2 RH LH

S=D mm	I mm	L mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
2,5	27	55		**363.025.21**	**363.025.22**
3	27	55		**363.030.21**	**363.030.22**
4	27	55		**363.040.21**	**363.040.22**
5	28	60		**363.050.21**	**363.050.22**

For use with the following items: 364-365

TECHNICAL DETAILS:
- Premium quality HWM.
- 2 precision ground cutting edges [Z2].
- 2 spiral flutes.
- Common shank and drilling diameter (S=D).

APPLICATION:
used in adaptor bushings.


Assembly Illustration



www.dahm.no

2 Flute Dowel Drills

CMT ORANGE TOOLS



310

HW Z2 V2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
4	27	57,5	10x27	**310.040.11**	**310.040.12**
4,5	27	57,5	10x27	**310.045.11**	**310.045.12**
4,76	27	57,5	10x27	**310.047.11**	**310.047.12**
5	27	57,5	10x27	**310.050.11**	**310.050.12**
5,1	27	57,5	10x27	**310.051.11**	**310.051.12**
5,2	27	57,5	10x27	**310.052.11**	**310.052.12**
5,55	27	57,5	10x27	**310.055.11**	**310.055.12**
6	27	57,5	10x27	**310.060.11**	**310.060.12**
6,35	27	57,5	10x27	**310.064.11**	**310.064.12**
6,5	27	57,5	10x27	**310.065.11**	**310.065.12**
7	27	57,5	10x27	**310.070.11**	**310.070.12**
8	27	57,5	10x27	**310.080.11**	**310.080.12**
8,2	27	57,5	10x27	**310.082.11**	**310.082.12**
9	27	57,5	10x27	**310.090.11**	**310.090.12**
9,52	27	57,5	10x27	**310.095.11**	**310.095.12**
10	27	57,5	10x27	**310.100.11**	**310.100.12**
11	27	57,5	10x27	**310.110.11**	**310.110.12**
12	27	57,5	10x27	**310.120.11**	**310.120.12**
12,7	27	57,5	10x27	**310.127.11**	**310.127.12**
13	27	57,5	10x27	**310.130.11**	**310.130.12**
14	27	57,5	10x27	**310.140.11**	**310.140.12**
15	27	57,5	10x27	**310.150.11**	**310.150.12**
16	27	57,5	10x27	**310.160.11**	**310.160.12**

Spare parts




990.003.00

Optional



990.088.00

2 Flute Dowel Drills



361

HW Z2 V2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	18	57,5	10x34	**361.050.11**	**361.050.12**
6	18	57,5	10x34	**361.060.11**	**361.060.12**
7	18	57,5	10x34	**361.070.11**	**361.070.12**
8	18	57,5	10x34	**361.080.11**	**361.080.12**
10	18	57,5	10x34	**361.100.11**	**361.100.12**

TECHNICAL DETAILS:
- Super-strength steel.
- Spiral portion coated with orange or black P.T.F.E.
- HW head with precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- 2 negatively ground spurs [V2]
- 2 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.

Spare parts




990.003.00

Optional




990.088.00

APPLICATION:
used on boring machines equipped with adaptors or chucks.
Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.



Negatively Ground Spurs

www.dahm.no




311

HW Z2 V2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
4	35	70	10x30	**311.040.11**	**311.040.12**
4,5	35	70	10x30	**311.045.11**	**311.045.12**
4,76	35	70	10x30	**311.047.11**	**311.047.12**
5	35	70	10x30	**311.050.11**	**311.050.12**
5,1	35	70	10x30	**311.051.11**	**311.051.12**
5,2	35	70	10x30	**311.052.11**	**311.052.12**
5,55	35	70	10x30	**311.055.11**	**311.055.12**
6	35	70	10x30	**311.060.11**	**311.060.12**
6,35	35	70	10x30	**311.064.11**	**311.064.12**
6,5	35	70	10x30	**311.065.11**	**311.065.12**
7	35	70	10x30	**311.070.11**	**311.070.12**
8	35	70	10x30	**311.080.11**	**311.080.12**
8,2	35	70	10x30	**311.082.11**	**311.082.12**
9	35	70	10x30	**311.090.11**	**311.090.12**
9,52	35	70	10x30	**311.095.11**	**311.095.12**
10	35	70	10x30	**311.100.11**	**311.100.12**
11	35	70	10x30	**311.110.11**	**311.110.12**
11,1	35	70	10x30	**311.111.11**	**311.111.12**
12	35	70	10x30	**311.120.11**	**311.120.12**
12,7	35	70	10x30	**311.127.11**	**311.127.12**
13	35	70	10x30	**311.130.11**	**311.130.12**
14	35	70	10x30	**311.140.11**	**311.140.12**
15	35	70	10x30	**311.150.11**	**311.150.12**
16	35	70	10x30	**311.160.11**	**311.160.12**

Spare parts 990.003.00 *Optional* 990.088.00

2 Flute Dowel Drills



362


HW Z2 V2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	44	77	10x30	**362.050.11**	**362.050.12**
6	44	77	10x30	**362.060.11**	**362.060.12**
7	44	77	10x30	**362.070.11**	**362.070.12**
8	44	77	10x30	**362.080.11**	**362.080.12**
10	44	77	10x30	**362.100.11**	**362.100.12**
12	44	77	10x30	**362.120.11**	**362.120.12**

TECHNICAL DETAILS:
- Super-strength steel.
- Spiral portion coated with orange or black P.T.F.E.
- HW head with precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- 2 negatively ground spurs [V2].
- 2 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.

Spare parts 990.003.00 *Optional* 990.088.00


APPLICATION:
used on boring machines equipped with adaptors or chucks.
Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.



Negatively Ground Spurs

www.dahm.no

4 Flute Dowel Drills



306

HW | HWM | Z2 | V2 | RH | LH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
• 3	18	55,5	8x20	**306.030.21**	
5	30	55,5	8x20	**306.050.11**	**306.050.12**
5,55	30	55,5	8x20	**306.055.11**	**306.055.12**
6	30	55,5	8x20	**306.060.11**	**306.060.12**
6,35	30	55,5	8x20	**306.064.11**	**306.064.12**
7	30	55,5	8x20	**306.070.11**	**306.070.12**
8	30	55,5	8x20	**306.080.11**	**306.080.12**
9	30	55,5	8x20	**306.090.11**	**306.090.12**
10	30	55,5	8x20	**306.100.11**	**306.100.12**
12	30	55,5	8x20	**306.120.11**	**306.120.12**

• **HWM**

Spare parts
990.003.00

Optional
990.088.00

4 Flute Dowel Drills



307

HW | Z2 | V2 | RH | LH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	40	67	8x20	**307.050.11**	**307.050.12**
5,55	40	67	8x20	**307.055.11**	**307.055.12**
6	40	67	8x20	**307.060.11**	**307.060.12**
6,35	40	67	8x20	**307.064.11**	**307.064.12**
7	40	67	8x20	**307.070.11**	**307.070.12**
8	40	67	8x20	**307.080.11**	**307.080.12**
9	40	67	8x20	**307.090.11**	**307.090.12**
9,52	40	67	8x20	**307.095.11**	**307.095.12**
10	40	67	8x20	**307.100.11**	**307.100.12**
12	40	67	8x20	**307.120.11**	**307.120.12**

Spare parts
990.003.00

Optional
990.088.00

Technical details:
- Super-strength steel.
- Cutter portion coated with black or orange P.T.F.E.
- HW head with precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- Negatively ground spurs [V2].
- 4 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.


Application:
used on boring machines equipped with adaptors or chucks.
Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.



Negatively Ground Spurs

www.dahm.no

4 Flute Dowel Drills



308


HW | Z2 | V2 | RH | LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
4	26	57,5	10x20	**308.040.11**	**308.040.12**
5	30	57,5	10x20	**308.050.11**	**308.050.12**
6	30	57,5	10x20	**308.060.11**	**308.060.12**
6,35	30	57,5	10x20	**308.064.11**	**308.064.12**
7	30	57,5	10x20	**308.070.11**	**308.070.12**
8	30	57,5	10x20	**308.080.11**	**308.080.12**
9	30	57,5	10x20	**308.090.11**	**308.090.12**
9,52	30	57,5	10x20	**308.095.11**	**308.095.12**
10	30	57,5	10x20	**308.100.11**	**308.100.12**
11	30	57,5	10x20	**308.110.11**	**308.110.12**
12	30	57,5	10x20	**308.120.11**	**308.120.12**
12,7	30	57,5	10x20	**308.127.11**	**308.127.12**
13	30	57,5	10x20	**308.130.11**	**308.130.12**
14	30	57,5	10x20	**308.140.11**	**308.140.12**
15	30	57,5	10x20	**308.150.11**	**308.150.12**
16	30	57,5	10x20	**308.160.11**	**308.160.12**

Spare parts
990.003.00

Optional
990.088.00

4 Flute Dowel Drills



309


HW | Z2 | V2 | RH | LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
4	43	70	10x20	**309.040.11**	**309.040.12**
5	43	70	10x20	**309.050.11**	**309.050.12**
6	43	70	10x20	**309.060.11**	**309.060.12**
6,35	43	70	10x20	**309.064.11**	**309.064.12**
7	43	70	10x20	**309.070.11**	**309.070.12**
7,5	43	70	10x20	**309.075.11**	**309.075.12**
8	43	70	10x20	**309.080.11**	**309.080.12**
9	43	70	10x20	**309.090.11**	**309.090.12**
9,52	43	70	10x20	**309.095.11**	**309.095.12**
10	43	70	10x20	**309.100.11**	**309.100.12**
11	43	70	10x20	**309.110.11**	**309.110.12**
12	43	70	10x20	**309.120.11**	**309.120.12**
12,7	43	70	10x20	**309.127.11**	**309.127.12**
13	43	70	10x20	**309.130.11**	**309.130.12**
14	43	70	10x20	**309.140.11**	**309.140.12**
15	43	70	10x20	**309.150.11**	**309.150.12**
16	43	70	10x20	**309.160.11**	**309.160.12**

Spare parts
990.003.00

Optional
990.088.00

TECHNICAL DETAILS:
- Super-strength steel.
- Cutter portion coated with black or orange P.T.F.E.
- HW head with precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- Negatively ground spurs [V2].
- 4 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.




Negatively Ground Spurs

APPLICATION:
used on boring machines equipped with adaptors or chucks.
Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.

www.dahm.no

4 Flute Dowel Drills

CMT ORANGE TOOLS™



373

HW Z2 V2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	50	85	10x27	**373.050.11**	**373.050.12**
6	50	85	10x27	**373.060.11**	**373.060.12**
7	50	85	10x27	**373.070.11**	**373.070.12**
8	50	85	10x27	**373.080.11**	**373.080.12**
10	50	85	10x27	**373.100.11**	**373.100.12**
12	50	85	10x27	**373.120.11**	**373.120.12**


Technical details:
- Super-strength steel.
- Cutter portion coated with black or orange P.T.F.E.
- HW head with precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- Negatively ground spurs [V2].
- 4 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.

Spare parts
990.003.00

Optional
990.088.00

Application:
used on boring machines equipped with adaptors or chucks.
Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.

4 Flute Dowel Drills



372

HW Z2 V2 RH LH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	65	105	10x30	**372.050.11**	**372.050.12**
6	65	105	10x30	**372.060.11**	**372.060.12**
7	65	105	10x30	**372.070.11**	**372.070.12**
8	65	105	10x30	**372.080.11**	**372.080.12**
10	65	105	10x30	**372.100.11**	**372.100.12**
12	65	105	10x30	**372.120.11**	**372.120.12**

Technical details:
- Super-strength steel.
- Cutter portion coated with black or orange P.T.F.E.
- HW head with precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- Negatively ground spurs [V2].
- 4 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.

Spare parts
990.003.00

Optional
990.088.00


Application:
used on boring machines equipped with adaptors or chucks.
Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.



Negatively Ground Spurs

www.dahm.no


Dowel Drills with Countersink



376-377

HW Z2 V2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
8	12	57,5	10	**376.080.11**	**376.080.12**
8	13	57,5	10	**376.083.11**	**376.083.12**
8	15	57,5	10	**376.081.11**	**376.081.12**
8	20	57,5	10	**376.082.11**	**376.082.12**
10	12	57,5	10	**376.100.11**	**376.100.12**
10	13	57,5	10	**376.103.11**	**376.103.12**
10	15	57,5	10	**376.101.11**	**376.101.12**
10	20	57,5	10	**376.102.11**	**376.102.12**
8	12	70	10	**377.080.11**	**377.080.12**
8	13	70	10	**377.083.11**	**377.083.12**
8	15	70	10	**377.081.11**	**377.081.12**
8	20	70	10	**377.082.11**	**377.082.12**
10	12	70	10	**377.100.11**	**377.100.12**
10	13	70	10	**377.103.11**	**377.103.12**
10	15	70	10	**377.101.11**	**377.101.12**
10	20	70	10	**377.102.11**	**377.102.12**




Negatively Ground Spurs

TECHNICAL DETAILS:
- Super-strength steel.
- Spiral portion coated with orange or black P.T.F.E.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- 2 ground spurs [V2].
- 2 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.

Spare parts	Optional
990.003.00	990.088.00

APPLICATION:
used for drilling and countersinking in solid wood, wood composites, plastic and laminated materials. Suitable for high performance speed on boring machines equipped with adaptors or chucks.

Dowel Drills for Through Holes with Countersink



378


HW Z2 V2 RH LH

D mm	I mm	I_1 mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	35	31	70	10	**378.052.11**	**378.052.12**
7	35	29,5	70	10	**378.072.11**	**378.072.12**
8	35	29	70	10	**378.082.11**	**378.082.12**
10	35	26,5	70	10	**378.102.11**	**378.102.12**

TECHNICAL DETAILS:
- Super-strength steel.
- Spiral portion coated with orange or black P.T.F.E.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- 2 ground spurs [V2].
- 2 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.

Spare parts	Optional
990.003.00	990.088.00

APPLICATION:
used for drilling and countersinking in solid wood, wood composites, plastic and laminated materials. Suitable for high performance speed on boring machines equipped with adaptors or chucks.




60° Through Holes

www.dahm.no

2 Flute Dowel Drills for Through Holes

CMT ORANGE TOOLS



313

HW Z2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	27	57,5	10x26	**313.050.11**	**313.050.12**
6	27	57,5	10x26	**313.060.11**	**313.060.12**
8	27	57,5	10x26	**313.080.11**	**313.080.12**
10	27	57,5	10x26	**313.100.11**	**313.100.12**

For panels with maximum 20mm in thickness.


Spare parts
990.003.00

Optional
990.088.00

TECHNICAL DETAILS:
- Super-strength steel.
- Spiral portion coated with orange or black P.T.F.E.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- 2 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.

APPLICATION:
used on boring machines and dowel drilling devices.
Use for drilling through holes in solid wood, wood composites, plastic and laminated materials.

2 Flute Dowel Drills for Through Holes




314

HW Z2 RH LH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
4	30	70	10x26	**314.040.11**	**314.040.12**
4,76	35	70	10x26	**314.047.11**	**314.047.12**
5	35	70	10x26	**314.050.11**	**314.050.12**
5,55	35	70	10x26	**314.055.11**	**314.055.12**
6	35	70	10x26	**314.060.11**	**314.060.12**
6,35	35	70	10x26	**314.064.11**	**314.064.12**
7	35	70	10x26	**314.070.11**	**314.070.12**
8	35	70	10x26	**314.080.11**	**314.080.12**
9	35	70	10x26	**314.090.11**	**314.090.12**
9,52	35	70	10x26	**314.095.11**	**314.095.12**
10	35	70	10x26	**314.100.11**	**314.100.12**
12	35	70	10x26	**314.120.11**	**314.120.12**
12,7	35	70	10x26	**314.127.11**	**314.127.12**

For panels with maximum 25-30mm in thickness.



60° Through Holes

366

5	44	77	10x26	**366.050.11**	**366.050.12**
6	44	77	10x26	**366.060.11**	**366.060.12**
8	44	77	10x26	**366.080.11**	**366.080.12**
10	44	77	10x26	**366.100.11**	**366.100.12**
12	44	77	10x26	**366.120.11**	**366.120.12**

For panels with maximum 30-40mm in thickness.

Spare parts
990.003.00


Optional
990.088.00


TECHNICAL DETAILS:
- Super-strength steel.
- Spiral portion coated with orange or black P.T.F.E.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- 2 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.

APPLICATION:
used on boring machines and dowel drilling devices.
Use for drilling through holes in solid wood, wood composites, plastic and laminated materials.

www.dahm.no

4 Flute Dowel Drills for Through Holes





60° Through Holes

HW Z2 RH LH

374 For panels with maximum 20-25mm in thickness.

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	30	57,5	10x20	**374.050.11**	**374.050.12**
8	30	57,5	10x20	**374.080.11**	**374.080.12**

375 For panels with maximum 30-35mm in thickness.

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
new 4	40	70	10x20	**375.040.11**	**375.040.12**
5	40	70	10x20	**375.050.11**	**375.050.12**
6	40	70	10x20	**375.060.11**	**375.060.12**
7	40	70	10x20	**375.070.11**	**375.070.12**
8	40	70	10x20	**375.080.11**	**375.080.12**
9	40	70	10x20	**375.090.11**	**375.090.12**
10	40	70	10x20	**375.100.11**	**375.100.12**

381 For panels with maximum 60-65mm in thickness.

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	70	115	10x30	**381.050.11**	**381.050.12**
6	70	115	10x30	**381.060.11**	**381.060.12**
8	70	115	10x30	**381.080.11**	**381.080.12**
10	70	115	10x30	**381.100.11**	**381.100.12**


TECHNICAL DETAILS:
- Super-strength steel
- Spiral portion coated with orange or black P.T.F.E.
- HW head with precision balanced centre point
- 2 precision ground cutting edges [Z2]
- 4 spiral flutes
- Parallel shank with driving flat and length adjusting screw.


Spare parts
990.003.00

Optional
990.088.00

APPLICATION:
used on boring machines and dowel drilling devices.
Use for drilling through holes in solid wood, wood composites, plastic and laminated materials.

2 Flute Dowel Drills for Through Holes





60° Through Holes

HW Z2 RH LH

367

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	30	56	8x20	**367.050.11**	**367.050.12**
8	30	56	8x20	**367.080.11**	**367.080.12**

For panels with maximum 20-25mm in thickness.

368

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	43	70	8x20	**368.050.11**	**368.050.12**
6	43	70	8x20	**368.060.11**	**368.060.12**
7	43	70	8x20	**368.070.11**	**368.070.12**
8	43	70	8x20	**368.080.11**	**368.080.12**

For panels with maximum 35-40mm in thickness

Spare parts
990.003.00


Optional
990.088.00

TECHNICAL DETAILS:
- Super-strength steel
- Spiral portion coated with orange or black P.T.F.E.
- HW head with precision balanced centre point
- 2 precision ground cutting edges [Z2]
- 2 spiral flutes
- Parallel shank with driving flat and length adjusting screw.

APPLICATION:
used on boring machines and dowel drilling devices.
Use for drilling through holes in solid wood, wood composites, plastic and laminated materials.

www.dahm.no

Countersinks for 2 Flutes Dowel Drills



315

HW Z2 RH LH

D2 mm	D mm			ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5 ~ 10	20			315.200.11	315.200.12
11 ~ 12	22			315.220.11	315.220.12

For assembly on the shank of the drill.
For use with the following parts: 310-311-362-313-314-366 HW

Spare parts



990.006.00


991.062.00

Technical details:
- Super-strength steel.
- 2 precision ground carbide tipped cutting edges [Z2].
- Direct clamp on the shank of the drills.

Application:
used for chamfering and drilling in solid wood, wood composites, plastic and laminated materials.

Countersinks for 4 Flutes Dowel Drills



For assembly on the spiral head of the bit.
Adjustable depth.
For use with the following parts:
306-307-308-309-373-374-375-338-339-340-341-342-343-344-346-352-353 HW

316

HW Z2 RH LH

D2 mm	D mm			ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
4	16			316.040.11	316.040.12
5	16			316.050.11	316.050.12
6	16			316.060.11	316.060.12
7	16			316.070.11	316.070.12
8	18			316.080.11	316.080.12
9	18			316.090.11	316.090.12
10	20			316.100.11	316.100.12
12	20			316.120.11	316.120.12

Spare parts


990.002.00


991.062.00

Technical details:
- Super-strength steel.
- 2 HW precision ground cutting edges [Z2].

Application:
used for drilling and chamfering in solid wood, wood composites, plastic and laminated materials.

315 Assembly Illustration




316 Assembly Illustration




www.dahm.no

Hinge Boring Bits



New construction with 1mm centre point



317

HW Z2 V2 RH LH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
14	57,5	10x26		**317.140.11**	**317.140.12**
15	57,5	10x26		**317.150.11**	**317.150.12**
16	57,5	10x26		**317.160.11**	**317.160.12**
17	57,5	10x26		**317.170.11**	**317.170.12**
18	57,5	10x26		**317.180.11**	**317.180.12**
19	57,5	10x26		**317.190.11**	**317.190.12**
20	57,5	10x26		**317.200.11**	**317.200.12**
22	57,5	10x26		**317.220.11**	**317.220.12**
24	57,5	10x26		**317.240.11**	**317.240.12**
25	57,5	10x26		**317.250.11**	**317.250.12**
26	57,5	10x26		**317.260.11**	**317.260.12**
28	57,5	10x26		**317.280.11**	**317.280.12**
30	57,5	10x26		**317.300.11**	**317.300.12**
32	57,5	10x26		**317.320.11**	**317.320.12**
34	57,5	10x26		**317.340.11**	**317.340.12**
35	57,5	10x26		**317.350.11**	**317.350.12**
38	57,5	10x26		**317.380.11**	**317.380.12**
40	57,5	10x26		**317.400.11**	**317.400.12**
42	57,5	10x26		**317.420.11**	**317.420.12**
45	57,5	10x26		**317.450.11**	**317.450.12**
50	57,5	10x26		**317.500.11**	**317.500.12**
55	57,5	10x26		**317.550.11**	**317.550.12**
60	57,5	10x26		**317.600.11**	**317.600.12**

TECHNICAL DETAILS:
- Super-strength steel.
- Cutter portion coated with orange or black P.T.F.E.
- HW head with precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- 2 negatively ground spurs [V2].
- Parallel shank with driving flat and length adjusting screw.

Spare parts: 990.003.00

Optional: 990.088.00

APPLICATION:
ideal for hinges. Use on boring machines equipped with adaptors or chucks.
Use for drilling accurate and clean-cut blind holes in solid wood, wood composites, plastic and laminated materials.

DP Hinge Boring Bits



317-369

DP LONG LIFE Z2 V2 RH LH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
15	57,5	10x26		**317.150.61**	**317.150.62**
35	57,5	10x26		**317.350.61**	**317.350.62**
15	70	10x26		**369.150.61**	**369.150.62**
35	70	10x26		**369.350.61**	**369.350.62**

TECHNICAL DETAILS:
- Super-strength steel.
- DP head with precision balanced centre point.
- 2 DP precision ground cutting edges [Z2].
- 2 DP negatively ground spurs [V2].
- Parallel shank with driving flat and length adjusting screw.

Spare parts: 990.003.00

Optional: 990.088.00


20X LONGER LIFE THAN CARBIDE

APPLICATION:
ideal for hinges. Use on boring machines equipped with adaptors or chucks.
Use for drilling accurate and clean-cut blind holes in wood composites, plastic and laminated materials. Boring performance 20 times longer than HW materials.


REMARK: *special dimensions available on request.*

www.dahm.no

Hinge Boring Bits



New construction with 1mm centre point



369

HW Z2 V2 RH LH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
14	70	10x26		**369.140.11**	**369.140.12**
15	70	10x26		**369.150.11**	**369.150.12**
16	70	10x26		**369.160.11**	**369.160.12**
18	70	10x26		**369.180.11**	**369.180.12**
20	70	10x26		**369.200.11**	**369.200.12**
22	70	10x26		**369.220.11**	**369.220.12**
25	70	10x26		**369.250.11**	**369.250.12**
26	70	10x26		**369.260.11**	**369.260.12**
30	70	10x26		**369.300.11**	**369.300.12**
35	70	10x26		**369.350.11**	**369.350.12**
40	70	10x26		**369.400.11**	**369.400.12**
45	70	10x26		**369.450.11**	**369.450.12**
50	70	10x26		**369.500.11**	**369.500.12**
55	70	10x26		**369.550.11**	**369.550.12**
60	70	10x26		**369.600.11**	**369.600.12**

370

D mm	L mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
18	77	10x30		**370.180.11**	**370.180.12**
20	77	10x30		**370.200.11**	**370.200.12**
25	77	10x30		**370.250.11**	**370.250.12**
30	77	10x30		**370.300.11**	**370.300.12**
35	77	10x30		**370.350.11**	**370.350.12**


Technical details:
- Super-strength steel.
- Cutter portion coated with orange or black P.T.F.E.
- HW head with precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- 2 negatively ground spurs [V2].
- Parallel shank with driving flat and length adjusting screw.

Spare parts
990.003.00

Optional
990.088.00

Application:
ideal for hinges. Use on boring machines equipped with adaptors or chucks. Use for drilling accurate and clean-cut blind holes in solid wood, wood composites, plastic and laminated materials.

Hinge Boring Bits with Chipbreaker for Boring Machines



317C - 369C

HW Z2R V2 RH LH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
35	57,5	10x26		**317.350.11C**	**317.350.12C**
40	57,5	10x26		**317.400.11C**	**317.400.12C**
45	57,5	10x26		**317.450.11C**	**317.450.12C**
35	70	10x26		**369.350.11C**	**369.350.12C**
40	70	10x26		**369.400.11C**	**369.400.12C**
45	70	10x26		**369.450.11C**	**369.450.12C**

Technical details:
- Super-strength steel.
- Cutter portion coated with orange or black P.T.F.E.
- HW head with precision balanced centre point.
- 2 HW precision ground cutting edges with chipbreaker [Z2R].
- 2 negatively ground spurs [V2].
- Parallel shank with driving flat and length adjusting screw.

Spare parts
990.003.00

Optional
990.088.00

Application:
Ideal for hinges. Used on boring machines equipped with adaptors or chucks.
For drilling accurate and clean-cut blind holes in solid wood.

www.dahm.no



344

HW Z2 V2 RH LH

D mm	I mm	LB mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	43	63	M8	**344.050.11**	**344.050.12**
6	43	63	M8	**344.060.11**	**344.060.12**
8	43	63	M8	**344.080.11**	**344.080.12**
10	43	63	M8	**344.100.11**	**344.100.12**
12	43	63	M8	**344.120.11**	**344.120.12**

For use on the following machines:
Nottmeyer (older models)

346

HW Z2 V2 RH LH

D mm	I mm	LB mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	43	63	M10	**346.050.11**	**346.050.12**
6	43	63	M10	**346.060.11**	**346.060.12**
8	43	63	M10	**346.080.11**	**346.080.12**
10	43	63	M10	**346.100.11**	**346.100.12**
12	43	63	M10	**346.120.11**	**346.120.12**

For use on the following machines:
Ayen, Holzma, Knoevenagel, Mayer, Torwegge.

Technical details:
- Super-strength steel.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- 2 ground spurs [V2].
- 4 spiral flutes.

Application:
used on boring machines equipped with chucks. Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.

Dowel Drills with Threaded Shank



352-353

HW Z2 V2 RH LH

D mm	I mm	LB mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	30	45	M8/9	**352.050.11**	**352.050.12**
6	30	45	M8/9	**352.060.11**	**352.060.12**
8	30	45	M8/9	**352.080.11**	**352.080.12**
10	30	45	M8/9	**352.100.11**	**352.100.12**
12	30	45	M8/9	**352.120.11**	**352.120.12**
5	40	55	M8/9	**353.050.11**	**353.050.12**
6	40	55	M8/9	**353.060.11**	**353.060.12**
8	40	55	M8/9	**353.080.11**	**353.080.12**
10	40	55	M8/9	**353.100.11**	**353.100.12**
12	40	55	M8/9	**353.120.11**	**353.120.12**


For use on the following machines:
Masterwood (Zangheri & Boschetti)
Morbidelli, Nottmeyer (new design)

Technical details:
- Super-strength steel.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- 2 ground spurs [V2].
- 4 spiral flutes.

Application:
used on boring machines equipped with chucks. Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.

www.dahm.no

Dowel Drills with Threaded Shank with Countersink



332-334-336-337

HW Z2 V2 RH LH

D mm	I mm	LB mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	20	45	M10/30°	**332.050.11**	**332.050.12**
6	20	45	M10/30°	**332.060.11**	**332.060.12**
8	20	45	M10/30°	**332.080.11**	**332.080.12**
10	20	45	M10/30°	**332.100.11**	**332.100.12**
12	20	45	M10/30°	**332.120.11**	**332.120.12**
5	30	55	M10/30°	**334.050.11**	**334.050.12**
6	30	55	M10/30°	**334.060.11**	**334.060.12**
8	30	55	M10/30°	**334.080.11**	**334.080.12**
10	30	55	M10/30°	**334.100.11**	**334.100.12**
12	30	55	M10/30°	**334.120.11**	**334.120.12**
5	40	65	M10/30°	**336.050.11**	**336.050.12**
6	40	65	M10/30°	**336.060.11**	**336.060.12**
8	40	65	M10/30°	**336.080.11**	**336.080.12**
10	40	65	M10/30°	**336.100.11**	**336.100.12**
12	40	65	M10/30°	**336.120.11**	**336.120.12**
5	50	75	M10/30°	**337.050.11**	**337.050.12**
6	50	75	M10/30°	**337.060.11**	**337.060.12**
8	50	75	M10/30°	**337.080.11**	**337.080.12**
10	50	75	M10/30°	**337.100.11**	**337.100.12**
12	50	75	M10/30°	**337.120.11**	**337.120.12**

Technical details:
- Super-strength steel.
- HW head with precision balanced centre point.
- 2 precision ground cutting edge [Z2].
- 2 ground spurts [V2].
- 2 spiral flutes.

Application:
used on boring machines equipped with chucks. Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.

Dowel Drills with Threaded Shank without Countersink



341-342-343

HW Z2 V2 RH LH


D mm	I mm	LB mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	30	55	M10/30°	**341.050.11**	**341.050.12**
6	30	55	M10/30°	**341.060.11**	**341.060.12**
8	30	55	M10/30°	**341.080.11**	**341.080.12**
10	30	55	M10/30°	**341.100.11**	**341.100.12**
12	30	55	M10/30°	**341.120.11**	**341.120.12**
5	40	65	M10/30°	**342.050.11**	**342.050.12**
6	40	65	M10/30°	**342.060.11**	**342.060.12**
8	40	65	M10/30°	**342.080.11**	**342.080.12**
10	40	65	M10/30°	**342.100.11**	**342.100.12**
12	40	65	M10/30°	**342.120.11**	**342.120.12**
5	50	75	M10/30°	**343.050.11**	**343.050.12**
6	50	75	M10/30°	**343.060.11**	**343.060.12**
8	50	75	M10/30°	**343.080.11**	**343.080.12**
10	50	75	M10/30°	**343.100.11**	**343.100.12**
12	50	75	M10/30°	**343.120.11**	**343.120.12**

Technical details:
- Super-strength steel.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- 2 ground spurs [V2].
- 4 spiral flutes.

Application:
used on boring machines equipped with chucks. Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.

www.dahm.no

Dowel Drills with Threaded Shank with Countersink



325-327-329-330

HW Z2 V2 RH LH

D mm	I mm	LB mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	20	35	M10/11x4	**325.050.11**	**325.050.12**
6	20	35	M10/11x4	**325.060.11**	**325.060.12**
8	20	35	M10/11x4	**325.080.11**	**325.080.12**
10	20	35	M10/11x4	**325.100.11**	**325.100.12**
12	20	35	M10/11x4	**325.120.11**	**325.120.12**
5	30	45	M10/11x4	**327.050.11**	**327.050.12**
6	30	45	M10/11x4	**327.060.11**	**327.060.12**
8	30	45	M10/11x4	**327.080.11**	**327.080.12**
10	30	45	M10/11x4	**327.100.11**	**327.100.12**
12	30	45	M10/11x4	**327.120.11**	**327.120.12**
5	40	55	M10/11x4	**329.050.11**	**329.050.12**
6	40	55	M10/11x4	**329.060.11**	**329.060.12**
8	40	55	M10/11x4	**329.080.11**	**329.080.12**
10	40	55	M10/11x4	**329.100.11**	**329.100.12**
12	40	55	M10/11x4	**329.120.11**	**329.120.12**
5	50	65	M10/11x4	**330.050.11**	**330.050.12**
6	50	65	M10/11x4	**330.060.11**	**330.060.12**
8	50	65	M10/11x4	**330.080.11**	**330.080.12**
10	50	65	M10/11x4	**330.100.11**	**330.100.12**
12	50	65	M10/11x4	**330.120.11**	**330.120.12**

TECHNICAL DETAILS:
- Super-strength steel.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- 2 spiral flutes.
- 2 ground spurs [V2].

APPLICATION:
used on boring machines equipped with chucks. Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.

Dowel Drills with Threaded Shank without Countersink



338-339-340

HW Z2 V2 RH LH

D mm	I mm	LB mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
5	30	45	M10/11x4	**338.050.11**	**338.050.12**
6	30	45	M10/11x4	**338.060.11**	**338.060.12**
8	30	45	M10/11x4	**338.080.11**	**338.080.12**
10	30	45	M10/11x4	**338.100.11**	**338.100.12**
12	30	45	M10/11x4	**338.120.11**	**338.120.12**
5	40	55	M10/11x4	**339.050.11**	**339.050.12**
6	40	55	M10/11x4	**339.060.11**	**339.060.12**
8	40	55	M10/11x4	**339.080.11**	**339.080.12**
10	40	55	M10/11x4	**339.100.11**	**339.100.12**
12	40	55	M10/11x4	**339.120.11**	**339.120.12**
5	50	65	M10/11x4	**340.050.11**	**340.050.12**
6	50	65	M10/11x4	**340.060.11**	**340.060.12**
8	50	65	M10/11x4	**340.080.11**	**340.080.12**
10	50	65	M10/11x4	**340.100.11**	**340.100.12**
12	50	65	M10/11x4	**340.120.11**	**340.120.12**

TECHNICAL DETAILS:
- Super-strength steel.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- 2 ground spurs [V2].
- 4 spiral flutes.

APPLICATION:
used on boring machines equipped with chucks. Used to drill blind holes in solid wood, wood composites, plastic and laminated materials.

www.dahm.no

Special Dowel Drills

CMT ORANGE TOOLS™

TOOL FEATURES

TOOL MATERIAL

☐ HW ☐ SP steel

QUANTITY AND ROTATION

Nr. ..... RH Bits Nr. ..... LH Bits

SHANK

- PARALLEL SHANK WITH DRIVING FLAT

☐ Ø8x20mm with driving flat and length adjusting screw

☐ Ø10x20mm with driving flat and length adjusting screw

- THREADED SHANK

☐ M8

☐ M10

☐ M8 with seating Ø9x4mm

☐ M10 with seating Ø11x4mm

☐ M 8 with 20°48' centring cone

☐ M10 with 30° centring cone

- PARALLEL SHANK

☐ S x A = ...
(Specify diameter and shank length)

☐ .....
(Specify other shank types)

HOLE FEATURES

HOLE TO PRODUCE

☐ Drawing 1 - Blind hole with more than one diameter

☐ Drawing 2 - Blind hole with counter

☐ Drawing 3 - Through hole with more than one diameter

☐ Drawing 4 - Through hole with countersink

DIMENSIONS

d x C .....
(Specify diameter and depth of first hole)

D x B .....
(Specify diameter and depth of second hole)


.....
(Specify countersink-angle) "standard 45°"

WORK MATERIAL

☐ Solid wood

☐ MDF/Melamine panels

☐ Chipboard panels and hardwood

☐ .....
(Specify other materials)


MACHINE DATA

Manufacturer/Model .....


RPM .....

Feed speed (metres/minute) .....


DRAWING 1




DRAWING 2



DRAWING 3



DRAWING 4



For orders, please fill out this form and fax it to:
#39 0721 481021 or mail to:
C.M.T. Utensili S.p.A. - Via della Meccanica, s.n. - 61122 Pesaro, Fraz. Chiusa di Ginestreto - Italia

www.dahm.no



Bits for Hand Power Tools

PRODUCTS	PAGE
Adaptors	280-281
Interchangeable Boring Bits	281
Boring Bits	282~285
Chisel & Bit Sets	285
Plug Cutters & Sets	286-287
Forstner Bits	288
Rosette Cutters	289
Brad Point Bits	290~293
Bits for Mafell® & Festool® Machines	291
Countersinks & Drills	294~297

www.dahm.no

Adaptors



509-532-533 ...with parallel shank for interchangeable bits

RH LH


S mm	LB mm			ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
8x30	35			**532.080.01**	
9,5x30	35			**532.095.01**	
10x50	60			**533.100.01**	**533.100.02**
12x30	35			**532.120.01**	
13x50	100			**509.130.01**	**509.130.02**
16x50	100			**509.160.01**	**509.160.02**

For use with the following parts: 501 HW

Technical details:
- Super strength steel.
- Parallel shank with driving flat and adjustable screw length.

Application:
used on boring machines with adaptor chucks.

Adaptors



511 ...with parallel shank for quick change drills

RH LH

S mm	LB mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
10x20 (with driving flat and screw)	27	**511.270.01**	**511.270.02**
10x35 (with driving flat and screw)	40	**511.400.01**	**511.400.02**

For use with the following parts: 501 HW

Spare parts
990.003.00

Technical details:
- Super strength steel.
- Parallel shank with driving flat and adjustable screw length.

Application:
used on boring machines with adaptor chucks.

Adaptors



506

RH LH

S mm	LB mm			ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
M10/11x4	15			**506.150.01**	**506.150.02**
M10/11x4	25			**506.250.01**	**506.250.02**
M10/11x4	35			**506.350.01**	**506.350.02**

For use with the following parts: 501 HW

Technical details:
- Super strength steel.
- Parallel shank with driving flat and adjustable screw length.

Application:
used on boring machines with adaptor chucks.

www.dahm.no

Adaptors



503

RH LH

S mm	LB mm			ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
M10/30°	25			**503.250.01**	**503.250.02**
M10/30°	35			**503.350.01**	**503.350.02**
M10/30°	45			**503.450.01**	**503.450.02**

For use with the following parts: 501 HW

TECHNICAL DETAILS:
- Super strength steel.
- Parallel shank with driving flat and adjustable screw length

APPLICATION:
used on boring machines with adaptor chucks.

Adaptors



534

RH


S			ORDER NO. Right-hand rotation	
MK2/Ø20x14F.x1"			**534.020.01**	
MK2/M30x1,5			**534.030.01**	

For use with the following parts: 501 HW

TECHNICAL DETAILS:
- Super strength steel.

APPLICATION:
used on CNC machines or hand-held routers equipped with adaptor chucks.

Interchangeable Boring Bits with Threaded Shank




501

HW Z2+2 RH LH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
20	30	M12x1		**501.200.11**	**501.200.12**
22	30	M12x1		**501.220.11**	**501.220.12**
24	30	M12x1		**501.240.11**	**501.240.12**
25	30	M12x1		**501.250.11**	**501.250.12**
26	30	M12x1		**501.260.11**	**501.260.12**
30	30	M12x1		**501.300.11**	**501.300.12**
32	30	M12x1		**501.320.11**	**501.320.12**
34	30	M12x1		**501.340.11**	**501.340.12**
35	30	M12x1		**501.350.11**	**501.350.12**
36	30	M12x1		**501.360.11**	**501.360.12**
38	30	M12x1		**501.380.11**	**501.380.12**
40	30	M12x1		**501.400.11**	**501.400.12**
45	30	M12x1		**501.450.11**	**501.450.12**
50	30	M12x1		**501.500.11**	**501.500.12**
55	30	M12x1		**501.550.11**	**501.550.12**
60	30	M12x1		**501.600.11**	**501.600.12**

www.dahm.no

Boring Bits with Parallel Shank



512

HW Z2 V2 RH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	
14	90	10x60		**512.140.11**	
15	90	10x60		**512.150.11**	
16	90	10x60		**512.160.11**	
17	90	10x60		**512.170.11**	
18	90	10x60		**512.180.11**	
19	90	10x60		**512.190.11**	
20	90	10x60		**512.200.11**	
21	90	10x60		**512.210.11**	
22	90	10x60		**512.220.11**	
23	90	10x60		**512.230.11**	
24	90	10x60		**512.240.11**	
25	90	10x60		**512.250.11**	
26	90	10x60		**512.260.11**	
27	90	10x60		**512.270.11**	
28	90	10x60		**512.280.11**	
29	90	10x60		**512.290.11**	
30	90	10x60		**512.300.11**	
31	90	10x60		**512.310.11**	
32	90	10x60		**512.320.11**	
33	90	10x60		**512.330.11**	
34	90	10x60		**512.340.11**	
35	90	10x60		**512.350.11**	
38	90	10x60		**512.380.11**	
40	90	10x60		**512.400.11**	
new 42	90	10x60		**512.420.11**	
45	90	10x50		**512.450.11**	
48	90	10x50		**512.480.11**	
50	90	10x50		**512.500.11**	
55	90	10x50		**512.550.11**	
58	90	10x50		**512.580.11**	
60	90	10x50		**512.600.11**	

Technical details:
- Super strength steel.
- HW precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- 2 HW negatively ground spurs [V2].
- Parallel shank.

Application:
used for drilling blind holes in solid wood, wood composites and plastic laminate materials.
Ideal for hinges.

5-Piece Boring Bit Set for Hinges



512

HW Z2 V2 RH


The perfect set for hinge work and other related applications.
Machined from special high speed steel with micrograin carbide tips, these bits are available in diameters of 15, 20, 25, 30 and 35mm.
Safely packaged in a solid plastic box with glass front for easy storage and inventory.

Technical details:
- Super strength steel.
- HW precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- 2 HW negatively ground spurs [V2].
- Parallel shank.

Application:
used for drilling blind holes in solid wood, wood composites and plastic laminated materials.
Ideal for hinges.

DESCRIPTION	S mm	L mm	BIT DIAMETER mm	ORDER NO. Right-hand rotation
5-Piece Boring Bit Set for Hinges	10	90	15-20-25-30-35	**512.001.01**

www.dahm.no



512

SP Z2 V2 RH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	
8	90	10x30		**512.081.31**	
10	90	10x30		**512.101.31**	
12	90	10x30		**512.121.31**	
14	90	10x30		**512.141.31**	
15	90	10x30		**512.151.31**	
16	90	10x30		**512.161.31**	
18	90	10x30		**512.181.31**	
20	90	10x30		**512.201.31**	
22	90	10x30		**512.221.31**	
24	90	10x30		**512.241.31**	
25	90	10x30		**512.251.31**	
26	90	10x30		**512.261.31**	
28	90	10x30		**512.281.31**	
30	90	10x30		**512.301.31**	
32	90	10x30		**512.321.31**	
34	90	10x30		**512.341.31**	
35	90	10x30		**512.351.31**	
38	90	10x30		**512.381.31**	
40	90	10x30		**512.401.31**	
45	90	10x30		**512.451.31**	
50	90	10x30		**512.501.31**	

TECHNICAL DETAILS:
- SP steel.
- Precision balanced centre point.
- 2 spurs [V2].
- 2 precision ground cutting edges [Z2].
- Long-lasting cutting performance.
- Parallel shank.

APPLICATION:
used for drilling blind holes in softwood.
Ideal for hinges.

5-Piece Boring Bit Set for Hinges



512

SP Z2 V2 RH

The perfect set for hinge work and other related applications. Machined from special high speed steel, these bits are available in diameters of 15, 20, 25, 30 and 35mm. Precisely ground, sharpened with round shanks and safely packaged in a solid plastic box with glass front for easy storage and inventory.


TECHNICAL DETAILS:
- SP steel.
- Precision balanced centre point.
- 2 spurs [V2].
- 2 precision ground cutting edges [Z2].
- Long-lasting cutting performance.

APPLICATION:
used for drilling blind holes in softwood. **Ideal for hinges.**

DESCRIPTION	S mm	L mm	BIT DIAMETER mm	ORDER NO. Right-hand rotation
5-Piece Boring Bit Set for Hinges	10	90	15-20-25-30-35	**512.001.00**

www.dahm.no

Boring Bits with Parallel Shank



513

HW Z2 V2 RH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	
15	120	13		**513.150.11**	
16	120	13		**513.160.11**	
18	120	13		**513.180.11**	
20	120	13		**513.200.11**	
22	125	13		**513.220.11**	
25	125	13		**513.250.11**	
26	125	13		**513.260.11**	
28	130	13		**513.280.11**	
30	130	13		**513.300.11**	
35	130	13		**513.350.11**	
40	130	13		**513.400.11**	
45	130	13		**513.450.11**	
50	130	13		**513.500.11**	
55	140	13		**513.550.11**	
60	140	13		**513.600.11**	

514

D mm	L mm	S mm		ORDER NO. Right-hand rotation	
15	120	16		**514.150.11**	
16	120	16		**514.160.11**	
18	120	16		**514.180.11**	
20	120	16		**514.200.11**	
22	125	16		**514.220.11**	
25	125	16		**514.250.11**	
26	125	16		**514.260.11**	
28	130	16		**514.280.11**	
30	130	16		**514.300.11**	
32	130	16		**514.320.11**	
35	130	16		**514.350.11**	
40	130	16		**514.400.11**	
45	130	16		**514.450.11**	
50	130	16		**514.500.11**	
55	140	16		**514.550.11**	
60	140	16		**514.600.11**	

Technical details:
- Super strength steel.
- HW precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- 2 HW negatively ground spurs [V2].
- Parallel shank.

Application:
used for drilling blind holes in solid wood, wood composites and plastic laminated materials.
Ideal for hinges.

www.dahm.no

Boring Bits with Parallel Shank



392

HW Z2 V2 RH

D mm	L mm	S mm		ORDER NO. Right-hand rotation	
15	60	8		**392.150.11**	
20	60	8		**392.200.11**	
25	60	8		**392.250.11**	
26	60	8		**392.260.11**	
30	60	8		**392.300.11**	
35	60	8		**392.350.11**	
35	60	12,7		**392.351.11**	
40	60	8		**392.400.11**	

TECHNICAL DETAILS:
- Super strength steel.
- HW precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- 2 HW negatively ground spurs [V2].
- Parallel shank.
- Right-hand rotation (RH).

APPLICATION:
for use on drilling machines and hand-held routers in solid wood, wood composites and plastic laminated materials.
Ideal for hinges and blind holes.

Mortise Chisel & Bit Sets



543

HS Z1 RH

D mm	D inches	S mm	S inches	ORDER NO. Right-hand rotation	
6,35	1/4	19	3/4	**543.064.51**	
8	5/16	19	3/4	**543.079.51**	
9,5	3/8	19	3/4	**543.095.51**	
12,7	1/2	19	3/4	**543.127.51**	
15,8	5/8	19	3/4	**543.158.51**	
19	3/4	19	3/4	**543.190.51**	

It's tough to beat the "old faithful" mortise and tenon joint for strength and accuracy, even with all the other joining options in the world of woodworking.
It isn't the easiest joint to make, but for sure it helps to have the best quality tools in your shop. That's why we've added a new selection of chisel and bit sets in all the popular sizes 6,35mm (1/4") to 19mm (3/4") diameter.

These sets are for use on any standard drill press mortising attachment of mortising machines.






Sample of Chisel Mortiser

www.dahm.no

Plug Cutters

CMT ORANGE TOOLS



529

SP RH

d mm	D mm	L mm	S mm	Z	ORDER NO. Right-hand rotation
8	18	140	13	4	**529.080.31**
10	20	140	13	4	**529.100.31**
12	24	140	13	4	**529.120.31**
14	26	140	13	4	**529.140.31**
15	27	140	13	4	**529.150.31**
16	28	140	13	4	**529.160.31**
18	30	140	13	4	**529.180.31**
20	32	140	13	4	**529.200.31**
22	34	140	13	5	**529.220.31**
25	37	140	13	5	**529.250.31**
30	42	140	13	5	**529.300.31**
32	44	140	13	5	**529.320.31**
35	47	160	16	6	**529.350.31**
40	52	160	16	6	**529.400.31**
45	57	160	16	6	**529.450.31**
50	62	160	16	6	**529.500.31**

d inches	D inches	L inches	S inches	Z	ORDER NO. Right-hand rotation
3/8	49/64	5-1/2	1/2	4	**529.095.31**
1/2	61/64	5-1/2	1/2	4	**529.127.31**
5/8	1-7/64	5-1/2	1/2	4	**529.158.31**
3/4	1-7/32	5-1/2	1/2	4	**529.191.31**
7/8	1-11/32	5-1/2	1/2	4	**529.222.31**
1	1-15/32	5-1/2	1/2	5	**529.254.31**
1-1/4	1-19/32	5-1/2	1/2	5	**529.317.31**
1-3/8	1-27/32	6-5/16	5/8	6	**529.349.31**
1-1/2	1-31/32	6-5/16	5/8	6	**529.381.31**
1-5/8	2-3/32	6-5/16	5/8	6	**529.413.31**
1-3/4	2-7/32	6-5/16	5/8	6	**529.445.31**
2	2-15/32	6-5/16	5/8	6	**529.508.31**

Use our D=16mm bushing to increase the 13mm shank (order no. 799.130.00 on page 303)

D mm	D inches	Max RPM Softwood	Max RPM Hardwood
< Ø16	5/8	1000	500
< Ø40	1-37/64	500	300
> Ø40	1-37/64	200	150

TECHNICAL DETAILS:
- SP steel.
- Long lasting cutter performance.

APPLICATION:
used to make plugs in hard and soft woods.

Plug Cutters



530

HS Z4 RH


D mm	S			ORDER NO. Right-hand rotation	
6,2	Ø21x14F.1"			**530.062.51**	
8	Ø21x14F.1"			**530.080.51**	
8,2	Ø21x14F.1"			**530.082.51**	
10	Ø21x14F.1"			**530.100.51**	
10,2	Ø21x14F.1"			**530.102.51**	
12	Ø21x14F.1"			**530.120.51**	
12,2	Ø21x14F.1"			**530.122.51**	

TECHNICAL DETAILS:
- Super strength HS steel.
- 4 precision ground cutting edges [Z4].
- Long lasting cutter performance.

APPLICATION:
used for cutting dowels.

REMARK:
available on request.

www.dahm.no



500.001/02/03

SP RH

We offer a wide range of boring bits and plug cutters in the most popular diameters. If you need to bore or to make plugs in softwood these sets are exactly what you need!



500.001.08 Boring Bit & Plug Cutter Set

SET CONTAINS	D mm	L mm	S mm	ORDER NO. Right-hand rotation
Boring Bit with Parallel Shank	8	90	10	**512.081.31**
Boring Bit with Parallel Shank	10	90	10	**512.101.31**
Boring Bit with Parallel Shank	12	90	10	**512.121.31**
Boring Bit with Parallel Shank	15	90	10	**512.151.31**
Plug Cutter	8	140	13	**529.080.31**
Plug Cutter	10	140	13	**529.100.31**
Plug Cutter	12	140	13	**529.120.31**
Plug Cutter	15	140	13	**529.150.31**

500.002.08 Boring Bit & Plug Cutter Set

SET CONTAINS	D mm	L mm	S mm	ORDER NO. Right-hand rotation
Boring Bit with Parallel Shank	16	90	10	**512.161.31**
Boring Bit with Parallel Shank	20	90	10	**512.201.31**
Boring Bit with Parallel Shank	25	90	10	**512.251.31**
Boring Bit with Parallel Shank	30	90	10	**512.301.31**
Plug Cutter	16	140	13	**529.160.31**
Plug Cutter	20	140	13	**529.200.31**
Plug Cutter	25	140	13	**529.250.31**
Plug Cutter	30	140	13	**529.300.31**

500.003.08 Boring Bit & Plug Cutter Set


SET CONTAINS	D mm	L mm	S mm	ORDER NO. Right-hand rotation
Boring Bit with Parallel Shank	15	90	10	**512.151.31**
Boring Bit with Parallel Shank	20	90	10	**512.201.31**
Boring Bit with Parallel Shank	25	90	10	**512.251.31**
Boring Bit with Parallel Shank	30	90	10	**512.301.31**
Plug Cutter	15	140	13	**529.150.31**
Plug Cutter	20	140	13	**529.200.31**
Plug Cutter	25	140	13	**529.250.31**
Plug Cutter	30	140	13	**529.300.31**

www.dahm.no

Forstner Bits

CMT ORANGE TOOLS™

SP Z2 V2 RH



toothed rim >=Ø25mm

537

D mm	L mm	S mm	ORDER NO. Right-hand rotation
10	90	8	**537.100.31**
12	90	8	**537.120.31**
14	90	8	**537.140.31**
15	90	8	**537.150.31**
16	90	8	**537.160.31**
18	90	8	**537.180.31**
20	90	8	**537.200.31**
22	90	8	**537.220.31**
24	90	8	**537.240.31**
25	90	8	**537.250.31**
26	90	8	**537.260.31**
28	90	8	**537.280.31**
30	90	8	**537.300.31**
32	90	10	**537.320.31**
35	90	10	**537.350.31**
38	90	10	**537.380.31**
40	90	10	**537.400.31**
45	90	10	**537.450.31**
50	90	10	**537.500.31**
55	90	10	**537.550.31**
68	157	12,7	**537.680.31**

D inches	L inches	S inches	ORDER NO. Right-hand rotation
1/4	3-35/64	3/8	**537.064.31**
3/8	3-35/64	3/8	**537.095.31**
1/2	3-35/64	3/8	**537.127.31**
5/8	3-35/64	3/8	**537.158.31**
3/4	3-35/64	3/8	**537.190.31**
7/8	3-35/64	3/8	**537.222.31**
1	3-35/64	3/8	**537.254.31**
1-1/8	3-35/64	3/8	**537.285.31**
1-1/4	3-35/64	3/8	**537.317.31**
1-3/8	3-35/64	3/8	**537.349.31**
1-1/2	3-35/64	3/8	**537.381.31**
1-5/8	3-35/64	3/8	**537.413.31**
1-3/4	3-35/64	3/8	**537.445.31**
1-7/8	3-35/64	3/8	**537.476.31**
2	3-35/64	3/8	**537.508.31**
2-1/8	3-35/64	3/8	**537.540.31**



standard rim <Ø25mm

Standard Rim and Toothed Rim:
Standard rims provide better guidance but tend to overheat.
To overcome heat the larger diameters (>=Ø25mm) are designed with toothed rims.

Technical details:
- Super strength SP steel.
- Precision balanced centre point.
- 2 spurs [V2].
- 2 precision ground cutting edges [Z2].
- Long-lasting cutting performance.

Application:
used to drill precise flat bottom holes with no chipping in any softwood thickness.

Forstner Bit Sets

SP Z2 V2 RH

We offer a wide range of Forstner bits in the most popular diameters. These bits are available separately or in beautiful wooden sets. The high performance stagger tooth design on the bits with larger diameters allows for sharp holes with straight sides and flat bottoms. Bits available for drill presses, electric and cordless drills. Suitable for working on any type of softwood.

537.000.04
537.000.05
537.000.07
537.000.12





DESCRIPTION	SHANK	BIT DIAMETER	ORDER NO. Right-hand rotation
5 pcs. Router Bit Set in clamshell	Ø8-10mm	Ø15-20-25-30-35mm	**537.000.05**
12 pcs. Router Bit Set in clamshell	Ø8-10mm	Ø10-12-14-15-16-18-20-22-25-26-30-35mm	**537.000.12**
4 pcs. Router Bit Set in clamshell	Ø3/8"	Ø1/4" - 1/2" - 3/4" - 1"	**537.000.04**
7 pcs. Router Bit Set in clamshell	Ø3/8"	Ø1/4" - 3/8" - 1/2" - 5/8" - 3/4" - 7/8" - 1"	**537.000.07**
16 pcs. Router Bit Set in plastic box	Ø3/8"	Ø1/4" - 3/8" - 1/2" - 5/8" - 3/4" - 7/8" - 1" - 1-1/8" - 1-1/4"-1-3/8"-1-1/2"-1-5/8"-1-3/4"-1-7/8"-2"-2-1/8"	**537.000.16**

www.dahm.no



531


HW Z2 RH


D mm	L mm	S mm	Max RPM	ORDER NO. Right-hand rotation
54	73,5	9,5	1500	**531.541**
54	71,3	9,5	1500	**531.542**
54	67,3	9,5	1500	**531.543**
54	72,3	9,5	1500	**531.544**
70	76,5	9,5	1000	**531.701**
70	74	9,5	1000	**531.702**

TECHNICAL DETAILS:
- Super strength HS steel.
- 2 HW precision ground cutting edges [Z2].
- Parallel exagonal shank.
- Right-hand rotation (RH).

APPLICATION:
to be used on drill presses and drilling power tools at low RPMs (see table). We recommend clamping your workpiece mechanically during boring operations.


Top of hexagonal shank











Drawings are 1:1 scale










531.541
531.701



531.542
531.702


531.543


531.544

www.dahm.no

Brad Point Bits



542-535


HS Z1 V1 RH

D mm	I mm	L mm	S	ORDER NO. Right-hand rotation
6	155	230	Hexagonal	**542.060.51**
8	155	230	Hexagonal	**542.080.51**
10	155	230	Hexagonal	**542.100.51**
12	155	230	Hexagonal	**542.120.51**
14	155	230	Hexagonal	**542.140.51**
16	155	230	Hexagonal	**542.160.51**
18	155	230	Hexagonal	**542.180.51**
20	155	230	Hexagonal	**542.200.51**
7	360	460	Hexagonal	**535.070.51**
8	360	460	Hexagonal	**535.080.51**
10	360	460	Hexagonal	**535.100.51**
12	360	460	Hexagonal	**535.120.51**
14	360	460	Hexagonal	**535.140.51**
16	360	460	Hexagonal	**535.160.51**
18	360	460	Hexagonal	**535.180.51**
20	360	460	Hexagonal	**535.200.51**

Technical details:
- Super strength HS steel.
- Precision balanced centre point.
- 1 precision ground cutting edge [Z1].
- 1 spiral flute.
- 1 spur [V1].
- Long-lasting cutting performance.

Application:
used for drilling deep holes in soft and hardwood.

Brad Point Bits



540

HW Z2 V2 RH

D mm	L mm	S mm		ORDER NO. Right-hand rotation
5	90	8x30		**540.050.11**
6	90	8x30		**540.060.11**
8	90	8x30		**540.080.11**
10	90	8x30		**540.100.11**
12	90	8x30		**540.120.11**

Technical details:
- Super strength steel.
- HW head with precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- 2 negatively ground spurs [V2].
- 2 spiral flutes

Application:
for use on hand-held router to drill blind holes in solid wood, wood composites or plastic laminates.


541 Stop Collars

D mm			ORDER NO.	Spare parts	
5			**541.050.00**	990.002.00	991.062.00
6			**541.060.00**	990.002.00	991.062.00
8			**541.080.00**	990.002.00	991.062.00
10			**541.100.00**	990.002.00	991.062.00
12			**541.120.00**	990.002.00	991.062.00

Stop collars with precision clamping nut and key for quick and easy assembly.

www.dahm.no

Dowel Drills for Mafell® & Hand-Held Routers



312

HW Z2 RH

D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
4	30	58	8	**312.040.11**
5	30	58	8	**312.050.11**
6	30	58	8	**312.060.11**
8	30	58	8	**312.080.11**
10	30	58	8	**312.100.11**
12	30	58	8	**312.120.11**
14	30	58	8	**312.140.11**
16	30	58	8	**312.160.11**

These drill bits are made with high-strength steel in order to work with high speed rotation.
They are perfect for boring all materials like solid wood, wood and composites, plastic and laminated with **hand-held routers and MAFELL® machine model DD40.**

Spare parts
990.003.00

Optional
990.088.00

TECHNICAL DETAILS:
- Super strength steel.
- Spiral portion coated with black P.T.F.E.
- HW precision balanced centre point.
- 2 HW precision ground cutting edges [Z2].
- 2 spiral flutes.
- Parallel shank with driving flat and length adjusting screw.

Router Bits for Domino® Joining Machines by Festool®



380


HW HWM Z2 RH


D mm	I mm	L mm	S mm	FESTOOL®	ORDER NO. Right-hand rotation
• 4	11	38	M6x0,75	DF500	**380.040.11**
5	20	49	M6x0,75	DF500	**380.050.11**
6	28	49	M6x0,75	DF500	**380.060.11**
8	28	49	M6x0,75	DF500	**380.080.11**
8	50	90	M8x1	DF700	**380.081.11**
10	28	49	M6x0,75	DF500	**380.100.11**
10	70	90	M8x1	DF700	**380.101.11**
12	70	90	M8x1	DF700	**380.121.11**
14	70	90	M8x1	DF700	**380.141.11**

• **HWM**

TECHNICAL DETAILS:
- Premium quality super-strength steel.
- Spiral portion coating with black P.T.F.E.
- Extra-fine micrograin carbide spiral portion.
- 2 cutting edges [Z2].
- 2 spiral flutes.


APPLICATION:
for use on "Domino®" machines to rout slots on solid wood and wood composites.





www.dahm.no

Brad Point Bits



517

SP HS Z2 RH

D mm	I mm	L mm	S mm	ORDER NO. SP Right-hand rotation	ORDER NO. HS Right-hand rotation
3	33	61	3	**517.030.31**	**517.030.51**
4	43	75	4	**517.040.31**	**517.040.51**
5	52	86	5	**517.050.31**	**517.050.51**
6	57	93	6	**517.060.31**	**517.060.51**
7	69	109	7	**517.070.31**	**517.070.51**
8	75	117	8	**517.080.31**	**517.080.51**
9	80	120	9	**517.090.31**	**517.090.51**
10	80	120	10	**517.100.31**	**517.100.51**
11	89	142	8	**517.110.31**	**517.110.51**
12	96	151	8	**517.120.31**	**517.120.51**
13	96	151	8	**517.130.31**	**517.130.51**
14	96	151	10	**517.140.31**	**517.140.51**
15	100	160	10	**517.150.31**	**517.150.51**
16	100	160	10	**517.160.31**	**517.160.51**
18	130	180	10	**517.180.31**	
20	135	200	10	**517.200.31**	

SP

Technical details:
- Super strength SP steel.
- Precision balanced center point.
- 2 precision ground cutting edges [Z2].
- 2 flutes.

Application:
used for drilling holes in softwood.

HS

Technical details:
- Super strength HS steel.
- Precision balanced center point.
- 2 precision ground cutting edges [Z2].
- 4 flutes.

Application:
used for drilling holes in soft and hardwood.
Long-lasting cutting performance.

Brad Point Bit Sets





517

HS SP Z2 RH


5-Piece Brad Point Bit Set
An economical collection of the five most popular sized brad points - 4, 5, 6, 8 and 10mm.
Safely packaged in a reusable plastic case for easy storage and access.

8-Piece Brad Point Bit Set
A complete collection of the most popular brad points in the most requested sizes - 3, 4, 5, 6, 7, 8, 9 and 10mm.
Safely packaged in a reusable plastic case for easy storage and access.

DESCRIPTION	Z	BIT DIAMETER	ORDER NO. Right-hand rotation
5-Pcs. HS Brad Point Set	4 flutes	(Ø4-5-6-8-10mm)	**517.001.01**
5-Pcs. SP Brad Point Set	2 flutes	(Ø4-5-6-8-10mm)	**517.001.00**
8-Pcs. HS Brad Point Set	4 flutes	(Ø3-4-5-6-7-8-9-10mm)	**517.002.01**
8-Pcs. SP Brad Point Set	2 flutes	(Ø3-4-5-6-7-8-9-10mm)	**517.002.00**

www.dahm.no

Drill Bits for ANUBA® Hinges



515

HS Z2 RH

ANUBA® no.	d mm	D-S mm	l_1 mm	l mm	LB mm	L mm	ORDER NO. Right-hand rotation
9,5	3,8	5,2	18	56	74	132	**515.095.51**
11	4,8	5,7	17	60	76	145	**515.110.51**
13	5,8	6,7	18	68	83	155	**515.130.51**
14,5	6,3	7,2	19	75	89	165	**515.145.51**
16	6,7	7,7	25	85	100	165	**515.160.51**
18	7,7	8,7	25	85	102	165	**515.180.51**
20	8,8	9,8	25	90	104	165	**515.200.51**

Parallel Shank with Driving Flat

ANUBA® no.	d mm	D mm	l mm	LB mm	S mm	L mm	ORDER NO. Right-hand rotation
9	3,8	5	20	40	10x35	75	**515.091.51**
11	4,2	5,7	20	45	10x35	80	**515.111.51**
13	5,2	6,5	15	50	10x35	85	**515.131.51**
14	5,5	7	15	55	10x35	90	**515.141.51**
16	6	7,7	15	60	10x35	95	**515.161.51**
18	6,6	8,2	20	70	10x35	105	**515.181.51**
20	7,2	8,7	20	80	10x35	115	**515.201.51**

TECHNICAL DETAILS:
- Super strength steel.
- HS steel.
- 2 HS precision ground cutting edges [Z2].
- 2 spiral flutes.


APPLICATION:
used for drilling blind holes in soft and hardwood.







Brad Point Bits



516

HS Z2 RH LH


D mm	l mm	L mm	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
2	24	49	2	**516.020.51**	**516.020.52**
2,5	30	57	2,5	**516.025.51**	**516.025.52**
3	33	61	3	**516.030.51**	**516.030.52**
3,5	39	70	3,5	**516.035.51**	**516.035.52**
4	43	75	4	**516.040.51**	**516.040.52**
4,5	47	80	4,5	**516.045.51**	**516.045.52**
5	52	86	5	**516.050.51**	**516.050.52**
5,5	57	93	5,5	**516.055.51**	**516.055.52**
6	57	93	6	**516.060.51**	**516.060.52**
7	69	109	7	**516.070.51**	**516.070.52**
8	75	117	8	**516.080.51**	**516.080.52**
9	81	125	9	**516.090.51**	**516.090.52**
10	87	133	10	**516.100.51**	**516.100.52**

TECHNICAL DETAILS:
- Super strength steel.
- Precision balanced centre point.
- 2 precision ground cutting edges [Z2].
- 2 spiral flutes.
- Common shank and cutting diameter (S=D).

APPLICATION:
used for drilling holes in soft and hardwood.

www.dahm.no

Countersinks with Threaded Shank



350

HW Z2 RH LH


B mm	S mm			ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
3	M10/Ø11x4			**350.030.11**	**350.030.12**
4	M10/Ø11x4			**350.040.11**	**350.040.12**
5	M10/Ø11x4			**350.050.11**	**350.050.12**

Technical details:
- Super strength steel.
- 2 HW precision ground cutting edges [Z2].
- Quick and easy drill change.

Application:
for use with spiral bits featuring parallel shank.

Spare parts
990.001.00

Countersinks with Threaded Shank



351


B mm	S mm			ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
3	M10/30°			**351.030.11**	**351.030.12**
4	M10/30°			**351.040.11**	**351.040.12**
5	M10/30°			**351.050.11**	**351.050.12**

Technical details:
- Super strength steel.
- 2 HW precision ground cutting edges [Z2].
- Quick and easy drill change.

Application:
for use with spiral bits featuring parallel shank.

Spare parts
990.001.00

Adjustable Countersink




521.001

HW Z2 RH

d mm	D mm		ORDER NO. Right-hand rotation
3 ~ 7	11 ~ 15		**521.001.11**

Spare parts
990.061.00 991.067.00




Twist drills	Overall diameter
Ø3	Ø11
Ø4	Ø12
Ø5	Ø13
Ø6	Ø14
Ø7	Ø15

Technical details:
- Premium quality HW.
- 2 HW precision ground cutting edges [Z2].
- Quick and easy drill change.

Application:
for use with spiral bits featuring parallel shank.
Twist drills not included.

www.dahm.no

Drill Bits with 45° Countersink Set




521A

HW Z2 RH

d mm	D mm	D₂ mm	A	S mm	ORDER NO. Right-hand rotation	Spare parts		
3	12	10	45°	8	**521.312.11A**	521.312.11	517.030.51	541.101.00
4	12	10	45°	8	**521.412.11A**	521.412.11	517.040.51	541.101.00
5	16	14	45°	10	**521.516.11A**	521.516.11	517.050.51	541.141.00
6	16	14	45°	10	**521.616.11A**	521.616.11	517.060.51	541.141.00

Spare parts
990.014.00 Screw
991.060.00 Hex key




TECHNICAL DETAILS:
- Super strength steel.
- Countersink: 2 HW precision ground cutting edges [Z2].

APPLICATION:
used for drilling holes in soft, hardwood and wood composites.

Stop collars with precision clamping nut for quick and easy assembly. The Delrin® protection sleeve lets you work without leaving marks on the workpiece.

Drill Bits with 90° Countersink Set




515A

HW Z2 V2 RH

d mm	D mm	D₂ mm	S mm	ORDER NO. Right-hand rotation	Spare parts		
4	12	10	10	**515.412.11A**	515.412.11	517.040.51	541.101.00
4	14	12	10	**515.414.11A**	515.414.11	517.040.51	541.121.00
5	15	14	10	**515.515.11A**	515.515.11	517.050.51	541.141.00
6	14	12	10	**515.614.11A**	515.614.11	517.060.51	541.121.00
6	15	14	10	**515.615.11A**	515.615.11	517.060.51	541.141.00

Spare parts
990.014.00 Screw
991.060.00 Hex key




TECHNICAL DETAILS:
- Super strength steel.
- Countersink: 2 HW precision ground cutting edges [Z2].
- Countersink: 2 HW negatively ground spurs [V2].

APPLICATION:
used for drilling holes in soft, hardwood and wood composites.

Stop collars with precision clamping nut for quick and easy assembly. The Delrin® protection sleeve lets you work without leaving marks on the workpiece.

Stop Collars with Delrin® Sleeve




541

B mm			ORDER NO.	Spare parts	
10			**541.101.00**	990.014.00	991.060.00
12			**541.121.00**	990.014.00	991.060.00
14			**541.141.00**	990.014.00	991.060.00

Stop collars with precision clamping nut for quick and easy assembly. The Delrin® protection sleeve lets you work without leaving marks on the workpiece.

www.dahm.no

45° Countersink with Parallel Shank




521

HW Z2 RH LH


d mm	D mm	D₂ mm	A	S mm	ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation	Spare parts
3	12	10	45°	8	**521.312.11**	**521.312.12**	990.014.00
4	12	10	45°	8	**521.412.11**	**521.412.12**	990.014.00
5	16	14	45°	10	**521.516.11**	**521.516.12**	990.014.00
6	16	14	45°	10	**521.616.11**	**521.616.12**	990.014.00

Spare parts **991.060.00** 2mm hex key



Technical details:
- Super strength steel.
- 2 HW precision ground cutting edges [Z2].

90° Countersink with Parallel Shank




515

HW Z2 V2 RH

d mm	D mm	D₂ mm	A	S mm	ORDER NO. Right-hand rotation		Spare parts
4	12	10	90°	10	**515.412.11**		990.014.00
4	14	12	90°	10	**515.414.11**		990.014.00
5	15	14	90°	10	**515.515.11**		990.014.00
6	14	12	90°	10	**515.614.11**		990.014.00
6	15	14	90°	10	**515.615.11**		990.014.00

Spare parts **991.060.00** 2mm hex key




Technical details:
- Super strength steel.
- 2 HW precision ground cutting edges [Z2].
- 2 HW negatively ground spurs [V2].

www.dahm.no

90° Countersink with Parallel Shank

new


CMT ORANGE TOOLS™



521

HWM | Z3 | RH


D mm	I mm	L mm	S mm	ORDER NO. Right-hand rotation
19,5	9	70	10x48	**521.002.11**



TECHNICAL DETAILS:
- Super strength steel.
- 3 HWM precision ground cutting edges [Z3].

Drill Bit with Countersink for Screw Joints

new




515


SP | Z1 | RH

D mm	D2 mm	L mm	S mm		ORDER NO. Right-hand rotation
4,2	7,6	87	9		**515.042.31**
5	7,6	93,7	9		**515.050.31**

TECHNICAL DETAILS:
- Super strength steel.
- SP steel.
- 1 SP precision ground cutting edge [Z1].
- 1 spiral flute.

APPLICATION:
used for drilling blind holes in soft and hardwood.





www.dahm.no

FASTX4® SYSTEM: THE HOLE SAW REVOLUTION!

CMT's innovative system offers great advantages to all professionals!

new

X1 FAST LOCK

ALL IN ONE CLICK!

We developed a unique patented Fast Lock System to quickly change between sizes and types in seconds!
It is the only system that allows the hole saw and the pilot drill to be changed without tools.



X2 FAST DRILL

FAST DRILLING IN ALL CONDITIONS!

Our hole saws have unique body geometry and teeth sharpening which provides fast, precise drilling at Xtreme angles.
- pre-drill at the desired angle
- push the hole saw forward back in position and complete the hole.



X3 FAST BORE ENLARGEMENT

UNIQUE SOLUTION FOR BORE ENLARGEMENT!


CMT's has a unique and fast solution to enlarge your bores. Our innovative pilot drill bit can fit two hole saws, allowing you to enlarge a hole in seconds.




X4 FAST PLUG REMOVAL


EASY PLUG REMOVAL IN ONE CLICK!


No more screwdrivers or tools!
The plug is effortlessly removed by reversing the pilot drill bit.





Hole Saw Blades





PRODUCTS	PAGE
Tungsten Carbide-Tipped	302-303
Tungsten Carbide-Tipped Long	304-305
Bi-Metal Plus 8% Cobalt	306-307
Diamond Dry	308-309
Hole Saw Sets	310

Join us on our

YouTube

channel and watch our
Hole Saws video tutorials.

FASTX4 SYSTEM: THE HOLE SAW REVOLUTION!

The innovative patented FASTX4 system makes the hole saw arbor obsolete. These hole saws have been specifically designed to ensure maximum productivity, lifetime and performance in all materials. CMT offers a professional range for electricians, carpenters, builders, kitchen fitters and all related heating, ventilation and plumbing trades.

new

SERIES 550 TUNGSTEN CARBIDE-TIPPED
SERIES 553 TUNGSTEN CARBIDE-TIPPED LONG



5X FASTER

10X LONGER LIFE



HW


Long Lasting Construction Grade Carbide.
A special formulated construction grade carbide is used for the cutting teeth, which provides 10 times longer cutting life.

Tungsten carbide-tipped multi-purpose hole saws are designed for use in a wide variety of materials such as soft and hardwoods, chipboard, plywood, MDF, plastic, gypsum/plasterboard, tiles, solid brick, brick with cavities, aerated concrete block, lightweight aggregate block, breeze block and soft density lime-sandstone building block (max 30 N/mm² hardness).

SERIES 551 BI-METAL PLUS 8% COBALT



2X LONGER LIFE



BIM

Bi-Metal Plus 8% Cobalt
Premium bi-metal with 8% cobalt provides Xtreme results in performance and up to 50% longer lifetime than the competition.

Special tooth geometry with regular pitch provides a smoother cut and better chip clearance preventing clogging and heat build-up. Teeth are alternate & side set to minimize binding and friction requiring less feed pressure. Ideal for mild steel (up to 1000 N/mm² strenght), stainless steel, non-ferrous metal, aluminium, cast iron, copper and zinc.

SERIES 552 DIAMOND DRY



10X LONGER LIFE



GRIT

Diamond Grit Premium Grade
Very well-shaped and extremely strong cubo-octahedral inclusion-free heat-resistant crystals to deliver fast clean cuts up to 10 times longer life.

Diamond grit edge hole saws have been specially developed for professionals that need to drill in extremely hard materials such as ceramic tile (porcelain, gres, quarry, granite, hard stone), fiberglass, gypsum/plasterboard, fibercement board, Perspex®, where it is increasingly difficult to drill with conventional hole saws. These hole saws guarantee excellent performance and superior lifetime even in the hardest materials.

EYE-CATCHING PACKAGING



03.01.0297 *(empty box)*



03.01.0296 *(empty box)*



Teeth are protected with heat shrink wrap film

www.dahm.no

FASTX4 Hole Saw Application Chart

new

CMT ORANGE TOOLS™

Material	Series 550-553	Series 551	Series 552	Tips
Soft and hardwood	>500 holes	<30 holes		
Plywood, table top	>500 holes	<30 holes		
MDF, chipboard, venereed	>500 holes	<30 holes		
Laminated, Trespa®, HPL	>500 holes	<10 holes		
Gypsum and plasterboard	>500 holes	<50 holes	<20 holes	
Fibercement boards, Eternit®	>50 holes	<10 holes	<20 holes	
Sandwich materials		50~75 holes		
Plastic	>100 holes	<20 holes		
Fiberglass	50~100 holes			
Acrylic glass	>100 holes			Use coolant
Roofing tiles	>50 holes			No concrete tiles
Solid bricks, masonry	>50 holes		<20 holes	
Perforated bricks	>50 holes		<20 holes	
Lime bricks	>50 holes			
Porous and lightweight concrete	>500 holes	<20 holes		
Metals and thin sheet metals		10~40 holes		Use coolant oil
Non-ferrous metals		50~75 holes		Use coolant oil
Aluminium		50~75 holes		Use coolant oil
Stainless steel		30~50 holes		Use coolant oil. Low speed
Cast iron		5~10 holes		Use coolant oil
Copper, zinc, brass		50~75 holes		Use coolant oil
Tiles (porcelain, gres, quarry)			10~50 holes	
Hard stone (granite, marble), Okite			10~50 holes	

The number of holes is approximate. Material type, thickness and speed can affect such performance.

Examples of applications by diameter and user (this may vary country to country)

Diameter in mm	19	22	25	30	35	40	44	48	51	54	57	60	64	68	70	76	83	86	92	102	105	127	152	
Application																								**User**
Fitted light	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●			Electrician
Cable feedthrough box				●	●							●						●						
Switch boxes													●											
Plug sockets														●										
Junction boxes															●	●								
Distributor boxes																	●	●						
Air conditioning pipes																				●	●			Heating fitter
Sanitary and heating pipes	●		●	●	●																			Plumber and heating fitter
Sanitary, drain and water pipes (insulated)						●	●	●																

www.dahm.no

FASTX4 Multi-Purpose Hole Saws

new

CMT ORANGE TOOLS™

550



HW **LONG LASTING CONSTRUCTION GRADE CARBIDE.**
Cutting teeth are made of a special formulated construction grade carbide which provides a longer cutting life.

SECURED TOOTH TECHNOLOGY
As a result of the latest technology, teeth are secured to prevent any breakage during impact with hard materials.

10X LONGER LIFE **5X FASTER**



The plug is effortlessly removed thanks to the innovative slots

MATERIALS

- soft, hardwood and plywood
- chipboard, MDF, veneered, laminated and table top
  (pre-drill the laminate/melamine by using left-hand rotation for clean finishing)
- gypsum, plasterboard, fibercement board, Eternit®
- plastics (PVC, nylon, Trespa®, polyester)
- fiberglass and acrylic glass
- tiles, solid bricks and bricks with cavities, aerated concrete blocks, lightweight aggregate blocks and breeze blocks, soft density lime-sandstone building blocks (max 30 N/mm2 hardness); for hardness >30 N/mm2 use the diamond dry hole saws.




Ceramic tiles



Wood & MDF



Trespa® & Plastic



Plasterboard



Soft bricks



Lime bricks

Use the recommended speeds to get optimum lifetime. The speed affects the hole quality.
Always pre-drill with the center drill to achieve best performance.
The percussion/hammer action mode must be turned off when using these hole saws.

NEVER USE HAMMER MECHANISM

www.dahm.no

FASTX4 Multi-Purpose Hole Saws

new

CMT ORANGE TOOLS™

D mm	D inches	Z	Wood & MDF RPM	PVC & Fiberglass RPM	Masonry, brick RPM	Tiles RPM	S	ORDER NO.
19	3/4	1	1.600	1.000	1.000	640	Hexagonal	**550-019**
20	25/32	1	1.600	1.000	1.000	640	Hexagonal	**550-020**
22	7/8	1	1.460	1.000	1.000	580	Hexagonal	**550-022**
25	1	1	1.280	1.000	1.000	510	Hexagonal	**550-025**
29	1-1/8	1	1.100	940	940	440	Hexagonal	**550-029**
30	1-3/16	1	1.070	910	910	430	Hexagonal	**550-030**
32	1-1/4	1	1.000	850	850	400	Hexagonal	**550-032**
35	1-3/8	1	920	780	780	370	Hexagonal	**550-035**
38	1-1/2	2	840	720	720	340	Hexagonal	**550-038**
40	1-9/16	2	800	680	680	320	Hexagonal	**550-040**
44	1-3/4	2	730	620	620	290	Hexagonal	**550-044**
51	2	3	630	540	540	250	Hexagonal	**550-051**
52	2-3/64	3	620	530	530	250	Hexagonal	**550-052**
54	2-1/8	3	590	510	510	240	Hexagonal	**550-054**
56	2-3/16	3	570	490	490	230	Hexagonal	**550-056**
57	2-1/4	3	560	480	480	220	Hexagonal	**550-057**
60	2-3/8	3	530	460	460	210	Hexagonal	**550-060**
64	2-1/2	3	500	430	430	200	Hexagonal	**550-064**
65	2-9/16	3	500	430	430	200	Hexagonal	**550-065**
68	2-43/64	3	470	400	400	190	Hexagonal	**550-068**
70	2-3/4	3	460	390	390	180	Hexagonal	**550-070**
73	2-7/8	3	440	370	370	180	Hexagonal	**550-073**
76	3	3	420	360	360	170	Hexagonal	**550-076**
79	3-1/8	3	410	350	350	160	Hexagonal	**550-079**
80	3-5/32	3	400	340	340	160	Hexagonal	**550-080**
82	3-15/64	3	390	330	330	160	Hexagonal	**550-082**
83	3-1/4	3	390	330	330	150	Hexagonal	**550-083**
89	3-1/2	3	360	310	310	140	Hexagonal	**550-089**
92	3-5/8	3	350	300	300	140	Hexagonal	**550-092**
102	4	5	310	270	270	130	Hexagonal	**550-102**
105	4-1/8	5	310	260	260	120	Hexagonal	**550-105**
108	4-1/4	5	300	250	250	120	Hexagonal	**550-108**
111	4-3/8	5	290	250	250	120	Hexagonal	**550-111**
114	4-1/2	5	280	240	240	110	Hexagonal	**550-114**
118	4-5/8	5	280	240	240	110	Hexagonal	**550-118**
127	5	5	250	220	220	100	Hexagonal	**550-127**
133	5-1/4	5	240	210	210	100	Hexagonal	**550-133**
152	6	5	210	180	180	80	Hexagonal	**550-152**
168	6-5/8	5	200	150	150	120	Hexagonal	**550-168**
210	8-5/16	5	200	150	150	120	Hexagonal	**550-210**
225	8-7/8	5	160	120	120	95	Hexagonal	**550-225**
260	10-15/64	5	150	110	110	80	Hexagonal	**550-260**
270	10-5/8	5	140	100	100	70	Hexagonal	**550-270**

550-HS1

For **Ø20-30mm (25/32" - 1-3/16")**.
Hexagonal shank for **10mm** (25/64") chuck, HSS center drill, total length 180mm (7-5/64").





550-HW1

For **Ø20-30mm (25/32" - 1-3/16")**.
Hexagonal shank for **10mm** (25/64") chuck, HW center drill, total length 180mm (7-5/64").





550-HS2

For **Ø32mm (1-1/4") and above**.
Hexagonal shank for **13mm** (1/2") chuck, HSS center drill, total length 180mm (7-5/64").







550-HW2

For **Ø32mm (1-1/4") and above**.
Hexagonal shank for **13mm** (1/2") chuck, HW center drill, total length 180mm (7-5/64").







550-DB1

For plug removal and bore enlargement (in hole saws with different hexagonal shank sizes).
Hexagonal shank for **13mm** (1/2") chuck.





**Bore enlargement: feasible with hole saws with 9mm minimum difference between largest and smallest diameter.*

www.dahm.no

FASTX4 Multi-Purpose Long Hole Saws


new

CMT ORANGE TOOLS

553

PERFECT ROUND BACK PLATE

FAST & EASY CHANGE




LARGE CHIP CLEARANCE SLOTS

10X LONGER LIFE 5X FASTER

HW **Long Lasting Construction Grade Carbide.**
Cutting teeth are made of a special formulated construction grade carbide which provides a longer cutting life.

Secured Tooth Technology
As a result of the latest technology, teeth are secured to prevent any breakage during impact with hard materials.







D mm	D inches	Z	Wood & MDF RPM	PVC & Fiberglass RPM	Masonry, brick RPM	Tiles RPM	S	ORDER NO.
32	1-1/4	1	800	600	600	400	Hexagonal	**553-032**
45	1-49/64	2	600	450	450	350	Hexagonal	**553-045**
51	2	3	600	450	450	350	Hexagonal	**553-051**
60	2-3/8	3	500	350	350	300	Hexagonal	**553-060**
65	2-9/16	3	500	350	350	300	Hexagonal	**553-065**
68	2-43/64	3	500	350	350	300	Hexagonal	**553-068**
70	2-3/4	3	500	350	350	300	Hexagonal	**553-070**
76	3	3	500	350	350	300	Hexagonal	**553-076**
80	3-5/32	3	300	250	250	200	Hexagonal	**553-080**
83	3-1/4	3	300	250	250	200	Hexagonal	**553-083**
86	3-3/8	3	300	250	250	200	Hexagonal	**553-086**
92	3-5/8	3	300	250	250	200	Hexagonal	**553-092**
102	4	5	300	250	250	200	Hexagonal	**553-102**
105	4-1/8	5	300	250	250	200	Hexagonal	**553-105**
111	4-3/8	5	200	150	150	120	Hexagonal	**553-111**
114	4-1/2	5	200	150	150	120	Hexagonal	**553-114**
121	4-49/64	5	200	150	150	120	Hexagonal	**553-121**
130	5-1/8	5	200	150	150	120	Hexagonal	**553-130**
133	5-1/4	5	200	150	150	120	Hexagonal	**553-133**
140	5-1/2	5	200	150	150	120	Hexagonal	**553-140**
152	6	5	200	150	150	120	Hexagonal	**553-152**
160	6-19/64	7	200	150	150	120	Hexagonal	**553-160**
190	7-1/2	7	200	150	150	120	Hexagonal	**553-190**
210	8-5/16	7	200	150	150	120	Hexagonal	**553-210**

542.100.51

Auger bit **Ø10mm (25/64")** to pre-drill deep holes in wood and wood-based.
Hexagonal shank, total length 200mm (7-7/8").





553-HW10

Carbide tipped bit **Ø10mm (25/64")** to pre-drill deep holes in masonry materials.
Hexagonal shank, total length 200mm (7-7/8").





553-CP2

Heavy Duty center pin Ø10mm (25/64").
Hexagonal shank, total length 330mm (13").



www.dahm.no


FASTX4 Multi-Purpose with Countersink Hole Saws

new

CMT ORANGE TOOLS™

550CS






Example of commercial electric flush-mount boxes.

FLUSH-MOUNT



APPLICATIONS in wood, plywood, chipboard, MDF, gypsum, plasterboard, fiber cement boards, Eternit®, plastics, bricks and tiles **to create holes in hollow walls for electric flush-mount boxes.**

NO FLUSH-MOUNT



D mm	D inches	Z	Wood & MDF RPM	PVC & Fiberglass RPM	Masonry, brick RPM	Tiles RPM	S	ORDER NO.
65	2-9/16	3	470	400	400	190	Hexagonal	**550-065CS**
68	2-43/64	3	470	400	400	190	Hexagonal	**550-068CS**

Hole Saws Accessories

550-HS2XL For **Ø32mm (1-1/4") and above**.
Long heavy duty hexagonal shank, HSS center drill, total length 320mm (12-19/32").





550-HW2XL For **Ø32mm (1-1/4") and above**.
Long heavy duty hexagonal shank, HW center drill, total length 320mm (12-19/32").





551-HS2XL For **Ø32mm (1-1/4") and above**.
Long heavy duty hexagonal shank, HSS center drill, total length 320mm (12-19/32").





550-EX1/550-EX2 **Extensions for center drills**
for Multi-Purpose hole saws serie 550 (with a cutting depth of 52mm) and HSS Bimetal hole saws serie 551.



S	L mm	L inches	For Chuck mm	ORDER NO.
Hexagonal	300	11-13/16	10	**550-EX1**
Hexagonal	300	11-13/16	13	**550-EX2**

550-SDS1/550-SDS2 **SDS Adaptors for center drills**
for Multi-Purpose hole saws serie 550 (with a cutting depth of 52mm) and HSS Bimetal hole saws serie 551.



S	L mm	L inches	For Chuck mm	ORDER NO.
SDS	95	3-3/4	10	**550-SDS1**
SDS	95	3-3/4	13	**550-SDS2**


www.dahm.no

FASTX4 Bi-Metal Plus Hole Saws

new

CMT ORANGE TOOLS™

551




MATERIALS

- metals (up to 1000 N/mm² strenght)
- mild steel,
- stainless steel
- non-ferrous metals, aluminium
- sandwich materials
- cast iron
- copper, zinc, brass


BIM — **BI-METAL PLUS 8% COBALT**
Premium bi-metal with 8% cobalt provides Xtreme results in performance and up to 50% longer lifetime than the competition.

2X LONGER LIFE



TEETH DESIGN
Special tooth geometry with regular pitch provides a smoother cut and better chip clearance preventing clogging and heat build-up. Teeth are alternate & side set to minimize binding and friction, requiring less feed pressure.





Stainless steel and cast iron



Zinc, aluminium and copper

SPEED KILLS!

Operating at higher speeds than those recommended will shorten hole saw life and produce very inefficient cutting.

FEED PRESSURE:

Variables in material, work configuration should be considered. Apply sufficient feed pressure to aid good chip removal. Reduce the pressure when hole saw becomes hot or if teeth start to clog with material.
Insufficient feed pressure will dull tooth points prematurely, but too much pressure can totally destroy teeth.

COOLING LUBRICANT:

Cutting oil serves several purposes when sawing in metals:
- it cools saw and workpiece
- it reduces heat and abrasion, which can shorten cutting life
- it also helps remove swarf from the cutting surface
- using a cooling lubricant will extend your hole saw life by 500%.

Percussion/hammer action mode must be turned off when using these hole saws.



www.dahm.no

FASTX4 Bi-Metal Plus Hole Saws

new

CMT ORANGE TOOLS™


D mm	D inches	Metal RPM	Stainless steel RPM	Cast iron RPM	Aluminium RPM	S	ORDER NO.
16	5/8	550	270	370	800	Hexagonal	**551-016**
19	3/4	470	230	310	670	Hexagonal	**551-019**
20	25/32	440	220	290	640	Hexagonal	**551-020**
22	7/8	400	200	270	580	Hexagonal	**551-022**
25	1	350	170	230	510	Hexagonal	**551-025**
27	1-1/16	330	160	220	470	Hexagonal	**551-027**
29	1-1/8	310	150	200	440	Hexagonal	**551-029**
30	1-3/16	300	140	190	430	Hexagonal	**551-030**
32	1-1/4	280	140	180	400	Hexagonal	**551-032**
35	1-3/8	250	120	170	370	Hexagonal	**551-035**
38	1-1/2	230	110	150	340	Hexagonal	**551-038**
40	1-9/16	220	110	150	320	Hexagonal	**551-040**
43	1-11/16	210	100	140	300	Hexagonal	**551-043**
44	1-3/4	200	100	130	290	Hexagonal	**551-044**
48	1-7/8	180	90	120	270	Hexagonal	**551-048**
51	2	170	85	110	250	Hexagonal	**551-051**
52	2-3/64	160	80	110	240	Hexagonal	**551-052**
54	2-1/8	160	80	110	240	Hexagonal	**551-054**
57	2-1/4	160	75	100	220	Hexagonal	**551-057**
60	2-3/8	150	70	95	210	Hexagonal	**551-060**
64	2-1/2	140	70	90	205	Hexagonal	**551-064**
65	2-9/16	140	70	90	205	Hexagonal	**551-065**
68	2-43/64	130	65	80	185	Hexagonal	**551-068**
70	2-3/4	130	60	80	185	Hexagonal	**551-070**
73	2-7/8	120	60	80	180	Hexagonal	**551-073**
76	3	120	55	75	170	Hexagonal	**551-076**
79	3-1/8	110	55	70	165	Hexagonal	**551-079**
83	3-1/4	105	50	70	155	Hexagonal	**551-083**
86	3-3/8	105	50	65	150	Hexagonal	**551-086**
89	3-1/2	100	50	65	145	Hexagonal	**551-089**
92	3-5/8	95	45	60	140	Hexagonal	**551-092**
102	4	85	45	55	130	Hexagonal	**551-102**
105	4-1/8	80	40	55	120	Hexagonal	**551-105**
108	4-1/4	80	40	55	120	Hexagonal	**551-108**
114	4-1/2	80	40	55	120	Hexagonal	**551-114**
127	5	70	35	45	90	Hexagonal	**551-127**
133	5-1/4	65	35	45	90	Hexagonal	**551-133**
140	5-1/2	65	30	40	85	Hexagonal	**551-140**
152	6	55	25	35	75	Hexagonal	**551-152**
168	6-5/8	55	25	35	75	Hexagonal	**551-168**
		Cutting oil	Cutting oil	Dry	Turpentine		





551-HS1

For Bi-Metal PLUS hole saws **Ø16-30mm (5/8" - 1-3/16")**. Hexagonal shank for **10mm** (25/64") chuck, HSS center drill, total length 160mm (6-5/16").





551-HS2

For Bi-Metal PLUS hole saws **Ø32 (1-1/4") and above**. Hexagonal shank for **13mm** (1/2") chuck, HSS center drill, total length 160mm (6-5/16").


www.dahm.no

FASTX4 Diamond Dry Hole Saws

new

CMT ORANGE TOOLS

552



MATERIALS

- floor tiles (porcelain, gres, quarry)
- wall tiles (porcelain, gres, quarry)
- hard stones (granite, marble), Okite
- solid bricks
- masonry
- gypsum/plasterboard
- fiber cement board
- fiberglass

GRIT


Diamond Grit Premium Grade
Well-shaped and extremely strong cubo-octahedral inclusion-free heat-resistant crystals deliver fast, clean cuts up to 10 times longer life.

10X LONGER LIFE

Diamond grit edge hole saws have been specially developed for professionals that need to drill in extremely hard materials where it is increasingly difficult to drill with conventional hole saws.
These hole saws guarantee excellent performance and superior lifetime!




Gres, porcelain and ceramic tiles



Granite and Marble



HARD STONE



GRANITE



GRES TILES

Percussion/hammer action mode must be turned off when using these hole saws.
NO angle grinder, just a high speed drilling machine (minimum 14V recommended).
Always pre-drill with the center drill to achieve the best performance.
Accurate drill positioning. Center drill reduces the risk of slipping.

www.dahm.no

new

CMT ORANGE TOOLS™



D mm	D inches	Tiles (ceramic & gres) Hard stone, bricks, masonry	S	ORDER NO.
5	13/64	RPM 1500 ~ 4000	Hexagonal	**552-005**
6	1/4	RPM 1500 ~ 4000	Hexagonal	**552-006**
8	5/16	RPM 1500 ~ 4000	Hexagonal	**552-008**
10	3/8	RPM 1500 ~ 4000	Hexagonal	**552-010**
12	15/32	RPM 1500 ~ 4000	Hexagonal	**552-012**
14	9/16	RPM 1500 ~ 4000	Hexagonal	**552-014**
16	5/8	RPM 1500 ~ 4000	Hexagonal	**552-016**

Filled with cooling wax




D mm	D inches	Tiles (ceramic & gres) Hard stone, bricks, masonry	S	ORDER NO.
18	45/64	RPM 1500 ~ 4000	Hexagonal	**552-018**
20	25/32	RPM 1500 ~ 4000	Hexagonal	**552-020**
25	1	RPM 1500 ~ 4000	Hexagonal	**552-025**
32	1-1/4	RPM 1500 ~ 4000	Hexagonal	**552-032**
35	1-3/8	RPM 1500 ~ 4000	Hexagonal	**552-035**
38	1-1/2	RPM 1500 ~ 4000	Hexagonal	**552-038**
51	2	RPM 1500 ~ 4000	Hexagonal	**552-051**
55	2-11/64	RPM 1500 ~ 4000	Hexagonal	**552-055**
68	2-43/64	RPM 1500 ~ 4000	Hexagonal	**552-068**
76	3	RPM 1500 ~ 4000	Hexagonal	**552-076**
111	4-3/8	RPM 1500 ~ 4000	Hexagonal	**552-111**



Filled with cooling wax

552-DD1

For diamond dry hole saws ≤ **Ø30mm (1-3/16")**. Hexagonal shank for **10mm** (25/64") chuck, 8mm diamond center drill, total length 143mm (5-5/8").



Filled with cooling wax

552-DD2

For diamond dry hole saws ≥ **Ø32mm (1-1/4")**. Hexagonal shank for **13mm** (1/2") chuck, 10mm diamond center drill, total length 143mm (5-5/8").



552-WAX

Jar **100ml. (3.4oz)**. Cooling Wax, for perfect cooling and lubrication.

Diamond dry step-by-step



NO WATER, LESS MESS!

www.dahm.no

BUY HOLE SAWS + ARBORS AND YOU'LL GET THE CASE TO COLLECT THE WHOLE SET FOR FREE!

new



03.01.0297
The big case is provided empty, image is purely indicative.



03.01.0296
The small case is provided empty, image is purely indicative.

HW SERIES 550 TUNGSTEN CARBIDE-TIPPED

ORDER NO.	Ø	ORDER NO.	Ø	ORDER NO.	Ø
550-020	20	550-056	56	550-HS2	
550-022	22	550-060	60	550-HW2	
550-025	25	550-064	64	550-HS1	
550-029	29	550-068	68	550-HW1	
550-030	30	550-070	70		
550-032	32	550-073	73		
550-035	35	550-076	76		
550-040	40	550-080	80		
550-044	44	550-102	102		
550-051	51	550-152	152		

20+4 pcs.

BIM SERIES 551 BI-METAL PLUS 8% COBALT

ORDER NO.	Ø	ORDER NO.	Ø	ORDER NO.	Ø
551-020	20	551-057	57	551-HS2	
551-022	22	551-060	60	551-HS1	
551-025	25	551-064	64		
551-027	27	551-068	68		
551-030	30	551-076	76		
551-035	35	551-079	79		
551-040	40	551-083	83		
551-043	43	551-089	89		
551-048	48	551-102	102		
551-051	51	551-108	108		

20+2 pcs.

HW SERIES 550 TUNGSTEN CARBIDE-TIPPED

ORDER NO.	Ø	ORDER NO.	Ø	ORDER NO.
550-025	25	550-060	60	550-HS2
550-032	32	550-064	64	550-HW2
550-035	35	550-068	68	550-HS1
550-040	40	550-080	80	550-HW1
550-051	51	550-102	102	

10+4 pcs.

BIM SERIES 551 BI-METAL PLUS 8% COBALT

ORDER NO.	Ø	ORDER NO.	Ø	ORDER NO.
551-020	20	551-040	40	551-HS2
551-022	22	551-043	43	551-HS1
551-025	25	551-051	51	
551-030	30	551-060	60	
551-035	35	551-079	79	

10+2 pcs.

GRIT SERIES 552 DIAMOND DRY

ORDER NO.	Ø	ORDER NO.	Ø	ORDER NO.
552-005	5	552-016	16	552-DD2
552-006	6	552-020	20	552-DD1
552-008	8	552-025	25	552-WAX
552-010	10	552-032	32	
552-012	12	552-035	35	

10+3 pcs.

www.dahm.no

Power Tools, Jig Accessories, Display Cabinets & Spare Parts







PRODUCTS	PAGE
Routers	313-314
Oscillating Multi-Tools	315
Router Tables	316-317
Professional Straight Edge Clamps	318
Superjaws Portable Clamping System	319
Dovetail Jig	320-321
Eclipse & Circle Cutting Jig	322
Kitchen Worktop Jig	323
CMT-Enlock Joining System	324
Inlay and Template Guide Kit	325
Boring Systems	326~330
Edge Banding Jigs	331
3D Router Carver System	332~334
Organizer	334
Blade & Bit Cleaner	335
Diamond Whetstones	336
Flexible Templates for Routing	337
Bowl & Tray System	338
Pocket-Pro Joinery System	339
Digital Moisture Meter	340
Digital Angle Gauge & Finder	340-341
Display Cabinets	342~348
Spare Parts	349~353

www.dahm.no

1010W Router

CMT ORANGE TOOLS

CMT8E

QUICK ACCESS BRUSHES
allows the end user to change worn brushes.



SAFETY SWITCH SHUTTER
locks closed in bit change mode to prevent power on.



ELECTRONIC SPEED CONTROL & SOFT START
From 8.000 - 20.000 RPM.

FULLY ENCLOSED GUARDING
provides maximum protection from the cut zone.

MULTI-FUNCTION FENCE
provides excellent control for hand-held use and circle cutting.


SIDE AIR VENTS
reduces intake of dust into the motor casing when mounted upside-down in a router table.

QUICK FIT PINS
for fast fitment and removal from its fence.



TOP OF TABLE HEIGHT ADJUSTMENT

Top of table height adjustment is possible using the height winder handle from the template guide kit.



Optional

Clamping nuts and collets for CMT8E and CMT7E

DIAMETER	ORDER NO.
D = 6mm	796.660.00
D = 6,35mm	796.664.00
D = 8mm	796.680.00
D = 10mm	796.700.00
D = 12mm	796.720.00
D = 12,7mm	796.727.00



Optional



DESCRIPTION	ORDER NO.
Prebored router plate for CMT7E and CMT8E	CMT300-SB
Guide bush Ø30mm	899.007.00

Standard Equipment

- Extended baseplate with adjustable fence
- Dust extraction outlet
- Easy adjustment
- Wrench for easy cutter change
- Ø8 and Ø12mm collets
- 1 year warranty
- Instruction manual

Worldwide Technical Assistance

Technical specifications

- Horsepower ..... 1.010 Watt
- No load speed ..... 8.000-20.000 RPM
- Plunge stroke 0-59mm
- Collet diameter Ø6-12,7mm
- Tool weight ..... 4 Kg

DESCRIPTION	ORDER NO.
Router complete with standard equipment	CMT8E

www.dahm.no

CMT ORANGE TOOLS

CMT7E

REMOVABLE PLUNGE SPRING
for easy bit adjustment when table mounted.



ELECTRONIC SPEED CONTROL & SOFT START
From 8.000 - 20.000 RPM

QUICK ACCESS BRUSHES
allows the end user to change worn brushes.



SWITCH FROM A PLUNGE TO A FIXED BASE ROUTER
by simply pressing or releasing the button.



SAFETY SWITCH SHUTTER
locks closed in bit change mode to prevent power on.



FULLY ENCLOSED GUARDING
provides maximum protection from the cut zone.

SIDE AIR VENTS
reduces intake of dust into the motor casing when mounted upside-down in a router table.

MULTI-FUNCTION FENCE
provides excellent control for hand-held use and circle cutting.

3 STAGE TURRET
with direct reading scales for precise preset cut depths.




QUICK FIT PINS
for fast fitment and removal from its fence.



TOP OF TABLE HEIGHT ADJUSTMENT

Top of table height adjustment is possible using the height winder handle from the template guide kit.



STANDARD EQUIPMENT

- Extended baseplate with adjustable fence
- Dust extraction outlet
- Infinite micro adjustment
- Wrench for easy cutter change
- Ø8 and Ø12mm collets
- 1 year warranty
- Instruction manual

Worldwide Technical Assistance

Optional



DESCRIPTION	ORDER NO.
Prebored router plate for CMT7E and CMT8E	CMT300-SB
Guide bush Ø30mm	899.007.00

Optional

Clamping nuts and collets for CMT8E and CMT7E

DIAMETER	ORDER NO.
D = 6mm	796.660.00
D = 6,35mm	796.664.00
D = 8mm	796.680.00
D = 10mm	796.700.00
D = 12mm	796.720.00
D = 12,7mm	796.727.00



Fine WoodWorking MAGAZINE
BEST VALUE · BEST OVERALL · READERS' CHOICE · BEST OVERALL · BEST VALUE

TECHNICAL SPECIFICATIONS

- Horsepower.....2.400 Watt
- No load speed .....8.000-20.000 RPM
- Plunge stroke 0-68mm
- Collet diameter.....Ø6-12,7mm
- Tool weight.....6 Kg

DESCRIPTION	ORDER NO.
Router complete with standard equipment	CMT7E


www.dahm.no

550W Professional Trimmer

new

CMT ORANGE TOOLS™


CMT10




Standard Equipment



Aluminium-embossed scale for accurate setting of the desired routing depth



Trimmer guide with Delrin® roller prevents marks on the workpiece



Fine depth adjustment



CMT10-54
Ø10mm guide bush

Standard Equipment
- Extended baseplate with adjustable fence
- Trimmer guide
- Guide bush
- 2 wrenches for easy cutter replacement
- Ø6mm and Ø8mm collet
- 1 year warranty
- Instruction manual

Worldwide Technical Assistance


TECHNICAL SPECIFICATIONS:
- Power.....550 Watt
- No load speed ..... 32.000 RPM
- Plunge stroke 0-24mm
- Collet diameter.....Ø6-8mm
- Tool weight..... 1,8 Kg

DESCRIPTION	ORDER NO.
550W Professional Trimmer	**CMT10**

Spare parts



CMT10-18 Collet Ø6mm
CMT10-18A Collet Ø6,35mm
CMT10-18B Collet Ø8mm



CMT10-30
Pair of carbon brushes



CMT10-17
Clamping nut

www.dahm.no

new

CMT ORANGE TOOLS™

CMT11

FAST LOCK



MULTI MATERIALS & APPLICATIONS:



- GRINDING
- SAWING
- JOINT OPENING
- PLASTIC CUTTING
- CARPET REMOVAL
- PLUNGE CUTTING
- WOOD CUTTING
- CUTTING LAMINATE SHEETS
- TUBE LENGTH TRIMMING
- NAIL CUTTING





DESCRIPTION	ORDER NO.
300W Oscillating Multi-Tools	CMT11

INCLUDED:



HANDLE



VACUM HOSE

Standard Equipment

- 1 x Oscillating Multi-tool
- 1 x handle
- 1 x vacuum hose
- 1 x manual
- 1 x plastic carry case

Worldwide Technical Assistance

TECHNICAL SPECIFICATIONS:

- Power..... 300 Watt
- Input..... 220/230V
- No load speed ..... 11.000~21.000 RPM
- aw (vibration)..... 19,7m/s2 - K=1,5m/s2
- Weight..... 1,2 Kg










www.dahm.no

New Professional Router Table

new

CE

CMT ORANGE TOOLS™

999.110.00

Router table dimensions:
80x60x(h)90cm. - 26,5 kg. weight

Our quality bits have been designed for you, the professional craftsman, to allow you to confidently work at your best. CMT now offers even more possibilities with our professional router table: the perfect place to combine your skills and CMT quality.
The professional router table system has a strong and sturdy MDF laminate work surface measuring 80x60x2,5cm for easy mobility when working. This free standing table sits at a comfortable height of 90cm on solid high gauge steel legs and weighs 26,5 kg.
The plate is already pre-bored for CMT routers CMT7E but is adaptable to all brands and models of routers on the market. Plate can also fit any router bit up to 98mm in diameter. Choose from our wide range of bits, including multi profile and molding bits or even kitchen bit set. Work easily and safely on this table!



Optional

999.100.11
(mandatory for CE legislation)



order separately

DESCRIPTION	ORDER NO.
CMT professional router table system:	**999.110.00**
Electric safety switch *(mandatory for CE legislation)*	**999.100.11**
CMT7E router and 999.110.00 Professional router table + 999.100.11 Electric safety switch	**CMT7E-PRO**
Parts included with the table:	
1) Plate (**pre-bored for CMT7E**) with reduction rings	**999.110.33**
2) Lexan® safety shield	**999.110.06**
3) Standing spring press	**999.110.08**
4) Moulded ABS feather board	**999.110.09**
5) Transversal mitre gauge	**999.110.10**
Optional:	
Plate with 2 reduction rings **not bored (not for CMT routers)**	**999.110.03**

www.dahm.no

Industrio Routing System

CE

CMT ORANGE TOOLS™

999.500.01


CMT has turned the Industrio routing system into a great tool with new accessories such as phenolic insert, integral aluminium scales and an improved fence. Also, you will find some new optional features, such as a rugged moulded featherboard and a new mitre gauge.

The system includes:

999.501.09

Router table dimensions:
79x59x(h)93cm. - 55 kg. weight

Unique phenol top



A new insert plate
Now featuring a 298x374mm (11-3/4"x14-3/4") insert plate, the top is milled from 12mm (15/32") thick phenol. Sturdy and very enduring material, phenol is much more resistant to warping than melamine. The top also features new aluminium scales on both ends to set the fence quickly and properly.

Easy fast bit change
No need to remove the router or fumble beneath the table top to change the bits. CMT's useful bent wrench allows you to replace the bits from above quickly and easily.
15 kg. shipping weight.




999.501.07_Moulded ABS featherboard setup on the table and in fence slots. It includes nuts, bolts and a plastic slide.



999.501.08_Mitre gauge.



999.501.18_Phenolic plate with aluminium rings (Ø103-69,5mm) ***for CMT7E***.



999.502.34_Centring device to position your router perfectly in the 8-12mm (5/16"- 15/32") insert plate.

999.501.10
Pivoting, zero-clearance fence with new clamping system
Our extruded aluminium fence can be used as conventional locked-in-place fence or as a pivoting fence. New, quick-adjusting clamps on both ends of the fence make adjustments a breeze, especially when used in conjunction with the aluminium scales that we've added to the table top.
The fence also includes a sub-fence of high density white plastic for an ultra smooth feeding surface, with a replaceable centre section to create zero-clearance inserts.
8,5 kg shipping weight.


999.501.03
Sturdy melamine cabinet
This sturdy 20mm-thick (25/32") melamine cabinet is easy to assembly with posts and cross dowels. It also, it includes a double-door storage area to keep bits, wrenches and more tools safe and dust-free. 32,5 kg. shipping weight.

Optional


Bent wrenches for easy bit replacement

17mm 991.005.00
21mm 991.002.00
22,2mm 991.004.00
23,8mm 991.003.00
24mm 991.006.00*
28,6mm 991.001.00

*** For CMT7E and CMT8E routers**




Included



999.502.10_Central section of the fence is removable for custom replacements.

Included



999.501.06_The dual and post-guard makes freehand work safer.

DESCRIPTION	ORDER NO.
Industrio routing system (with plate prebored for CMT7E)	**999.500.01**
CMT7E router and 999.500.01 Industrio routing system + 999.100.11 Electric safety switch	**CMT7E-IND**
Electric safety switch *(mandatory for CE legislation)*	**999.100.11**
Optional:	
Universal phenolic plate with aluminium rings (Ø103-69,5mm), **not bored (not for CMT routers)**	**999.501.26**
Phenolic plate with (Ø103-69,5mm) aluminium rings **for CMT8E router**	**999.501.27**
Pair of (Ø103-69,5mm) reduction rings	**999.501.05N**

www.dahm.no

Professional Straight Edge Clamps

CMT ORANGE TOOLS™

PGC


Used as a fence for your bandsaw, drill press or even as an auxiliary fence on your router table or table saw, CMT's professional straight edge clamps represent a two-in-one tool, allowing you to either use them as an edge guide, or to easily clamp your boards or any object for woodworking. Available in different sizes. Here are the main features:

- Made of extruded aluminium for easy carriage and enhanced durability.
- Light, yet more rigid than any other clamps on the market.
- Measuring scales, low-profile jaws, built-in T-tracks on the top allowing the use of accessories or jigs.
- Either single or back-to-back clamps.

DESCRIPTION	ORDER NO.
Professional Straight Edge Clamp 610mm	PGC-24
Professional Straight Edge Clamp 915mm	PGC-36
Professional Straight Edge Clamp 1270mm	PGC-50


Low-profile clamps allow for accurate cuts, dados and grooves. In addition they properly work as an auxiliary fence on your drill press or router table. Sturdy jaws hold your workpiece to the full length of the clamp without any side-to-side play. Back-to-back clamps with the suitable accessories also let you manage your woodworking operations with a lot of versatility. Adjustable scale and two T-tracks allow you to use many accessories.





Back-to-Back Connectors for Straight Edge Clamps *(optional)*

Lay two more straight edge clamps on the back of the other pair of straight edge clamps and secure them by using your back-to-back connectors. Fasten the bottom jaw pads to the table top and clamp wood with the top jaw pads. Thanks to the low profile jaws your work surface is never obstructed. The back-to-back straight edge clamps can also be taken apart for making two separate clamps.







DESCRIPTION	ORDER NO.
Back to Back Connectors for straight edge clamps (8-Pieces)	PGC-B2B

www.dahm.no

CMT200

LOCK / RELEASE SWITCH
allows fast, trouble-free release of the jaws.



FOOT OPERATED CLAMPING
frees up your hands for full control of the job.



QUICKLY FOLDS DOWN FOR STORAGE AND TRANSPORT

URETHANE JAW FACINGS
provide a protective, slip-resistant grip.



TRIPOD BASE
for all-terrain stability.

REVERSIBLE SLIDING JAWS
allow for extra wide 956mm clamping width capacity.



ROBUST, ALL-STEEL CONSTRUCTION WITH POWDERCOAT FINISH
for long-lasting operation.

POWERFUL 1 TONNE CLAMPING FORCE
allows the ability to apply as much or as little clamping pressure as you require.



The **CMT200** SuperJaws is the workstation you take right to the job; indoors, outdoors, construction sites or the factory floor.
It provides fast and easy hands-free clamping action of material up to 956mm and features a massive force of up to 1000kg, for all clamping or pressing applications. It holds anything: car parts, bicycles, timber and tubing.

ACCESSORIES OPTIONAL



Log Jaws
Pair of jaws for clamping logs and pole for chain sawing, etc.



Support foot
To enhance work station stability.



Extension tray
To keep all your tools within reach.

Technical Specifications

- Clamping Range ..... 0 – 956mm
- Clamping Force ..... Up to 1000kg
- Clamping Method ..... Foot operated
- Standard Jaws ..... Urethane
- Max. Load: ..... 100kg approx.
- Folding Time ..... 20 seconds approx.
- Folded Size ..... 275 x 775 x 295mm
- Standing Size ..... 980 x 1000 x 860mm
- Weight 16,5kg

DESCRIPTION	ORDER NO.
SuperJaws Portable Clamping System	**CMT200**
Optional	
Pair of jaws for clamping logs and pole for chain sawing, etc.	**CMT200-01**
Support foot to enhance work station stability	**CMT200-03**
Extension tray to keep all your tools within your hand's reach	**CMT200-04**
Pair of black polyurethane jaws	**CMT200-05**

www.dahm.no

Universal Dovetail Jig

CMT ORANGE TOOLS™


CMT300

305mm max length
11~25mm joint thickness

Dovetail joints give a touch of craftsmanship to your work, but many woodworkers avoid these joints, because of their apparent complexity. CMT's new 305mm dovetail jig is the fast easy solution! Thanks to precise templates, permanent stops and easy adjustments, we have taken the "tinkering" out of the dovetail joinery. Simply clamp your workpiece in with the edges against the factory-set stops, set your bit depth and then you are ready to rout. Also, we haven't cut corners on quality either. This jig features steel body, templates, stops and clamping bars, so it produces perfect long-lasting joints for all your woodworking needs. The machine accepts stock from 11mm to 25mm thick, and is capable of producing a variety of joints with the available templates. Standard jig includes a template for 12,7mm half blind joints and a template guide. Optional templates are available for through dovetail and box joints.



Standard equipment
- Standard Ø12,7mm silver blind template **CMT300-T128**
- Ø15,8x4mm template guide **899.005.00**




DESCRIPTION	ORDER NO.
Universal Dovetail Jig	**CMT300**

IMPORTANT TIP



HW DOVETAIL BITS (not included):

718.127.11	D=12,7mm	A=14°	S=6mm
818.128.11	D=12,7mm	A=14°	S=6,35mm
918.127.11	D=12,7mm	A=14°	S=8mm
818.628.11	D=12,7mm	A=14°	S=12,7mm



Will the template fit my router?


Standard template guide attaches using two screwed spaced 50mm on centre. Many routers accept this design. If your router does not, order one of the listed universal router bases below:

Universal router bases	ORDER NO.
For Ø8 and Ø12mm shank	CMT300-SB1
For Ø6,35 and Ø12,7mm shank	CMT300-SB2
Prebored router plate for CMT7E and CMT8E	CMT300-SB

Here's how it works:








www.dahm.no

Half Blind Template CMT300-T064



Template length mm	Dovetail size mm	Thickness mm	Colour	ORDER NO.
300	6,3	8 ~ 12	green	CMT300-T064

Supplied with Ø7,8x4mm precision guide — **899.003.00**

To be used with CMT dovetail router bits:
Ø6x8mm HW bit (Ø6mm shank) — **718.060.11**
Ø6,35x8,3mm HW bit (Ø6,35mm shank) — **818.064.11**



Box Joint Templates CMT300-T080 - CMT300-T127



Template length mm	Dovetail size mm	Thickness mm	Colour	ORDER NO.
300	8	8 ~ 20	blue	CMT300-T080

Supplied with Ø11,1x4mm precision guide — **899.004.00**

To be used with CMT straight router bits:
Ø8x25mm HW bit (Ø6,35mm shank) — **811.081.11**
Ø8x30mm HW bit (Ø8mm shank) — **912.080.11**




Template length mm	Dovetail size mm	Thickness mm	Colour	ORDER NO.
300	12,7	8 ~ 20	red	CMT300-T127

To be used with CMT straight router bits:
Ø12,7x30mm bit HW (Ø6,35mm shank) — **812.127.11**
Ø12,7x30mm bit HW (Ø8mm shank) — **912.127.11**
Ø12,7x25mm bit HW (Ø12,7mm shank) — **811.627.11**



Through Dovetail Templates CMT300-T129 - CMT300-T190



Template length mm	Dovetail size mm	Thickness mm	Colour	ORDER NO.
300	12,7	8 ~ 20	brown	CMT300-T129

Supplied with Ø11,1x4mm precision guide — **899.004.00**

To be used with CMT straight router bits:
Ø8x25mm HW bit (shank Ø6,35mm) — **811.081.11**
Ø8x30mm HW bit (shank Ø8mm) — **912.080.11**

To be used with CMT dovetail router bits:
Ø12,7x20mm HW bit (Ø6,3mm shank) — **818.129.11**
Ø12,7x20mm HW bit (Ø8mm shank) — **918.129.11**



Template length mm	Dovetail size mm	Thickness mm	Colour	ORDER NO.
300	19	15 ~ 22	violet	CMT300-T190

Supplied with Ø22x4mm precision guide — **899.006.00**


To be used with CMT straight router bits:
Ø12,7x30mm HW bit (Ø6,35mm shank) — **812.127.11**
Ø12,7x30mm HW bit (Ø8mm shank) — **912.127.11**
Ø12,7x25mm HW bit (Ø12,7mm shank) — **811.627.11**

To be used with CMT dovetail router bits:
Ø19x22mm HW bit (Ø6mm shank) — **718.190.11**
Ø19x22mm HW bit (Ø6,35mm shank) — **818.190.11**
Ø19x22mm HW bit (Ø8mm shank) — **918.190.11**
Ø19x22mm HW bit (Ø12mm shank) — **918.690.11**
Ø19x22mm HW bit (Ø12,7mm shank) — **818.690.11**




Precision guide for router:

DIAMETER	ORDER NO.
7,8 x 4mm	899.003.00
11,1 x 4mm	899.004.00
15,8 x 4mm	899.005.00
22 x 4mm	899.006.00
27 x 6mm	899.008.00
30 x 6mm	899.007.00




Here are a few of the beautiful dovetail joints you can produce using CMT bits

Half blind




CMT300 - T064
CMT300 - T128 (INCLUDED with CMT300)

Box joint



CMT300 - T080
CMT300 - T127

Through dovetail




CMT300 - T129
CMT300 - T190

www.dahm.no

Ellipse & Circle Cutting Jig

CMT ORANGE TOOLS

CMT3000




This product has been designed for cutting ellipses and circles with any router types. You can make ellipses and circles for windows, doors and any other application. By using two slides into the T-slot you can cut ellipses, whereas if you use one slide, you can cut circles.



Slider in the T-slot of the cross frame

CMT3000 ellipse jig includes:




1 x Cross Frame
2 x Sliders
1 x Connector Plate
3 x 400mm Bars
2 x Ø10mm Fence Rod
1 x Spanners Set
1 x Instruction Manual

Ellipse and circle cutting jig:

- Precise and rapid creation of ellipses and circles.
- Simple setup and effective operating.
- Clamping system for any type of routers.
- Special plastic cross frame with excellent sliding performance.
- Precisely machined T-slots and steel sliders.
- Zinc-coated metal parts to prevent rust.
- Delivered in a carton box along with instruction manual.

Major axis	Minor axes	
	Max	Min.
3000	2890	2590
1800	1690	1390
1500	1390	1090
1030	920	620
900	790	620
730	620	620
Min/max cutting radius		550/1500
Package dimension (mm)		405x360x54
Weight		6,6 kg.

Here are a few examples you can produce using CMT3000 Ellipse



Optional



CMT3000-SB1
Ø170x15mm Delrin® guide plate for CMT3000 to be used with CMT7E & CMT8E

DESCRIPTION	ORDER NO.
Ellipse & Circle Cutting Jig	**CMT3000**
Optional:	
400mm robust bar to extend the working radius	**CMT3000-7**
2-Pcs. of fence rod for routers with bars up to Ø8mm in diameter	**CMT3000-8**
new Ø170x15mm Delrin® guide plate for CMT3000 to be used with CMT7E & CMT8E	**CMT3000-SB1**

www.dahm.no



CMT650

For perfect joints


For kitchen worktops
from 420mm to 650mm in width.

CMT650 is designed to cut kitchen worktop joints with any type of router.

Letter code system for different operations makes the jig work much easier and very quick.




Joints made in 15 minutes! Including setup time



JIG INCLUDES:

1pc. Phenolic template
3pc. Zinc-coated steel location bush
1pc. Adjustable end stop
1pc. Instruction manual




Optional


- Portable router
- Guide bush Ø30mm*
- HW straight bit Ø12mm
- Two clamps

*** COMBINATION ROUTERS/ACCESSORIES**

Router	Bush guide	Base Plate
CMT7E	899.007.00	CMT300-SB
CMT8E	899.007.00	CMT300-SB
NO-CMT	899.007.00	CMT300-SB1



Bush guide



Base plate



Bits for the jig:
We recommend the use of these Ø12mm straight bits:

ORDER NO.	DESCRIPTION
912.120.11	Ø12x31,7 S=8mm
652.120.11	Ø12x28,3 S=8mm
912.621.11	Ø12x38,1 S=12mm
912.622.11	Ø12x50,8 S=12mm
812.620.11	Ø12x31,7 S=12,7mm
812.621.11	Ø12x38,1 S=12,7mm
652.121.11	Ø12x48,3 S=12mm
652.621.11	Ø12x48,3 S=12,7mm

***CMT650** is designed for Ø12mm straight bits.*

- Template made of stable and hardened material.
- For 90° and 45° joints
- Integrated templates for rounding over and chamfering edges.
- Extra location bush for worktop width of 600mm.
- Two integrated templates for panel bolt recesses.
- Delivered with a clear and comprehensive instruction manual.

DESCRIPTION	ORDER NO.
Kitchen Worktop Jig	**CMT650**

www.dahm.no

CMT-Enlock Joining System

CMT ORANGE TOOLS™

The innovative CMT-Enlock joining system is designed to build the strongest "T", "Mitre" joints and "Edge-to-edge" assemblies using the patented E15 and E10 dovetail keys. The dovetail slots in each part to be joined are machined quickly and accurately using the CMT Enlock jig. Simply clamp your workpiece in the jig, set the bit depth and you are ready to rout. The jig features strong cast aluminium construction throughout the body, top plate, stops and clamping bar to produce perfect strong joints for life!

CMT-Enlock1

PCT/AU2006/000957

Width range	30~75mm
Thickness range	19~35mm

The strong and versatile clamping bar ensures no workpiece movement.

Adjustable mitre blocks for mitre joints in picture frames.

Solid cast aluminium body.

Support foot to fix the jig on the table.

Adjustable mitre plate to suit the workpiece width.








Clamp extension arm to make widening joints.

Standard equipment
CMT-Enlock1 joining system
CMT-Enlock10 masterpack (50 keys)
Instruction manual (in five languages)
Video available on www.cmtutensili.com
Hw dovetail bits not included



The CMT-Enlock dovetail key expands when the cap is forced in.
This widens the dovetail producing a strong clamping force across the joint.
No other dovetail system on the market produces this clamping force.


Here are a few of the beautiful joints you can produce using CMT-Enlock Jig








"T" joints



A few seconds and your joints are ready!





Order now!

DESCRIPTION	L x A x H mm	ORDER NO.
Complete joining system		**CMT-Enlock1**
Optional		
Ø9,5mm 50 key masterpack	16 x 9,3 x 12	**CMT-Enlock10**
Ø12,7mm 50 key masterpack	22 x 12,5 x 18	**CMT-Enlock15**
Ø9,5mm dovetail bit (Ø6mm shank)		**718.098.11B**
Ø12,7mm dovetail bit (Ø6mm shank)		**718.127.11B**
Ø9,5mm dovetail bit (Ø6,35mm shank)		**818.098.11B**
Ø12,7mm dovetail bit (Ø6,35mm shank)		**818.128.11B**

www.dahm.no


CMT Inlay Kit

CMT ORANGE TOOLS™

899



Beautiful, professional-quality inlays aren't as difficult as they teem. In fact, they are easy with the CMT inlay kit. Just remove and reassemble the small bushing to make the recess in the workpiece and cut out the inlay. Perfect for toy making, puzzle making, lettering and lots of other decorative projects.
Use the spiral bit for routing MDF, or the straight bit for natural wood.



899.000.02
Router base for CMT7E/CMT8E

192.001.11
812.032.11
192.630.11
712.030.11

899.001.00
Inlay kit





Complete instructions for assembling and using CMT inlay kit are included.

DESCRIPTION		ORDER NO.
Inlay kit with 3,2mm (1/8") HWM spiral bit	(Ø6,35mm shank)	**899.051.00**
Inlay kit with 3,2mm (1/8") HWM straight bit	(Ø6,35mm shank)	**899.052.00**
Solid brass template guide		**899.001.00**
Universal router base		**899.000.01**
Router base for CMT7E/CMT8E		**899.000.02**
3,2mm (1/8") HWM spiral bit	(Ø6,35mm shank)	**192.001.11**
3,2mm (1/8") HWM straight bit	(Ø6,35mm shank)	**812.032.11**
3mm HWM spiral bit	(Ø6mm shank)	**192.630.11**
3mm HWM straight bit	(Ø6mm shank)	**712.030.11**

Template Guide Kit

new


A practical 7-bushing kit that will extend the possibilities of your router. For template-controlled operations such as dovetailing, stair routing, hinge butt routing, lock face routing and more general template tasks.
These template guides can be used with any router featuring a 30mm (1-3-/16") bore baseplate.
Fits the most popular routers. Some routers require CMT's base 899.000.02.



CMT-TGA

DESCRIPTION	ORDER NO.
Template Guide Kit	**CMT-TGA**

Optional



DESCRIPTION	ORDER NO.
Prebored router plate for CMT7E and CMT8E	899.000.02

Set contains:

Q.TY	1	1	1	1	1	1	1	2	1
Internal diameter	15,87mm	16,66mm	13,49mm	10,31mm	8,73mm	7,14mm	6,35mm	Lock Nut	Adapter
Outside diameter	20,24mm	19,05mm	15,87mm	12,7mm	11,11mm	9,52mm	7,93mm	Lock Nut	
Height	14,28mm	14,28mm	14,28mm	7,93mm	3,96mm	7,93mm	3,96mm		

www.dahm.no

Universal Boring Template


CMT ORANGE TOOLS™

CMT900

For dowelling into surfaces and shelf supports and hinges

CMT's universal boring template has been designed for precise and productive manual dowelling of furniture elements by using 32mm Euro-System screws, for boring shelf supports with 3mm or 5mm diameter and for making and marking hinge holes.
By using this template you can prebore the most popular hinge types and also to bore holes for pivots, wooden screws and hinges on the base element, as well as prebore door hinges, included the marking of holes featuring 35mm in diametre for hinges.
This template will guarantee high precision work and productivity and has been designed to be used in pair with the specific CMT400-1 boring adaptor supporting any Ø8mm shank drill bits featuring different diametres.





Laminated phenolic material | **Clear and comprehensible template marking** | **Precise end stops**



BORING ADAPTORS *(not included):*

- End stop for different boring depths
- Suitable for any type of drilling machine
- Duralumin body with holes for better chip ejection
- Precise and flat seating for proper alignment.

ORDER NO. **CMT400-1**
Boring adaptor for **CMT656, CMT900 JIGS**
to be used with drill bits up to 30mm depth:
306.030.21 - 306.050.11 - 306.080.11

QUICK AND EASY:


TECHNICAL DETAILS:	CMT900
Max. board width in one tightening:	900mm
Max board width:	no limits
Board thickness:	no limits
For dowels:	Ø8mm
Hole distance:	32mm
Number of holes:	26
For shelf support:	Ø3mm, Ø5mm
For hinges:	Ø3mm for wooden screws Ø5mm for Euro screws



HW DOWEL BITS *(not included):*

DESCRIPTION			ORDER NO.
D=3x18mm	S=8x20mm	HWM	306.030.21
D=5x30mm	S=8x20mm	HW	306.050.11
D=8x30mm	S=8x20mm	HW	306.080.11

Other sizes available in 306-307 series



Boring into a surface for dowel joints using the template.

Boring Ø3mm and Ø5mm holes for shelf supports.

Preboring holes for hinges (base and panel).

CMT900 Boring Template Includes:

- Boring template from laminated pertinax
- End stop set
- End stop set for large elements
- Centring pin for hinges

DESCRIPTION	ORDER NO.
Universal Boring Template	CMT900

www.dahm.no

Universal Boring Jig

CMT ORANGE TOOLS

CMT656

This universal boring jig has been designed for precise and productive manual dowelling of furniture elements and guarantees high precision work and productivity. The holes have been made with a distance of 32mm between one another, in compliance with the European regulations for doweling machine production.
Also, the dowel jig fits CMT Ø8mm shank HW drill bits, clamped into a special boring adaptor.


For edge dowelling and jointing

Precise holes

Detachable end stops


Ergonomic manual tighteners

Precise and flat duralumin profile



SPARE CLAMP *(optional)*
To speed up your work with elements of different width.
Order no. **CMT400-3**

UNIQUE SOLUTION



Our unique solution consists of boring holes by using the jig safely, avoiding damage to the bit cutting edges, for this last goes through the adaptor.



BORING ADAPTORS *(not included):*

- End stop for different boring depths
- Suitable for any type of drilling machine
- Duralumin body with holes for better chip ejection
- Precise and flat seating for properly alignement.

ORDER NO. **CMT400-1**
Boring adaptor for **CMT656, CMT900 JIGS**
to use with drills bit:
306.030.21 - 306.050.11 - 306.080.11 - 307.050.11

ORDER NO. **CMT400-2** (for screw joints)
Boring adaptor for **CMT656, CMT900 JIGS**
to use with the drill bit: **307.050.11**



HW DOWEL BITS *(not included):*

DESCRIPTION			ORDER NO.
D=3x18mm	S=8x20mm	HWM	306.030.21
D=5x30mm	S=8x20mm	HW	306.050.11
D=8x30mm	S=8x20mm	HW	306.080.11
D=5x40mm	S=8x20mm	HW	307.050.11 for screw joints
D=7x40mm	S=8x20mm	HW	307.070.11 for screw joints

Other sizes available in 306-307 series

3 easy steps in creating dowel joints




Place the jig onto the board, fix the end stop and tighten the workpiece. Set the bore depth and clamp the boring adaptor on your drilling machine. Bore vertical holes.



Fasten the jig on the other element, fix the end stop and set the bore depth. Bore horizontal holes.



Now insert the dowels with glue into the holes and join both elements.



As an alternative, use through hole bits and screw the elements together.

TECHNICAL DETAILS:	CMT656
Max board width in one tightening:	656mm
For dowels:	Ø8mm
For through holes:	Ø7mm
Hole distance:	32mm
Number of Ø18mm holes :	2x20
Board thickness:	16-40mm
Facet (elements lap):	0,8mm

DESCRIPTION	ORDER NO.
Universal Boring Jig (656mm in one tightening)	CMT656


www.dahm.no

Universal Hinges Boring System

CMT ORANGE TOOLS™

CMT333

The innovative CMT333 hinge boring system with 3 spindle-heads allows you to bore holes for any hinge brand, such as Salice, Blum, Hettich, Würth, Mepla, Grass, etc..
The universal modular base supports the installation of 5 different boring heads, engineered by the worldwide leading company in industrial boring machines.
Use the CMT333 universal hinge boring system on all hand-held or standing drilling power tools.





For use on standing drilling machines



To use on standing drilling power tools




For use on CMT Industrio router table

TECHNICAL FEATURES AND SPECIFICATIONS
- Complete anti-rust parts
- Ground aluminium (Avional)
- Max 5000 RPM
- Six radial antifriction bearings

SAFETY TIPS:
for lubrication use oil SHC100 Mobil

CMT333-325
Boring head with 5 adaptors for system 32







8

8	Boring head with 5 adaptors for system 32	CMT333-325


www.dahm.no



1 **CMT333-4211**
for Grass hinges




2 **CMT333-4595**
for Blum hinges




3 **CMT333-4809**
for Mepla hinges




Assembly




4 **CMT333-4300**
for window handles



5 **CMT333-4806**
for Salice hinges





6 **CMT333-5255**
for Hettich, Würth hinges



7 **CMT333-3875**
for small hinges

MAXIMUM VERSATILITY FOR ANY BRAND

Make your set		Support modular base		Boring heads		Drill bits		Boring bit
	=		+		+		+	

Choose your hinge		
1	Grass	42/11
2	Blum	45/9,5
3	Mepla	48/9
4	Window handles	43/00
5	Salice	48/6
6	Hettich, Würth	52/5,5
7	Small hinges	38/7,5
8	System 32	

ORDER NO.	ORDER NO.		ORDER NO. Left-hand rotation	ORDER NO. Right-hand rotation
CMT333	CMT333-4211	Grass	310.080.12 (2-Pcs.)	317.350.11
CMT333	CMT333-4595	Blum	310.080.12 (2-Pcs.)	317.350.11
CMT333	CMT333-4809	Mepla	310.080.12 (2-Pcs.)	317.350.11
CMT333	CMT333-4300	W/handles	310.100.12 (2-Pcs.)	317.260.11
CMT333	CMT333-4806	Salice	310.100.12 (2-Pcs.)	317.350.11
CMT333	CMT333-5255	Hettich	310.100.12 (2-Pcs.)	317.350.11
CMT333	CMT333-3875	Small	(2-Pcs.)	317.260.11
CMT333	CMT333-325	System 32	(3 pcs. RH + 2-Pcs. LH)	


www.dahm.no


Blum Hinges Boring Head

CMT ORANGE TOOLS

CMT334

The innovative CMT334 Universal Hinge Boring Head employs three spindles which allow you to bore the holes for all of the major hinge brands. The head can be utilized on boring and point to point machines.






For use on boring and point to point machines

DESCRIPTION	ORDER NO.
Hinge Boring Head (bits not included)	**CMT334-4595**
Boring Bit Ø35mm x 38,5mm. Right-hand rotation	**393.350.11**
Dowel Drill Ø8mm x 38,5mm. Left-hand rotation	**393.080.12**

Standard



CMT334-4595
for Blum hinges 45/9.5

Bench Block Set

new

BBS-001

These blocks are great for holding your workpiece without any clamps. Their anti-slip surface grip both your bench top and the underside of your workpiece. Raise your work above the bench and benefit from plenty of clearance for your router bits, cutters, etc.

Lenght: 75mm
Width: 50mm
Height: 25mm



DESCRIPTION	ORDER NO.
Bench block set (4-Pcs.) 75x50x25	**BBS-001**

Folding Ruler

new

FR2M

- Fiberglass material, water & scratch resistant.
- Impact resistant, tough yet flexible.
- No rust.
- Guaranteed professional quality.
- Merchanding display with 12 rulers.





DESCRIPTION	ORDER NO.
Folding Ruler	**FR2M**

www.dahm.no

Laminate/Veneered-Panel Cutter

new

CMT ORANGE TOOLS™

DET-003

A very useful hand tool for clean, splinter-free cuts on laminates and veneered with no waste. Place your material into the fence provided and have the cutter run along the edge of the panel. The two opposing steel-made circular cutting blades mounted on roller bearings will trace the cutting line. Use the micrometer knob on the top of the tool to set the cutting thickness, or adjust the strip width by using the metric/inch scale provided. Loosen the lock knob on the scale, move the metal bracket which holds the fence and tighten the lock knob again on the desired cutting width.



TECHNICAL FEATURES:

- Cutting width: 12~110mm (15/32" ~ 4-21/64").
- Cutting depth: 0~2mm (0 ~ 5/64").
- Weight: 1.2 kg (2.65 lbs).

DESCRIPTION	ORDER NO.
Laminate/veneered-Panel Cutter	**DET-003**


Edge Banding Iron

new

DET-004

Apply pre-glued edge banding easily and accurately. The iron non-stick surface allows smooth and easy application. The thermostatically controlled short preheat time gets you working quicker. Includes heat resistant metal base to place iron when not in use.

- Includes thermostatic heat control.
- Non-stick coating.
- Specially shaped shoe with rounded edges.
- Metal stand.
- 154cm (5-1/2') power cord, 230V.



TECHNICAL FEATURES:

- Voltage: 230V.
- Electric current: 2.5A.
- Low temperature: 70° ±10° C.
- High temperature: 220° ±10° C.


DESCRIPTION	ORDER NO.
Edge Banding Iron	**DET-004**

Edge Banding End Trimmer

new

DET-002

An indispensable tool for easy and safe end trimming after edge banding. Position the tool on the banding, press down on the handle to operate the blade in a shearing action. The cutting knives are interchangeable, so when the cutting knife becomes dull, you can simply replace it with the anvil knife for a double lifetime. For cutting banding up to 0,5mm thick with a maximum cutting width of 54mm.
This tool can also be paired up with our double edge trimmer DET-001. We recommend using our edge banding end trimmer DET-002 before using our double-edge trimmer DET-001.



DESCRIPTION	ORDER NO.
Edge Banding End Trimmer	**DET-002**

Spare parts **DET-002K** 2-Pcs replacement blade set 55x13x1,5mm

Double-Edge Trimmer

new

DET-001

Attach this trimmer to your workpiece, press both ends against the board for a cutting range between 13mm (1/2") and 25mm (1"), move the trimmer in the correct direction indicated by the arrow. This will cut on both sides easily. The first cutter will cut straight, the second one can be adjusted for a tapering cut. Both cutters are made from high-quality hardened steel and can be easily replaced when worn out.



DESCRIPTION	ORDER NO.
Double-Edge Trimmer	**DET-001**

Spare parts **DET-001K** Spare knives for double-edge trimmer

www.dahm.no


3D Router Carver System

CMT ORANGE TOOLS™

Exclusively from your CMT distributor

RCS

Turn your router into a remarkable carving tool. It's fast, easy, and a whole lot of fun!
Who says that intricate woodcarving requires an artist's touch? Thanks to the patented 3D Router Carver system, anyone with a plunge router can create any of the beautiful designs shown on these pages in just minutes. Decorate doors, drawers, cabinets, furniture or just about any flat wooden surface with one or more of these designs. How does it work? The secret is in the 3D Router Carver Bit and the way that bit interacts with the carving templates. The V-Groove router bit is enclosed in a 45° cone-shaped guide. You rout with the plunge mechanism of your router unlocked, allowing the bit to move up or down as the router moves forward. As the slot in the template get wider, the bit moves down, producing a wider, deeper V-groove. As the slot gets narrower, the bit moves up, and the groove gets narrower and shallower. It sounds simple, and it is! (that's why the system is patented worldwide). Please see the illustrations below for more details on the carving technique. You'll receive complete instructions with your 3D Carver templates. For an informative visual demonstration, check out the 3D Router Carver video on our web site.



What do you need to get started?

- The 3D Router Carver bit
- The Carver template of your choice
- The Holding frame to match your template
- Your plunge router


(Note: Be sure the opening in the base of your router is at least 47,6mm in diameter.
If it isn't, you'll need to make a sub-base to accept the large diameter of the 3D Carver bit.)

3D Router Carver Bit & Sleeve


S mm	ORDER NO. Right-hand rotation	Spare parts						Optional
			44,5					39
8	**RCS-BIT8**	RCS-CUT8	RCS-SLE8	RCS-SHIELD		RCS-NUT8	991.007.00	RCS-SLEEVE8
12,7	**RCS-BIT**	RCS-CUT	RCS-SLE	RCS-SHIELD	990.091.00	990.092.00		RCS-SLEEVE

Here's how it works:


1. Clamp or tack the holding frame to your workpiece



2. Drop the template into the holding frame




3. Plunge the bit into a wide part of the slot and rout with the router's plunge mechanism unlocked.




Allow the plunge mechanism to move up and down as you advance. Wider template slots allow wider, deeper grooves. Narrower slots produce shallower grooves.

4. With the frame still in place, flip the template & rout again. Some templates will be routed 2 to 4 times, depending on the complexity of the design.




5. Remove the frame and you're finished!





Cabinet door & panel carvings



These designs are ideal for the doors or panels of cabinets, entertainment centers, fireplace surrounds or almost any flat surface. See the designs below for complementary patterns for drawers, rails and corners. Approximate carving time is 5 minutes.

DESCRIPTION	Carving dimensions mm	No. of templates	ORDER NO.
Classical cabinet door - A	440 x 185	2	**RCS-302**
Florentine cabinet door - B	415 x 170	2	**RCS-304**
Cascade cabinet door - C	365 x 210	1	**RCS-305**
Roma cabinet door - D	375 x 200	1	**RCS-306**
Fleur-de-Lys door - E	250 x 180	4	**RCS-805**
Spanish fan template - F	380 x 200	2	**RCS-806**
Cabinet door holding frame			**RCS-003**

www.dahm.no






Tip: many carvings, like the Florentine rail, are enhanced with the additional of a rosette.



Panel & Rail Carvings

RCS




With a long, horizontal shape, these designs are perfect for door rails, headboards, cabinet face frames and valences. Approximate carving time is 4 minutes.

DESCRIPTION	Carving dimensions mm	No. of templates	ORDER NO.
Classical Rail - A	550 x 120	2	RCS-402
Florentine Rail - B	550 x 130	2	RCS-404
Cascade Rail - C	530 x 110	3	RCS-405
Folklore Rail - D	550 x 110	3	RCS-406
Rail Holding Frame			RCS-004





Drawer & Furniture Carvings




Originally intended for drawer fronts, these designs are great for lots of other projects: small doors, side panels of cabinets, furniture and more. For door and drawer combinations, match the style of the door designs above. Approximate carving time is 4 minutes.


DESCRIPTION	Carving dimensions mm	No. of templates	ORDER NO.
Classical Drawer - A	210 x 70	2	RCS-502
Florentine Drawer - B	195 x 85	2	RCS-504
Cascade Drawer - C	250 x 65	1	RCS-505
Folklore Drawer - D	250 x 40	2	RCS-506
Roma Drawer - E	190 x 65	2	RCS-507
Blaze Drawer - F	250 x 110	2	RCS-510
Drawer Holding Frame			RCS-005



Corner & Small Decoration Carving Designs




DESCRIPTION	Carving dimensions mm	No. of templates	ORDER NO.
Classical Corner - A	155 x 40	3	RCS-602
Florentine Corner - B	120 x 30	3	RCS-604
Cascade Corner - C	190 x 40	3	RCS-605
Folklore Corner - D	150 x 45	3	RCS-606
Corner Holding Frame			RCS-006



Rosette Carvings

You get two templates for the price of one with these designs! Each item includes templates for two sizes of rosette. Use with the rosette frame sold above, or use the large rosettes with the cabinet door frame or small rosettes with rail frame.




DESCRIPTION	Carving diameter mm	No. of templates	ORDER NO.
Rosette #1 & #5 - A	85 & 68	2 & 2	RCS-701
Rosette #2 & #6 - B	88 & 70	1 & 1	RCS-702
Rosette #3 & #7 - C	82 & 65	1 & 1	RCS-703
Rosette #4 & #8 - D	79 & 62	1 & 1	RCS-704
Rosette holding Frame			RCS-007

www.dahm.no


CMT ORANGE TOOLS™

RCS




Southwestern Carving Designs

These popular Southwestern designs are actually several shapes in one. Both sizes can be routed as circular carvings, or use only portions of the template to suit your project.



Rout the complete spanish fan design or make partial rosettes






DESCRIPTION	Carving dimensions mm	No. of templates	ORDER NO.
Large Spanish Fan	400	1	**RCS-801**
Small Spanish Fan	200	1	**RCS-802**
Rosette Holding Frame			**RCS-007**

Just for fun: Designs For every animal lover!



Your imagination will be your guide on these neat designs. Furniture or decorations for the kids, paneling for the den or rec room, a gift for the sportsman.



DESCRIPTION	Carving dimensions mm	No. of templates	ORDER NO.
Dolphin - A	200 x 290	4	**RCS-803**
Eagle - B	178 x 298	4	**RCS-804**
Deer - C	394 x 190	4	**RCS-901**
Horse - D	445 x 203	3	**RCS-902**
Longhorn - E	419 x 194	4	**RCS-904**
Teddy bear - F	394 x 203	3	**RCS-906**
Cabinet Door Holding Frame			**RCS-003**

Organizer

03.51

100 bits at your fingertips
When you constantly work on projects, you always need your most used bits right within reach and safely organized.
CMT gives you the perfect solution for keeping them all in sight, thanks to the 100 piece organizer.
This conveniently holds any size router or drill bit by using CMT's interchangeable bushings to fit all CMT shank diameters.
See options listed below.







DESCRIPTION	ORDER NO.
Bit Organizer (without bushings)	**03.51.0106**
Interchangeable Bushings for Ø6mm shank (20-Pcs.)	**03.51.0046A**
Interchangeable Bushings for Ø6,35mm shank (20-Pcs.)	**03.51.0047A**
Interchangeable Bushings for Ø8mm shank (20-Pcs.)	**03.51.0048A**
Interchangeable Bushings for Ø9,5mm shank (20-Pcs.)	**03.51.0057A**
Interchangeable Bushings for Ø10mm shank (20-Pcs.)	**03.51.0058A**
Interchangeable Bushings for Ø12mm shank (20-Pcs.)	**03.51.0059A**
Interchangeable Bushings for Ø12,7mm shank (20-Pcs.)	**03.51.0049A**

www.dahm.no

Formula 2050: Blade & Bit Cleaner

Finally a safe, environmentally-friendly cleaner that is more effective than all those hazardous chemicals used for cleaning cutting tools.

998

Saw shops know how to get the most out of cutting tools.
They know that the pitch and resin left by wood on tools greatly shortens the life of carbide. Therefore we asked many blade sharpeners to test Formula 2050 and they rated it as an excellent product. Most blade and bit cleaning products work with dissolving action, but it takes some power and nasty chemicals to dissolve wood residues and adhesives. CMT's non-toxic and safe Formula 2050 penetrates the microscopic cracks in the resin and attacks the bond between carbide or steel surfaces and the resin itself.
Formula 2050 keeps your tools clean and helps you increase the life span between sharpening and replacement.



12 spray bottles 0,500 lt (18 oz.) in merchandising display



★★★★★
This product received a five-star performance rating from "Wood® Magazine"

DESCRIPTION	ORDER NO.
0,500 lt. spray bottle	**998.001.01**
3,780 lt. plastic jug	**998.001.03**
12 spray bottles 0,500 lt (18 oz.) in merchandising display	**998.001.01-X12**
Empty merchandising display (suitable for 12 spray bottles)	**998-DIS**

- **Removes pitch, resin and adhesive residue from all woodworking cutting tools (saw blades, router bits, drill bits, shaper cutters, planer blades, etc.).**
- **Completely non-toxic, non-flammable and certified biodegradable. Formula 2050 is a safe, earth-friendly product.**
- **Do not rinse after cleaning. Formula 2050 provides protection from rust and corrosion. Keeps your table saw top rust free too!**
- **Can be applied by spray bottle or used in ultrasonic cleaners and dip tanks.**

Lubricant for Wood, *Neutralizes Resin*

998

- Neutralizes resin, preventing it from being stuck on chips and sawdust.
- Cleans knobs, barbell handles, etc.
- Anti-corrosion action on woodworking machine table.
- Excellent against humidity.

Instruction:
Spray or apply the product on the desired parts of your woodworking machine. You will obtain a uniform layer on its surface that will aid in the sliding of your workpiece.

FLAMMABLE PRODUCT.
AIR FREIGHT IS NOT ALLOWED.



DESCRIPTION	ORDER NO.
1 lt. spray bottle (master packaging 12 bottles)	**998.002.01**
5 lt. plastic jug	**998.002.03**

www.dahm.no

Diamond Whetstones

CMT ORANGE TOOLS™

DSS

For professional, industrial and home users

FAST: real quality diamond, the hardest known material, reduces the sharpening process.

EASY: stoke the blade across the surface with little pressure.

DURABLE: we use natural diamonds for long-lasting performance.

VERSATILE: for sharpening any hard material, steel, glass, ceramic, tungsten carbide, etc.



For sharpening, honing and lapping


- axes
- bayonets
- broadheads
- cable cutters
- carbide cutters
- chainsaws
- chisels
- climbing equipment
- engraving tools
- farm and garden tools
- fish hooks
- Fostner bits
- knives
- lapidary tools
- lawn mower blades
- masonry drills
- moulds and dies
- plane blades
- planer /jointer knives
- pruners
- ring tool
- router bits
- saw blades
- scissors
- shears
- ski and snowboard edges
- small contact area and pointed tools
- speed and hockey skates
- woodcarving scrapers
- woodturning tools

For abrading hard materials

- ceramic
- composites
- fibreglass
- glass
- stainless steel
- stone
- titanium
- tool steel
- tungsten carbide


For flattening

- chisel backs
- engine heads
- machine bolsters and ways




Universal diamond whetstone in leather sheaths

Dimensions mm	Grain	Colour	ORDER NO.
115 x 25 x 3	D15 extrafine	green	DSS-115E
115 x 25 x 3	D25 fine	red	DSS-115F
115 x 25 x 3	D46 coarse	blue	DSS-115M
115 x 25 x 3	D76 extracoarse	black	DSS-115G



Diamond whetstone file

Dimensions mm	Grain	Colour	ORDER NO.
100 Ø4,8	D54 coarse	blue	DSS-048M




Universal diamond whetstones in hardwood case

Dimensions mm	Grains	Colour	ORDER NO.
150 x 52 x 16	D15 extrafine	green	DSS-150E
150 x 52 x 16	D25 fine	red	DSS-150F
150 x 52 x 16	D46 coarse	blue	DSS-150M
150 x 52 x 16	D76 extracoarse	black	DSS-150G

A unique production process to guarantee long tool life

A perforated steel plate is moulded onto a strong plastic base by applying high pressure. The steel is then covered with natural diamonds embedded into a nickel plate. The pattern ed diamond coating ensures fast sharpening, whereas the plastic indents hold the lubricating water and disperse the fine dust emitted by the diamonds during sharpening.



The diamond whetstones are available in four meshes for multiple purposes:

D15 EXTRAFINE/GREEN (9 microns, 1200 mesh)
To refine and polish sharp edges to razor sharp perfection. If you are new to sharpening or need your knife or tool edges as sharp as possible, this grain type is not recommended, but if this suffice, then this is what you are looking for.

D25 FINE/RED (25 microns. 600 mesh)
To restore any slightly dull knife or tool edges to perfect sharpness. Many customers consider the fine grit grain to be suitable to satisfy any working need. Professional chefs and gourmet cooks prefer using this grit grain too. For woodworkers and sportsmen who are stepping through this grit, it is the edge refinement process before micro-refinement and polishing.


D46 COARSE/BLUE (45 microns, 325 mesh)
To quickly restore dull edges. For workers who require faster cutting action and less edge refinement often use this grit grain.

D76 EXTRA-COARSE/BLACK (60 microns, 220 mesh)
Recommended for aggressive removal of metal on damaged tools or for heavy-duty outdoor tools such as axes and lawn mower blades. Also, this grit grain is commonly used as a first step for flattening the back of chisel and plane irons or for rapid stock removal from chipped or badly damaged edges.


Instructions

Use water for lubrication, after use, rinse and store dry.


1. Keep your knife with cutting edge away from you.



2. Apply some water to the stone surface. Hold blade 20° to diamond surface.



3. With little pressure and in long strokes push the blade across surface. From edge heel to edge tip, alternately on both sides. For pointed tools. Use the unperforated diamond area.




www.dahm.no

Flexible Templates for Curved & Arched Routing

The CMT flexible template is easy to screw on any kind of wooden panels, MDF or chipboard for creating forms, arcs and curved elements easily and rapidly. In order to fix your template you can use countersunk screws, which are widely available on the market. The CMT template is made of a highly-resistant flexible plastic, which can be tied in knots without any risk of ruining or reducing flexibility.

Screw your template to the edge of the panel and follow its shape and rout the border on the guide ring. The template is suitable for manual feed on routers, router tables and spindle moulders. Rout easily, safely and accurately to make multiple forms such as arcs, curved elements and cut-out forms. Mark the edge of your form precisely and screw it onto a previously-placed panel from underneath.

If you rout with a guide ring mounted onto your spindle moulder, keep your hands a safe distance behind the template. Two different profiles in three lengths are available. Please notice that the smallest profile features a short radius, whereas the larger profile features a larger opening in case of flat and long curves.




TECHNICAL SPECIFICATIONS:
- Special plastic without any plasticizer.
- Made in Germany.
- Lasts more than 10 years!


DESCRIPTION	L mm	ORDER NO.
Flexible template for routing 18x18mm	1000	**TMP-1000**
Flexible template for routing 12x12mm	1200	**TMP-1200**
Flexible template for routing 18x18mm	2000	**TMP-2000**














12 Corner Radius Router Template Set from 3mm to 25mm

Our useful 3-piece corner radius template set includes 8mm thick acrylic templates that will allow you to make 12 different radii (4 per template) by using a flush trim or a pattern bit (sold separately). Included with the templates you will also find 4 alignment pins and 4 wood screws. Use the pins to align the template onto your workpiece, then use the four wood screws provided to secure it. Remove the alignment pins and use the bit to cut the corner of your workpiece to the same radius as the template.

RADIUS	
mm	inches
3	1/8”
5	3/16”
6	1/4”
8	5/16”
10	3/8”
11	7/16”
12	1/2”
14	9/16”
16	5/8”
19	3/4”
22	7/8”
25	1”

DESCRIPTION	ORDER NO.
12 Corner Radius Router Template	**TMP-R12**
Set contains:	
12 Different Radii (3 templates)	
4 Alignment Pins	
4 Wood Screw	



www.dahm.no

Bowl & Tray System

CMT ORANGE TOOLS™

BTS-002

CMT System BTS-002 provides a fun and easy way for you to make divided bowls and trays in your shop. No lathe? No problem. This bowl making technique uses a router and CMT's unique bowl and tray router bit. The resulting bowls and trays are beautiful. This kit also provides an excellent way to use up scrap wood. Glue pieces together, butcher block style, to make a beautiful pattern of colors and species.


The templates will withstand a lifetime of use and can be used to make a variety of bowl or tray styles. The collet extension, used to make extra deep bowls, is also useful whenever your general woodworking requires extra deep cuts.



TMP-012
MDF Template



TMP-011
MDF Template



DESCRIPTION	ORDER NO. S=Ø12mm
Bowl & Tray System	**BTS-002**
The kit includes	
Router Bit	951.502.11B
Router Collet Extension	796.002.00
MDF Template nr. 1	TMP-011
MDF Template nr. 2	TMP-012
Instruction manual	



Trace the templates onto the bowl blank.



Rough out the interior using a drill press and a 50,8mm Forstner bit.



Rout the interior to final shape using the bowl and tray router bit and collet extension.



Bandsaw the exterior to final shape.

Optional



TMP-101
MDF Template
400x400mm.



TMP-103
MDF Template
400x400mm.



TMP-105
MDF Template
330x300mm.

www.dahm.no

Pocket-Pro™ Joinery System

CMT ORANGE TOOLS™

PPJ-002

For fast, easy and accurate cabinet & furniture construction.
Designed by CMT and professional cabinetmakers, this new system allows you to make rock-solid pocket hole joints in stock 12,7mm (1/2") to 40mm (1-5/8") thick with unprecedented speed and accuracy.

The heart of the Pocket-Pro™ system is our unique moulded jig, which features hardened drill bushings and an interlocking two-piece design.
Sliding the jig up or down enables you to adjust the stock thickness in preset 1,6mm (1/16") increments without test joints or measurements!
If you have used other pocket hole jigs you will be familiar with many joint applications, but you will benefit from many Pocket-Pro™ system advantages.

For example:
- some jigs require adding or removing various parts of the jig to join different stock thicknesses.
With the Pocket-Pro™ system you simply have to adjust the interlocking jig up or down for the full range of joints 12,7mm (1/2") to 40mm (1-5/8") thick;


- other jigs require frequent repositioning of the depth stop collar for different joint styles. CMT's Pocket-Pro™ joinery system allows you to make most of the adjustments leaving the stop collar in the same position of the drill bit;

- plus, with CMT's Pocket-Pro™ system you can quickly adjust the location of the pocket in relation to the end of your workpiece to create a stronger joint by using longer screws, or to leave more "meat" in the joint.

Check out the Pocket-Pro™ joinery system today.
Easy enough for beginners and accurate enough for professional workers, it is the world's most versatile pocket hole jig.



515.001.51+541.095.00



999.505.10



999.505.05



990.101X30



999.505.08

DESCRIPTION	ORDER NO.
Pocket-Pro™ joinery system set	**PPJ-002**
Set contains:	
Pocket-Pro™ main parts	**999.505.10**
Toggle clamp	**999.505.05**
9,5mm (3/8") step drill bit	**515.001.51**
9,5mm (3/8") depth collar for step drill bit	**541.095.00**
152mm (6") Square drive screw driver bit	**999.505.08**
Masterpack 30 screw 1-1/4"	**990.101X30**


DESCRIPTION OPTIONAL	ORDER NO.
500 fine screws (31,7mm)	**990.101X500**
500 coarse screws (31,7mm)	**990.102X500**
500 fine screws (38,1mm)	**990.103X500**
500 coarse screws (38,1mm)	**990.104X500**
Face clamp swivel pad	**999.505.06**
6mm (3") square drive screwdriver bit	**999.505.07**

Optional




999.505.06
Face clamp with swivel pad

Enjoy Easy Pocket Hole Joinery!



Build almost anything!



www.dahm.no

Digital Height Gauge

CMT ORANGE TOOLS

DHG-001



Horizontal and vertical measuring.

Self-standing for setting cutting depth on router tables and low profiles for backfence adjustment.

Measuring ruler with metric/imperial scale and locking screw.

Instruction manual.












Place your gauge on a flat surface and set to “0” on the display.










Position your gauge on the tool.









Insert needle and set to “0”.







TECHNICAL DETAILS:

- Measuring range: Scale: 0~80mm (0~3”)
  Needle: 0~50mm (0~2”).
- Resolution: 0.05mm/0.002”.
- Accuracy: ±0.1mm (±0.004”).
- Power: CR2032 3V - 1500 hours.

DESCRIPTION	ORDER NO.
Digital Height Gauge	**DHG-001**

Digital Moisture Meter

new

DMM-001



Ideal for use in woodworking, building construction and agriculture industries. The DMM-001 is also an invaluable tool in the restoration field. Ideal for locating moisture in carpets and sub-flooring. Generals ultra-sensitive Digital Moisture Meter easily detects hidden leaks in wood, concrete, plaster and carpet. The accurate moisture level readings make this tool great for new home inspections, locating roof leaks or even selecting dry lumber at the yard.
Ideal to use in woodworking, building construction, agriculture restoration and floor-laying. Used to check wood, drywall and concrete before painting, sealing or treating and to locate and identify water leaks in roofs, floors and walls. Display will show the moisture content in Percent Moisture Content directly. Ergonomically designed and CE approved.

TECHNICAL FEATURES:

Measuring range in wood:	5~50%
Measuring range in building material:	1.5~33%
Measuring accuracy:	±2%
Backlight shut off:	In about 15 seconds
Auto power off:	3 minutes idle
Low battery indicator:	<7V
Power supply:	a 9V battery block (6F22 or 6LR6)
Working current:	<25mA
Working temperature:	32°F~122°F
Working humidity:	<90%RH non-condensing
Storage:	-4°F~140°F ≤85% (without battery)
Dimensions:	5-11/16” x 2-7/16” x 1-1/16”
Weight:	About 3oz (without battery)







DESCRIPTION	ORDER NO.
Digital Moisture Meter	**DMM-001**

www.dahm.no

Digital Angle Gauge





DAG-001


The digital angle gauge is a mini waterproof digital protractor that provides digital readings between ±180° with a resolution of 0,1° and auto shut off after 5 minutes. It is small enough to be carried around in a pocket and the LED screen is convenient to read.
It incorporates magnets in the base for adhesion to any ferrous surface to accurately measure mitre and bevel angles on mitre saws, saw benches, etc.


TECHNICAL DETAILS:
- battery voltage/type 3V/L lithium;
- 51x51x33mm size;
- ±180° range;
- 0,1° resolution.
- Set to ZERO.


DESCRIPTION	ORDER NO.
Digital Angle Gauge	DAG-001














Digital Angle Finder

DAF-001





This digital angle finder is a multi-functional tool for many measuring applications. Easy to operate the base unit carries the electronics giving a very clear detailed LCD display as well as a pair of levelling vials and a pivoting measuring arm. When the arm is extended the angle it makes with the base is indicated clearly on digital read-out to the nearest 0,05°.
The measuring range is 0 - 360°.
The vials allow variations from the vertical and the horizontal to be accurately measured.
Other features include a lock function to prevent the last measurement being lost, a low battery indicator and automatic shut off function.
Being robust but light in weight this is a very well thought out tool with a lot of uses. Instructions included.

Easy and simple to use;
Calculates angles in seconds;
Large detailed LCD display;
Robust, lightweight aluminium construction;
0 - 360° measuring range.


TECHNICAL DETAILS:
- 265x50x25mm size;
- ±0-360° range;
- 0,05° resolution.

DESCRIPTION	ORDER NO.
Digital Angle Finder	DAF-001






Four holes locking when measuring specifically angle; screw off the locking knob, the measuring range could reach 360°.



Lock the moving blade at any angle, make precise drawing and cutting directly.



www.dahm.no

Display Cabinets for Saw Blades

A sturdy steel-made saw blade display cabinet with backlight to place anywhere you want in your store. You can hang up different types of saw blades. Please contact your CMT salesman to get advice on the most suitable saw blades composition to display. Saw blades not included. Dimensions are in cm.

03.00.0038




Image may not depict actual product included. Refer to table.

03.53.0012-X24

DISPLAYS THAT SELL!

03.00.0030



We also offer a practical wire counter display for saw blades up to Ø350mm.

Suitable for all blades types

ORANGE CHROME™



XTREME PERFORMANCE



ITK PLUS™



CMT CONTRACTOR TOOLS



DESCRIPTION	ORDER NO.
Wire counter display only ***(empty)***	**03.00.0030**
Display cabinet with backlight (220V) for saw blades ***(empty)*** hooks not included, order separately	**03.00.0038**
Short hooks 50mm. (24-pc pack)	**03.53.0012-X24**
Lighted header sign CMT ORANGE 220V ***(spare parts)***	**03.54.0084**
220V lamp for neon sign for display cabinet ***(spare parts)***	**03.54.0087**

www.dahm.no

Display Cabinets for Sabre & Jig Saw Blades

new

CMT ORANGE TOOLS™

A sturdy steel-made sabre and jig saw blade display cabinet with backlight to place anywhere you want in your store. You can hang up different types of blades. Please contact your CMT salesman to get advice on the most suitable blades composition to display. Blades not included. Dimensions are in cm.

IMBALL0143



Counter cardboard display for jig saw blades
CMT's end cap cardboard display for jig saw blades takes advantage of the existing space in your store and is designed for being placed on a counter, existing shelves or inside CMT's display cabinets. Suitable for stocking up to 12 different jig saw blade types, 10 packs each, 120 packs in total. The end cap cardboard display helps increase product visibility and sell more!



5-PIECE MASTERPACK



20-PIECE MASTERPACK



5-PIECE MASTERPACK



25-PIECE MASTERPACK

03.00.0038




Image may not depict actual product included. Refer to table.

Dimensions: 120 x 45 x 223cm.



03.53.0012-X24

DISPLAYS THAT SELL!

DESCRIPTION	ORDER NO.
Counter display only ***(empty)***	**IMBALL0143**
Display cabinet with backlight (220V) for sabre and jig saw blades ***(empty)*** hooks not included, order separately	**03.00.0038**
Short hooks 50mm. (24-pc pack)	**03.53.0012-X24**
Lighted header sign CMT ORANGE 220V ***(spare parts)***	**03.54.0084**
220V lamp for neon sign for display cabinet ***(spare parts)***	**03.54.0087**

www.dahm.no


Display Cabinet for Multi-Cutters

new

CMT ORANGE TOOLS™

A sturdy steel-made multi-cutters display cabinet with backlight to place anywhere you want in your store. You can hang up different types of cutters. Please contact your CMT salesman to get advice on the most suitable cutters composition to display. Cutters not included. Dimensions are in cm.

WOOD



WOOD&METAL



MULTI-MAT



MASONRY



1-PIECE CLAMSHELL
5-PIECE MASTERPACK

03.00.0038



Image may not depict actual product included. Refer to table.

Dimensions: 120 x 45 x 223cm.



03.53.0012-X24



03.53.0013-X24

DISPLAYS THAT SELL!

DESCRIPTION	ORDER NO.
Display cabinet with backlight (220V) for multi-cutters ***(empty)*** hooks not included, order separately	**03.00.0038**
Short hooks 50mm. (24-pc pack)	**03.53.0012-X24**
Long hooks 200mm. (24-pc pack)	**03.53.0013-X24**
Lighted header sign CMT ORANGE 220V ***(spare parts)***	**03.54.0084**
220V lamp for neon sign for display cabinet ***(spare parts)***	**03.54.0087**

www.dahm.no

Display Cabinet for Router Bits

This sturdy structure is hand-crafted using MDF, tempered glass and iron and is free-standing to offer 360° visibility and to give you the versatility of positioning the display anywhere you like in the store. The front is a convenient 2 component assembly. The upper section is designed to display 141 of the best selling router bits from the CMT router bits line and 20 corresponding spare parts; while 10 of the popular wooden box sets or saw blades can fit perfectly in the lower section if required. Secured glass with key lock. Dimensions are in cm.

WOOD® Magazine Best Overall

CMT Overall Rating 10!
Top Performing Router Bits



Deluxe packaging



03.53.0010-X104



03.53.0011-X16



03.53.0017

03.00.0042



Image may not depict actual product included. Refer to table.

Dimensions: 120 x 45 x 223cm.

DESCRIPTION	ORDER NO.
Display cabinets with: 240 HW router bits (S=Ø6mm), 66 spare parts (saw blades at your choice)	**700.300.00L**
Display cabinets with: 240 HW router bits (S=Ø8mm), 66 spare parts (saw blades at your choice)	**900.300.00L**
21 pcs. HW router bits with shank Ø12mm for our display cabinet ***(optional)***	**900.021.00**
Display cabinet for router bits / cutter heads ***(empty)*** includes 145 hooks (125 long and 20 short)	**03.00.0042**
Additional long hooks 200mm. (104-pc pack)	**03.53.0010-X104**
Additional short hooks 150mm. (16-pc pack)	**03.53.0011-X16**
Toolholder shelf (270x209x1,5cm.) for CMT display cabinet 03.00.0042 for router bit sets	**03.53.0017**
220V lamp for neon sign for display cabinet ***(spare parts)***	**03.54.0087**
Set 2 led 220V for display cabinet ***(spare parts)***	**03.54.0089**
Set of 2 metal support (RH-LH) for light header sign ***(spare parts)***	**03.53.0109**
Lighted header sign CMT ORANGE 220V ***(spare parts)***	**03.54.0084**

www.dahm.no

Display Cabinet for Router Bits and Forstner Bits

A beautiful, well-organized display of router bits in your shop is the best way to encourage customers to buy.
CMT has produced this beautiful cabinet to best show off our wide selection of high quality bright orange bits, Forstner bits, boring bits.
Made with a sturdy MDF frame and three glass panels, it is the ideal counter-top display.
The wooden slat back wall allows for easy bit organization and comes standard with front door lock. Secured glass with key lock. Dimensions are in cm.

03.00.0002



03.00.0002



Suitable for boring and Forstner Bits
(at your choice)



Deluxe packaging



Forstner clamshell

WOOD® Magazine
Best Overall
CMT Overall Rating 10!
Top Performing Router Bits

DISPLAYS THAT SELL!



03.53.0011-X16

DESCRIPTION	ORDER NO.
Display cabinet with: 76 HW Router bits (S=Ø6mm), 8 Spare parts (2 pcs. each)	**700.084.00**
Display cabinet with: 76 HW Router bits (S=Ø8mm), 8 Spare parts (2 pcs. each)	**900.084.00**
Display cabinet for router bits / Forstner bits ***(empty)*** includes 42 short hooks	**03.00.0002**
Additional short hooks 150mm. (16-pc pack)	**03.53.0011-X16**

www.dahm.no

Display Cabinet for Hole Saws

new

CMT ORANGE TOOLS™

A sturdy steel-made hole saws display cabinet with backlight to place anywhere you want in your store. You can hang up different types of hole saws. Please contact your CMT salesman to get advice on the most suitable hole saws composition to display. Hole saws not included. Dimensions are in cm.

NO LIMITS with the FASTX4® hole saws you can bore any material of any hardness!

SERIES 550 TUNGSTEN CARBIDE-TIPPED
SERIES 553 TUNGSTEN CARBIDE-TIPPED LONG



10X LONGER LIFE

5X FASTER



SERIES 551 BI-METAL PLUS 8% COBALT



2X LONGER LIFE



SERIES 552 DIAMOND DRY



10X LONGER LIFE



03.00.0038




Image may not depict actual product included. Refer to table.

Dimensions: 120 x 45 x 223cm.



03.53.0012-X24



03.53.0013-X24

DISPLAYS THAT SELL!

DESCRIPTION	ORDER NO.
Display cabinet with backlight (220V) for hole saws ***(empty)*** hooks not included, order separately	**03.00.0038**
Short hooks 50mm. (24-pc pack)	**03.53.0012-X24**
Long hooks 200mm. (24-pc pack)	**03.53.0013-X24**
Lighted header sign CMT ORANGE 220V ***(spare parts)***	**03.54.0084**
220V lamp for neon sign for display cabinet ***(spare parts)***	**03.54.0087**

www.dahm.no

Display Cabinet for Drill and Boring Bits

CMT ORANGE TOOLS™

03.00.0042

Start your stock of CMT drill and boring bits now by ordering a convenient display to help you get organized and keep your tools within your hand's reach.
Contact our office for terms and for choosing the drill bits you need from our very broad range.

- **Fit Top Selling 120 SKUs.**
- **Fit up to 20 Deep**
- **Secured Glass with Key Lock**

XTREME BORING BITS

Setting a new standard for performance and value







Image may not depict actual product included. Refer to table.

Dimensions:
120 x 31 x 223cm.


DISPLAYS THAT SELL!


03.53.0017 Toolholder steel shelf for drill & boring bits.
Fit up to 40 shelves into tower.

Dimensions: 270 x 209 x 1,5mm.

DESCRIPTION	ORDER NO.
Display cabinet for drill and boring bits ***(empty)*** Toolholder shelf not included, order separately	**03.00.0042**
Toolholder shelf (270x209x1,5mm.) for CMT display cabinet 03.00.0042 for drill and boring bits (order separately)	**03.53.0017**
220V lamp for neon sign for display cabinet ***(spare parts)***	**03.54.0087**
Set 2 led 220V for display cabinet ***(spare parts)***	**03.54.0089**
Set of 2 metal support (RH-LH) for light header sign ***(spare parts)***	**03.53.0109**
Lighted header sign CMT ORANGE 220V ***(spare parts)***	**03.54.0084**

www.dahm.no





Be Sure: to keep the black washer right side up to correspond with the bearing rotation during reassembly.



***10° Delrin® Conical Bearing**



****Delrin® Triangular Bearing**




*****Delrin® Cylindrical Bearings**

Bearings

791

D mm	D inches	B mm	B inches	P mm	ORDER NO.
6,35	1/4	3,17	1/8	2,8	**791.035.00**
9,5	3/8	4,76	3/16	3,2	**791.002.00**
12,7	1/2	4,76	3/16	5	**791.003.00**
12,7	1/2	6,35	1/4	4,8	**791.010.00**
13		5		4	**791.022.00**
13		6		5	**791.023.00**
15		6		5	**791.024.00**
15,8	5/8	4,76	3/16	5	**791.018.00**
15,8	5/8	6,35	1/4	5	**791.009.00**
16		5		5	**791.006.00**
16		8		5	**791.025.00**
19	3/4	4,76	3/16	7,5	**791.019.00**
19		6		6	**791.007.00**
19	3/4	6,35	1/4	7	**791.004.00**
19		8		6	**791.034.00**
19	3/4	12,7	1/2	4	**791.011.00**
22		8		6	**791.012.00**
22		8		7	**791.005.00**
22,2	7/8	4,76	3/16	7,5	**791.017.00**
22,2	7/8	9,52	3/8	7	**791.021.00**
22,2	7/8	12,7	1/2	7	**791.013.00**
24		8		8	**791.036.00**
28		12		8	**791.026.00**
28,5	1-1/8	4,76	3/16	8,4	**791.014.00**
28,5	1-1/8	8		8,5	**791.030.00**
28,5	1-1/8	12,7	1/2	8	**791.027.00**
31,7	1-1/4	8		5	**791.033.00**
31,7	1-1/4	12,7	1/2	8	**791.015.00**
34,9	1-3/8	4,76	3/16	11,5	**791.016.00**
34,9	1-3/8	8		11,6	**791.031.00**
34,9	1-3/8	12,7	1/2	11	**791.029.00**
37		12		12	**791.028.00**
38,1	1-1/2	12,7	1/2	13,3	**791.020.00**
62		30		16	**791.051.00**
62		35		14	**791.052.00**
80		40		18	**791.054.00**
80		50		16	**791.053.00**
10° Delrin® Conical Bearings					
19	3/4	4,76	3/16	6,8	**791.041.00***
new 22	7/8	4,76	3/16	6,8	**791.048.00***
Delrin® Triangular Bearings					
12,7	1/2	4,76	3/16	5,8	**791.042.00****
19	3/4	4,76	3/16	7	**791.043.00****
Delrin® Cylindrical Bearings					
12,7	1/2	4,76	3/16	5	**791.044.00*****
15,87	5/8	4,76	3/16	7,2	**791.045.00*****
19,05	3/4	4,76	3/16	6,8	**791.046.00*****
37,4		12,7	1/2	15,7	**791.047.00*****




Shields for Assembly

541

B mm	D mm	P mm	ORDER NO.	B mm	D mm	P mm	ORDER NO.
3,25	9	1,6	**541.550.00**	8	14,7	5,8	**541.519.00**
3,25	15,8	2	**541.552.00**	12	20	2	**541.512.00**
5,2	15,8	2,5	**541.551.00**	12	20	3	**541.511.00**
6,4	9,52	2,2	**541.514.00**	12	21	0,1	**541.513.00**
8	14	0,1	**541.515.00**	12	21	0,3	**541.520.00**
8	14	0,3	**541.516.00**	12	21	1,59	**541.521.00**
8	14	0,5	**541.517.00**	12	21	3,18	**541.522.00**
8	14	1	**541.518.00**	12	21	6,16	**541.523.00**
8	14,7	3	**541.500.00**	12	21	1	**541.524.00**
8	14,7	4	**541.501.00**	12	21	0,5	**541.525.00**


www.dahm.no



Arbors — 797

S mm	S1 mm		ORDER NO.
8	M10x1,5		797.580.00
10	M12x1		797.100.00
12	M12x1		797.120.00
12,7	M12x1		797.127.00

TECHNICAL DETAILS:
- Super strength steel.
- Precisely machined for accuracy.



Collet Chucks — 796

S1 mm	B mm	L mm	ORDER NO.
M10x1,5	6 - 6,35 - 8 - 9,5	38	796.100.00
M12x1	6 - 6,35 - 8 - 9,5	38	796.000.00
M12x1	10 - 12 - 12,7	47	796.121.00

TECHNICAL DETAILS:
- Super strength steel.
- Precisely machined for accuracy.

Collet not included.




Router Chuck Extensions with Collet — 796.001/002

S mm	Collet included mm	For collets mm	L mm	ORDER NO.
12	8	6 - 6,35 - 8 - 9,5	81	796.002.01
12	12	10 - 12 - 12,7	88	796.002.00
12,7	6,35	6 - 6,35 - 8 - 9,5	81	796.001.01
12,7	12,7	10 - 12 - 12,7	88	796.001.00

TECHNICAL DETAILS:
- Super strength steel.
- Precisely machined for accuracy.

Collet included.



Collet Chucks — 796

S mm	For collets mm	LB mm	ORDER NO.
M14x2	6 - 6,35 - 8 - 9,5	32	796.140.00
M14x2	10 - 12 - 12,7	38	796.141.00
M16x2	6 - 6,35 - 8 - 9,5	32	796.160.00
M16x2	10 - 12 - 12,7	38	796.161.00

TECHNICAL DETAILS:
- Super strength steel.
- Precisely machined for accuracy.


Collet not included.



Collets — 796.500/600

B mm	ORDER NO.	B mm	ORDER NO.
6	796.560.00	10	796.600.00
6,35	796.564.00	12	796.620.00
8	796.580.00	12,7	796.627.00
9,5	796.595.00		


www.dahm.no



Arbors 798

S mm	S1 mm		ORDER NO.
M10x1,5	M10x1,5		798.101.00
M10x1,5	M12x1		798.102.00
M12x1	M10x1,5		798.121.00
M12x1	M12x1		798.122.00

TECHNICAL DETAILS:
- Super strength steel.
- Precisely machined for accuracy.




"ER20" Chucks 796

S mm	For collets "ER20" mm	LB mm	ORDER NO.
M12x1,75	3 ~ 12,7	43	796.122.00
M14x2	3 ~ 12,7	43	796.142.00
M16x2	3 ~ 12,7	43	796.162.00

Spare parts: 992.483.03 M25x1,5mm clamping nut
991.483.00 "ER20" key


TECHNICAL DETAILS:
Super strength steel. Precisely machined for accuracy.

Collet not included.



"ER20" Precision Collets for 796.122/142/162 Items 184


B mm	ORDER NO.	B mm	ORDER NO.
3	184.030.20	8	184.080.20
5	184.050.20	10	184.100.20
6	184.060.20	12	184.120.20
6,35	184.064.20	12,7	184.127.20



Collets for CMT1E, CMT2E, DeWalt®, Felisatti®, Fein®, Metabo® Hand-Held Routers 796.8


B mm	ORDER NO.	B mm	ORDER NO.
6	796.860.00	10	796.900.00
6,35	796.864.00	12	796.920.00
8	796.880.00	12,7	796.927.00
9,5	796.895.00		

Spare parts: 992.100.01 M22 clamping nut



Collets for Freud®/Casals® Hand-Held Routers 796.780

B mm	L mm		ORDER NO.
8	14		796.780.00



Bushings 799


B mm	D mm	L mm	ORDER NO.	B mm	D mm	L mm	ORDER NO.
6	8	25	799.060.00	8	10	25	799.280.00
6	9,5	25	799.160.00	8	12	25	799.380.00
6	12	25	799.260.00	8	12,7	25	799.480.00
6,35	8	25	799.064.00	9,5	12,7	25	799.001.00
6,35	9,5	25	799.164.00	10	12	25	799.100.00
6,35	12,7	25	799.264.00	13	16	45	799.130.00
8	9,5	25	799.180.00				

www.dahm.no


Screws

990





1_STIC



7_TCEI



2_STEI Flat




8_TSPEI



3_STEI Conical



9_TCPTI



4_STEI Pin




10_TSPTI




5_TCEI Guide



11_TBPTI



6_WEEKE



12_TCEI

d x l x L mm	D mm	TIPO	ORDER NO.	d x l x L mm	D mm	TIPO	ORDER NO.
M5x8		1_STIC	990.008.00	M4x12x16	7	7_TCEI	990.061.00
M5x10		1_STIC	990.003.00	M6x25x31	10	7_TCEI	990.098.00
M2x2		2_STEI	990.060.00	M8x25x33	13	7_TCEI	990.099.00
M4x20		2_STEI	990.091.00	1/8"x1/2"x5/8"	5,5	7_TCEI	990.059.00
M5x4		2_STEI	990.015.00	M5x10x15	8,5	7_TCEI	990.010.00
M5x5		2_STEI	990.001.00	M4x3,7x6	8	8_TSPEI	990.004.00
M5x5 p/coppa		2_STEI	990.006.00	M5x9x12	10	8_TSPEI	990.055.00
M3x3		3_STEI	990.005.00	M5x5,2x8	9	8_TSPIC	990.067.00
M5x5		3_STEI	990.002.00	M6x8x10	9	8_TSPEI	990.083.00
M6x6		3_STEI	990.007.00	1/4"x11/16"x7/8"	12	9_TSPEI	990.097.00
M4x3		3_STEI	990.013.00	1/8"x3/8"x1/2"	7	12_TCEI	990.058.00
M4x4		3_STEI	990.014.00	**Torx screw**			
M6x5		3_STEI	990.009.00	M5x12x18	6,8	8_TSPEI	990.063.00
M6x8		4_STEI	990.087.00	M3x4x5,7	4,6	9_TCPTI	990.082.00
M6x10		4_STEI	990.106.00	M3,5x6x8,5	6	9_TBPTI	990.077.00
M6x16		4_STEI	990.066.00	M2,5x3x4,5	3,5	10_TSPTI	990.070.00
M6x20		4_STEI	990.084.00	M2,5x4,5x6	3,7	10_TSPTI	990.071.00
M6x25		4_STEI	990.085.00	M4x2x3	7,6	10_TSPTI	990.079.00
M8x12		4_STEI	990.065.00	M5x4,75x6,5	9	10_TSPTI	990.080.00
M8x16		4_STEI	990.064.00	M5x5x8	9	10_TSPTI	990.093.00
M8x20		4_STEI	990.086.00	M3,5x3,5x6	6	11_TBPTI	990.072.00
M5x5x9	6	5_STEI	990.068.00	M3,5x5x7,2	8,8	11_TBPTI	990.073.00
M5x11,5x17		6_WEEKE	990.088.00	M4x3,5x5,7	8,8	11_TBPTI	990.074.00
M2,5x6x8,5	4,5	7_TCEI	990.062.00	M4x4x6,2	5,8	11_TBPTI	990.076.00
M3x6x9	5,5	7_TCEI	990.051.00	M4x4x6,2	9	11_TBPTI	990.056.00
M3x10x13	5,5	7_TCEI	990.053.00	M4x4,5x8	7,5	11_TCPTI	990.094.00
M3x16x19	5,5	7_TCEI	990.054.00	M4x6x8	6	11_TBPTI	990.078.00
M4x6x10	7	7_TCEI	990.052.00	M4x6x8,2	8,8	11_TBPTI	990.075.00

Keys for Screws

991



Hex Keys



Torx Key

DESCRIPTION	ORDER NO.	DESCRIPTION	ORDER NO.
Hex Keys		6mm	991.066.00
0,9mm	991.055.00	**Torx Key**	
1,5mm (for M3 screws)	991.056.00	T8	991.063.00
2mm	991.060.00	T9	991.069.00
3/32" (for 1/8W screws)	991.057.00	T15	991.061.00
2,5mm (for M4 screws)	991.062.00	T20	991.072.00
3mm	991.067.00	T25	991.073.00
4mm	991.064.00	T30	991.071.00
5mm	991.065.00		

Shields for Bearings

990



DESCRIPTION	ORDER NO.	DESCRIPTION	ORDER NO.
Ø9,5mm	990.422.00	Ø12,7mm	990.423.00

Nuts for Arbors


990.0



DESCRIPTION	ORDER NO.	DESCRIPTION	ORDER NO.
M4	990.092.00	M8	990.020.00
M6	990.095.00	M12x1,25mm	990.022.00


Stop Collars

541




B mm	ORDER NO.	B mm	ORDER NO.
3,175	541.008.00	9,5	541.006.00
6	541.003.00	12	541.005.00
6,35	541.001.00	12,7	541.002.00
8	541.004.00		

www.dahm.no




Threaded Rings for 694.001 Cutter Heads — 695.996

DESCRIPTION	ORDER NO.
M4 (Ø10x1,6mm)	**695.996.01**
M4 (Ø12x1,7mm)	**695.996.02**




Spacers Set — 695.998

DESCRIPTION D x B x P mm	FOR CUTTER HEAD	ORDER NO.	DESCRIPTION D x B x P mm	FOR CUTTER HEAD	ORDER NO.
Spacer Sets			**Spacer sets with Pin Hole**		
50 30 9	694.015	**695.998.01**	65 30 8	694.001 & 694.015	**695.998.21**
50 31,75 9	694.015	**695.998.02**	65 31,75 8	694.001 & 694.015	**695.998.22**
55 35 9	694.015	**695.998.03**	65 35 8	694.001 & 694.015	**695.998.23**
60 40 9	694.015	**695.998.04**	70 40 8	694.001 & 694.015	**695.998.24N**
70 50 9	694.015	**695.998.05**	70 50 8	694.001 & 694.015	**695.998.25N**
50 30 33	694.005	**695.998.11**			
50 31,75 33	694.005	**695.998.12**			
55 35 33	694.005	**695.998.13**			
60 40 33	694.005	**695.998.14**			
70 50 22	694.005	**695.998.15**			



Wedges for Cutter Heads — 651-692-693-695

DESCRIPTION	ORDER NO.	DESCRIPTION	ORDER NO.
Wedge for Cutter Heads		31x11x9,5mm	**695.999.31**
38x15x16mm	**692.999.01**	38x11x9,5mm	**695.999.38**
38x22,5x13mm	**692.999.02**	39x11x9,5mm	**695.999.39**
38x26x13mm	**693.999.01**	41x11x9,5mm	**695.999.41**
38x28x12,5mm	**693.999.02**	42x11x9,5mm	**695.999.42**
38x15x16mm (per/para 695.018)	**695.018.01**	46x11x9,5mm	**695.999.46**
7x11x9,5mm	**695.999.07**	49x11x9,5mm	**695.999.49**
16x11x9,5mm	**695.999.16**	53x11x9,5mm	**695.999.53**
17x11x9,5mm	**695.999.17**	**Wedges for Router Bits with Knives**	
22x11x9,5mm	**695.999.22**	D=8x20mm	**651.999.01**
23x11x9,5mm	**695.999.23**	D=10-12-12,7x30mm	**651.999.02**
23x11x9,5mm	**695.999.24**	D=12-12,7x50mm	**651.999.03**



Slot Cutter Arbors — 7/8/924

D mm	L1 mm	LB mm	L mm	ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12mm	ORDER NO. S=Ø12,7mm
Arbors for 822 Slot Cutters								
M8	26	32	61	**724.060.00**	**824.064.00**	**924.080.00**		
M8	40	38	86			**924.083.00**		
M8	26	38	67,5				**924.120.00**	**824.127.00**
M8	40	38	81				**924.128.00**	**824.128.00**
M12	54	38	97				**924.129.00**	**824.129.00**
M8	47	38	97				**924.130.00**	**824.130.00**
M8	29,75	32	71				**924.131.00**	**824.131.00**
M8	35,5	28,5	71				**924.132.00**	**824.132.00**
M8	23	41	71				**924.133.00**	**824.133.00**
M12	39,5	38	85				**924.134.00**	**824.134.00**
M12	54,5	38	100					**824.135.00**
Arbors for 823 Slot Cutters with Counterbore								
		40	55	**724.061.00**	**824.061.00**	**924.081.00**		**824.121.00**
8	11	41	61	**724.062.00**	**824.062.00**	**924.082.00**		**824.122.00**

www.dahm.no

Alphabetical index

DESCRIPTION	PAGE
"ER20" Precision Collets for 796.122/142/162 Items	110
1 Piece Rail & Stile Cutter Heads	92
1010W Router	312
12 Corner Radius Router Template Set from 3mm to 25mm	337
12-Piece Router Bit Set with Wooden Case	204
13 Piece Multiprofile Cutter Head Sets without Limiters	94
13-Piece Dovetail & Straight Bit Sets	203
13-Piece Router Bit Set with Wooden Case	204
15° Dovetail Cutter with Insert Knives for Roof-Frames	162
2 Flute Dowel Drills	264-265
2 Flute Dowel Drills for Through Holes	270-271
2 Piece Adjustable Grooving Sets	77
2 Piece Adjustable Rounding & Chamfering Sets	79
2-Piece Entry Door Router Bit Set	206
2400W Router	313
3 piece Adjustable Grooving Sets	76
3-in-1 Flush Trim Bits for MDF/Laminate	140
300W Oscillating Multi-Tools	315
3D Router Carver System	332~334
4 Flute Dowel Drills	266~268
4 Flute Dowel Drills for Through Holes	271
4-Wing Cut Out Slot Cutters for Solid Surfaces	198
45° Chamfer Cutter Heads	80
45° Countersink with Parallel Shank	296
45° Lock Miter Cutter Heads	87
5-Piece Boring Bit Set for Hinges	282-283
5-Piece Spiral Bit Sets	208
5-Piece Straight Bit Set & Profile Bit Set	207
5%co HS Spiral Bits for Aluminium Positive Single Flute	129
5%co HS Spiral Bits for Aluminium Positive Single Flute for High Cutting Depth	129
550W Professional Trimmer	314
6-Piece Mortising Bit Sets	248
6-Piece Mortising Bit Sets	249
6-Piece Profile Bit Set with Wooden Case	205
60° Lettering Bit	163
7 Piece Multiprofile Cutter Head Sets with Limiters	95
8-Piece Dovetail & Straight Bit Sets	203
9° Dovetail Cutters	162
90° Countersink with Parallel Shank	296-297

A

Adaptors	254~256, 280-281
Adaptors for Twist Drills	262
Additional Templates, Bits & Accessories	321
Adjustable Chamfer Cutter Heads with Positive Stop	81
Adjustable Chamfering CNC Cutter	242
Adjustable Countersink	294
Adjustable Double Roundover Router Bits	180
Adjustable Roundover & Bevel Router Bits	180
Adjustable Scoring Blades Industrial Line	23
Adjustable Shaker Router Bit Sets	213
Adjustable Tongue & Groove Bit Set for Mission Style Cabinet Doors	213

B

Back-to-Back Connectors for Straight Edge Clamps (optional)	318
Ball Milling	170
Bead & Bull Nose Bits	182
Beading Bits	173
Bench Block Set	330
Bi-Metal Plus Hole Saws	306-307
Biscuit Joiner Saw Blades	36
Blank Knives & Limiters (to be sharpened)	110
Blum Hinges Boring Head	330
Boring Bit & Plug Cutter Sets	287
Boring Bits with Parallel Shank	282~285
Bowl & Tray Bits	163
Bowl & Tray System	338
Brad Point Bit Sets	292
Brad Point Bits	290, 292-293
Bushings for Twist Drills	262

DESCRIPTION	PAGE

C

C-Spanner	223
C-Spanner for "DIN6388" & "ER40"	220
C-Spanner for "ER32" Precision Collets	219
C-spanner for "ER40" Precision Collets	217
Calibration & Sanding Disks	37
Cap Nuts for CNC Machines	222
Cavetto Edge Mould Bits	172
Chamfer Bits	167-168
Chamfer Bits with Insert Knives	167
Chamfer Set	168
Chucks & "ER20" Collets for Spindle Moulder Machine	110
Chucks for "ER32" Precision Collets	219
Clamping Nuts	220, 223
Clamping Nuts for Chucks with "ER32" Collets	219
Clamping Nuts for Chucks with "ER40" Precision Collets	217
Classical Bead Bits	176
Classical Ogee Bits	178
CMT Inlay Kit	325
CMT Moulding System	183
CMT-Enlock Joining System	324
CMT's Complete Kitchen Set	209
Collet Chucks Clamp with MK2 Tapered Shank	223
Collets for 123 Chucks	223
Combination Trimmer Bits	136-137
Complete Set for Decorating on MDF	243
Complete Set for MDF Doors	244
Complete Set for MDF Doors Insert Knives for Optional Profiles	245
Conical Scoring Blades Industrial Line	22
Contractor Saw Blade Combo	32
Contractor Saw Blade Masterpack	32
Corner Beading Bit with 45° Chamfer	181
Corner Beading Bits	182
Countersinks for 2 Flutes Dowel Drills	272
Countersinks for 4 Flutes Dowel Drills	272
Countersinks with Threaded Shank	294
Cove Bit Set	171
Cove Bits	171
Crosscut Saw Blades for Portable Machines	33
Cutter Arbor with HSK Tapered Shank	222
Cutter Arbor with ISO30 Tapered Shank	222
Cutter Heads for Rabbeting and 40mm Profile Knives	75
Cutter Heads with Limiters	93
Cutter Heads without Limiters	93

D

Dado & Planer Bits	133
Dado Saw Blades	35
Decorative Beading Bits	176
Decorative Ogee Bits	175~177
Diamond Dry Hole Saws	308-309
Diamond Router Cutters with 20° Shear Angle	236
Diamond Router Cutters with 40° Shear Angle	237
Diamond Router Cutters with 45° Shear Angle	235
Diamond Whetstones	336
Digital Angle Finder	341
Digital Angle Gauge	341
Digital Height Gauge	340
Digital Moisture Meter	340
Display Cabinet for Drill and Boring Bits	348
Display Cabinet for Hole Saws	347
Display Cabinet for Multi-Cutters	344
Display Cabinet for Router Bits	345
Display Cabinet for Router Bits and Forstner Bits	346
Display Cabinets for Sabre & Jig Saw Blades	343
Display Cabinets for Saw Blades	342
Divided Light Door Sets	212
Double-Bearing Spiral Flush Trim Bits	140
Double-Edge Trimmer	331
Dovetail Bits	160-161
Dowel Drills	260
Dowel Drills for Mafell® & Hand-Held Routers	291
Dowel Drills for Through Holes	261

www.dahm.no

Alphabetical index

DESCRIPTION	PAGE
Dowel Drills for Through Holes with Countersink	269
Dowel Drills with Countersink	269
Dowel Drills with Threaded Shank	275
Dowel Drills with Threaded Shank with Countersink	276-277
DP Conical Scoring Blades XTreme Line	20
DP Flush Trim Bits for Laminates	139
DP Hinge Boring Bits	273
DP Laminated & Chipboard Saw Blades XTreme Line	20
DP Router Cutters with Shear Angle	234~236
DP Router Cutters with Shear Angle for Nesting (Densimet® Tungsten Heavy Metal Alloys)	236
DP Saw Blades for Ultra-Hard Materials	31
DP Spiral Router Cutters with Shear Angle	237
Drawer Lock Bits	155
Drill Bit with Countersink for Screw Joints	297
Drill Bits for ANUBA® Hinges	293
Drill Bits with 45° Countersink Set	295
Drill Bits with 90° Countersink Set	295
Dry Cutter Saw Blades for Metal Industrial Line	26
E	
Edge Banding Bits Set	159
Edge Banding End Trimmer	331
Edge Banding Iron	331
Edge-Fluting Bits	183
Ellipse & Circle Cutting Jig	322
Entry & Interior Door Router Bit Set	205
F	
FILE-FREE Flush Trim Bits for Laminate	141
Fine Cut-Off Saw Blades for Portable Machines	34
Fine Cut-Off Saw Blades for Two-Sided Melamine Industrial Line	15~17
Finger Joint Bit	158
Finger Pull Bit	187
Finishing Saw Blades Industrial Line	13
Flexible Templates for Curved & Arched Routing	337
Flooring Router Bits	148
Flush Trim Bit Set	138
Flush Trim Bits	138
Flush Trim Bits with Insert Knives	141
Flush Trim Router Bits with Double Bearing	142
Flute & Bead Set	152
Folding Ruler	330
Formula 2050: Blade & Bit Cleaner	335
Forstner Bit Sets	288
Forstner Bits	288
G	
Garden Trimmer Saw Blades	30
Glass Panel Sets	212
Grand Rabbeting Bits with Insert Knives	146
Grinding Wheels for XTreme Sharpening	258
Grooving Saw Blades Industrial Line	36
Guide to Choosing the Most Suitable Jig Saw Blade	48
H	
Hinge Boring Bits	273-274
Hinge Boring Bits with Chipbreaker for Boring Machines	274
Hinge Recesser Bits	133
Hole Saw Application Chart	301
HS Corrugated Back Moulder Knives	111
HSK Chuck for “DIN6388” - EOC25 Precision Collet	220
HSK Chuck for “ER32” Precision Collets	218
HSK Chucks for “ER40” Precision Collets	217
HWM Reversible Knives	114-115
HWM Reversible Knives for Portable Planers	116
I	
Industrial Chrome-Coated Adjustable Blades	23
Industrial Chrome-Coated Scoring Blades	22
Industrio Routing System	317
Interchangeable Boring Bits with Threaded Shank	281
ISO30 Chucks for “ER32” Precision Collets	218
ISO30 Chucks for “ER40” Precision Collets	217
ISO30 Retaining Studs	222
ITK Plus Crosscut Saw Blades	29
ITK Plus Fine Cut-Off Saw Blades	29
ITK Plus Rip & Crosscut Saw Blades	28
ITK Plus Ripping Saw Blades	28
J	
Jig Saw Blades	49~52
Junior Ogee Rail & Stile Set	191
K	
Keyhole Bits	147
Kinetic Dust Extractor	216
Kitchen Sets	210
Kitchen Worktop Jig	323
L	
Laminate/Veneered-Panel Cutter	331
Laminated & Chipboard Saw Blades Industrial Line	19
Laminated & Chipboard Saw Blades XTreme Line	19
Laser Point Bit	165
Lock Miter Bits	153
Lock Miter Set	152
Low Noise & Chrome Coated Saw Blades with ATB Grind	14
Low Noise & Chrome Coated Saw Blades with TCG Grind	18
Lubricant for Wood, Neutralizes Resin	335
M	
Melamine & Laminated Long-Lasting Saw Blades XTreme Line	18
Mini-Spot Circular Saw Blade for Lamello®	37
Mortise Chisel & Bit Sets	285
Mortising Bits	132
Moulding Bits	185-186
Multi-Purpose Hole Saws	302-303
Multi-Purpose Long Hole Saws	304
Multi-Purpose with Countersink Hole Saws	305
Multi-Rip Anti-Kickback Saw Blades Industrial Line	9
Multi-Rip Saw Blades with Rakers Industrial Line	9
Multiprofile Bits	184
Multiradius Roundover Cutter Heads	82-83
N	
New Professional Router Table	316
Non-Ferrous Metal & Laminated Panel Saw Blades Industrial Line	25
Non-Ferrous Metal & Plastic Material Saw Blades Industrial Line	24
O	
Ogee Bits	179
Ogee with Fillet Bits	179
Organizer	334
Ovolo Bits	172
Ovolo Sash Bits	157
P	
Pair of Bore Reducers	110
Panalign Strips	209
Panel Pilot Bits with Guide	143
Panel Sizing Saw Blades Industrial Line	21
Pattern Bits	134
Pattern Router Bits with Insert Knives	135
Pattern Router Bits with Insert Knives for Laminates	135
Pattern/Flush Trim Bits with Insert Knives	142
Planer & Jointer Knives	112-113
Planing & Jointing Spiral Cutter Heads	78
Plug Cutters	286
Plunge Ogee Bits	177
Plywood Groove Set	126
Pocket-Pro™ Joinery System	339
Precision Collets “DIN6388”	220
Precision Collets “DIN6499”	221
Professional Adjustable Chamfer Cutter Heads with Gear Box	81
Professional Finger Joint Bit	158
Professional Finger Joint Cutter Heads	85

www.dahm.no

Alphabetical index

DESCRIPTION	PAGE
Professional Raised Panel Cutter Heads	89
Professional Straight Edge Clamps	318
Profile & Counter Profile Cutter Head Sets	90-91
Profile Knives & Limiters	96~109
PVC & Plexiglass Saw Blades Industrial Line	27

R

Rabbeting Bits	145
Rabbeting Bits with Insert Knives	146
Rabbeting Cutter Heads	74
Rabbeting Sets	145
Rail & Stile Set	191-192
Raised Panel Bit with Back Cutter	189
Raised Panel Bits	190
Raised Panel Cutter Heads	88
Reciprocating Slot Mortising Bits	250~252
Reduction Rings for Saw Blades	37
Reverse Glue Joint Bits	154
Reverse Glue Joint Cutter Heads	86
Rip & Crosscut Saw Blades Industrial Line	12
Rip Saw Blades for Portable Machines	31
Rip Saw Blades Industrial Line	11
Roman Ogee Bits	178
Rosette Cutters	289
Round Nose Bits	169
Round Nose Set	170
Round Nose Solid Carbide Upcut Spiral Bits	234
Roundover & Cove Cutter Heads	84
Roundover Bits	174
Roundover Bits with Insert Knives	173
Roundover Set	174
Router Bit Set with Insert Knives	208
Router Bit Sets	202
Router Bits for Domino® Joining Machines by Festool®	291
Router Cutters	238~240

S

Sabre Saw Blades	56~62
Sabre Saw Blades Application Chart	54-55
Saw Blade Arbor with Parallel Shank	223
Saw Blade Index	40~46
Saw Blades for Building Contractors	11
Saw Blades for Portable Machines	38-39
Saw Blades Stabilizers	37
Screw Slot Bits	148
Set of 2 Magnetic Knife Setting Jigs	111
Slot & Mortise Boring Bits	246-247
Slot Cutter Sets	207
Slot Cutters	150-151
Slot Mortising Bits	252
Slot Mortising Bits with Chip-Breaker	248
Small Arch Door Sets	211
Solid Carbide Dowel Drills	258-259
Solid Carbide Dowel Drills for Through Holes	259
Solid Carbide Downcut Spiral Bits	231
Solid Carbide Downcut Spiral Bits with Chip-Breaker	227
Solid Carbide Router Cutters	238-239
Solid Carbide Spiral Bits	122-123
Solid Carbide Spiral Bits Downcut	228
Solid Carbide Twist Drills "V" Point Sharpening	263
Solid Carbide Twist Drills Negatively Ground Spurs Sharpening	263
Solid Carbide Up & Downcut Spiral Bits	224
Solid Carbide Upcut Spiral Bits	225, 228, 230
Solid Carbide Upcut Spiral Bits for Locksets	232
Solid Carbide Upcut Spiral Bits with Chip-Breaker	226
Solid Carbide Upcut Spiral Bits without Chip-Breaker for 60° V-Point Locksets	232
Solid Carbide Upcut with Spiral Bits Chip-Breaker for 60° V-Point Locksets	232
Solid Surface - Inlay Bits	200
Solid Surface Bevel Bit	197
Solid Surface Bevel Bowl Bits	197
Solid Surface Cut & Plug Repair Set	198
Solid Surface Decorative Edge Profile Bits	195
Solid Surface Drainboard Bits	200

DESCRIPTION	PAGE
Solid Surface No-Drip Bit	199
Solid Surface Rounding Over Bits	195
Solid Surface Rounding Over Bowl Bit (ogee profile)	196
Solid Surface Rounding Over Bowl Bits	196
Solid Surface Saw Blades Industrial Line	27
Solid Surface Sink & Trim Bits with Delrin® Bearing	201
Solid Surface Sink & Trim Bits with Insert Knives & Delrin® Bearing	201
Solid Surface Wavy Joint Bit	199
Spare Parts & Accessories	349~353
Special Dowel Drills	278
Spiral Bits with Insert Knives & Chip-Breaker for Locksets	233
Spoilboard Surfacing Router Cutters with Insert Knives	241
Step-By-Step Window Sash Construction	156
Stepped Rebate Router Bit	166
Stile & Panel Router Bits	194
Stop Collars with Delrin® Sleeve	295
Straight Bits	126
Straight Bits with Centre Tip	124
Straight Bits, Long Series	125
Straight Bits, Short Series	127
Straight Cutters with Threaded Shank	128
Straight Router Bits with Insert Knives	130-131
Straight Router Bits with Insert Knives for Laminates	130
Straight Router Cutters with Insert Knives	241
Super Fine Finishing Blade XTreme Line	16
Super Finishing Saw Blades for Cutting Frames XTreme Line	13
Super-Duty Flush Trim Bits	139
Superjaws Portable Clamping System	319

T

T-Slot Bits	147
Table Edge & Hand Rail Bits	188
Template Guide Kit	339
Tenon Cutting Router Bits	206
The ABC's of Panel Door Construction	193
The Cabinetmaking Sets	211
The CMT Grand Rabbet Set	144
The Hole Saw Revolution	298~300
The Raised Panel Sets with Backcutter	210
Thick-Kerf Multi-Rip Saw Blades with Rakers Industrial Line	10
Thin-Kerf Multi-Rip Saw Blades with Rakers Industrial Line	10
Three Wing Slot Cutter Set	149
Tongue & Groove Set	149
Tools for Multi-Cutters	64~72
Twisted Slot Mortising Bits with Chip-Breaker	249

U

Ultra Thin-Kerf Saw Blades for Cordless Saws	30
Universal Assembly Supports for Chucks	216
Universal Boring Jig	327
Universal Boring Template	326
Universal Dovetail Jig	320
Universal Hinges Boring System	328-329
Upcut Spiral Bits with Chipbreaker for Glue-Laminated Wooden Beams	233

V

V-Groove - Folding - Signmaking CNC Router Cutters with Insert Knives	242
V-Grooving & Signmaking Router Bits with indexable knives (90°)	166
V-Grooving Bits (90°)	164
V-Grooving Bits for Alucobond®	165
V-Tongue & Groove Set	159
Vertical Raised Panel Bits	188

W

Wainscot/Paneling Bits	181
Weatherseal Bits	136
Window Sash Set	156
Window Sill & Finger Bits	187

www.dahm.no

Numerical index

ORDER NO.	PAGE
01.02	257
03.00.0002	346
03.00.0030	342
03.00.0038	342~344, 347
03.00.0042	345, 348
03.51	334
03.53.0010-X104	345
03.53.0011-X16	345
03.53.0011-X16	346
03.53.0012-X24	342~344, 347
03.53.0013-X24	344, 347
03.53.0017	345, 348
102	248
103	251
104	250
105	250
106	252
107	252
112	239
113	239
123	223
124	223
140	235
141	234
142	236
143	236-237
145	237
160	249
161	249
163	246
164	247
166	247
167	247
170	128
171	128
172	248
173	128
174	124, 238
175	240
176	240
177	124, 240
179	251
180	128
181	128
182	128
183	216
183.000	219
183.100	219
183.200	218
183.201	217
183.210	218
183.211	217
183.220	218
183.221	217
183.250	218
183.251	218
183.260	222
183.300	218
183.310	217
183.320	220
183.360	222
183.400	219
183.410	223
184	110, 221, 351
185	220
188	129
189	129
190	122, 224
190B	140
191	123, 208, 230
191.143	232
191.163	232
191.635	136
191B	140
192	123, 208, 231
192B	140
193	228
194	229
195	226, 232-233
195.143	232
195.163	232
196	227
197	225
198	122, 225
199	169, 234
222	27
223	27
226	26, 30
230	35
236	31
237	20
238	20
240	36
240.004.04	37
241	36
250	30
251	30
271	28, 30
272	29-30
273	29
274	16
277	10
278	9
279	9
280	10
281	18-19, 21, 34
282	21
283	15
284	24
285	11~14, 33-34
285.5	13
286	11
287	16-17
288	22
289	23
290	11, 31
291	12, 33
292	34
293	11
294	12-13
295	18
296	25
297	25
298	24
299	37
299.10	37
299.11	37
301	254
302	254
303	254
304	254
305	255
306	266
306.301	256
307	266
308	267
309	267
310	264
310.21/22	257
310.41/42	260
311	265
311.21/22	257
311.41/42	260
312	291
313	270
313.41/42	260
314	270
314.21/22	258
314.41/42	260
315	272
317	273
317C	274
325	277
327	277
329	277
330	277
332	276
334	276
336	276
337	276
338	277
339	277
340	277
341	276
342	276
343	276
344	275
346	275
350	294
351	294
352	275
353	275
358	255
359	255
360.001	255
360.101	256
360.201	256
360.401	256
361	264
362	265
363	263
364	262
365	262
367	271
368	271
369	273-274
369C	274
370	274
372	268
373	268
374	271
375	271
376	269
377	269
378	269
380	291
381	271
382	259
392	285
500.001	287
500.002	287
500.003	287
501	281
503	281
506	280
509	280
511	280
512	282-283
513	284
514	284
515	293, - 296-297
515A	295
516	293
517	292
521	296-297
521.001	294
521A	295
522	162
523	162
529	286
530	286
531	289
532	280
533	280
534	281
535	290
537	288
537.000.04	288
537.000.05	288
537.000.07	288
537.000.12	288
537.000.16	288
540	290
541	290, 295, 349, 352
542	290
543	285
550	302-303
550-DB1	303
550-EX1	305
550-EX2	305
550-HS1	303
550-HS2	303
550-HS2XL	305
550-HW1	303
550-HW2	303
550-HW2XL	305
550-SDS1	305
550-SDS2	305
550CS	305
551	306-307
551-HS1	307
551-HS2	307
551-HS2XL	305
552	308-309
552-DD1	309
552-DD2	309
552-WAX	309
553	304
600.005.01	208
615.004.01	244-245
616.000.01	243
651	130, 353
652	130
652B	135
653	131, 241
654	131
655	131
656	135
657.1	141
657.9	141
657B	142
658	167
659	167
660	146
660.9	146
661	173
662	233
663	241
663.101	242
663.201	242
663.301	246
664	162
665	166
690	96~110
691	96~110
692	93-94, 353
693	93, 95, 353
694.001	76
694.002	80
694.003	82
694.004	83
694.005	79
694.007	84
694.008	85
694.009	86

www.dahm.no

Numerical index

ORDER NO.	PAGE
694.011	87
694.012	88
694.013	89
694.014	92
694.015	90-91
694.017	81
694.018	81
694.019	78
694.020	75
694.021	77
694.022	77
694.100	74
695	353
695.996	353
695.998	353
699	110
700.001	202
700.003	202
700.005.03	207
701	132
701B	132
702	133
703	167
704	167
705	167
706	138-139
707	137, 140
709	137
710	137
711	126-127
711.031	136
711B	134
712	125
712.030	136
712.040	136
712B	134
713.001	136
714	169
714B	169
715	164
715B	164
716	143
718	160-161
718B	160-161
721	136
722A	150
724	151, 353
724.xxx.00	150
724.xxx.10	150
727	172
735	145
735.001	145
736	168
737	171
738	174, 195
739	173
740	178
741	178
742	137
743	137
744	178
745	178
746	179
747	179
748	177
748B	177
749	163
750.001	147
751	163
751B	163
753	143
754	182
755.002	155
758	165
759	179
760	179
761	182
762	183
763	172
764	172
765	175~177
765B	176
790	114~116
791	349
792	112
793	111
795	113
796	110, 350-351
796.001	350
796.002	350
796.500	350
796.600	350
796.780	351
796.8	351
797	350
798	351
799	351
800.001	202
800.005.01	207
800.500	203
800.501	203
800.503	204
800.504	205
800.505	204
800.506	149
800.509	209
800.510	209
800.511	209
800.512	210
800.513	210
800.514	210
800.515	211
800.516	210
800.517	210
800.518	210
800.519	203
800.520	211
800.521	210
800.522	210
800.524	211
800.525	212
800.527	205
800.606	158
800.616	158
800.622	180
800.623	180
800.624	213
800.625	213
800.626	149
800.627	206
800.628	206
801	132
801B	132
806	138-139
806B	142
807	140-141
809	137
811	126-127
811B	134
812	125
812.032	136
812B	134
813	148
813.001	136
814	169-170
814B	169
815	164
815B	164
816	143
818	160-161
818B	160-161
821	136
822	150
822.023B	148
822.024B	148
822.033B	198
822A	150
822B	150
823	151
823.001	207
823B	151
824	151, 353
824.xxx.00	150
824.xxx.10	150
827	172
835	145
835.001	145
835.503	144
835.990	144
836	168
837	171
838	174, 195
839	173
840	178
841	178
842	137
843	137
844	178
845	178
846	179
847	179
848	177
848B	177
849	163
849B	163
850.001	147
850.6	147
851	163
851B	163
852	133
852B	133
853	143
854	182
855	152, 187
855.002	155
855.3	157
855.501	154
855.502	155
855.503	153
855.504	153
855.506	159
855.508	155
855.510	159
855.701	152
855.801	156
855.802	157
855.803	212
855.804	187
855.804B	187
855.805	187
855.805B	187
855.806	206
855.901	185
855.902	185
856.501	185
856.601	188
856.701	188
856.702	188
856.8	184
856.851	183
856.852	183
857	168
858	165
859	179
860	179
861	182
861.6	181
862	183
863	172
864	172
865	175~177
865B	176
866.501	197
866.601	196
866.602	196
867.5B	186
867.6B	186
868	170
870	193
880.5	195
880.511	200
880.512	200
880.513	200
880.521	195
880.531	199
880.541	196
880.542	196
880.551	197
880.561	201
880.562	201
880.571	201
880.571	201
880.572	201
881.501	199
881.511	200
881.512	200
881.521	197
881.531	199
881.541	198
890	189
890.5	190
890.6	188
891.5	192
891.512	191
891.517	191
891.521	192
899	325
900.001	202
900.003	202
900.005.01	207
900.005.03	207
900.024	211
900.025	212
900.506	149
900.509	209
900.510	209
900.511	209
900.512	210
900.513	210
900.514	210
900.516	210
900.517	210
900.518	210
900.521	210
900.522	210
900.527	205
900.606	158
900.616	158
900.622	180
900.623	180
900.624	213
900.625	213
900.626	149
900.627	206
900.628	206

www.dahm.no

Numerical index

ORDER NO.	PAGE
901	132
901B	132
902	133
903	167
904	167
905	167
906	138-139
906B	142
907	137, 140-141
909	137
910	137
911	126-127
911B	134
912	125
912B	134
913	148
914	169
914B	169
915	164-165
915B	164
916	143
918	160-161
921	136
922.033B	198
922A	150
922B	150
923.001	207
923A	151
924	151, 353
924.xxx.00	150
924.xxx.10	150
927	172
935	145
935.001	145
935.503	144
935.990	144
936	168
937	171
938	174, 195
939	173
940	178
941	178
944	178
945	178
947	179
948	177
948B	177
949	163, 179
949B	163
950.001	147
950.6	147
951	163
953	143
954	181-182
955	152, 187
955.002	155
955.008	155
955.3	157
955.302	157
955.501	154
955.502	155
955.503	153
955.504	153
955.506	159
955.510	159
955.701	152
955.801	156
955.803	212
955.804	187
955.804B	187
955.805	187
955.805B	187
955.806	206
955.901	185
955.902	185
956.501	185
956.601	188
956.701	188
956.702	188
956.8	184
956.851	183
956.852	183
957	168
958	165
959	179
960	179
961	182
961.6	181
963	172
964	172
965	166, 175~177
965B	176
966.501	197
966.601	196
966.602	196
967.5B	186
967.6B	186
968	170
970	193
980.5	195
980.511	200
980.512	200
980.513	200
980.521	195
980.531	199
980.541	196
980.542	196
980.551	197
980.561	201
980.562	201
980.571	201
981.501	199
981.511	200
981.512	200
981.521	197
981.531	199
981.541	198
990	189, 352
990.0	352
990.088	256
990.5	190
990.6	188
991	352
991.123	223
991.183	219
991.184	217
991.283	220
991.5	192
991.512	191
991.517	191
991.521	192
992	216
992.123	223
992.183	219
992.283	220
992.383	217
993.0	222
998	335
999.110.00	316
999.500.01	317
BBS-001	330
BTS-002	338
CMT-Enlock1	324
CMT-TGA	325
CMT10	314
CMT11	315
CMT200	319
CMT300	320-321
CMT3000	322
CMT333	328-329
CMT334	330
CMT650	323
CMT656	327
CMT792	111
CMT7E	313
CMT8E	312
CMT900	326
DAF-001	341
DAG-001	341
DET-001	331
DET-002	331
DET-002	331
DET-004	331
DHG-001	340
DMM-001	340
DSS	336
FR2M	330
GLAS/RTBRN	212
IMBALLO143	343
JS1025VF	61
JS1110VF	59
JS1111DF	59
JS1111K	56
JS1120CF	62
JS1122AF	60
JS1122BF	61
JS1122EF	60
JS1122HF	57
JS1122VF	58
JS1125VF	61
JS1210VF	59
JS1222VF	58
JS1225VF	62
JS123XF	61
JS1243HM	62
JS1411DF	59
JS1531L	56
JS1617K	56
JS2243HM	62
JS2345X	57
JS3456XF	57
JS610VF	59
JS611DF	58
JS617K	56
JS641HM	60
JS644D	56
JS711DF	58
JS725VFR	57
JS920CF	62
JS922AF	60
JS922BF	61
JS922EF	60
JS922HF	57
JS922VF	58
JS925VF	61
JT101AO	50
JT101B	50
JT101BIF	51
JT101BR	50
JT101D	51
JT111C	49
JT118A	52
JT118B	52
JT119BO	49
JT123X	52
JT127D	52
JT141HM	51
JT144D	49
JT218A	52
JT234X	51
JT244D	49
JT244DDC	49
JT301CD	51
JT341HM	51
JT344D	50
JT718BF	52
JT744D	50
K	32
OMA30	72
OMA30000	72
OMA31	64
OMM01	65
OMM02	65
OMM03	65
OMM04	65
OMM05	66
OMM06	66
OMM07	66
OMM08	66
OMM09	67
OMM10	67
OMM11	67
OMM12	67
OMM13	68
OMM14	68
OMM15	68
OMM16	68
OMM17	69
OMM18	69
OMM19	69
OMM20	69
OMM21	70
OMM22	70
OMM23	70
OMM24	70
OMM25	71
OMM26	71
OMM27	71
OMM28	71
OMM29	72
OMM30	72
OMS01	65
OMS02	65
OMS03	65
OMS04	65
OMS05	66
OMS06	66
OMS07	66
OMS08	66
OMS09	67
OMS10	67
OMS11	67
OMS12	67
OMS13	68
OMS14	68
OMS15	68
OMS16	68
OMS17	69
OMS18	69
OMS19	69
OMS20	69
OMS21	70
OMS22	70
OMS23	70
OMS24	70
OMS27	71
OMS29	72
OMS30	72
PGC	318
PNL	209
PPJ-002	339
RCS	332~334
TMP	337
TMP-R12	337

www.dahm.no


Conversion Table

CMT ORANGE TOOLS™

Inch Decimals	Inch Fractions (x)						Millimeters					
	1/64	1/32	1/16	1/8	1/4	1/2	mm	1" + (x)	2" + (x)	3" + (x)	4" + (x)	5" + (x)
								25.400	50.800	76.200	101.600	127.000
0.015625	1/64						0.397	25.797	51.197	76.597	101.997	127.397
0.031250		1/32					0.794	26.194	51.595	76.994	102.394	127.794
0.046875	3/64						1.191	26.591	51.991	77.391	102.791	128.191
0.062500			1/16				1.588	26.988	52.388	77.788	103.188	128.588
0.078125	5/64						1.984	27.384	52.784	78.184	103.584	128.984
0.093750		3/32					2.381	27.781	53.181	78.581	103.981	129.381
0.109375	7/64						2.778	28.178	53.578	78.978	104.378	129.778
0.125000				1/8			3.175	28.575	53.975	79.375	104.775	130.175
0.140625	9/64						3.572	28.972	54.372	79.772	105.172	130.572
0.156250		5/32					3.969	29.369	54.769	80.169	105.569	130.969
0.171875	11/64						4.366	29.766	55.166	80.568	105.966	131.366
0.187500			3/16				4.762	30.162	55.562	80.962	106.362	131.762
0.203125	13/64						5.159	30.559	55.959	81.359	106.759	132.159
0.218750		7/32					5.556	30.956	56.356	81.756	107.156	132.556
0.234375	15/64						5.953	31.353	56.753	82.153	107.553	132.953
0.250000					1/4		6.350	31.750	57.150	82.550	107.950	133.350
0.265625	17/64						6.747	32.147	57.547	82.947	108.347	133.747
0.281250		9/32					7.144	32.544	57.944	83.344	108.744	134.144
0.296875	19/64						7.541	32.941	58.341	83.741	109.141	134.541
0.312500			5/16				7.938	33.338	58.738	84.138	109.538	134.938
0.328125	21/64						8.334	33.734	59.134	84.534	109.934	135.334
0.343750		11/32					8.731	34.131	59.531	84.931	110.331	135.731
0.359375	23/64						9.128	34.528	59.928	85.328	110.728	136.128
0.375000				3/8			9.526	34.925	60.325	85.725	111.125	136.525
0.390625	25/64						9.922	35.322	60.722	86.122	111.522	136.922
0.406250		13/32					10.319	35.719	61.119	86.519	111.919	137.319
0.421875	27/64						10.716	36.116	61.516	86.916	112.316	137.716
0.437500			7/16				11.112	36.512	61.912	87.312	112.712	138.112
0.453125	29/64						11.509	36.909	62.309	87.709	113.109	138.509
0.468750		15/32					11.906	37.306	62.706	88.106	113.506	138.906
0.484375	31/64						12.303	37.703	63.103	88.503	113.903	139.303
0.500000						1/2	12.700	38.100	63.500	88.900	114.300	139.700
0.515625	33/64						13.097	38.497	63.897	89.297	114.697	140.097
0.531250		17/32					13.494	38.894	64.294	89.694	115.094	140.494
0.546875	35/64						13.891	39.291	64.691	90.091	115.491	140.891
0.562500			9/16				14.288	39.688	65.088	90.488	115.888	141.288
0.578125	37/64						14.684	40.084	65.484	90.884	116.284	141.684
0.593750		19/32					15.081	40.481	65.881	91.281	116.681	142.081
0.609375	39/64						15.478	40.878	66.278	91.678	117.078	142.478
0.625000				5/8			15.875	41.275	66.675	92.075	117.475	142.875
0.640625	41/64						16.272	41.672	67.072	92.472	117.872	143.272
0.656250		21/32					16.669	42.069	67.469	92.869	118.269	143.669
0.671875	43/64						17.066	42.466	67.866	93.266	118.666	144.066
0.687500			11/16				17.462	42.862	68.262	93.662	119.062	144.462
0.703125	45/64						17.859	43.259	68.659	94.059	119.459	144.859
0.718750		23/32					18.256	43.656	69.056	94.456	119.856	145.256
0.734375	47/64						18.653	44.053	69.453	94.855	120.253	145.653
0.750000					3/4		19.050	44.450	69.850	95.250	120.650	146.050
0.765625	49/64						19.447	44.847	70.247	95.647	121.047	146.447
0.781250		25/32					19.844	45.244	70.644	96.044	121.444	146.844
0.796875	51/64						20.241	45.641	71.041	96.441	121.841	147.241
0.812500			13/16				20.638	46.038	71.438	96.838	122.238	147.638
0.828125	53/64						21.034	46.434	71.834	97.234	122.634	148.034
0.843750		27/32					21.431	46.831	72.231	97.631	123.031	148.431
0.859375	55/64						21.828	47.228	72.628	98.028	123.428	148.828
0.875000				7/8			22.225	47.625	73.025	98.425	123.825	149.225
0.890625	57/64						22.622	48.022	73.422	98.822	124.222	149.622
0.906250		29/32					23.019	48.419	73.819	99.219	124.619	150.019
0.921875	59/64						23.416	48.816	74.216	99.616	125.016	150.416
0.937500			15/16				23.812	49.212	74.612	100.012	125.412	150.812
0.953125	61/64						24.209	49.609	75.009	101.409	126.809	152.209
0.968750		31/32					24.606	50.000	75.406	100.806	126.206	151.606
0.984375	63/64						25.003	50.403	75.803	101.203	126.603	152.003


www.dahm.no

Saw blade safety




ALWAYS thoroughly check all blades for damage and flaws before using. Do not use blades with missing or damaged teeth.
ALWAYS wear safety glasses and ear protection when using power tools.
ALWAYS thoroughly read the owners manual and manufacturer's instructions before working with tools.
ALWAYS use a fence and splitter when using the table saw. Do not make freehand cuts.
ALWAYS use pusher blocks or a pusher stick, especially when working with small or narrow pieces.
ALWAYS unplug your saw before cleaning or adjusting the tool, or before making blade changes.
ALWAYS keep your tools sharpened, clean and stored in a safe place to avoid breakage and accidents and to extend the life of your bits and blades.
ALWAYS feed the work against the rotation of the blade on table saws.
ALWAYS be sure your workpiece is completely supported, before and after the cut.
NEVER remove guards from radial arm saws and miter saws.
NEVER remove the splitter or anti-kickback devices from table saws.
NEVER use dull or damaged blades.
NEVER use blades with missing or chipped teeth.
NEVER force the cut or overload the saw.
NEVER change blades with the saw plugged in.
NEVER make adjustments to any saw while the blade is turning.

Cutter head safety



ALWAYS thoroughly check all cutters for damage and flaws before using.
ALWAYS wear safety glasses and ear protection when using power tools.
ALWAYS thoroughly read the owners manual and manufacturer's instructions before working with tools.
ALWAYS use guards that were supplied with your shaper.
ALWAYS use a fence with your shaper. Do not make freehand cuts.
ALWAYS use pusher blocks, especially when working with small or narrow pieces.
ALWAYS unplug your shaper before cleaning or adjusting the tool, or before making cutter or knife changes.
ALWAYS be sure the spindle nut is tight before plugging in the shaper.
ALWAYS check that knives are properly and securely installed in the cutterhead when using interchangeable-knife systems.
ALWAYS keep your tools sharpened, clean and stored in a safe place to avoid breakage and accidents and to extend the life of your bits and blades.
ALWAYS feed the work against the rotation of the knives.
ALWAYS be sure your workpiece is completely supported, before and after the cut.
NEVER remove guards or any other safety devices from your shaper.
NEVER use dull or damaged knives.
NEVER force the cut or overload the shaper.
NEVER change cutters or knives or make adjustments with the shaper plugged in.
NEVER make adjustments to the shaper while the cutter is turning.

Router bits safety



ALWAYS thoroughly check all tools for possible flaws before using.
ALWAYS wear safety glasses and ear protection.
ALWAYS thoroughly read the owners manual and manufacturer instructions before using.
ALWAYS check that at least 75% of the shank is securely inserted into the collet of the router.
ALWAYS use template guide collars when possible to absorb lateral bit deflection.
ALWAYS use a fence when working on the router table.
ALWAYS reduce the router speed when working with larger diameter bits.
ALWAYS keep your fence adjusted so there is some clearance between the bearing guide and the workpiece.
ALWAYS take care to remove large quantities of stock (cross section > 10mm) in more than one run.
ALWAYS keep your tools sharpened, clean and stored in a safe place to avoid breakage and accidents and to extend the life of your bits and blades.
NEVER use dull or defective, even suspiciously defective, tools.
NEVER force the shank entirely into the collet (bottoming out). Leave about a 3,2mm (1/8") space from the bottom.
NEVER force the bit into your router or overload the router.

Explanation of symbol

HW Tungsten carbide tipped	HWM Solid tungsten carbide	HS High speed steel	SP Alloyed tools steel
HL High-alloyed tool steel	HPS High performance steel	HCS High carbon steel	BIM Bimetal
HSS High speed steel	BIM TiN TiN coated bimetal with 8% cobalt teeth	CERMET CARBIDE Cermet Carbide	INSERT CARBIDE Insert carbide
CARBIDE GRIT Carbide grit	DP Polycrystalline diamond	Polycrystalline diamond	GRIT Diamond grit
Z1 One cutting edge	Z1+1 One + one cutting edges	Z2 Two cutting edges	Z2+1 Two + one cutting edges
Z2+2 Two + two cutting edges	Z3 Three cutting edges	Z3+3 Three + three cutting edges	Z3R Three cutting edges with chipbreaker
Z4 Four cutting edges	Z12 Twelve cutting edges	V1 One spur	V2 Two spur
V4 Four spur	RH Right-hand rotation	LH Left-hand rotation	RH LH Right-hand & Left-hand rotation
Antikick-back	Radial relief	Tool with plunging capacity	Axial angle
MEC Mechanical feed	MAN Manual feed	Grooving, sizing	Rebating
Slooting	Non-axial boring	Spiral boring	Tool with bearing
Plastic box for cutter head	Plastic carry case for saw blades	Clamshell carry case for saw blades	Cardboard box for saw blades
Industrial Thin-kerf blade	ORANGE CHROME	High-Density Carbide	XTREME High performance tool
Non-Stick Orange Shield Coating™	Shear Angle Grind	Saw blade with dampening slots with fill	Saw blade with dampening slots without fill
Warning	Not for hand held use for router table only	Wear safety shoes	Wear five finger gloves
Wear safety glasses	Wear ear protection	Wear dust mask	Wear safety helmet

Conditions of trading

PREMISE
C.M.T.. products are the result of technological innovation achieved through continuous research applied on a vast scale. Drawings, technical data, photos of the products and packaging are supplied for the sole purpose of informing the customer and are not binding in any manner. **C.M.T.** may undertake, when necessary, modifications and improvements without applying these innovations to the parts already supplied.
The operational tolerances conform to technical standards that are acceptable for this range of tools.

ACCEPTANCE OF THE CONTRACT
All orders for our products are meant to be accepted at the price and sale conditions that are legally in force at the date of delivery.
Every order will be treated and supplied according to the following general sale conditions. By placing an order or accepting an offer, the customer accepts, without any reservations, all conditions expressly mentioned hereafter.
Any other derogation will only be accepted upon written consent by **C.M.T.** All other cases not contained within these conditions will fall under the Italian Civil Code.
Offers and order confirmations will be processed according to stock availability. Any order, even those taken by our representative agents, will be subject to our acceptance, which could also be a partial one.
We will notify the acceptance of any order by an order confirmation in which we will indicate all details pertaining to the items purchased, their price and expected delivery date. Therefore, we will not be able to accept any modification after three working days from the date of receipt.

MINIMUM AMOUNT ACCEPTABLE
C.M.T. will only be able to accept and process orders for a minimum net amount of € 100,00.
In case of acceptance of the order, we will add € 15,00 for shipping and handling.

PRICES
The prices stated in **C.M.T.'s** quotation and price lists are gross and are intended to be "ex-works".
Prices and VAT will be those in force at the date of shipping. To the best of our knowledge, the prices indicated in our catalogues, price lists and order confirmations are correct. However, **C.M.T.** cannot be held legally liable for reserving the right to change prices without notification in line with the manufacturer's cost increases.

DELIVERY
Delivery dates in the order confirmation are given as an indication of the estimated delivery time. They have to be considered as reliable only in case of normal operating conditions, and there shall be no liability on the part of the Seller for any failure to deliver due to causes beyond the Seller's control. **C.M.T.** will also not be able to accept any cancellation of existing orders which were not delivered in time due to external impediments.
Standard products will be shipped within five working days from receipt of the order.

SHIPPING AND HANDLING
The packing of our products will be charged on the final invoice, while shipping is "ex-works" from our factory at Chiusa di Ginestreto (Pesaro).
All products supplied by C.M.T. travel at the customer's own risk.
C.M.T. retains the right to charge freight costs on the invoice in case of value under the minimum amount acceptable of €100,00.
C.M.T. will not be held responsible for any damage, theft or tampering that might occur during transport, and for which the forwarder will be legally liable according to article 1693 of the Civil Code. The customer, for his part, will have to check the goods at the moment of receipt and, in case any anomaly or damage is found, he will have to apply for a refund to be addressed to the forwarder.

PAYMENT
Cash payments can only be accepted for purchases done directly at the **C.M.T.** factory located in Chiusa di Ginestreto (Pesaro) in accordance with article 1182, sub-section 3 of the Civil Code, or upon delivery of the goods provided there is a written agreement between the parties.
Deferred methods of payment will have to be previously agreed with the Seller. In this case, if one or more instalments are not paid, the agreement will automatically expire according to article 1186 of the Civil Code.
A delay in payment, even partial, will automatically incur interest in the amount of an extra 5% to be charged to the customer's account.
In case of non payment, **C.M.T.** reserves the right to suspend any further supply of its products.

WARRANTY
All professional tools by **C.M.T.** are manufactured according to high standards of technology and are therefore warranted against any possible defect. This warranty does not cover damage or tampering which can be ascribed to inappropriate use. It is also not applicable for tools that have been re-sharpened.
This warranty does not cover the possible injuries resulting from inappropriate use of defective tools.
C.M.T.will repair or replace any goods which the buyer shall prove to have been defective in material or workmanship upon analysis by its technical department. Any complaint must be communicated within fifteen days from receipt of the goods together with a written form in which the customer provides a detailed description of the defect.Any return of tools will only be accepted upon authorisation by **C.M.T.** and the freight will be at the customer's own expense.

OWNERSHIP RIGHTS
All rights are reserved in accordance with Italian law and with international agreements, and the whole or any part of this catalogue may not be reproduced in any way or form.

PLACE OF JURISDICTION
For any legal matter the place of jurisdiction is Pesaro.
All contracts, even those made with foreign Buyers or for goods to be sent abroad, are regulated by Italian legislation.

TM: CMT, the CMT logo and the orange color applied to tool surfaces are trademarks of C.M.T. UTENSILI S.P.A.
Any other brand names mentioned in CMT product catalogues and on the CMT website are the property of their respective owners.
© C.M.T. UTENSILI S.P.A.
This document has been sent for your personal use only.
All usage and reproduction is forbidden without written permission from C.M.T. UTENSILI S.P.A.

www.dahm.no

CMT ORANGE TOOLS™

C.M.T. UTENSILI S.p.A.

Via della Meccanica
61122 Pesaro - Fraz. Chiusa di Ginestreto - Italia

Tel. #39 0721 48571
Fax #39 0721 481021
e-mail info@cmtutensili.com

www.cmtutensili.com

ORDER NO. 03.60.3006



www.dahm.no