

Portable circular saw K 65 cc Cross-cutting systems KSS 60 cc | KSS 60 36B

### Light, strong, deep: the new MAFELL cross-cutting system for cutting depths up to 67 millimeters.

### SIMPLY IN TUNE WITH THE TIMES: CUTTING DEPTHS UP TO 67 MM



Impressive cuts in an extremely wide range of materials. At the same time, the saws are lightweight and offer easy and safe handling.

#### SIMPLY GO FREE: CORDLESS VERSION KSS 60 36B



The battery-powered KSS 60 36B gives you exceptional flexibility and freedom. What's more, the high-performance 36 V battery technology delivers ample power for a whole range of tasks.

Modeled on the 55-class design, MAFELL is offering a new generation of extremely powerful and lightweight portable circular saws for cutting depths up to 67 millimeters. Their motor output of up to 1,800 Watt and the combination of cross-cutting system and cordless operation are unique in this class of saw.

#### SIMPLY FIRST-RATE: CHIP HANDLING



The chip management system was designed and optimized for cutting fiberboard. The superb chip removal system offers substantial benefits, including when executing plunge cuts in the fiber direction.

# From solid wood to insulating materials: versatility at every level.

#### **CROSS CUTS**

It couldn't be simpler: With the cross-cutting system, the machine is permanently attached to the guide track. One fixed and one adjustable stop on the underside of the track allow precision angle cuts from  $-60^{\circ}$  to  $60^{\circ}$  to be made. Simply push the system up against the workpiece edge with the two stops, and execute the cut. Afterwards the track automatically returns to the starting position.

#### **MITER CUTS**



Thanks to the generously-sized angle scale and precise double clamp, miter cuts can be realized that ensure a perfect fit - as illustrated here on exterior cladding.



It's not just their cutting depth and exemplary user concept that make MAFELL's new saws stand out, but also their wide range of applications. Be it for cross, plunge or bevel cuts up to 67 mm in depth, the new machines do a perfect job, especially with solid structural timbers and wood fiber insulating materials.

600 110

#### PLUNGE CUTS



Dispensing with a detachable riving knife, the FLIPPKEIL permits reliable, convenient and straightforward plunge cutting.





Using the MAFELL guide tracks or the parallel fence included in the delivery scope, which is graduated in millimeters, decking boards for instance can be made to fit exactly.

## Cross-cutting systems KSS 60 cc and KSS 60 36B.

BATTERY CHARGE INDICATOR



Always in the picture: the battery charge can be checked at any time by pressing a button.

#### SAWBLADE LOCK



Pressing the battery release button interrupts the power supply and automatically locks the sawblade. The blade can then be changed safely and without risk with the Allen key attached to the machine.

#### FLIPPKEIL

Dispensing with a detachable riving knife, the spring-mounted FLIPPKEIL facilitates reliable and accurate plunge cuts



**PIVOTING GUARD RETRACTION LEVER** 

The pivoting guard is retracted quickly and easily by means of a lever for convenience and safety when executing bevel and plunge cuts.



TILTING SYSTEM

Thanks to the unique tilting system, a cutting depth of 47 mm (including rail) is always available in the angle range from 0° to 45°. With their low weight and cutting depths of up to 60 mm on the track, MAFELL's new, powerful cross-cutting systems are making a big impact when it comes to interior work, for example. In addition, the innovative, powerful battery technology of the KSS 60 36B means you can work with greater freedom and efficiency on the construction site.



If repeat cuts have to be made at the same depth, the cutting depth can be preset and locked exactly in the range from 2 to 61 mm.

**REPEAT STOP FOR CUTTING DEPTH** 





**DETACHING THE TRACK** 

The machine can be removed from the cross-cut track at the single press of a button, allowing its use for the full range of applications offered by the K 65 cc.

# Portable circular saw K 65 cc.

#### SAWBLADE LOCK



To change blades, the K 65 cc sawblade is locked simply by pressing a button, which automatically engages the starting lockout. The sawblade can then be changed quickly and easily using the Allen key attached to the machine.

#### FLIPPKEIL

Dispensing with a detachable riving knife, the spring-mounted FLIPPKEIL permits reliable plunge cutting every time.

#### **PIVOTING GUARD**



The pivoting guard is retracted quickly and easily by means of a lever for convenience and safety when executing bevel and plunge cuts. With the compact and ultra-performing K 65 cc, you can achieve superb quality cuts at depths of up to 67 millimeters - and this from a portable circular saw with the best power-to-weight ratio in its class. It offers all the weight and handling advantages of a 55-series machine with the cutting depth of a 65 mm model.

#### CUTTING DEPTH ADJUSTMENT

On the K 65 cc too, the exact cutting depth can be set quickly and reliably. Simply release the lock and set to the exact depth on the scale.



THE CUPREX HIGH-PERFORMANCE MOTOR stands for sheer strength and outstanding motive power.

#### REPEAT STOP FOR CUTTING DEPTH



The K 65 cc's cutting depth can be preset and locked in the range from 8 to 67 mm.



TRACKING POINTER

The innovative pointer automatically follows the machine as it is tilted and therefore always accurately tracks the actual cutting edge.



TILTING SYSTEM

Thanks to the unique tilting system, a cutting depth of 54 mm is always available in the angle range from  $0^{\circ}$  to 45°.

## Technical data and accessories.



#### **Technical data**

Nominal input	1,800 W		1,800 W
Nominal no-load speed	2,700 – 4,700 1/min	3,300 1/min	2,700 – 4,700 1/min
Cutting depth at 0° • with guide rail • without guide rail	0 – 61 mm 0 – 67 mm	0 – 61 mm 0 – 67 mm	_ 0 – 67 mm
Cutting depth at 45° • with guide rail • without guide rail	0 – 47 mm 0 – 53 mm	0 – 47 mm 0 – 53 mm	– 0 – 53 mm
Cutting length	408 mm	408 mm	
Tilting range	<mark>0 – 45 °</mark>	0 – 45 °	0 – 45 °
Angle cuts	-60° bis +60°	-60° bis +60°	-
Nominal voltage	230 V	36 V	230 V
Weight	6.1 kg	6.6 kg	4.7 kg
Battery		36 V, 94 Wh, Li-Ion	1

Order No.

#### Boxed | 919101 In carrying case | 919102

#### In carrying case | 919501

#### Boxed | 919001 In T-MAX | 919002

1 TCT sawblade

#### **Delivery scope**

- 1 TCT sawblade
- 185 x 1.4/2.4 x 20 mm, ATB, 32 teeth
- 1 Parallel guide fence
- 1 Guide track 370
- 1 Allen key 5 mm
- 1 Mains cable 4 m (13.1 ft)
- 1 TCT sawblade 185 x 1.2/1.8 x 20 mm, ATB, 32 teeth, Battery ideal
- 2 Battery PowerTank 36 B 94 36 V, 94 Wh, Li-Ion
- 1 Battery PowerStation APS 36 1 Parallel guide fence
- 1 Guide track 370
- 1 Allen key 5 mm
- 24 teeth 1 Parallel guide fence 1 Allen key 5 mm
  - 1 Mains cable 4 m (13.1 ft)

185 x 1.4/2.4 x 20 mm, ATB,

With the new all-rounders in the 60/65 millimeter class, you are perfectly equipped for a wide range of tasks. Thanks to specially matched accessories, you can tailor your new cross-cutting system or portable circular saw exactly to your specific applications.



11



Here at MAFELL, we often adopt a new approach in our quest to develop better machines. We take a fresh look and reconsider the crucial aspects of the tool concerned. And we always give due consideration to the future needs of the woodworking trades.

Time and again, together with outstanding material and build quality, our strategy spawns astounding solutions. We thus continuously enhance functionality and user-friendliness, for example. We strive to ensure that, while you are working, you no longer need to give the tool a second thought. Simply because MAFELL has already done the thinking for you. You focus on your job – and as far as everything else is concerned:

### Follow your instinct.

MAFELL AG · P. O. Box 1180 · 78720 Oberndorf a.N. · Germany · Phone +49 7423 812-114 Fax +49 7423 812-102 · E-Mail export@mafell.de · **www.mafell.com**